
References:

Achar BN., Fohlen GG., Parker JA., “Phthalocyanine polymer II. Synthesis and characterization of some metal phthalocyanine sheet oligomers”, *J Polym Sci Polym Chem* 20,2480–2484, 1982.

Ang C., Yu Z., Guo R., Bhalla AS., “Calculation of dielectric constant and loss of two-phase composites”, *J Appl Phys*, 93, 3475–3480, 2003.

Arbatti M., Shan X., Cheng Z., “Ceramic–polymer composites with high dielectric constant”, *Adv Mater*, 19, 1369–1372, 2007.

Arbatti M., Shan X., Cheng Z., “Novel Ceramic-Polymer Composites with High Dielectric permittivity”, *Adv Mater*, 19, 1369-1372, 2007.

Bai Y., Cheng ZY., Bharti V., Xu HS., Zhang QM., “High-dielectric-constant ceramic-powder polymer composites”, *Appl Phys Lett*, 76, 3804–3806, 2000.

Balasubramanian K., Burghard M., “Asymmetric end-functionalization of carbon nanotubes”, *Small*, 1, 1148–1150, 2005.

Bar-Cohen Y., “Electroactive polymer actuators as artificial muscles”, Bellingham (WA), SPIE, 2001.

Bar-Cohen Y., “Electroactive polymers as artificial muscles: a review. *J Spacecraft Rockets*”, 39, 822–827, 2002.

Barsoum M. W., “Fundamentals of Ceramics”. Institute of Physics Publishing:behavior observed in Mn-doped $\text{CaCu}_3\text{Ti}_4\text{O}_{12}$ ceramic”, *Applied Physics Letter*, 91.

Bhattacharya SK., Tummala RR., “Next generation integral passives: materials, processes, and integration of resistors and capacitors on PWB substrates”, *J Mater Sci*, 11, 253–268, 2000.

Bidstrup-Allen SA., Tanikella RV., Kohl P., “Novel low-temperature processing of polymer dielectrics on organic substrates by variable frequency microwave processing”, *IEEE Trans Adv Pack*,23, 313–317, 2002.

Blythe AR., “Dielectric breakdown. Electrical properties of polymers”, New York: Cambridge University Press, 1979.

Bobnar V., Levstik A., Huang C., Zhang QM., “Dielectric properties and charge transport in all-organic relaxor like CuPc–P(VDF–TrFE–CFE) composites and its constituents”, *Ferroelectrics*, 338, 107–116, 2006.

Bobnar V., Levstik A., Huang C., Zhang QM., “Intrinsic dielectric properties and charge transport in oligomers of organic semiconductor copper phthalocyanine”, *Phys Rev B*, 71,041202, 2005.

Bottcher CJF., Van Belle OC., Bordewijk P., Rip A., Yue DD., “Theory of electric polarization”, *J Electrochem Soc*121:211C, 1974.

Bruggeman DAG., “The calculation of various physical constants of heterogeneous substances. I. The dielectric constants and conductivities of mixtures composed of isotropic substances”, *Ann Phys*, 24,636–642, 1935.

Carpi F., De Rossi D., “Improvement of electromechanical actuating performances of a silicone dielectric elastomer by dispersion of titanium dioxide powder”, *IEEE Trans Dielect Electr Insul* 12, 835–843, 2005.

Chahal P., Tummala RR., Allen MG., Swaminathan M. “A novel integrated decoupling capacitor for MCM-L technology,” *IEEE Trans Compon Packag Manufact Technol B*,21,184–193, 1998.

Chanmal C. V., Jog J. P., “Dielectric relaxations in PVDF/BaTiO₃ nanocomposites”, *eXPRESS Polymer Letters Vol.2, No.4*, 294–301, 2008.

Cheong-Han Kim., Kyung-Sik Oh., Yeong-Kyeun Paek., “Microstructure Evolution and Dielectric Characteristics of $\text{CaCu}_3\text{Ti}_4\text{O}_{12}$ Ceramics with Sn-Substitution”, *Journal of the Korean Ceramic Society*, Vol. 50, No. 1, pp. 87~91, 2013.

Chiang C.K., Yin K.Y., Yen F.S. Hwang C.Y., “Effect of particle size of BaTiO_3 powder on the dielectric properties of BaTiO_3 /polyvinylidene fluoride Composites”, *Jl.Mater.Sci*, 36, 3809-3815,2001.

Chiodelli G., Massarotti V., Capsoni D., “Electric and dielectric properties of pure and doped $\text{CaCu}_3\text{Ti}_4\text{O}_{12}$ perovskite materials”, *Solid State Communications*, 132, 241-246, 2004.

Cho SD., Lee JY., Hyun JG., Paik KW., “Study on epoxy/ BaTiO_3 composite embedded capacitor films (ECFs) for organic substrate applications”, *Mater Sci Eng B*,110, 233–237, 2004.

Chu B., Zhou X., Ren K., Neese B., Lin M., Zhang Q., “A dielectric polymer with high electric energy density and fast discharge speed”, *Science*, 313,334–337, 2006.

Dang Z M., Nan C W., “Dielectric properties of LTNO ceramics and LTNO/PVDF composites”, *Ceramics International*, 31, 349–351, 2005.

Dang Z M., Zhou T., Yao S H., Yuan J K., Zha J W., Song H T., Li J Y., Chen Q., Yang W T., Bai J., “Advanced Calcium Copper Titanate/Polyimide Functional Hybrid Films with High Dielectric Permittivity”, *Adv. Matter*, 21, 2077- 2082, 2009.

Dang ZM., Fan LZ., Nan CW., “Dielectric behavior of novel three-phase carbon nanotubes/ BaTiO_3 /PVDF composites”, *Mater Sci Eng B*, ,103,140–144, 2003.

Dang ZM., Fan LZ., Shen Y., Nan CW., “Study on dielectric behavior of a three-phase CF/(PVDF+ BaTiO_3) composite”, *Chem Phys Lett*,369,95–100, 2003.

Dang ZM., Lin YH., Nan CW., “Novel ferroelectric polymer composites with high dielectric constants”, *Adv Mater*,15,1525–1529, 2003.

Dang ZM., Lin YQ., Xu HP., Shi CY., Li ST., Bai J., “Fabrication and dielectric characterization of advanced BaTiO₃/polyimide nanocomposite films”, *Adv Funct Mater*,18,1509–1517, 2008.

Dang ZM., Nan CW., “Dielectric properties of carbon fiber filled low-density polyethylene”, *J Appl Phys* ,93,5543–5545, 2003.

Dang ZM., Nan CW., “Dielectric properties of LTNO ceramics and LTNO/PVDF composites”, *Ceram Int*,31,349–351, 2005.

Dang ZM., Peng B., Xie D., Yao SH., Jiang MJ., Bai J., “High dielectric permittivity silver/polyimide composite films with excellent thermal stability”. *Appl Phys Lett*, 92,1129 10, 2008.

Dang ZM., Shen Y., Nan CW., “Dielectric behavior of three-phase percolative Ni–BaTiO₃/polyvinylidene fluoride composites”, *Appl Phys Lett*,81,4814–4816, 2002.

Dang ZM., Tian CY., Zha JW., Yao SH., Xia YJ., Shi CY., “Potential bioelectroactive bone-recovery polymer nanocomposites with high dielectric permittivity”, *Adv Eng Mater*,11,144–147, 2009.

Dang ZM., Wang HY., Peng B., Nan CW., “Effect of BaTiO₃ size on dielectric property of BaTiO₃/PVDF composites”, *J Electroceram*,21,381–384, 2008.

Dang ZM., Wang HY., Xu HP., “Influence of silane coupling agent on morphology and dielectric property in BaTiO₃/polyvinylidene fluoride composites”, *Appl Phys Lett*,89,112902, 2006.

Dang ZM., Wang HY., Zhang YH., Qi JQ., “Morphology and dielectric property of homogenous BaTiO₃/PVDF nanocomposites prepared via the natural adsorption action of nanosized BaTiO₃”, *Macro Rap Commun*, 26,1185–1190, 2005.

Dang ZM., Wang L., Wang HY., Yin Y., Tjong SC., Xie D., “Rescaled temperature dependence of dielectric behavior in ferroelectric PVDF–LTNO composites”, *Appl Phys Lett*,86,179205, 2005.

Dang ZM., Wang L., Yin Y., Zhang Q., Lei QQ., “Giant dielectric permittivities in functionalized carbon–nanotube/electroactivepolymer nanocomposites”, *Adv Mater* ,19,852–857, 2007.

Dang ZM., Wu JB., Fan LZ., Nan CW., “Dielectric behavior of Li and Ti co-doped NiO/PVDF composites”, *Chem Phys Lett*,376,389–393, 2003.

Dang ZM., Wu JP., Xu HP., Yao SH., Jiang MJ., Bai J., ‘Dielectric properties of upright carbon fiber filled poly(vinylidene fluoride) composite with low percolation threshold and weak temperature dependence”, *Appl Phys Lett*, 91,072912, 2007.

Dang ZM., Xia B., Yao SH., Jiang MJ., Song HT., Zhang LQ., “High-dielectric-permittivity three-component high-elasticity nanocomposites with low percolation threshold and low dielectric loss”, *Appl Phys Lett*, 94,042902, 2009.

Dang ZM., Xie D., Shi CY., “Theoretical prediction and experimental study of dielectric properties in poly(vinylidene fluoride) matrix composites with micro–nanosize BaTiO₃ filler”, *Appl Phys Lett*, 91,222902, 2007.

Dang ZM., Xu HP., Wang HY., “Significantly enhanced low-frequency dielectric constant in BaTiO₃/poly(vinylidene fluoride) nanocomposite”, *Appl Phys Lett*,90,012901, 2007.

Dang ZM., Yao SH., Xu HP., “Effect of tensile strain on morphology and dielectric property in nanotubes/polymer composites”, *Appl Phys Lett*,90,012907, 2007.

Dang ZM., Yu YF., Xu HP., Bai J., “Study on microstructure and dielectric property of the BaTiO₃/epoxy resin composites”, *Composite Science Technology*, 68,171–177, 2008.

Dang ZM., Zhang YH., TJong SC., “Dependence of dielectric behavior on the physical property of fillers in the polymer–matrix composites”, *Synthetic Met*, 146,79–84, 2004.

Dang ZM., Zheng Y., Xu HP., “Effect of ceramic particle sizes on morphology and dielectric properties in the BaTiO₃/polystyrene composites”, *J Appl Polym Sci*,111,3473–3479, 2008.

Dang ZM., Zhou T., Yao SH., Yuan JK., Zha JW., Song HT., “Advanced calcium copper titanate/polyimide hybrid films with high dielectric permittivity”, *Adv Mater*, 21,2077–2082, 2009.

Dang ZM., Zhou T., Yao SH., Yuan JK., Zha JW., Song HT., “Advanced calcium copper titanate/polyimide functional hybrid films with high dielectric permittivity”, *Adv Mater*, 21,2077-2082, 2009.

Dang ZM., Zhou T., Yao SH., Yuan JK., Zha JW., Song HT., “Advanced calcium copper titanate/polyimide hybrid films with high dielectric permittivity”, *Adv Mater*, 21,2077–2082, 2009.

Dario P., Carrozza M., Benvenuto A., Menciassi A., “Microsystems in biomedical applications.” *J Micromech Microeng*, 10, 235–244, 2000.

Dasgupta DK., Doughty K., “Polymer–ceramic composite materials with high dielectric constants”, *Thin Solid Films*, 158, 93–105, 1988.

DevaraJu NG., Lee BI., “Dielectric behavior of three phase polyimide percolative nanocomposites”, *J Appl Polym Sci*,99:3018–3022, 2006.

Dias C.J., Das-Gupta K.K., “Inorganic ceramic/polymer ferroelectric composite electrets”, IEEE Trans Dielect Electr Insul, 3, 706–710, 1996.

Fan Z., Luo G., Zhang Z., Zhou L., Wei., “Electromagnetic and microwave absorbing properties of multi-walled carbon nanotubes/polymer composites”, Mater Sci Eng B, 132, 85–89, 2006.

Frolich H. “Theory of dielectrics”, Oxford: Clarendon Press, 1949.

Gallone G., Carpi F., De Rossi D., Rossi D.D., Levita G., Marchetti A., “Dielectric constant enhancement in a silicone elastomer filled with lead magnesium niobate–lead titanate”, Mater Sci Eng C, 27, 110–116, 2007.

Garner C.M., Kloster G., Atwood G., Mosley L., Palanduz A.C., “Challenges for dielectric materials in future integrated circuit technologies”, Microelectr Reliab, 45, 919–924, 2005.

Goyal R.K., Katkade S.S., Mule D.M. “Dielectric, mechanical and thermal properties of polymer/BaTiO₃ composites for embedded capacitor”. Composites Part B 44, 128-132, 2013.

Gregoria Jr R., Cestari M., “Effect of crystallization temperature on the crystalline phase content and morphology of poly(vinylidene fluoride)”, J PolySci, B: Poly Phys, 32, 859-870, 1994.

He F., Lau S., Chan H.L., Fan J., “High dielectric permittivity and low percolation threshold in nanocomposites based on poly(vinylidene fluoride) and exfoliated graphite nanoplates”, Adv Mater, 21, 710–715, 2009.

Hong S.H., Kim D.Y., Park H.M., Kim Y.M., “Electric and Dielectric Properties of Nb-Doped CaCu₃Ti₄O₁₂ Ceramics” J. Am. Ceram. Soc., 90, 2118–2121, 2007.

Huang C., Zhang Q.M., “Fully functionalized high-dielectric-constant nanophase polymers with high electromechanical response”, Adv Mater, 17, 1153–1158, 2005.

Huang C., Zhang QM., Botton G., Bhattacharya K., “All-organic dielectric-percolative three-component composite materials with high electromechanical response”, *Appl Phys Lett*, 84,4391–4393, 2004.

Huang C., Zhang QM., Li JJ., “Colossal dielectric and electromechanical responses in self-assembled polymeric nanocomposites”, *Appl Phys Lett*, 87,182901, 2005.

Huang C., Zhang QM., Su J., “High-dielectric-constant all-polymer percolative composites”, *Appl Phys Lett*, 82,3502–3504, 2003.

Hutagalung SD., Ikhawan M Ibrahim M., Ahmad ZA., “Microwave assisted sintering of Immergut EH., Brandrup J., McDowell W., “Polymer handbook”, New York: Wiley, 2008.

Jayasundere N., Smith BV., “Dielectric constant for binary piezoelectric 0–3 composites”, *J Appl Phys*, 73, 2462–2466, 1993.

Jesurani S., Kanagesan S., Hashim M., Ismai I., “Dielectric properties of Zr doped $\text{CaCu}_3\text{Ti}_4\text{O}_{12}$ synthesized by sol–gel route”, *Journal of Alloys and Compounds*, 551, 456–462, 2013.

Jesurani S., Kanagesan S., Hashim M., Ismail I., “Dielectric properties of Zr doped $\text{CaCu}_3\text{Ti}_4\text{O}_{12}$ synthesized by sol–gel route”, *Journal of Alloys and Compounds*, 551, 456–462, 2013.

Jiang MJ., Dang ZM., Xu HP., “Giant dielectric constant and resistance-pressure sensitivity in carbon nanotubes/rubber nanocomposites with low percolation threshold”, *Appl Phys Lett*, 90,042914, 2007.

Jin S., Xia H., Zhang Y., Guo J., Xu J., “Synthesis of $\text{CaCu}_3\text{Ti}_4\text{O}_{12}$ ceramic via a sol-gel” *Ceram. Intern.* 35, 309, 2009.

Jonker GH., “On dielectric Curie-Weiss law and diffuse phase transition in ferroelectrics”, *Material Research Bulletin*, 18, 301, 1983.

Kakimoto M., Takahashi A., Tsurumi T., Hao J., Li L., Kikuchi R., ”Polymer–ceramic nanocomposites based on new concepts for embedded capacitor”, *Mater Sci Eng B*, 132,74–78, 2006.

Kapadia H., Cole H., Saia R., Durocher K., “Evaluating the need for integrated passive substrates. *Adv Microelectron*”, 26,12–6,1999.

Kilbride BE., Coleman JN., Fraysse J., Fournet P., Cadek M., Drury., “Experimental observation of scaling laws for alternating current and direct current conductivity in polymer–carbon nanotube composite thin films”, *Appl Phys Lett*, 92,4024–4026, 2002.

Kittel C., “Introduction to Solid State Physics”, 5th Ed., New York: Wiley, 1976.

Kumar R, Zulfequar M, Kaur H, Singh VN, Senguttuvan TD (2011) Impedance Spectroscopic Studies of Sol–Gel Derived Nanocrystalline $\text{CaCu}_3\text{Ti}_4\text{O}_{12}$. *Advanced Science, Engineering and Medicine* 3(3): 197– 201.

Kumar R., Zulfequar M., Kaur H., Singh VN., Senguttuvan TD., “Impedance Spectroscopic Studies of Sol–Gel Derived Nanocrystalline $\text{CaCu}_3\text{Ti}_4\text{O}_{12}$ ”, *Advanced Science, Engineering and Medicine* 3, 197– 201, 2011.

Landauer R., “The electrical resistance of binary metallic mixtures”, *J Appl Phys*,23,779–784, 1952.

Landi BJ., Raffaele RP., Heben MJ., Alleman JL., VanDerveer W., Gennett T., “Single wall carbon nanotube–nafion composite actuators”, *Nano Lett*, 2,1329–1333, 2002.

Lau J., “Chip on board technologies for multichip modules”, Kluwer Academic Publishers, 1994.

Li JY., Huang C., Zhang QM., “Enhanced electromechanical properties in all-polymer percolative composites”, *Appl Phys Lett*, 84,3124–3126, 2004.

Li JY., Zhang L., Ducharme S., “Electric energy density of dielectric Composites”, *Appl Phys Lett*, 90,132901, 2007.

Li YJ., Xu M., Feng JQ., Dang ZM., “Dielectric behavior of a metal–polymer composite with low percolation threshold”, *Appl Phys Lett*,89:072902, 2006.

Linfeng Chen and Vijay K. Varadan (2004). *Microwave electronics: measurement and materials characterization*. John Wiley and Sons. p. 8, eq.(1.15). doi:10.1002/0470020466. ISBN 0-470-84492-2.

Lu J., Moon KS., Xu J., Wong CP., “Synthesis and dielectric properties of novel high-k polymer composites containing in-situ formed silver nanoparticles for embedded capacitor applications”, *J Mater Chem*,16,1543–1548, 2006.

Luo B C., Wang X., Wang Y., Li L., “Fabrication, characterization, properties and theoretical analysis of ceramic/PVDF composite flexible films with high dielectric constant and low dielectric loss”, *J. Mater. Chem A*, 2, 510, 2014.

Masingboon C., Maensiri S., Yamwong T., Anderson PL., Seraphin S., Nanocrystalline CaCu₃Ti₄O₁₂ powders prepared by egg white solution route: synthesis, characterization and its giant dielectric properties, *Applied Physics A*, 91(1), 87–95, 2008.

Maxwell J.C. “A treatise on electricity and magnetism”, New York: Dover Publ. Co, 1954.

Maxwell-Garnett JC., “Colours in metal glasses and in metallic films”, *Philos Trans Roy Soc Lond* 203,385–389, 1904.

Mc Pherson J., Kim JK., Shanware A., Mogul H., “Thermochemical description of dielectric breakdown in high dielectric constant materials”, *Appl Phys Lett*, 13, 2121–2123, 2003.

McCrum NG., Read BE., Williams G., “Anelastic dielectric effect in polymeric solids”, London: Wiley, p.108-11, 1967.

McLachlan DS., Blaszkiewics M., Newnham RE., “Electrical resistivity of composites”, *J Am Ceram Soc*, 73, 2187–2203, 1990.

Mijovic J, Lee H, Kenny J, Mays J., “Dynamics in polymer silicate nanocomposites as studied by dielectric relaxation spectroscopy and dynamic mechanical spectroscopy”, *Macromolecules*, 39, 2172, 2006.

Moniruzzaman M., Winey KI., “Polymer nanocomposites containing carbon nanotubes”, *Macromolecules*, 39, 5194–5205, 2006.

Mu C., Jhang H., He Y., Liu P., Shen J., “The origin of multiple dielectric relaxation processes in Fe-substituted $\text{CaCu}_3\text{Ti}_4\text{O}_{12}$ ceramics”, *Material Science Engineering B*, 162, 195-199, 2009.

Nalwa H.S., “Ferroelectric polymers”, New York: Ed. Marcel Dekker, 1995 [Chapter 11].

Nan CW., “Physics of inhomogeneous inorganic materials”, *Prog Mater Sci*, 37, 1–126, 1993.

Nan CW., Comment on ‘Effective dielectric function of a random medium’. *Phys Rev B* 63, 176201-1, 2001.

Nelson SO., You TS., “Relationships between microwave permittivities of solid and pulverized plastics”, *J Phys D Appl Phys*, 23, 346–353, 1990.

Newnham RE., Skinner DP., Cross LE., “Connectivity and piezoelectric–pyroelectric composites”, *Mater Res Bull*, 13, 525–536, 1978.

Ni L., Chen XM., “Enhancement of giant dielectric response in $\text{CaCu}_3\text{Ti}_4\text{O}_{12}$ ceramics by Zn Substitution”. *J. Am. Ceram. Soc.*, 93, 184-189, 2010.

Omar A., Abdelal A., Ahmed A., Hassan El-Sayed M Ali., “Dielectric Properties of Calcium Copper Titanates ($\text{CaCu}_3\text{Ti}_4\text{O}_{12}$) Synthesized by Solid State Reaction”, *Arab Journal of Nuclear Science and Applications*, 45, 354-361, 2012.

P. Thomas, R. S. Ernest Ravindran, K. B. R.Varma. Dielectric properties of Poly(methyl methacrylate) (PMMA)/ $\text{CaCu}_3\text{Ti}_4\text{O}_{12}$ Composites. *IEEE, ICPADM*, 2012.

Parkash O., Kumar D., Goyal A., Agrawal A., Mukherjee A., Singh S., Singh P., “Electrical behavior of zirconium doped calcium copper titanium oxide”, *J.Phys. D: Appl. Phys*, 41, 035401, 2008.

Patterson EA., Kwon SH., Huang CC., “Effects of ZrO_2 additions on the dielectric properties of $\text{CaCu}_3\text{Ti}_4\text{O}_{12}$ ”, *Appl. Phys. Lett.*, 87, 182911, 2005.

Popielarz R., Chiang CK., Nozaki R., “Obrzut dielectric properties of polymer/ferroelectric ceramic composites from 100 Hz to 10 GHz”, *Macromolecules* 34, 5910–5915, 2001.

Pothukuchi S., Li Y., Wong CP., “Development of a novel polymer–metal nanocomposite obtained through the route of in situ reduction for integral capacitor application”, *J. Appl Polym Sci*, 93, 1531–1535, 2004.

Prymark J., Bhattacharya S., Paik K., Tummala RR., “Fundamentals of microsystems packaging”, New York McGraw-Hill, 2001.

Qi L., Lee BI., Chen S., Samuels WD., Exarhos GJ., “High-dielectric-constant silver–epoxy composites as embedded dielectrics”, *Adv Mater*, 17:1777–1782, 2005.

Rai Alok Kumar., Singh Nitish Kumar., Lee Sang-Kwon., Mandal K.D., Kumar D., Parkash Om., “Dielectric properties of iron doped calcium copper titanate, $\text{CaCu}_{2.9}\text{Fe}_{0.1}\text{Ti}_4\text{O}_{12}$ ”
Journal of Alloys and Compounds 509, 8901– 8906, 2011.

Rai Alok Kumar., Singh Nitish Kumar., Lee Sang-Kwon., Mandal K.D., Kumar D., Parkash Om., “Dielectric properties of iron doped calcium copper titanate, $\text{CaCu}_3\text{Ti}_{3.9}\text{Fe}_{0.1}\text{O}_{12}$ ceramic”
J Mater Sci: Mater Electron 22, 1286–1289, 2011.

Ramajo LA., Ramfrez MA., Bueno PR., Reboredo MM., Castro MS., “Dielectric Behaviour of $\text{CaCu}_3\text{Ti}_4\text{O}_{12}$ - Epoxy Composites. Material Research”, 11, 85-88, 2008.

Rao Y, Qu J, Marinis T, Wong C.P., “A precise numerical prediction of effective dielectric constant for polymer–ceramic composite based on effective medium theory”, IEEE Trans Compon Packag Technol, 23, 680, 2000.

Rao Y., Ogitani S., Kohl P., Wong CP., “Novel polymer–ceramic nanocomposite based on high dielectric constant epoxy formula for embedded capacitor application”, J Appl Poly Sci ,83,1084–1089, 2002.

Rao Y., Wong CP., “Material characterization of high dielectric constant polymer–ceramic composite for embedded capacitor to RF application,” J Appl Polym Sci, 92, 2228–2231, 2004.

Rao Y., Wong CP., “Ultra high dielectric constant polymer metal composite for embedded capacitor application”, US Patent 6864306, 2005.

Roy A K., Amar Nath K., Prasad K., Prasad A., “Effective complex permittivity and AC conductivity of $(\text{Bi}_{0.5}\text{Na}_{0.5})_{0.94}\text{Ba}_{0.06}\text{TiO}_3$ -PVDF 0-3 composites”, Adv. Mat. Lett, 5(2), 100-105, 2014.

Shalev VM., “Electromagnetic properties of small-particle composites”, Phys Rep, 272, 61–137, 1996.

Shannon RD, Prewitt CT. “Revised values of effective ionic radii”, *Acta Cryst*, B26, 1046–1048, 1970.

Shen LC., Savret WC., Price JM., Athavale K., “Dielectric properties of reservoir rocks at ultra-frequencies”, *Geophysics*, 50,692, 1985.

Sihvola AH., Pekonen OPM., “Effective medium formula for bi-anisotropic mixtures”, *J Phys D: Appl Phys*, 29,514–521, 1996.

Sillars RW., “The properties of a dielectric containing semi-conducting particles of various shapes”, *J Inst Elect Eng*, 378–94, 1937.

Singh L., Rai US., Mandal KD., “Dielectric properties of zinc doped nano-crystalline calcium copper titanate synthesized by different approach”, *Materials Research Bulletin*, 48,2117-2122, 2013.

Singh L., Rai US., Rai AK., Mandal KD., “Effects of partial substitutions of transition metal cations on dielectric properties of $\text{Ca}_{1-x}\text{La}_x\text{Cu}_{3-x}\text{Mn}_x\text{Ti}_{4-x}\text{Ni}_x\text{O}_{12}$ ($x= 0.05, 0.10$) electro-ceramics synthesized by semi-wet chemical method”, *Journal of Advanced Ceramics*, 2, 119–127, 2013.

Smith GB., “Dielectric constant for mixed media”, *J Phys D Appl Phys*,10,39–43, 1977.

Su Y L., Sun C., Zhang W Q., Huang H., “Fabrication and dielectric properties of $\text{Na}_{0.5}\text{Bi}_{0.5}\text{Cu}_3\text{Ti}_4\text{O}_{12}$ /poly(vinylidene fluoride) composites”, *J Mater Sci*, 48,8147–8152, 2013.

Subramanian MA., Li D., Duan N., “High dielectric permittivity in $\text{ACu}_3\text{Ti}_4\text{O}_{12}$ and $\text{ACu}_3\text{Ti}_3\text{FeO}_{12}$ phases”, *J. Solid State Chem.*, 151, 323-32, 2000.

Sulaiman M A., Hutagalung S D., Mohd F A., Ahmad Z A., “Dielectric properties of Nb-doped $\text{CaCu}_3\text{Ti}_4\text{O}_{12}$ electroceramics measured at high frequencies”, *Journal of Alloys and Compounds*, 493, 486–492, 2010.

Thomas P., Dwarkanath K., Varama KBR., Kutty TRN., “Nanoparticles of the giant dielectric material, $\text{CaCu}_3\text{Ti}_4\text{O}_{12}$ from a precursor route”, *Journal of Physics and Chemistry, of Solids*, 69, 2594- 2604, 2008.

Thomas P., Satapathy S., Dwarakanath K., K.B.R.Varma., “Dielectric properties of Poly(vinylidene fluoride)/ $\text{CaCu}_3\text{Ti}_4\text{O}_{12}$ nanocrystal composite thick films”, *eXPRESS Polymer Letters* Vol.4, No.10, 632-643, 2010.

Thomas P., Satapathy S., Dwarakanath K., Varma KBR., “Dielectric properties of poly(vinylidene fluoride)/ $\text{CaCu}_3\text{Ti}_4\text{O}_{12}$ nanocrystal composite thick films”, *eXPRESS Polymer Letters* Vol.4, No.10 632–643, 2010.

Thomas P., Varughese K T., Dwarakanath K., Varma KBR., “Dielectric properties of Poly(vinylidene fluoride)/ $\text{CaCu}_3\text{Ti}_4\text{O}_{12}$ composites”, *Composite science and technology*, 70, 539-545, 2010.

Tsangaris G. M., Psarras G. C., “The dielectric response of a polymeric three-composite”, *Journal of Materials Science*, 34, 2151–2157, 1999.

Tummala RR., “Electronic packaging for high reliability, low cost electronics”, Kluwer Academic Publishers, 1999.

Tuncer E., Gubanske SM., Nettelblad B., “Dielectric relaxation in dielectric mixtures: application of the finite element method and its comparison with mixture formulas”, *Appl Phys*, 89, 8092–8100, 2001.

Uchino K., "Piezoelectric actuators and ultrasonic motors," Kluwer Academic Publisher, 1997.

Ulrich RK., Schaper LW., “Integrated passive component technology. Piscataway (NJ)” IEEE Press, 2003.

Van Beek L. K. H., “Dielectric behaviour of heterogeneous systems in ‘Progress in Dielectrics’ (ed.: Birks J. B.)”, Heywood Books, London, 69–117, 1967.

Wagner KW., “The after effect in dielectrics”, Arch Electrotech, 2,378–280, 1914.

Wang CC., Song JF., Bao HM., Shen QD., Yang CZ., “Enhancement of electrical properties of ferroelectric polymers by polyaniline nanofibers with controllable conductivities”, Adv Funct Mater. 18, 1299–1306, 2008.

Wang JW., Shen QD., Bao HM., Yang CZ., Zhang QM., “Microstructure and dielectric properties of P(VDF–TrFE–CFE) with partially grafted copper phthalocyanine oligomer”, Macromolecules, 38,2247–2252, 2005.

Wang JW., Shen QD., Yang CZ., Zhang QM., “High dielectric constant composite of P(VDF–TrFE) with grafted copper phthalocyanine oligomer”, Macromolecules, 37:2294–2298, 2004.

Wang L., Dang ZM., “Carbon nanotube composites with high dielectric constant at low percolation threshold”, Appl Phys Lett, 87, 042903, 2005.

Wei T., Jin CQ., Zhang W., Liu JM., “High permittivity polymer embedded with Co/ZnO core/shell nanoparticles modified by organophosphorus”, Appl Phys Lett, 91,222907, 2007.

West AR., Adams TB., Morrison FD., Sinclair DC., “Novel high capacitance materials:- BaTiO₃:La and CaCu₃Ti₄O₁₂”, Journal of European Ceramic Society, 24, 1439-1448, 2004.

Wilson SA., Maistros GM., Whatmore RW., “Structure modification of 0–3 piezoelectric ceramic/polymer composites through dielectrophoresis”, J Phys D: Appl Phys 38,175–182, 2005.

Xu D., Zhang C., Lin Y., Jiao L., Yuan H., “Influence of zinc on electrical and micro structural properties Of CaCu₃Ti₄O₁₂ ceramics prepared by sol–gel process”, Journal of Alloys and Compounds, 522, 157–161, 2012.

Xu HP., Dang ZM., “Electrical property and microstructure analysis of poly(vinylidene fluoride)-based composites with different conductive fillers”, *Chem Phys Lett* 438,196–202, 2007.

Yang W., Shuhui Y., Rong S., Ruxu D., “Nano- and microsize effect of CCTO fillers on the dielectric behaviour of CCTO/PVDF composites,” *Acta Materialia*, 59, 5593 – 5602, 2011.

Yang W., Yu S., Sun R., Du R., “Nano- and microsize effect of CCTO fillers on the dielectric behavior of CCTO/PVDF composites”, *Acta Materialia*, 59, 5593–5602, 2011.

Yao SH., Dang ZM., Jiang MJ., Bai J., “BaTiO₃-nanotube/polyvinylidene fluoride three-phase composites with high dielectric constant and low dielectric loss”, *Appl Phys Lett*,93,182905, 2008.

Yao SH., Dang ZM., Jiang MJ., Xu HP., Bai J., “Influence of aspect ratio of carbon nanotube on percolation threshold in ferroelectric polymer nanocomposite”, *Appl Phys Lett*, 91,212901, 2007.

Yao SH., Dang ZM., Xu HP., Jiang MJ., Bai J., “Exploration of dielectric constant dependence on evolution of microstructure in nanotube/ferroelectric polymer nanocomposites”, *Appl Phys Lett*,92,082902, 2008.

Yu HT., Liu HX., Hao H., “Dielectric properties of CaCu₃Ti₄O₁₂ ceramics modified by SrTiO₃”. *Mater. Lett.*, 63,1353-1355, 2008.

Yuan JK., Dang ZM., Bai J., “Unique dielectric properties of ferroelectric polyaniline/poly(vinylidene fluoride) composites induced by temperature variation”, *Phys Status Solidi: Rap Res Lett*, 2,233–235, 2008.

Yuan JK., Dang ZM., Yao SH., Zha JW., Zhou T., Li ST., “Fabrication and dielectric properties of advanced high permittivity polyaniline/poly(vinylidene fluoride) nanohybrid films with high energy storage density”, *J Mater Chem*,20,2441–2447, 2010.

Zhang L., Shan X., Wu P., Cheng Z Y., “Dielectric characteristics of $\text{CaCu}_3\text{Ti}_4\text{O}_{12}/\text{P}(\text{VDF-TrFE})$ nanocomposites”, *Appl Phys A*, DOI 10.1007/s00339-012-6836-3.

Zhang L., Shan X., Wu P., Cheng ZY., “Dielectric characteristic of $\text{CaCu}_3\text{Ti}_4\text{O}_{12}/\text{P}(\text{VDF-TrFE})$ ”, *Appl Phys A*, 107,597–602, 2012.

Zhang QM., Furukawa T., Bar-Cohen Y., Scheinbeim J., “Electroactive polymers”, In: *MRS Symp Proc*, Warrendale, PA, 600, 2000.

Zhang QM., Li H., Poh M., Xu H., Cheng ZY., Xia F., “An all-organic composite actuator material with a high dielectric constant”, *Nature*, 419, 284–287, 2002.

Zhao J., Liu J., Ma G., “Preparation, characterization and dielectric properties of $\text{CaCu}_3\text{Ti}_4\text{O}_{12}$ Ceramics”. *Ceramics International*, 38, 1221– 1225, 2012.

Zhi Min Dang, Jin Kai Yuan, Jun Wei Zha, Tao Zhou, Sheng Tao Li, Guo Hua Hu. “Fundamentals, processes and applications of high-permittivity polymer–matrix composites”. *Progress in Materials Science* 57, 660–723, 2012.