

# Mathematical and Experimental Analysis of Solar Still Systems Using Q-Dot Glass Evaporator



Thesis submitted in partial fulfillment for the  
Award of Degree

## **Doctor of Philosophy**

Submitted by

**Vikash Kumar Chauhan**

Under the Supervision of

**Prof. S.K. Shukla**

**DEPARTMENT OF MECHANICAL ENGINEERING  
INDIAN INSTITUTE OF  
TECHNOLOGY (BANARAS  
HINDU UNIVERSITY)  
VARANASI-221005**

**Roll No. 19131006**

**December, 2022**

## DECLARATION BY THE CANDIDATE

I, “**VIKASH KUMAR CHAUHAN**”, Roll no. 19131006, hereby certify that the work embodied in this thesis entitled “**Mathematical and Experimental Analysis of Solar Still Systems Using Q-Dot Glass Evaporator**” is my bona fide work and carried out by me under the supervision of “**Prof. Shailendra Kumar Shukla**” from July 2019 to December 2022, in the **Department of Mechanical Engineering, Indian Institute of Technology (BHU), Varanasi**. The matter embodied in this thesis has not been submitted for the award of any other degree/diploma in this university or any other university/deemed university. I declare that I have faithfully acknowledged and given credits to the research workers wherever their works have been cited in my work in this thesis.

**Date:** 26-12-2022

**Place:** Varanasi



**VIKASH KUMAR CHAUHAN**

## CERTIFICATE BY THE SUPERVISOR

It is certified that the above statement made by the student is correct to the best of my knowledge.



**Prof. S.K. Shukla**

Supervisor

Dept. of Mechanical Engineering  
IIT (BHU), Varanasi - 221005



**Prof. Santosh Kumar**

Head

Dept. of Mechanical Engineering  
IIT (BHU), Varanasi - 221005

## **COPYRIGHT TRANSFER CERTIFICATE**

---

**Title of the Thesis: Mathematical and Experimental Analysis of  
Solar Still Systems Using Q-Dot Glass Evaporator.**

**Name of the Student: Vikash Kumar Chauhan**

*Vikash Chauhan*

### ***Copyright Transfer***

---

**The undersigned hereby assigns to the Indian Institute of  
Technology (Banaras Hindu University), Varanasi all rights  
under copyright that may exist in and for the above thesis  
submitted for the award of the “DOCTOR OF PHILOSOPHY”**

**Date: 26-12-2022**

**Place: Varanasi**

*Vikash Chauhan*

**VIKASH KUMAR CHAUHAN**

**Note: However, the author may reproduce or authorize others  
to reproduce material extracted verbatim from the thesis or  
derivative of the thesis for author’s personal use provided that  
the source and the institute’s copyright notice are indicated.**

## Acknowledgment

I would like to take this opportunity to express my profound gratitude and deep regards to my esteemed supervisor, *Prof. Shailendra Kumar Shukla and RPEC members* for their guidance and constant encouragement were invaluable and they were the motive force for the completion of this dissertation work. Without their guidance it would have never been possible for me to experience working in the area of Solar energy and Desalination. I am thankful to the staff of entire *CERD Lab* for providing me with this opportunity and believing in me.

I am also thankful to *Prof. Santosh Kumar*, Head, Department of Mechanical Engineering, IIT BHU, along with staff members, the **Central Instrument Facility lab**, and its member for their cooperation and for providing necessary facilities during the work.

Above all, I would like to express my gratitude toward my father, Shri Lakshmi Narayan Chauhan, and mother, Smt Vidhanti Devi, for their belief, support, and encouragement throughout this working period and my partner for care and endurance to achieve my goal. Lastly, I thank my friends, colleagues, and seniors who have constantly encouraged and helped me carry out the work.

**Date:** 26-12-2022

**Place:** Varanasi



**VIKASH KUMAR CHAUHAN**

# Table of Contents

<b>List of Figures.....</b>	<b>ix</b>
<b>List of Tables .....</b>	<b>xii</b>
<b>Abstract.....</b>	<b>xiv</b>
<b>Chapter 1 INTRODUCTION.....</b>	<b>1</b>
1.1 History.....	1
1.2 Water Scarcity.....	1
1.2.1 Saline water.....	2
1.3 Desalination.....	3
1.3.1 Membrane Desalination .....	4
1.3.2 Thermal Desalination .....	5
1.4 Solar Energy.....	7
1.5 Solar Desalination .....	9
1.5.1 Solar Still.....	9
1.6 Phase Change Material.....	11
1.7 Quantum Dot Material .....	14
1.8 Organization of Thesis .....	17
<b>Chapter 2 LITERATURE REVIEW.....</b>	<b>18</b>
2.1 Introduction.....	18
2.2 Direct solar desalination.....	19
2.2.1 Passive Solar stills.....	19
2.2.2 Active Solar Still .....	21
2.3 Modifications in Design of SS .....	22
2.3.1 Design of cover plate.....	22
2.3.2 Absorber Area Augmentation .....	25
2.4 Solar Desalination with Heat Storage .....	26
2.4.1 SHS with Passive SS.....	28
2.4.2 SHS with Active SS .....	29
2.4.3 LHS with Passive SS.....	29
2.4.4 LHS with Active SS .....	32
2.5 Economic Analysis of solar stills .....	37
2.6 Research gap .....	38
2.7 Objectives.....	39

<b>Chapter 3 EXPERIMENTAL SETUPS AND MATERIALS .....</b>	<b>40</b>
3.1 Introduction .....	40
3.2 Parametric Study of solar still .....	40
3.2.1 Study of tilt angle of solar still .....	40
3.3 Study of QD concentration on SS .....	45
3.4 Study of Prismatic SS.....	47
3.5 Preparation of material .....	50
3.5.1 QD coating. ....	50
3.5.2 Phase change material .....	51
<b>Chapter 4 THEORETICAL MODELLING.....</b>	<b>54</b>
4.1 Introduction.....	54
4.2 Assumptions.....	54
4.3 Modelling .....	56
4.3.1 Energy balance on Basin water .....	58
4.3.2 Energy balance on Glass (Condenser).....	59
4.3.3 Energy balance on Basin liner.....	61
4.3.4 Heat balance on Insulation .....	62
4.3.5 Block diagram of algorithm.....	67
<b>Chapter 5 ECONOMIC ANALYSIS.....</b>	<b>68</b>
5.1 Introduction.....	68
5.2 Cost analysis of modified solar still .....	68
5.2.1 Overall Cost .....	69
5.2.2 Salvage Value.....	70
5.2.3 Working Life.....	70
5.2.4 Interest rate.....	71
5.2.5 Sinking fund factor.....	71
5.2.6 Annual Salvage Value.....	71
5.2.7 Money Recovery Factor .....	72
5.2.8 Annual First cost .....	72
5.2.9 Annual Maintenance cost .....	72
5.2.10 Annual total cost.....	73
5.2.11 Average annual Production .....	73
5.2.12 Monetary cost.....	73
5.2.13 Annual equivalent energy.....	74
5.2.14 Overall annual gain .....	74

5.2.15	Payback period .....	74
5.3	Cost analysis with QD.....	76
<b>Chapter 6 RESULT AND DISCUSSION.....</b>		<b>79</b>
6.1	Introduction.....	79
6.2	Effect of tilt angle on SS .....	79
6.2.1	Hourly variation of climate condition .....	79
6.2.2	Variation of SS inside condition and Yield.....	83
6.2.3	Effect of wind velocity.....	88
6.2.4	Nocturnal Productivity.....	90
6.3	Efficiency comparison.....	91
6.3.1	Thermal Efficiency.....	91
6.3.2	Exergy analysis .....	93
6.3.3	Effect of tilt angle.....	94
6.4	Effect of BPQD concentration on SS.....	95
6.4.1	Variation of climatic condition .....	95
6.4.2	Hourly variation of $T_{bw}$ and $T_{ig}$ .....	96
6.4.3	Experimental and Theoretical Comparison.....	97
6.4.4	Yield of solar stills .....	99
6.4.5	Effect of wind on Convective HTC .....	102
6.5	Efficiency comparison.....	103
6.5.1	Energy efficiency .....	103
6.5.2	Exergy Efficiency.....	103
6.6	Performance of Prismatic SS.....	105
6.6.1	Conventional and Prism type SS.....	105
6.6.2	Effect of PCM on Conventional and Prism type SS .....	108
6.6.3	Effect of QD and PCM on Conventional and Prism SS.....	112
6.6.4	Yield of modified solar still .....	115
6.7	Efficiency comparison.....	116
6.7.1	Utilization efficiency.....	116
6.7.2	Heating efficiency .....	117
6.7.3	Exergy analysis .....	119
6.8	Distilled water quality .....	120
6.9	Uncertainty analysis.....	121
<b>Chapter 7 CONCLUSION AND FUTURE SCOPE .....</b>		<b>124</b>
7.1	Introduction.....	124

7.2	Effect of tilt angle.....	124
7.3	Effect of QD concentration .....	126
7.4	Performance of Prismatic SS with QD and PCM.....	127
7.5	Future Scope.....	129
	<b>References .....</b>	<b>130</b>
	<b>Appendix-A Nomenclature.....</b>	<b>145</b>
	<b>Appendix-B Numerical Data.....</b>	<b>149</b>
	<b>B.1 Numerical data related to Tilt angle .....</b>	<b>149</b>
	<b>B.2 Numerical data related to concentration of QD.....</b>	<b>154</b>
	<b>B.3 Numerical data related to modified Solar still .....</b>	<b>159</b>
	<b>B.4 Monthly Solar radiation and Wind velocity Data .....</b>	<b>164</b>
	<b>B.5 Monthly Ambient temperature (°C) .....</b>	<b>165</b>
	<b>Appendix-C MATLAB program .....</b>	<b>166</b>
	<b>MATLAB Program.....</b>	<b>166</b>
	<b>Publications.....</b>	<b>172</b>

## List of Figures

<i>Figure 1. 1 Composition of salts in saline water</i> .....	3
<i>Figure 1. 2 Osmosis and Reverse Osmosis Process [9]</i> .....	5
<i>Figure 1. 3 Schematic diagram of Multi-Stage Flash distillation [10]</i> .....	6
<i>Figure 1. 4 Schematic diagram of Multi-effect distillation [10]</i> .....	7
<i>Figure 1. 5 Annual average global solar insolation on India [11]</i> .....	8
<i>Figure 1. 6 Proportion of solar spectrum wavelength in IR, Visible, and UV range</i> .....	9
<i>Figure 1. 7 Various modes of heat transfer and physical variables in solar still</i> .....	11
<i>Figure 1. 8 Classification of PCM [12]</i> .....	12
<i>Figure 1. 9 Lauric acid as a PCM to store the heat during daylight and releases during night period</i> .....	13
<i>Figure 1. 10 Classification of nano-materials with their characteristics [14–16]</i> .....	15
<i>Figure 1. 11 Illustration of quantum confinement effect in QD's</i> .....	16
<i>Figure 2. 1 Solar desalination techniques</i> .....	19
<i>Figure 3. 1 Three experimental models of conventional roof top solar stills with different tilt angle of glass cover in winter season</i> .....	43
<i>Figure 3. 2 Instruments (1). Temperature indicator (2). Measuring flash with container</i> .....	44
<i>Figure 3. 3 Weather measuring instruments (1). Solarimeter (2). Digital thermometer</i> .....	44
<i>Figure 3. 4 Solar still (a). without QD's (b). with QD's coated on absorber surface</i> .....	46
<i>Figure 3. 5 Preparation of coating material a). weighted BPQD b). QD with black dye c). Mixing by Magnetic stirrer</i> .....	47
<i>Figure 3. 6 Schematic diagram of (A) SSSS and (B) Prism-shaped SS with dimensions</i> .....	49
<i>Figure 3. 7 BPQD-black paint mixture coated on solar still</i> .....	50
<i>Figure 3. 8 SEM images of Quantum dot material at 20 K and 50 K resolution</i> .....	51
<i>Figure 3. 9 Sample of Lauric acid used in the experiment with heat transfer in sunshine and off sunshine period</i> .....	52
<i>Figure 3. 10 DSC result of Lauric acid with melting point (onset) and latent heat (area) [16]</i> .....	52
<i>Figure 4. 1 Thermal network diagram of Solar still with QD</i> .....	57
<i>Figure 4. 2 Mathematical algorithm to find the yield and HTC's of modified solar stills</i> .....	67
<i>Figure 6. 1 Hourly variation of solar insolation and Ambient temperature with three models on Day-1</i> ....	81
<i>Figure 6. 2 Hourly variation of solar insolation and Ambient temperature with three models on Day-2</i> ...	82
<i>Figure 6. 3 Hourly variation of solar insolation and Ambient temperature with three models on Day-3</i> ..	82

Figure 6. 4 Hourly variation of basin water and inner glass surface temperature on Day-1 .....	84
Figure 6. 5 Hourly variation of productivity during daylight time on Day-1 .....	84
Figure 6. 6 Hourly variation of basin water and inner glass surface temperature on Day-2 .....	85
Figure 6. 7 Hourly variation of productivity during daylight time on Day-2 .....	86
Figure 6. 8 Hourly variation of basin water and inner glass surface temperature on Day-3 .....	87
Figure 6. 9 Hourly variation of productivity during daylight time on Day-3 .....	87
Figure 6. 10 Comparative analysis of day time cumulative yields of models on three days in winter. ....	88
Figure 6. 11 Hourly variation of wind velocity .....	89
Figure 6. 12 Effect of wind velocity on the outer surface glass temperature of condenser cover .....	89
Figure 6. 13 Nocturnal productivity of solar stills .....	90
Figure 6. 14 Efficiency variation of models on three different days .....	92
Figure 6. 15 Exergy efficiency of all three model .....	94
Figure 6. 16 Solar radiation and ambient temperature variation. ....	96
Figure 6. 17 Hourly variation of basin water and inner glass cover temperature with different concentration of pyrex glass .....	97
Figure 6. 18 Experimental and Theoretical variation of basin water .....	98
Figure 6. 19 Variation of average basin water temperature in experimental and theoretical condition ...	98
Figure 6. 20 Hourly variation of distilled water yield in different QD concentration .....	100
Figure 6. 21 Cumulative yield from solar stills at different concentration of Pyrex glass in 500 mL of black dye.....	101
Figure 6. 22 Comparison of Thermal efficiency and Exergy efficiency on different concentration of Pyrex glass in black dye .....	104
Figure 6. 23 Temperature variation of inner glass condenser surface and basin water with time .....	106
Figure 6. 24 Variation of change in temperature difference ( $\Delta T$ ) between inner glass condenser surface and basin water with time .....	107
Figure 6. 25 Variation of hourly yield, total cumulative yield, and solar radiation intensity with time ....	108
Figure 6. 26 Temperature variation of inner glass condenser surface and basin water with time .....	109
Figure 6. 27 Variation of change in temperature difference ( $\Delta T$ ) between inner glass condenser surface and basin water with time .....	110
Figure 6. 28 Hourly temperature variation of basin water and PCM in PSS .....	111
Figure 6. 29 Hourly temperature variation of basin water and PCM in CSS.....	111
Figure 6. 30 Variation of hourly yield, total cumulative yield, and solar radiation intensity with time ....	112
Figure 6. 31 Temperature variation of inner glass condenser surface and basin water with time .....	113
Figure 6. 32 Variation of change in temperature difference ( $\Delta T$ ) between inner glass condenser surface and basin water with time .....	114
Figure 6. 33 Hourly temperature variation of basin water and PCM in PSS .....	115
Figure 6. 34 Hourly temperature variation of basin water and PCM in CSS .....	115

*Figure 6. 35 Variation of hourly yield, total cumulative yield, and solar radiation intensity with time .... 116*

*Figure 6. 36 Comparison of cumulative yield of all three set of arrangement of CSS and PSS..... 118*

*Figure 6. 37 Exergy comparison of solar stills ..... 120*

## List of Tables

<i>Table 1. 1 Thermophysical properties of Lauric acid</i> .....	13
<i>Table 1. 2 Properties of black phosphorus quantum dot material</i> .....	16
<i>Table 2. 1 Required properties for thermal energy storage materials [54,55]</i> .....	26
<i>Table 2. 2 Comprising the sensible heat storage materials and its properties [56–58]</i> .....	27
<i>Table 2. 3 Synopsis of investigations performed on solar still with TES</i> .....	32
<i>Table 2. 4 Cost of distilled water in previous studies</i> .....	37
<i>Table 3.1 Summary of design parameter of three models</i> .....	41
<i>Table 3.2 Design value of different parameters of CSS and PSS</i> .....	48
<i>Table 3.3 List of thermophysical properties of Lauric acid</i> .....	53
<i>Table 5. 1 Cost breakup for CSS and PSS coated with QD material and PCM</i> .....	69
<i>Table 5. 2 Summary of economic analysis of CSS and PSS</i> .....	75
<i>Table 5. 3 Summary of economic analysis of QD coated SS</i> .....	77
<i>Table 6. 1 The productivity and efficiency of models on different days</i> .....	91
<i>Table 6. 2 Summary of yield and efficiency of CSS and PSS</i> .....	118
<i>Table 6. 3 Water quality test results</i> .....	120
<i>Table 6. 4 Standard uncertainty of the measurements</i> .....	122
<i>Table B- 1 On day-1 (Oct. 28, 2019) for Model-1</i> .....	149
<i>Table B- 2 On day-1 for Model-2</i> .....	149
<i>Table B- 3 On day-1 for Model-3</i> .....	150
<i>Table B- 4 On day-2 (Oct. 29, 2019) for Model-1</i> .....	151
<i>Table B- 5 On day-2 for Model-2</i> .....	151
<i>Table B- 6 On day-2 for Model-3</i> .....	152
<i>Table B- 7 On day-3 (Nov. 29, 2019) for Model-1</i> .....	152
<i>Table B- 8 On day-3 for Model-2</i> .....	153
<i>Table B- 9 On day-3 for Model-3</i> .....	154
<i>Table B- 10 Experimental data with 0 g QD</i> .....	154
<i>Table B- 11 Theoretical data with 0 g QD</i> .....	155
<i>Table B- 12 Experimental data with 5 g QD</i> .....	156

<i>Table B- 13 Theoretical data with 5 g QD .....</i>	<i>156</i>
<i>Table B- 14 Experimental data with 10 g QD .....</i>	<i>157</i>
<i>Table B- 15 Theoretical data with 10 g QD .....</i>	<i>157</i>
<i>Table B- 16 Experimental data with 15 g QD .....</i>	<i>158</i>
<i>Table B- 17 Theoretical data with 10 g QD .....</i>	<i>158</i>
<i>Table B- 18 Experimental data for CSS without PCM and QD .....</i>	<i>159</i>
<i>Table B- 19 Experimental data for PSS without PCM and QD .....</i>	<i>160</i>
<i>Table B- 20 Experimental data for CSS with PCM only.....</i>	<i>161</i>
<i>Table B- 21 Experimental data for PSS with PCM only.....</i>	<i>161</i>
<i>Table B- 22 Experimental data for CSS with PCM and QD .....</i>	<i>162</i>
<i>Table B- 23 Experimental data for PSS with PCM and QD .....</i>	<i>163</i>
<i>Table B- 24 Global solar radiation and wind velocity data throughout year .....</i>	<i>164</i>
<i>Table B- 25 Ambient temperature variation from 8 o'clock to 17 o'clock throughout year .....</i>	<i>165</i>

## Abstract

Fresh water is an essential gradient of life however, a rapid increase in population and shrinking freshwater bodies make it a commodity for a large world population, specifically in remote locations and minimal rain areas, people are poorly thrashed by water scarcity. In this work, an attempt is made to resolve this issue sustainably by using solar energy. Solar desalination is a technique that uses solar energy to convert saline water into distilled water, and solar still (SS) is a device that is used for this purpose. This device works on evaporation and condensation phenomenon. The low yield and low efficiency of SS make it a low-esteem device. To take as a challenge, an experimental setup of novel SS is designed, fabricated, and compared with conventional SS performance. Also, the effect of quantum dot (QD) material with phase change material (PCM) is analyzed with solar still. In the first phase, a parametric study is done on the effect of the tilt angle of the condenser surface on SS performance during daylight and nocturnal period in the winter season. Three models are fabricated, namely Model-1, a single slope SS with a tilt angle of  $25^\circ$  facing south, Model-2 a single slope SS with a tilt angle of  $30^\circ$  facing south, and Model-3, a double slope SS with a tilt angle of  $15^\circ$  from both sides facing east-west. After several experimental investigations, the results showed that Model-1 and 2 give a maximum yield of 760 and 925 mL/m<sup>2</sup>. In contrast, Model-3 gives a maximum yield of 320 mL/m<sup>2</sup> with maximum thermal and exergy efficiency of 17.15% and 0.6%, 17.25%, and 1.1%, and 7% and 0.3% respectively, over seven hours working period in the winter season. This investigation also reveals the heat retaining capacity of SS and the effect of polystyrene coverage on glass cover that helps to obtain a maximum nocturnal yield of 435, 735, 320 mL/m<sup>2</sup>, from Model-1, 2, and 3, respectively,

on different days that make total distilled output to 1195, 1660, 560 mL/m<sup>2</sup> on a particular day. In the second phase, a novel black phosphorus QD-doped Pyrex glass material is coated on the basin liner to improve the solar absorbance range. Four different concentrations of QD material are developed as 0g, 5g, 10g, and 15g by weight in the black paint of 500 mL and coated on the absorber surface of the basin. The experimental results showed a maximum yield of 991, 1282, 2010, and 2710 mL/m<sup>2</sup> with energy and exergy efficiencies of 15.21% and 0.50%, 19.68% and 0.84%, 30.57% and 1.41%, 41.22% and 2.75% for SS with 0g, 5g, 10g, and 15g QD material respectively. Theoretical modeling is also performed and validated by experimental results with a maximum deviation of 7.6%.

Moreover, the economic study gives a payback period of 1 year and 11 months with 15g QD-coated SS. In the third phase, black phosphorus QD is used with lauric acid. Prismatic solar still (PSS, modified design) performance is compared with conventional solar still (CSS). The results showed that CSS and PSS without PCM and BPQD yield up to 1660 mL/m<sup>2</sup> and 1830 mL/m<sup>2</sup> with heating efficiency and exergy efficiency of 19.72% and 0.36% for CSS and 25.59%, and 1.08% for PSS. Whereas, with PCM and BPQD, yields reached up to 3040 mL/m<sup>2</sup> and 3400 mL/m<sup>2</sup> with exergy and heating of 1.79% and 37.23% for CSS and 2.20%, and 49.30% for PSS. Moreover, the economic analysis showed that the monetary and energy cost of distilled water with PSS incurs only INR 1.6/liter and INR 2.48/kWh as compared to CSS of INR 2.71/liter and INR 4.10/kWh with a payback period of 3 years and 3 months for CSS and 2 years and 10 months for PSS.