
LIST OF TABLES

Table 2.1	Electrooxidation of methanol or ethanol at anode in alkaline condition and techniques used for analysis of the system.	17
Table 2.2	Oxygen reduction at cathode in alkaline condition and techniques used for analysis of the system.	25
Table 2.3	Single cell study using PVA based alkaline membrane without crosslinking/pristine.	42
Table 2.4	Single cell study using physically crosslinked PVA based alkaline membrane	43
Table 2.5	Single cell study using chemically crosslinked PVA based alkaline membrane	46
Table 3.1	Typical properties of Toray carbon paper (TGP-H-60, Alfa Aesar, USA)	52
Table 3.2	Properties and composition of Nafion [®] solution (Grade: D-520, Alfa Aesar, USA)	53
Table 3.3	Properties of PTFE dispersion (Sigma Aldrich, USA)	53
Table 3.4	Properties of polyvinyl alcohol (Loba chemie, India)	54
Table 3.5	Typical properties of the fuels at 1.01 bar and 298 K	54
Table 4.1	Water uptake (W_U), and KOH uptake (Q_U) of pristine and physically crosslinked PVA membrane	69
Table 4.2	Ionic conductivity of pristine and physically crosslinked PVA membrane impregnated at different concentration of KOH solution	73

Table 4.3	Variation of operating cell potential with time at a constant load.	123
Table 4.4	KOH uptake (Q_U) and water uptake (W_U) of pristine and chemically crosslinked PVA membrane with different glutaraldehyde concentration as a function of KOH concentration at a temperature of 30 °C.	125
Table 4.5	Ionic conductivity of chemically crosslinked PVA membrane with different glutaraldehyde concentration as a function of KOH concentration at a temperature of 30 °C	131
Table 4.6	Variation of operating cell potential (OCP) with time at a constant load.	168
Table 4.7	Performance comparison of physical and chemical crosslinked PVA membrane at a temperature of 30 °C using optimum conditions	169
Table 4.8	Individual efficiencies for different fuels used in direct alcohol fuel cell for physical crosslinked PVA membrane at a temperature of 30 °C.	172
Table 4.9	Individual efficiencies for different fuels used in direct alcohol fuel cell for chemical crosslinked PVA membrane at a temperature of 30 °C.	172