

## *Table of Contents*

<b>Contents</b>	<b>Page No.</b>
Certificates	ii-iv
Acknowledgment	v-vi
Table of Contents	ix-xiii
List of Figures	xv-xix
List of Tables	xxi-xxii
List of Symbols	xxiii-xxviii
Abstract	xxix-xxxiv
<b>1 Introduction</b>	<b>1</b>
Background and Motivation	1
1.1 Advantages of Waste Heat Recovery Systems	3
1.2 Thermoelectric generator as a Waste Heat recovery method	5
1.3 Applications of TEG	7
1.4 Objectives	7
1.5 Contribution of the study	9
1.6 Thesis structure and methodology	9
<b>2 Literature review</b>	<b>13</b>
2.1 TEG hot side performance enhancement	14
2.2 TEG device performance improvement	20
2.2.1 TEG materials	21
2.2.2 TEG multi-staging	25
2.2.3 TEG leg geometry	27
2.3 TEG Cold side heat transfer enhancement	32

2.3.1 Shape-based performance of nanofluids and hybrid nanofluids	32
2.3.2 Mini channel heat sinks for nanofluids and hybrid nanofluids	35
2.4 Optimization methodology	38
2.5 Solar-assisted TEG hybrid WHR systems	39
2.6 Highlights	40
2.7 Research gaps and scope	41
<b>3 TEG Hot Side Performance Enhancement using Vortex Generators</b>	<b>43</b>
3.1 Setup description	43
3.1.1 Arrangement of VGs	46
3.1.2 Mathematical Modeling	48
3.2 Results and Discussion	52
3.2.1 Effect of vortex generators on the heat transfer coefficients	52
3.2.2 Effect of vortex generators on the pressure drops	55
3.2.3 Effect of vortex generators on thermal enhancement factors	57
3.2.4 Effect of vortex generators on TEG power output	60
3.3 Highlights	62
<b>4 Dissimilar Material-based Multistage Thermoelectric Generator with Varying Leg Geometry</b>	<b>65</b>
4.1 Mathematical Modeling of MVS-TEG	65
4.2 Results and Discussion	73
4.2.1 Variation in TEG performance with number of rows	73

4.2.2 Variation in TEG performance with exhaust inlet temperature	80
4.2.3 Variation in TEG performance with the coolant flow rate	86
4.3 Highlights	91
<b>5 Thermohydraulic and TEG performance analysis with dissimilar shape-based hybrid nanofluids</b>	93
5.1 Mathematical modeling	93
5.1.1 Design of Mini channel Heat Sink	93
5.1.2 Boundary Conditions	95
5.1.3 Fluid flow correlations	96
5.1.4 Heat transfer correlations	97
5.1.5 Nanoparticles and Nanofluid	98
5.1.6 Performance parameters	101
5.1.7 TEG performance	102
5.2 Validation	102
5.3 Results and Discussion	104
5.3.1 Heat transfer coefficient	104
5.3.2 Nusselt number	106
5.3.3 Inlet and Outlet Exergy	108
5.3.4 Effect on the Performance parameters	111
5.3.5 Effect on TEG performance	113
5.4 Highlights	116
<b>6 Taguchi optimization and ANN modeling for Uni-array Vortex Generators</b>	119
6.1 Geometry, Governing equation, and Boundary conditions	119

6.2 Grid Independence Test and Data Validation	123
6.3 Taguchi's Analysis-Design of Experiments	126
6.4 Artificial Neural Network	128
6.5 Results and Discussion	129
6.5.1 Numerical Analysis	129
6.5.2 Heat transfer capability	132
6.5.3 Impact on pressure drop	135
6.5.4 Thermal Enhancement Factor	137
6.5.5 S/N ratio analysis	139
6.5.6 ANN model	142
6.6 Highlights	143
<b>7 Solar Water Heater and TEG-based Hybrid System with Fishtail</b>	<b>145</b>
<b>Vortex Generators</b>	
7.1 System description	145
7.1.1 Evacuated U-tube solar water heater	146
7.1.2 Thermoelectric Generator	149
7.1.3 Water flow channels	152
7.1.4 Hybrid system	154
7.1.5 Validation and Grid Independence Test	154
7.2 Results and Discussion	157
7.2.1 EUSWH performance	157
7.2.2 TEG performance	163
7.2.3 Hybrid system performance	168
7.3 Highlights	169
<b>8 Concluding Remarks and Future Scope</b>	<b>171</b>

8.1 Concluding remarks	171
8.2 Future scope	175
8.2.1 Recommendations for improving the present work	177
8.2.2 Recommendations for application and implementation	177
<b>References</b>	179
<b>List of Publications</b>	191

---