

Contents

	Page No.
List of Figures	xix-xxii
List of Tables	xxiii
List of Abbreviations	xxv-xxvi
Preface	xxvii-xxix
Chapter 1	
Introduction and Literature Review	1-33
1.1 Introduction	2
1.2 Overview of Reconfigurable Antenna	3
1.2.1 Classification of Reconfigurable Antennas	4
1.2.1.1 Frequency Reconfigurable Antennas	4
1.2.1.2 Pattern Reconfigurable Antennas	5
1.2.1.3 Polarization Reconfigurable Antennas	6
1.2.1.4 Hybrid Reconfigurable Antennas	6
1.2.2 Advantages and Disadvantages of Reconfigurable Antennas	6
1.2.3 Design Techniques of Reconfigurable Antennas	7
1.2.3.1 Electrically Reconfigurable Antennas	8
1.2.3.2 Optically Reconfigurable Antennas	9
1.2.3.3 Physical/Mechanical Reconfigurable Antennas	10
1.2.3.4 Reconfigurable Antennas Based on Smart Materials	10
1.2.3.5 Comparison Between Different Technique	11
1.3 State-of-the-art Review on Reconfigurable Antennas	16
1.3.1 Pattern Reconfigurable Antennas	17
1.3.2 Polarization Reconfigurable Antennas	20
1.3.3 Antenna with Hybrid Reconfigurability	26
1.4 Objective and Scope of the Thesis	29

1.5	Thesis Structure	31
-----	------------------	----

Chapter 2

Electronically Reconfigurable Antenna with Switchable Beams		35-50
2.1	Introduction	36
2.2	Design of Beam Steerable Antenna Array	38
2.2.1	Two-Element Antenna Array Design	38
2.2.2	Reconfigurable Antenna Array Design	40
2.2.3	PIN Diode Equivalent Circuit Model	41
2.2.4	Switching Mechanism	43
2.2.5	DC Biasing Circuit	43
2.3	Results and Discussion	45
2.4	Comparison and Review	48
2.5	Summary	49

Chapter 3

Beam Steerable and Circular Polarization Reconfigurable Antenna		51-74
3.1	Introduction	52
3.2	Antenna Geometry and Reconfigurable Mechanism	54
3.2.1	Antenna Configuration	54
3.2.2	Beam Switching Analysis and Feed Network	57
3.2.3	Polarization Reconfigurability Analysis	57
3.2.4	Working Principle	61
3.2.5	Specification of PIN Diodes and its Biasing Circuit	61
3.2.6	Parametric Analysis	63
3.3	Results and Discussion	66
3.4	Comparison and Review	72
3.5	Summary	73

Chapter 4

Stacked Array Antenna with 2-D Beam Switching and Quad-Polarization Reconfigurability	75-97
4.1 Introduction	76
4.2 Reconfigurable Array Design and Working Mechanism	78
4.2.1 Design of a Quad-Polarized Antenna Element	78
4.2.2 Design of 2x2 Pattern and Polarization Reconfigurable Array	84
4.2.3 Pattern Reconfiguration Implementation and Operating Principle	86
4.3 Results and Discussion	89
4.4 Comparison and Review	96
4.5 Summary	96

Chapter 5

Conclusion and Future Scope	99-104
5.1 Summary and Conclusion	100
5.2 Future Scope	103
References	105-115
List of Publications	117

List of Figures

Fig. 1.1:	Classification of reconfigurable antenna	5
Fig. 1.2:	Various design techniques to realize reconfigurable antenna	8
Fig. 1.3:	Comparison between different design techniques	12
Fig. 1.4:	A cognitive radio cycle	14
Fig. 1.5:	Application scenario of polarization reconfigurable antenna. (a) reconfigurable CP antenna for satellite application [35], (b) polarization reconfigurable antenna for body-centric wireless communication system [36]	15
Fig. 1.6:	Overview of present thesis work	33
Fig. 2.1:	The design process of the two-element antenna array. (a) Ant-A, (b) Ant-B, (c) Ant C, and (d) Reflection coefficient of Ant-A, Ant-B, and Ant-C	39
Fig. 2.2:	The geometry of two elements reconfigurable antenna array	40
Fig. 2.3:	Reconfigurable feeding network with DC biasing circuit	41
Fig. 2.4:	(a) The equivalent circuit of RF Switches consists of DC blocking capacitors and RF chokes, (b) ON state of PIN diode, and (c) OFF state of PIN diode	42
Fig. 2.5:	Fabricated view of the proposed antenna along with the switching circuit	45
Fig. 2.6:	Simulated and measured reflection coefficient for all states	46

Fig. 2.7:	Simulated and measured radiation patterns in the XZ plane for states. (a) S_1 , (b) S_2 , S_4 and (c) S_3 , S_5	47
Fig. 2.8:	Simulated and measured gain for all states	48
Fig. 3.1:	Proposed CP-agile and beam switchable array antenna structure. (a) Side view (b) Driven Patch Layer (c) Feed Network layer.	55
Fig. 3.2:	Proposed reconfigurable array antenna design evolution	58
Fig. 3.3:	Simulated results of antenna in different cases (Ant_1- Ant_5). (a) reflection coefficient (b) axial ratio	59
Fig. 3.4:	Simulated 5.2 GHz surface current distributions of the CP-agile array antenna. (a) for state 1 (LHCP) (b) for state 2 (RHCP) at four different time phases	60
Fig. 3.5	Simulated S_{11} and axial ratio characteristics of the antenna with different values of slot length (L_s). (a) S_{11} and (b) Axial Ratio.	63
Fig. 3.6:	Simulated S_{11} and axial ratio characteristics of the antenna with different values of slot width (W_s). (a) S_{11} and (b) Axial Ratio.	64
Fig. 3.7:	Simulated S_{11} and axial ratio characteristics of the antenna with different values of slot distance (S). (a) S_{11} and (b) Axial Ratio.	65
Fig. 3.8:	Prototype of the fabricated CP agile and beam switchable array antenna. (a) feeding network layer and patch layer (b) assembled array antenna with external switching circuit.	66
Fig. 3.9:	The proposed array antenna measured and simulated S-parameter in (a) LHCP mode (b) RHCP mode.	67
Fig. 3.10:	The proposed array antenna measured and simulated axial ratios in (a) LHCP mode (b) RHCP mode.	69

Fig. 3.11:	The proposed array antenna measured and simulated peak gain in (a) LHCP mode (b) RHCP mode.	70
Fig. 3.12:	The proposed array antenna measured and simulated normalized radiation pattern at the XZ cut plane (a) LHCP, RHCP (b) LHCP (c) RHCP (d) LHCP (e) RHCP	71
Fig. 4.1:	Structure of the proposed reconfigurable array element. (a) side view. (b) driven patch layer. (c) feed network layer	79
Fig. 4.2:	Design steps of the proposed reconfigurable element (a) single probe fed patch radiator, (b) parasitic patch loaded element, (c) 2-bit polarization reconfigurable element	80
Fig. 4.3:	Simulated results of the proposed antenna element with parasitic patch (Case 2) or without parasitic patch (Case 1) (a) surface current distribution, (b) reflection coefficient and (c) radiation directivity	81
Fig. 4.4:	Simulated results of the array element with different exciting probes and corresponding polarization states. (a) reflection coefficient. (b) axial ratio	82
Fig. 4.5:	Simulated vector surface current distribution of the array element in four different polarization states. (a) VP. (b) LP. (c) LHCP. (d) RHCP	83
Fig. 4.6:	Schematic of the proposed polarization and 2-D beam steering antenna array (a) isometric view (b) parasitic patch layer (c) driven patch layer	85
Fig. 4.7	(a) Designed feed network of the proposed polarization and 2-D beam switchable antenna array (b) zoomed-in view of the 2-bit phase shifter	86
Fig. 4.8:	Fabricated prototype of the proposed antenna (a) Feed Layer (b) Parasitic layer (c) Driven patch layer (d) Assembled antenna.	89

Fig. 4.9:	Simulated and measured S- parameter in VP state. (a) XZ Plane and (b) YZ Plane.	90
Fig. 4.10:	Simulated and measured S- parameter in RHCP state. (a) XZ Plane and (b) YZ Plane	91
Fig. 4.11:	Measured and simulated axial ratios in RHCP. (a) XZ plane and (b) YZ plane	92
Fig. 4.12:	Measured and simulated gain in (a) VP mode and (b) RHCP mode	93
Fig. 4.13:	Measured and simulated normalized radiation pattern VP mode. (a), (b) XZ Plane and (c) YZ Plane	94
Fig. 4.14:	The proposed array antenna measured and simulated normalized radiation pattern RHCP mode. (a), (b), (c) XZ Plane and (d), (e) YZ Plane	95

List of Tables

Table 2.1:	PIN Diode Biasing Conditions for Different States	42
Table 2.2:	PIN diode biasing conditions for different states	44
Table 2.3:	DC node voltages for all states	44
Table 2.4:	Comparison of the proposed beam steering antenna with the similar antenna	49
Table 3.1:	Optimized geometrical parameters of the array antenna	56
Table 3.2:	Biasing conditions of PIN diodes in different radiation modes	56
Table 3.3:	Connection of dc biasing pads for different pattern and polarization states	62
Table 3.4:	Comparison of the proposed array antenna characteristics with previously reported work	73
Table 4.1:	Optimized dimensions of the antenna element	80
Table 4.2:	PIN diode biasing conditions and coding scheme for different polarization states	84
Table 4.3:	PIN diode biasing conditions and their coding for different feeding paths	88
Table 4.4:	Coding schemes in different polarization and phase controlling modes of array antenna	88
Table 4.5:	Comparison of the proposed beam steering antenna with the similar antenna	97