CERTIFICATE

It is certified that the work contained in the thesis titled ***"RIVER AQUIFER EXCHANGE STUDY OF A STRETCH OF THE RIVER GANGA"*** by ***Mr. PADAM JEE OMAR*** has been carried out under my supervision and that this work has not been submitted elsewhere for a degree.

It is further certified that the student has fulfilled all the requirements of Comprehensive Examination, Candidacy and SOTA for the award of Ph.D. Degree.

Signature of Supervisors:

Prof. Prabhat Kumar Singh Dikshit
Department of Civil Engineering
Indian Institute of Technology (BHU)
Varanasi

Prof. Shyam Bihari Dwivedi
Department of Civil Engineering
Indian Institute of Technology (BHU)
Varanasi

DECLARATION BY THE CANDIDATE

I, ***PADAM JEE OMAR***, certify that the work embodied in this thesis is my own bonafide work and carried out by me under the supervision of ***Prof. Prabhat Kumar Singh Dikshit*** and ***Prof. Shyam Bihari Dwivedi*** from ***July 2015*** to ***May 2021*** at the ***Department of Civil Engineering***, ***Indian Institute of Technology (BHU) Varanasi***. The matter embodied in this thesis has not been submitted for the award of any other degree/diploma. I declare that I have faithfully acknowledged and given credits to the research workers wherever their works have been cited in my work in this thesis. I further declare that I have not willfully lifted up any other's work, paragraphs, text, data, results, *etc*., reported in journals, books, magazines, reports dissertations, thesis, *etc*., or available at websites and included them in this thesis and cited as my own work.

Date: Signature of the Student

Place: Varanasi (PADAM JEE OMAR)

CERTIFICATE BY THE SUPERVISOR(S)

It is certified that the above statement made by the student is correct to the best of our knowledge.

Prof. Prabhat Kumar Singh Dikshit
Department of Civil Engineering
Indian Institute of Technology (BHU)
Varanasi

Prof. Shyam Bihari Dwivedi
Department of Civil Engineering
Indian Institute of Technology (BHU)
Varanasi

Signature of Head of the Department

COPYRIGHT TRANSFER CERTIFICATE

Title of the Thesis: River Aquifer Exchange Study of a Stretch of the River Ganga

Name of the Student: Padam Jee Omar

Copyright Transfer

The undersigned hereby assigns to the Indian Institute of Technology (Banaras Hindu University) Varanasi all rights under copyright that may exist in and for the above thesis submitted for the award of the *DOCTOR OF PHILOSOPHY*.

Date: Signature of the Student

Place: Varanasi (PADAM JEE OMAR)

Note: However, the author may reproduce or authorize others to reproduce material extracted verbatim from the thesis or derivative of the thesis for author's personal use provided that the source and the Institute's copyright notice are indicated.

To my Parents,

Brother,

who taught me how to live & dream

Acknowledgement

"*If I have seen further, it is by standing upon the shoulders of giants.*"

Sir Isaac Newton

The time I have devoted to my Ph.D. has been the most intriguing time of my life. I have learned a lot in these years, both professionally and personally. I wish to thank all the people whose assistance was a milestone for accomplishing this thesis. Without any of them, my anticipated completion of Ph.D. requirements in Civil Engineering would have probably been very implausible, if not impossible.

First and foremost, I would like to express my sincere gratitude to my supervisors, Prof. Prabhat Kumar Singh Dikshit and Prof. Shyam Bihari Dwivedi, for their endless support, guidance, and encouragement throughout my Ph.D. They have been a very kind, approachable, and patient supervisors. Their attitude, motivation, and knowledge have had a profound impact on me. They are truly an inspiration for their advice, patience, and faith. Prof. P. K. S. Dikshit and Prof. S. B. Dwivedi also offered me immense freedom in research. I cannot express my all thanks to them, but I indeed will make them very proud.

My special thanks must go to Dr. Shishir Gaur, who always had his time (at any hours) to give advice and inspiration. His guidance style is genuinely refreshing and energizing. The extent of time, effort, and personal sacrifice he puts into research will be a model for me for years to come. I am also grateful to Prof. Rajendra Prasad, Dr. Anurag Ohri for their guidance, feedback, and suggestions to drive this thesis well. I am very privileged to have met exceptional pedagogues at each important stage of my research career. I have a deep sense of gratitude for all Teachers of the Department of Civil Engineering, Indian Institute of Technology, Banaras Hindu University, Varanasi for their cooperation and inspiration. I am thankful to the non-teaching staff of the Department of Civil Engineering, Indian Institute of Technology, Banaras Hindu University, Varanasi. I would like to express my deepest

gratitude to all those people who have contributed directly or indirectly in the course of my research work.

I express my heartfelt gratitude to Mr. Anupam Prasad Sir, Superintending Engineer, Central Water Commission, Varanasi for giving his support in the data collection. I also acknowledge Central Ground Water Board, Indian Meteorological Department, UP Jal Nigam for providing the necessary data. I would like to convey my sincere thanks to Rahul Soni and Vinayak Mishra for their precious time, support, and assistance in the field data collection.

The acknowledgements will not be complete till I express gratitude to my colleagues especially Ravi Prakash Tripathi, Nitesh Gupta, Surender, Nikita Shivhare, Shiwanshu Shekhar, Ashwani Kumar Agnihotri, Amiya Abhash, Atul Kumar Rahul at IIT (BHU) Varanasi for the endless support and motivation for the research. I especially thank Dr. Subash Prasad Rai (Director, Floodkon), for his support and giving me the strength in my difficult times.

I am also thankful to MHRD for providing financial assistance during my research work.

I would like to thank my younger brother, Ganesh Ji Omar, who taught me how to *be strong, live, and dream* in the toughest times and always endorsed my determination. I owe everything I am and everything I will ever be to him. I wish to thank my Parents…next to God, for their great love, support, and unceasing encouragement. My wife, Sonali Omar deserves my wholehearted thanks as well. She pushed me forward, and this work would not have been possible without her support.

Finally, I would like to thank God Almighty for giving me strength and blessing that had guided me in the right direction.

Padam Jee Omar

List of Figures

Figure 1.1 Schematic of the distribution of Earth's Water 1

Figure 2.1 Effect of pumping schedule on the groundwater level 20

Figure 2.2 Schematic sketch showing the groundwater and surface water interaction 22

Figure 2.3 Process of the groundwater and surface water interactions 23

Figure 3.1 Location map of the Study Area 29

Figure 3.2 Administrative division and Major River network in the study area 30

Figure 3.3 Elevation Model of two tiles used in the study area. 35

Figure 3.4 Digital Elevation Model of the Study area 36

Figure 3.5 Fence diagram showing the lateral extent of the study area 41

Figure 3.6 Two Cross-sections AA' and BB' marked on the study area 41

Figure 3.7 Lateral disposition of the cross sections AA' and BB' with their legend 42

Figure 4.1 Flowchart of methodology for preparation of the Groundwater flow model 49

Figure 4.2 Numerical and Analytical solutions for one dimensional groundwater flow. 59

Figure 4.3 Scales of the groundwater system 60

Figure 5.1 Adopted methodology for Groundwater flow Model using GMS 66

Figure 5.2 Computational Mesh with the River boundary conditions 68

Figure 5.3 Groundwater model with five layers 68

Figure 5.4 Values of River Head stage (m) in transient condition 69

Figure 5.5 Values of River Bottom Elevation (m) in transient condition 70

Figure 5.6 Recharge rate value (m/d) in transient condition 70

Figure 5.7 Model discretization with five layers of the model 71

Figure 5.8 Borehole data entry into the Borehole editor of GMS 72

Figure 5.9 Network of borehole data in the study area. 73

Figure 5.10 Borehole data representation in the GMS 73

Figure 5.11 Interpolation of Solid data into the Model 74

Figure 5.12 Model Boundary conditions in the study area 75

Figure 5.13 Elevation values for the top surface of model 77

Figure 5.14 Elevation values for the bottom surface of the model 78

Figure 5.15 Location of observation wells in the study area. 88

Figure 5.16 Comparison of computed and observed head for fourteen observation wells..... 94

Figure 5.17 Relationship between the SEE and Recharge Rate 95

Figure 5.18 Soil Moisture Index Map of the study area. 98

Figure 5.19 Observed head Vs Computed head (in m)..... 101

Figure 6.1 Groundwater flow lines along with colour bar, and calibration target..... 103

Figure 6.2 Time series graph for three observation wells (a) Varanasi (b) Barwaon (c) Aurai 104

Figure 6.3 Calibration targets with the observed head values 105

Figure 6.4 Scatter plot between computed head and observed head 106

Figure 6.5 Observed head vs modelled head 107

Figure 6.6 Observed head Vs Residual (in m)..... 108

Figure 6.7 Soil Moisture Index map of the study area showing two cross-sections AB and CD 109

Figure 6.8 Soil Moisture profile at two cross-sections a) A-B, and b) C-D 109

Figure 6.9 Groundwater flow direction map..... 114

List of Tables

Table 1.1 Statistics regarding water resources in India 6

Table 2.1 Status of Hydrological modeling systems 11

Table 3.1 Annual Rainfall Variation in the study area 31

Table 3.2 Characteristics of the two tiles used in the study area. 35

Table 3.3 Stratigraphic Sequence in the Study Area 37

Table 3.4 Aquifer characteristics and their lateral extent for 4 borehole locations. 40

Table 3.5 Hydraulic Conductivity value (m/day) at 25 different locations of study area 42

Table 3.6 Name of sites for collecting the Meteorological data. 45

Table 5.1 Details of LULC of the study area.....79

Table 5.2 Agricultural Groundwater demands in the study area 81

Table 5.3 Total Population and Groundwater demand in the study area.....82

Table 5.4 Livestock Population in the study area 83

Table 5.5 Livestock Groundwater demand in study area 84

Table 5.6 Total monthly water Demand for the study area 85

Table 5.7 Total Number of pumping wells required for the study area.....86

Table 5.8 Duration of four periods 87

Table 5.9 Observed water head elevation in Jakkhini Observation well 88

Table 5.10 Observed water head elevation in Varanasi Observation Well 89

Table 5.11 Observed water head elevation in Kakrahwan Observation Well 90

Table 5.12 Observed water head elevation in Babatpur Observation Well 91

Table 5.13 Parameters values used in the model calibration 93

Table 5.14 Model Parameters values used in the AEM model calibration.....100

Table 6.1 Movement of water flow between River and Aquifer 113

Acronyms and Abbreviations

AEM	:	Analytic Element Method
AnAqSim	:	Analytic Aquifer simulator
ANN	:	Artificial Neural Network
ASCII	:	American Standard Code for Information Interchange
ASTER	:	Advanced Spaceborne Thermal Emission and Reflection Radiometer
BCM	:	Billion Cubic Meter
BEM	:	Boundary Element Method
BGL	:	Below Ground Level
BHU	:	Banaras Hindu University
CGWB	:	Central Ground Water Board
CWC	:	Central Water Commission
DEM	:	Digital Elevation Model
DGPS	:	Differential Global Positioning System
DSS	:	Decision Support System
FDM	:	Finite Difference Method
FEFLOW	:	Finite Element Flow
FEM	:	Finite Element Method
FEMWATER	:	Finite Element Model of Water Flow
FVM	:	Finite Volume Method
GA	:	Genetic Algorithm
GDEM	:	Global Digital Elevation Model
GIS	:	Geographic Information System
GLCF	:	Global Land Cover Facility
GMS	:	Groundwater Modeling System

GPS	:	Global Positioning System
IFDM	:	Integrated Finite Difference Method
IMD	:	Indian Meteorological Department
KVP	:	Kashi Vidya Peeth
L/MIN	:	Liter per Minute
LPS	:	Liter per Second
LULC	:	Land Use Land Cover
MCM	:	Million Cubic Meters
MO	:	Monsoon
MSL	:	Mean Sea Level
NASA	:	National Aeronautics and Space Administration
NRMSE	:	Normalized Root Mean Square Error
NRSC	:	National Remote Sensing Centre
PDE	:	Partial Differential Equation
POMK	:	Post Monsoon Kharif
POMR	:	Pre-monsoon Ravi
PRM	:	Pre Monsoon
RMSE	:	Root Mean Square Error
SD	:	Standard Deviation
SEE	:	Standard Error of Estimate
SMI	:	Soil Moisture Index
SOI	:	Survey of India
SRTM	:	Shuttle Radar Topography Mission
USGS	:	United States Geological Survey
WRIS	:	Water Resource Information System

Table of Contents

CERTIFICATE i

DECLARATION BY THE CANDIDATE ii

CERTIFICATE BY THE SUPERVISOR(S) ii

COPYRIGHT TRANSFER CERTIFICATE iii

ACKNOWLEDGEMENT v

LIST OF FIGURES vii

LIST OF TABLES ix

ACRONYMS AND ABBREVIATIONS x

TABLE OF CONTENTS xii

PREFACE xvi

CHAPTER 1 1-8

Introduction 1

1.1 Background 1

1.2 Groundwater Modeling 2

1.3 Motivation: Groundwater Scenario in India 4

1.4 Aim and Research Objectives (Groundwater Management) 6

1.5 Organization of the Thesis 7

CHAPTER 2 9-27

Literature review 9

2.1 General 9

2.2 Groundwater Models 10

2.3 Groundwater codes/programs 13

2.4 Numerical models 14

2.5 Groundwater and surface water Interaction 20

2.5.1 Process Driven by Groundwater 22

2.5.2 Processes Driven by Surface water 24

2.5.2.1 Overland Flow and Through-Flow 24

2.5.2.2 River Flow Attenuation 25

2.5.2.3 In-Stream Storages 25

2.5.2.4 Off-Stream Storages 26

2.6 Summary 27

CHAPTER 3 28-46

Study Area 28

3.1 General 28

3.2 Physiography and topography 29

3.3 Climate and rainfall 30

3.4 Field Data 32

3.4.1 Digital Elevation Model 33

3.4.2 Geological properties 36

3.4.3 Stratigraphic features 37

3.5 Aquifer Geometry 38

3.6 Hydraulic Conductivity 42

3.7 River Network 43

3.8 Meteorological data 45

3.9 Summary 46

CHAPTER 4 47-62

Methodology 47

4.1 General 47

4.2 An approach to the Modeling 47

4.2.1 Conceptual Model 48

4.3 Groundwater Flow simulation 51

4.4 Boundary and initial conditions 51

4.4.1 Examples of Different Boundaries 53

4.5 Recharge 54

4.6 Hydraulic conductivity 56

4.7 Well discharge (Pumping) 57

4.8 Calibration 57

4.9 Validation 58

4.10 Model Development using Analytical Approach 58

4.11 Groundwater-surface water (river) interaction 59

4.12 Summary 61

CHAPTER 5 63-101

Model setup 63

5.1 General 63

5.2 Groundwater Model Conceptualization of the study area 65

5.3 Borehole Module 71

5.4 Boundary Conditions 74

5.4.1 River Boundary 74

5.4.2 Specified flux Boundary 76

5.5 Top and bottom layers 76

5.6 Depth of Groundwater Level 78

5.7 Well Discharge 79

5.8 Observation wells 87

5.9 Model Calibration 91

5.10 Model sensitivity 94

5.11 Model validation 96

5.12 Soil Moisture Study 97

5.13 Groundwater Model Development using AEM 98

5.13.1 Boundary conditions 99

5.13.2 Recharge and discharge well 99

5.14 AEM model calibration 99

5.15 Summary 101

CHAPTER 6 102-115

Result and Discussion 102

6.1 General 102

6.2 Current state of study area and Model output 102

6.3 Scenario Generation 110

6.4 Comparison of outputs produced by FDM and AEM approach. 111

6.5 Result of River-Aquifer (R-A) Exchange 112

6.6 Sustainable Management of the Water Resources System 114

6.7 Summary 115

CHAPTER 7 116-122

Conclusion 116

7.1 General 116

7.2 Limitations of the study 121

7.3 Recommendations 122

REFERENCES 123-133

LIST OF PUBLICATIONS 134

Appendix A 135-136

Appendix B 137-152

Appendix C 153-156

PREFACE

Groundwater plays a vital role as a source of drinking water and other purposes for billions of urban or rural families. Therefore, sustainable management and planning of groundwater resources became crucial and necessary to predict the impact of global climate change. Groundwater management includes efficient and effective management of groundwater resources at both quantity and quality levels. Due to the depletion of groundwater, conservation measures have become a challenging issue for the current scenario. These possible measures can be assessed by developing various models for groundwater flow simulation, which have also been used as decision support systems.

Groundwater flow modeling is an important technique used by researchers and engineers to study groundwater systems dynamics and provide the information to the decision-makers. Although, a complex groundwater system with a large set of parameters and associated uncertainty with those parameters makes modeling exercise difficult. Groundwater flow modeling provides the head and flows direction that helps in the management of the groundwater under various hydrological stresses. High contamination in the surface water like the Ganga River in Varanasi and surrounding areas forces human beings to use the groundwater to fulfill their daily needs. Thus, excessive and unplanned groundwater extraction is becoming the main reason for the depletion of groundwater in the different parts of Varanasi and surrounding areas. Despite numerous previous studies, the groundwater flow dynamics in the alluvial aquifer and the characteristics of the river-aquifer exchanges are still partially unknown. Therefore, the local water management service requires a decision support system (DSS) based on numerical models to ensure better groundwater management.

In this study, the development of a transient groundwater flow model for the Varanasi district and nearby area was prompted to understand groundwater dynamics and future groundwater

resource scenarios in the region. Therefore, modeling exercise has been done using two approaches: the grid-based numerical method (Finite Difference Method - FDM). The second is the analytical method (Analytic Element Method - AEM).

In the first part of the study, a hydraulic flow model has been set up using FDM techniques by considering precipitation, evapotranspiration, groundwater recharge, groundwater extraction, and river-aquifer exchanges. The non-documented groundwater extraction for agricultural use, domestic use, and livestock use has been calculated manually. The model was developed for the area of 2,785 km^2, where aquifer thickness extended up to 222 m. The model grid consisted of 210 rows and 210 columns with each cell size of 250 m × 250 m. The model was built for five layers with recharge entering the aquifer from surface infiltration through the overlying confining unit and seepage through riverbeds to realize the different types of underground formations. The maximum part of the model domain is surrounded by the Ganga River, which was taken as a hydrologic boundary for the model.

Model simulations were made to quantify groundwater flow within the alluvial aquifer as well as flow into and out of the system. The groundwater flow model was developed in the transient state condition for the years 2006 to 2017. Several criteria were used to determine how fine the model simulated conditions in the aquifer during the model development and calibration. Model calibration was done on the values of hydraulic conductivity and recharge rates. These two parameters are fixed based upon the sensitivity analysis of the model. A root-mean-square error analysis was performed during calibration to serve as a criterion to minimize differences between observed and model computed water levels. Further, the model is validated with a simulation of 1096 days. Fourteen points are chosen to evaluate the model efficiency. Then, model validation has been done using another method, i.e., by calculating Soil Moisture Index (SMI). After that, calibrated model was used to analyze the three different scenarios considering the future development and growth of the city.

In the second part of the study, a groundwater flow model was set up with AnAqSim software by considering rivers of the study area and pumping wells in DXF format. AnAqSim software uses the Analytic Element Method approach for the model development. After developing the model, based on the ease of model development, data requirement, and performances, a comparison has been made between FDM and AEM. The study suggested that AEM does not require a fixed boundary condition, and in FDM, pumping wells are approximately located and averaged over the cell, which becomes a cause of the inaccurate location of wells. Therefore, it can conclude that AEM-based modeling is more accurate as compared to FDM-based flow modeling. This study can be beneficial for groundwater professionals in deciding the best suitable method for their study area.

The study of the river-aquifer exchange has been done. In this, groundwater flow direction and quantification of flux exchanges have been calculated with the help of a developed transient multi-layered groundwater model. From the aquifer, 253.674 m^3/sec groundwater moves to the Ganga River over a stretch of approx. 70 km, and 81.581 m^3/sec groundwater moves towards the Gomati River over a stretch of approx. 65 km. Simultaneously, 198.82 m^3/sec water moves towards the aquifer from 75 km-long stretches of the River. In the dry period of the season, this value has been increased, and the aquifer comes under pressure. In the future, when the pumping schedule would like to increases, exchange between River and aquifer will be affected. Reducing the Ganga River level by 0.5 m or 1 m will slightly affect the leakage from the River and the study area's groundwater level. To control the impact on the groundwater aquifer and its connection with the River, it is highly recommended to remove some wells from the pumping schedule and reduce the pumping rate of the other wells, and constantly monitor the behavior of both over time. It is expected that the results obtained from the study can provide critical information for sustainable and effective management of the groundwater resources for Varanasi and the surrounding area.