

---



---

## List of figures

---



---

<b>Figure No.</b>	<b>Caption of figures</b>	<b>Page no.</b>
<b>Figure 1.1:</b>	Hyperthermia-induced cellular changes that could lead to tumor cell death	2
<b>Figure 2.1:</b>	Geometry of conventional MDHs (a) top view, (b) side view, (c) terminated in a biological phantom.	31
<b>Figure 2.2:</b>	Different views of fabricated prototype for operation at 2450 MHz	31
<b>Figure 2.3:</b>	(a) Experimental setup for measurement of power level (proportional to square of the magnitude of induced electric field) in the phantom bio-medium, (b) coaxial straight monopole probe, and (c) coaxial L-shaped monopole probe.	37
<b>Figure 2.4:</b>	Normalized SAR distributions in phantom muscle in direct contact with water-loaded conventional MDHs at 2450 and 915 MHz along z-direction ( $x = y = 0$ ).	41
<b>Figure 2.5:</b>	Normalized SAR distributions in phantom muscle in direct contact with water-loaded conventional MDHs at 2450 and 915 MHz along (a) x-direction at $z = 10$ mm ( $y = 0$ ) and (b) y-direction at $z = 10$ mm ( $x = 0$ ).	41
<b>Figure 2.6:</b>	Theoretical normalized SAR distribution inside the biological phantom in xy-plane at $z = 10$ mm due to water-loaded conventional MDH antenna designed at (a) 2450 MHz and (b) 915 MHz.	43
<b>Figure 2.7:</b>	Conventional MDH antenna designed at a given frequency and terminated in tri-layered bio-media.	44
<b>Figure 2.8:</b>	Two-dimensional realistic tri-layered bio-model with embedded (a) tumor1/tumor2 (applicable for the horn designed at 2450 MHz) and (b) tumor3/tumor4 (applicable for the horn designed at 915 MHz).	45
<b>Figure 2.9:</b>	Variations of peak SAR with input power at (a) 2450 MHz and (b) 915 MHz.	46
<b>Figure 2.10:</b>	Simulated normalized SAR distributions inside the tri-layered bio-model without and with embedded tumors along z-direction ( $x = y = 0$ ) due to the water-loaded conventional MDH for 1 W input power designed at (a) 2450, and (b) 915 MHz.	47

- Figure 2.11:** Simulated normalized SAR distributions inside the tri-layered bio-model without tumor, with embedded tumor1 and with embedded tumor2 due to the water-loaded conventional MDH at 2450 MHz along (a) x-direction at  $z = 10$  mm (middle of tumor1/tumor2) ( $y = 0$ ), and (b) y-direction at  $z = 10$  mm (middle of tumor1/tumor2) ( $x = 0$ ). 47
- Figure 2.12:** Simulated normalized SAR distributions inside the tri-layered bio-model without tumor, with embedded tumor3 and with embedded tumor4 due to the water-loaded conventional MDH designed at 915 MHz along (a) x-direction at  $z = 17.5$  mm (middle of tumor3/tumor4) ( $y = 0$ ), and (b) y-direction at  $z = 17.5$  mm (middle of tumor3/tumor4) ( $x = 0$ ). 47
- Figure 2.13:** Temperature distribution inside the tri-layered bio-media without tumor for different input power levels along z-direction ( $x=y=0$ ) due to water-loaded conventional MDH designed at 915 MHz. 49
- Figure 2.14:** Variations of temperature in the realistic tri-layered bio-media without and with embedded tumor4 versus time due to the conventional MDH designed at 915 MHz by taking depth in the tumor as a parameter for  $x = y = 0$ . 50
- Figure 2.15:** Simulated temperature distributions inside the tri-layered bio-models without and with embedded tumors along z-direction ( $x = y = 0$ ) due to the conventional MDH for 13 W optimum input power at 915 MHz. 50
- Figure 2.16:** Simulated temperature distributions inside the tri-layered bio-model without tumor, with embedded tumor3 and with embedded tumor4 along x-/y-direction ( $y/x=0$ ) at (a)  $z = 5$  mm, (b)  $z = 17.5$  mm, and (c)  $z = 30$  mm due to the conventional MDH designed at 915 MHz for optimum input power of 13 W. 51
- Figure 2.17:** Simulated temperature distributions inside the realistic tri-layered bio-media without and with embedded tumor3/tumor4 due to the conventional MDH at 915 for 13 W optimum input power in (a) xz-plane, (b) yz-plane, (c) xy-plane with tumor3, and (d) xy-plane with tumor4. 52
- Figure 3.1:** Geometry of water-loaded improved MDH antenna (a) top view, and (b) side view. 58
- Figure 3.2:** (a) Improved MDH antenna terminated in single layer bio-medium and (b) Different views of fabricated antenna for operation at 2450 MHz. 58

<b>Figure 3.3:</b>	Simulated field distribution(s) at the aperture of (a) conventional MDH, (b) horn with pins along x-and y-directions, and (c) improved MDH, all designed at 2450 MHz.	65
<b>Figure 3.4:</b>	Simulated field distribution at the aperture of (a) conventional MDH, and (b) improved MDH, both designed at 915 MHz.	65
<b>Figure 3.5:</b>	Predicted normalized field distribution at the aperture of improved MDH at 2450 MHz for different values of excitation coefficients $a_{30}/a_{10} = a_{03}/a_{01}$ , (assuming $a_{30} = a_{03}$ and $a_{10} = a_{01}$ ) (a) 0.5, (b) 0.7, (c) 0.9, and (d) 1.	67
<b>Figure 3.6:</b>	Predicted normalized field distribution at the aperture of improved MDH at 915 MHz for different values of excitation coefficients $a_{30}/a_{10} = a_{03}/a_{01}$ , (assuming $a_{30} = a_{03}$ and $a_{10} = a_{01}$ ) (a) 0.5, (b) 0.7, (c) 0.9, and (d) 1.	67
<b>Figure 3.7:</b>	Predicted normalized field distribution(s) at the aperture of (a) conventional MDH, and (b) horn with pins along x-and y-directions.	67
<b>Figure 3.8:</b>	Effects of (a) pins' location ' $d_2$ ' at 2450 MHz, (b) inter-pin spacing ' $d_3$ ' at 2450 MHz, (c) pins' radius ' $r$ ' at 2450 MHz, (d) pins' location ' $d_2$ ' at 915 MHz, (e) inter-pin spacing ' $d_3$ ' at 915 MHz, (f) pins' radius ' $r$ ' at 915 MHz on normalized SAR distributions along z-direction in phantom muscle due to the improved MDH antennas for 1 W input power.	69
<b>Figure 3.9:</b>	Normalized SAR distributions inside the phantom muscle due to improved/conventional MDHs along (a) z-direction ( $x = y = 0$ ) at 2450 MHz, (b) x-/y-direction at $z = 10$ mm ( $y/x = 0$ ) at 2450 MHz, (c) z-direction ( $x = y = 0$ ) at 915 MHz, and (d) x-/y-direction at $z = 20$ mm ( $y/x = 0$ ) at 915 MHz.	72
<b>Figure 3.10:</b>	Improved MDH antenna designed at a given frequency and terminated in tri-layered bio-media.	75
<b>Figure 3.11:</b>	Two-dimensional realistic tri-layered bio-model with embedded (a) tumor1/tumor2 (applicable for the improved MDH designed at 2450 MHz) and (b) tumor3/tumor4 (applicable for the improved MDH designed at 915 MHz).	75
<b>Figure 3.12:</b>	Simulated normalized SAR distributions inside the bio-model without and with embedded tumor1/tumor2 due to improved MDHs at 2450 MHz along z-direction ( $x = y = 0$ ).	76

<b>Figure 3.13:</b>	Simulated normalized SAR distributions inside the bio-model without and with embedded tumor3/tumor4 due to improved MDHs at 915 MHz along z-direction ( $x = y = 0$ ).	76
<b>Figure 3.14:</b>	Simulated normalized SAR distributions inside the bio-models due to the improved MDH at 2450 MHz along (a) x-direction at $z = 10$ mm (middle of tumor1/tumor2) ( $y = 0$ ), and (b) y-direction at $z = 10$ mm (middle of tumor1/tumor2) ( $x = 0$ ).	77
<b>Figure 3.15:</b>	Simulated normalized SAR distributions inside the bio-models due to the improved MDH at 915 MHz along (a) x-direction at $z = 20$ mm (middle of tumor3/tumor4) ( $y = 0$ ), and (b) y-direction at $z = 20$ mm (middle of tumor3/tumor4) ( $x = 0$ ).	77
<b>Figure 3.16:</b>	Temperature distribution inside the tri-layered bio-media without tumor for different input power levels along z-direction ( $x=y=0$ ) due to improved MDH at (a) 2450 MHz and (b) 915 MHz.	77
<b>Figure 3.17:</b>	Variations of temperature with time due to the improved MDHs in the realistic tri-layered bio-media without and with embedded (a) tumor2 for $x = y = 0$ at 2450 MHz, (b) tumor4 for $x = y = 0$ at 915 MHz.	79
<b>Figure 3.18:</b>	Simulated temperature distributions inside the tri-layered bio-models without and with embedded tumors along z-direction ( $x = y = 0$ ) due to the improved horn at (a) 2450, and (b) 915 MHz.	79
<b>Figure 3.19:</b>	Simulated temperature distributions inside the tri-layered bio-model without tumor, with embedded tumor1 and with embedded tumor2 along x-/y-direction ( $y/x=0$ ) at (b) $z = 5$ mm, (b) $z = 10$ mm, and (c) $z = 15$ mm, due to the improved MDH at 2450 MHz for optimum input power of 4 W.	80
<b>Figure 3.20:</b>	Simulated temperature distributions inside the tri-layered bio-model without tumor, with embedded tumor3 and with embedded tumor4 along x-/y-direction ( $y/x=0$ ) at (b) $z = 5$ mm, (b) $z = 20$ mm, and (c) $z = 35$ mm, due to the improved MDH designed at 915 MHz for 10 W input power.	81
<b>Figure 3.21:</b>	Temperature distributions inside the realistic tri-layered bio-media without and with embedded tumor1/tumor2 due to the improved MDH at 2450 for 4 W input power in (a) xz-plane, (b) yz-plane, (c) xy-plane with tumor1, and (d) xy-plane with tumor2.	82

<b>Figure 3.22:</b>	Temperature distributions inside the realistic tri-layered bio-media without and with embedded tumor3/tumor4 due to the improved MDH at 915 MHz for 10 W input power in (a) xz-plane, (b) yz-plane, (c) xy-plane with tumor3, and (d) xy-plane with tumor4.	83
<b>Figure 4.1:</b>	Geometry of water-loaded MDWDH antenna (a) top view, and (b) side view.	87
<b>Figure 4.2:</b>	(a) Water-loaded MDWDH antenna terminated in bio-medium and (b) Fabricated antenna for study at 2450 MHz.	87
<b>Figure 4.3:</b>	Simulated field distributions for 2450 MHz at the aperture of (a) conventional MDH, (b) the horn with Perspex near the corners of antenna walls, and (c) the proposed MDWDH.	90
<b>Figure 4.4:</b>	Simulated field distributions for 915 MHz at the aperture of (a) conventional MDH, (b) the horn with Perspex near the corners of the antenna walls, and (c) the proposed MDWDH.	90
<b>Figure 4.5:</b>	Effects of dielectric location, its dielectric property, dimensions (a) $c_1$ , (b) $c_2$ , and (c) dielectric constant value, and (d) location of dielectric material on normalized SAR distributions along z-direction in phantom muscle due to the due to the MDWDH at 2450 MHz.	91
<b>Figure 4.6:</b>	Effects of dielectric location, its dielectric property, dimensions (a) $c_1$ , (b) $c_2$ , and (c) dielectric constant value, and (d) location of dielectric material on normalized SAR distributions along z-direction in phantom muscle due to the MDWDH at 915 MHz.	92
<b>Figure 4.7:</b>	Figure 4.7: Normalized SAR distributions inside the phantom muscle due to MDWDH/Conventional MDH antennas at 2450 and 915 MHz along (a) z-direction ( $x = y = 0$ ), (b) x-direction at $z = 10$ mm ( $y = 0$ ), and (c) y-direction at $z = 10$ mm ( $x = 0$ ).	94
<b>Figure 4.8:</b>	Metal-dielectric wall diagonal horn antenna designed at a given frequency and terminated in tri-layered bio-media.	97
<b>Figure 4.9:</b>	Two-dimensional realistic tri-layered bio-model with embedded (a) tumor1/tumor2 (applicable for the horn designed at 2450 MHz), and (b) tumor3/tumor4 (applicable for the horn designed at 915 MHz).	97
<b>Figure 4.10:</b>	Simulated normalized SAR distributions inside the bio-model without and embedded tumor1/tumor2 due to MDWDH at 2450 MHz along z-direction ( $x = y = 0$ ).	98

<b>Figure 4.11:</b>	Simulated normalized SAR distributions inside the bio-model without and with embedded tumor3/tumor4 due to MDWDH at 915 MHz along z-direction ( $x = y = 0$ ).	98
<b>Figure 4.12:</b>	Simulated normalized SAR distributions inside the bio-models due to the MDWDH at 2450 MHz along (a) x-direction at $z = 10$ mm (middle of tumor1/tumor2) ( $y = 0$ ), and (b) y-direction at $z = 10$ mm (middle of tumor1/tumor2) ( $x = 0$ ).	98
<b>Figure 4.13:</b>	Simulated normalized SAR distributions inside the bio-models due to the MDWDH at 915 MHz along (a) x-direction at $z = 20$ mm (middle of tumor3/tumor4) ( $y = 0$ ), and (b) y-direction at $z = 20$ mm (middle of tumor3/tumor4) ( $x = 0$ ).	99
<b>Figure 4.14:</b>	Temperature distribution inside the tri-layered bio-media without tumor for different input power levels along z-direction ( $x=y=0$ ) due to the MDWDH at (a) 2450 MHz and (b) 915 MHz.	99
<b>Figure 4.15:</b>	Variations of temperature with time due to the MDWDHs in the realistic tri-layered bio-media without and with embedded (a) tumor2 for $x = y = 0$ at 2450 MHz, (b) tumor4 for $x = y = 0$ at 915 MHz.	100
<b>Figure 4.16:</b>	Simulated temperature distributions inside the tri-layered bio-models without and with embedded tumors along z-direction ( $x = y = 0$ ) due to the MDWDH at (a) 2450 MHz, and (b) 915 MHz.	100
<b>Figure 4.17:</b>	Simulated temperature distributions inside the tri-layered bio-model without tumor, with embedded tumor1 and with embedded tumor2 along x-/y-direction ( $y/x=0$ ) at (b) $z = 5$ mm, (b) $z = 10$ mm, and (c) $z = 15$ mm, due to the MDWDH designed at 2450 MHz for 4 W input power.	102
<b>Figure 4.18:</b>	Simulated temperature distributions inside the tri-layered bio-model without tumor, with embedded tumor3, and embedded tumor4 along x-/y-direction ( $y/x=0$ ) at (a) $z = 5$ mm, (b) $z = 20$ mm, and (c) $z = 35$ mm, due to the MDWDH designed at 915 MHz for 9 W input power.	103
<b>Figure 4.19:</b>	Temperature distributions inside the realistic tri-layered bio-media without and with embedded tumor1/tumor2 due to the MDWDH at 2450 MHz for 4 W input power in (a) xz-plane, (b) yz-plane, (c) xy-plane with tumor1, and (d) xy-plane with tumor2.	104
<b>Figure 4.20:</b>	Temperature distributions inside the realistic tri-layered bio-media without and with embedded tumor3/tumor4 due to the MDWDH at 915 for 9 W input power in (a) xz-plane, (b) yz-plane, (c) xy-plane with tumor3, and (d)	105

xy-plane with tumor4.

<b>Figure 5.1:</b>	Proposed antenna geometry (a) top and back views, and (b) fabricated prototype. (All dimensions are in mm)	110
<b>Figure 5.2:</b>	Antenna in close proximity with phantom bio-medium.	112
<b>Figure 5.3:</b>	Different antenna configurations with various combinations of slotted ground plane and feed.	112
<b>Figure 5.4:</b>	Simulated variations of input reflection coefficient of various antenna configurations and conventional rectangular patch antenna versus frequency.	112
<b>Figure 5.5:</b>	Configuration of the conventional rectangular patch antenna designed at 2.45 GHz.	113
<b>Figure 5.6:</b>	Simulated relative SAR distributions in the phantom muscle medium along z-direction ( $x = y = 0$ ) due to various configurations of microstrip slot antenna and conventional microstrip patch antenna.	113
<b>Figure 5.7:</b>	Near E-field distributions in xz-plane from various configurations of the slot antenna radiating into phantom bio-medium.	114
<b>Figure 5.8:</b>	(a) Unit cell structure of square patch and ring AMCs, (b) Unit cell structure of proposed AMC, and (c) Fabricated prototype of proposed AMC reflector of $4 \times 4$ unit cells. (All dimensions are in mm)	118
<b>Figure 5.9:</b>	Reflection phase profiles of (a) square patch, ring and proposed AMC structure, (b) proposed AMC design for TE and TM polarizations, (c) proposed AMC for different polarization angles, and (d) proposed AMC for different angles of incidence.	118
<b>Figure 5.10:</b>	Proposed applicator with AMC terminated in phantom bio-medium.	118
<b>Figure 5.11:</b>	Simulated variation of input reflection coefficient of the proposed applicator versus frequency by taking antenna-AMC separation $d$ as a parameter.	120
<b>Figure 5.12:</b>	Simulated and measured variations of input reflection coefficient of the proposed antenna (with AMC) versus frequency.	120
<b>Figure 5.13:</b>	Simulated variations of input reflection coefficient of the proposed antenna with AMC versus frequency for various dielectric constant values of the phantom bio-medium.	120
<b>Figure 5.14:</b>	E-field distributions in xz-plane from proposed antenna with AMC for various AMC sizes, radiating into	122

	phantom bio-medium.	
<b>Figure 5.15:</b>	Simulated and measured variations of normalized SAR distributions in the phantom muscle medium due to proposed antenna (a) without/with AMC along z-direction ( $x = y = 0$ ), and (b) with AMC along x-/y-direction ( $y/x = 0$ ) at $z = 10$ mm.	122
<b>Figure 5.16:</b>	Illustration of the proposed antenna with PEC reflector.	124
<b>Figure 5.17:</b>	Simulated variations of input reflection coefficient of the proposed antenna with AMC/PEC versus frequency.	124
<b>Figure 5.18:</b>	Simulated variations of normalized SAR distributions in the phantom muscle medium due to proposed antenna with AMC/PEC along (a) z-direction ( $x = y = 0$ ), (b) x-direction ( $y = 0$ ) at $z = 10$ mm, and (c) y-direction ( $x = 0$ ) at $z = 10$ mm.	126
<b>Figure 5.19:</b>	Near E-field distributions in xz-plane in the central regions of proposed antenna with AMC for different value of system's curvature, radiating into phantom biomedium.	127
<b>Figure 5.20:</b>	Variations of input reflection coefficient of the proposed antenna with AMC versus frequency for different values of system's radius of curvature 'R'.	127
<b>Figure 5.21:</b>	SAR patterns in muscle tissue for various values of radius of curvature of the bio-model/proposed antenna.	128
<b>Figure 5.22:</b>	Variation of EFS with system's radius of curvature 'R' at $z = 10$ mm.	129
<b>Figure 5.23:</b>	Proposed applicator with AMC reflector in close proximity with tri-layered bio-media.	130
<b>Figure 5.24:</b>	Two-dimensional realistic tri-layered bio-model with embedded oval/irregular-shaped tumor.	130
<b>Figure 5.25:</b>	Simulated normalized SAR distributions inside the bio-model without and with embedded tumors due to the proposed applicator along z-direction ( $x = y = 0$ ).	131
<b>Figure 5.26:</b>	Variations of EFS with the system's radius of curvature for inhomogeneous bio-models (without and with embedded tumor) at $z = 10$ mm.	132
<b>Figure 5.27:</b>	SAR patterns in tri-layered bio-model without tumor for various values of system's radius of curvature.	132
<b>Figure 5.28:</b>	SAR patterns in tri-layered bio-model embedded with oval-shaped tumor for various values of system's radius of curvature.	132

<b>Figure 5.29:</b>	SAR patterns in tri-layered bio-model embedded with irregularshaped tumor for various values of system's radius of curvature.	133
<b>Figure 5.30:</b>	E-field distribution in the central regions of proposed antenna with AMC for different values of system's radius of curvature, radiating into tri-layered bio-media.	133
<b>Figure 5.31:</b>	Temperature distributions inside the tri-layered bio-model at 2.45 GHz due to proposed applicator without and with embedded tumor in xy-plane at $z = 10$ mm for various values of system's radius of curvature (a) $R = 50$ mm, (b) 500 mm, and (c) $R = \infty$ (planar).	135
<b>Figure 5.32:</b>	Five-layered cylindrical bio-models in close proximity with the proposed applicator.	136
<b>Figure 5.33:</b>	E-field distribution in the central regions of proposed antenna with AMC having same radius of curvature as that of the bio-model, radiating into (a) Thigh model, and (b) Arm model.	137
<b>Figure 5.34:</b>	Simulated normalized SAR distributions in the five-layered cylindrical bio-media without and with embedded oval-/irregular-shaped tumor due the proposed applicator along z-direction ( $x=y=0$ ) in (a) thigh-model, and (b) arm-model.	138
<b>Figure 5.35:</b>	Simulated normalized SAR distributions in the five-layered cylindrical bio-media without and with embedded oval-/irregular-shaped tumor due the proposed applicator along x-/y-direction ( $z = 10$ mm) in (a) thigh-model, and (b) arm-model.	139
<b>Figure 5.36:</b>	SAR patterns in thigh-model without and with embedded oval-/irregular-shaped tumor due to the proposed applicator.	139
<b>Figure 5.37:</b>	SAR patterns in arm-model without and with embedded oval-/irregular-shaped tumor due the proposed applicator.	139
<b>Figure 5.38:</b>	Temperature distribution in the five-layered cylindrical bio-media without and with embedded oval-/irregular-shaped tumor ( $z = 10$ mm) due the proposed applicator in (a) thigh-model, and (b) arm-model.	140