

TABLE OF CONTENTS

LIST OF FIGURES	iii
LIST OF TABLES	v
LIST OF ABBREVIATIONS	vii
LIST OF SYMBOLS	viii
PREFACE	ix
Chapter-1	1
Introduction and Scope of the Thesis	1
1.1 Semiconducting Materials	2
1.2 Classification of Semiconductor Materials	4
1.3 Organic Semiconducting Materials.....	6
1.4 Charge Transport Mechanism in Organic Semiconducting Material.....	11
1.5 Thiophene Based Organic Polymers	12
1.6 Basics of Photodetectors	14
1.7 Basics of Gas Sensors	18
1.8 Instruments used for Device Fabrication and Characterization	21
1.9 Literature Review on Organic Semiconductor Materials-based Devices	25
1.10 Thesis Motivation.....	29
1.11 Thesis Objective.....	30
1.12 Scope of the Thesis	31
Chapter-2	33
A Low-Cost Solution Processed PTB7 Based MSM Visible Photodetector	33
2.1 Introduction.....	34
2.2 Experimental Details	35
2.3 Results and Discussions.....	36
2.4 Working of the Device	42
2.5 Conclusion.....	44
Chapter-3	45
Highly Responsive Al/PTB7/Si/Al Vertical Structure Based White Light Photodetector using FTM Method	45
3.1 Introduction.....	46
3.2 Experimental Details	47
3.3 Results and Discussion	48
3.4 Conclusion.....	52
Chapter-4	53
PTB7 Decorated ZnO Nanorod-Based Room Temperature Ammonia Gas Sensor	53
4.1 Introduction.....	54
4.2 Experimental Details	55

4.3 Results and Discussion	57
4.4 Conclusion	65
Chapter-5	67
Conclusions and Future Scope.....	67
5.1 Major Conclusions	68
5.2 Future Work	71
Author's Publications	73
References.....	74

LIST OF FIGURES

Figure 1.1 Band gap of metals, semiconductors, and insulators.	3
Figure 1.2 Broad area applications of semiconductor materials.....	4
Figure 1.3 Classification of semiconducting materials.	4
Figure 1.4 Broad area applications of organic semiconducting material-based devices.	7
Figure 1.5 Splitting of molecular orbitals in organic semiconducting materials [28].	11
Figure 1.6 HOMO and LUMO levels and bandgap representation in organic/inorganic semiconducting materials [29].	12
Figure 1.7 Chemical structure of PTB7.....	14
Figure 1.8 Classification of photodetectors.....	15
Figure 1.9 Figure of merits of photodetector.	15
Figure 1.10 Structures used for photodetectors.	17
Figure 1.11 Classification of gas sensors.	18
Figure 1.12 Figure of merits of gas sensors.....	19
Figure 1.13 Gas sensing mechanism: (a) physisorption and (b) chemisorption.....	20
Figure 1.14 Various steps involved in device fabrication and characterization.	21
Figure 1.15 Various thin film deposition techniques.	22
Figure 1.16 Spin coating and FTM method of thin film deposition.	23
Figure 1.17 Resources used in fabrication and characterizations of devices used in this thesis.	25
Figure 1.18 Photodetectors market demand forecast and analysis 2023-2027.	29
Figure 1.19 Gas sensor market size, growth, trends, report 2023-2032.	30
Figure 2.1 Fabrication steps used for device fabrication.....	37
Figure 2.2 Fabricated device image and device schematics are shown (a) and (b).	37
Figure 2.3 AFM image of the polymer thin film (a) 2D and (b) 3D for surface morphology analysis.	38
Figure 2.4 (a) UV-Vis spectrum of the polymer film and (b) band gap calculation.	38
Figure 2.5 (a) I-V measurements of the fabricated device under dark/illuminated (665 nm wavelength) conditions, (b) wavelength-dependent responsivity curve of the fabricated device for visible range from 400 to 900 nm.	39
Figure 2.6 (a) Specific detectivity curve of the fabricated device for visible light spectrum, and (b) EQE curve of the fabricated device with wavelength ranging from 400 nm to 900 nm.....	40
Figure 2.7 (a) Transient analysis of the fabricated device and (b) rise time and fall time calculation from single peak of wavelength 665 nm.....	41
Figure 2.8 Energy band representation of the fabricated device structure (a) before	

equilibrium (b) at equilibrium under dark conditions and (c) under light illumination. ..	42
Figure 3.1 Steps of floating film transfer method.	48
Figure 3.2 (a) Schematic of device structure, (b) 3D AFM image of the polymer film.	48
Figure 3.3 (a) Energy band diagram of the fabricated device representing the HOMO and LUMO energy levels of polymer before biasing, (b) UV absorbance spectra of the polymer thin film, (c) UV absorbance spectra of the Al contact.	49
Figure 3.4 Current - Voltage plot of the as-fabricated device with varying incident white light irradiation and device image in inset.	50
Figure 3.5 (a) Device current as a function of incident optical power, (b) responsivity and Specific detectivity plot of the fabricated device with respect to the power intensity of incident white light.	50
Figure 3.6 (a) Transient response characteristics of the fabricated photodetector at -2 V under the illumination of 12.98 mW/cm ² white light power, (b) rise time and fall time calculation of the fabricated device.	51
Figure 4.1 Hydrothermal method of ZnO nanorods synthesis.	56
Figure 4.2 In-house developed gas sensing setup.	57
Figure 4.3 XRD of ZnO nanorods.	58
Figure 4.4 (a) High-resolution SEM image of PTB7 deposited ZnO nanorods with the HRSEM image of the ZnO nanorods in the inset, (b) 3-D AFM image of the polymer film on ZnO nanorods, (c) cross-sectional view of the pristine ZnO nanorods, and (d) cross-sectional view of the PTB7 decorated ZnO nanorods.	58
Figure 4.5 (a) Current-voltage characteristics of PTB7-ZnO NRs device with varying ammonia concentration. (b) comparison of the current-voltage characteristics of ZnO NR device with and without PTB7 layer under 20-ppm ammonia.	60
Figure 4.6 (a) Gas response of the PTB7-ZnO NR device with varying gas concentration from 2 ppm to 50 ppm, (b) comparison of gas response of only ZnO NR device and PTB7-ZnO NR device at 20 ppm ammonia.	60
Figure 4.7 (a) Transient gas response characteristics of the proposed PTB7- ZnO NR device at 2 V for different concentrations of ammonia gas varying from 2 ppm to 50 ppm, (b) enlarged view of the transient gas response at 20 ppm for analyzing the response and recovery times.	61
Figure 4.8 (a) Gas response analysis for different values of relative humidity, (b) selectivity analysis of the proposed device.	62
Figure 4.9 The stability study of the device over a 7-week period.	63
Figure 4.10 (a) Ammonia sensing mechanism, (b) adsorption and desorption of ammonia molecules on the surface of active layer.	65

LIST OF TABLES

Table 1.1 Advantages and disadvantages of inorganic materials	5
Table 1.2 Comparison between small molecule and polymers type of organic materials....	9
Table 1.3 Types of organic semiconducting material, some examples and their applications [22][23].	9
Table 1.4 Comparison between organic and inorganic semiconducting materials.....	10
Table 1.5 Resistance of the device according to the type of material used and target gas	21
Table 1.6 Comparison of spin coating and FTM for thin film deposition	24
Table 2.1 Optical parameters of fabricated photodetector	42
Table 2.2 Comparison with other visible photodetector.....	44
Table 3.1 Comparison of the optical parameters of white light photodetectors.....	52
Table 4.1 Gas sensing performance of ammonia sensor	63

