

LIST OF FIGURES

Figure No.	Figure Caption	Page No.
Figure 1.1	Greenhouse gas emissions by economic sectors	5
Figure 1.2	World gross electricity production by source in 2016	5
Figure 1.3	Schematics of passive distribution network	8
Figure 1.4	Representation of active distribution network	8
Figure 1.5	(a) Single line diagram of distribution network components (b) Series feeder component connection representation	9
Figure 1.6	Voltage profile along a feeder supplying residential loads	15
Figure 1.7	Proposed smart VVC framework for Active Distribution Network	17
Figure 1.8	Voltage distribution along the feeder length with and without CVR	18
Figure 1.9	Interest cycle of CVR	19
Figure 1.10	Centralized and decentralized controls	23
Figure 2.1	Proposed substation based smart grid enabled CVR	40
Figure 2.2	Schematics of LDC mechanism	41
Figure 2.3	Capacitor Banks Controller with monitored devices	44
Figure 2.4	Peak real power consumption with and without CVR for different load models	48
Figure 2.5	Peak real power losses with and without CVR for different load models	48
Figure 2.6	Flowchart of VVC operation for CVR mode	51
Figure 2.7	Flow chart for optimization Using Autoadd	52
Figure 2.8	Peak demand and peak Losses with ZIP load model	55
Figure 2.9	Peak demand and peak losses with load model 4	56
Figure 2.10	Percentage load demand in peak during CVR operation	57
Figure 3.1	PV Inverter P/Q Capability Curve	62
Figure 3.2	Volt-VAR droop characteristics	64
Figure 3.3	Flow chart of VVC mode of operation	67

Figure 3.4	Modified IEEE 123 node distribution test feeder	69
Figure 3.5	Load demand profile for 24 hours	71
Figure 3.6	Active power demand at feeder head in all modes of operation in Case-I (Peak demand Hours)	72
Figure 3.7	Minimum node voltage profile in all modes of operation in Case-I (Peak demand Hours)	74
Figure 3.8	P and Q power feed by PV system during Mode-3 operation in Case-I (Peak demand Hours)	75
Figure 3.9	Active power losses and inverter losses during Mode-3 operation in Case-I (Peak demand Hours)	76
Figure 3.10	Active power demand at feeder head in all modes of operation in Case-II (whole day operation)	78
Figure 3.11	Minimum node voltage profile in all modes of operation in Case-II (whole day operation)	78
Figure 3.12	Active power losses during Mode-3 operation in Case-II (whole day operation)	79
Figure 3.13	Active and reactive power feed by PV system during Mode-3 operation Case-II (whole day operation)	80
Figure 3.14	Tap Position of OLTC transformer in Case II for whole day operation	80
Figure 3.15	Tap Positions of AVR-1 in Case II for whole day operation	80
Figure 3.16	Tap Positions of AVR-2 (in Case II for whole day operation)	81
Figure 3.17	Tap Positions of AVR-3 in Case II for whole day operation	81
Figure 4.1	Proposed closed loop VVO based smart grid enabled CVR	85
Figure 4.2	Schematic layout of CES system	89
Figure 4.3	Charging /discharging control strategy of BMS	91
Figure 4.4	CES power flow control	92
Figure 4.5	Interacting framework of OpenDSS and MATLAB platforms.	99

Figure 4.6	Flowchart of CVR methods implementation (a) Traditional CVR Approach (b) SG enabled VVO based CVR	100
Figure 4.7	(a) Modified IEEE 123 node distribution test feeder (b) Secondary distribution system (SDS) configuration connect to CES at POC node 65	10.3
Figure 4.8	Annual load variation in percentage	105
Figure 4.9	Wind power generation at node 95 and node 151 with varying load demand annually	106
Figure 4.10	Distributions of peak load hours throughout the year.	108
Figure 4.11	Iteration wise convergence characteristics for (a) Case-2 (VVO with CVR) (b) Case-3 (CVR with CES)	111
Figure 4.12	Feeder lowest voltage profile in different cases with varying load demand annually (a) Case 1 (without CVR) (b) Case 2 (with VVO based CVR) (c) Case 3 (CVR with CES)	115
Figure 4.13	CES Active and reactive power profile	115
Figure 4.14	Energy savings (kWh) in Case 2 and Case 3 with varying load demand annually	116
Figure 5.1	Proposed substation based closed loop CVR	123
Figure 5.2	Volt/VAR droop characteristics	130
Figure 5.3	Flow chart of implementation of three stages of proposed method	132
Figure 5.4	Modified IEEE 123 node distribution test feeder	134
Figure 5.5	Hourly load demand and grid electricity price curve	135
Figure 5.6	(a) Pareto dominance front for mode-2 (b) Pareto dominance front for CVR with PV	138
Figure 5.7	Active (kW) power demand reduction with different % V_{CVR} at peak load during Mode-2 operation	139
Figure 5.8	Active (kW) power demand reduction with different % V_{CVR} at peak load during Mode-3 operation and PV only	139
Figure 5.9	Active power profile of PV power systems	142

Figure 5.10	Optimal reactive power support from PV inverters	143
Figure 5.11	OLTC tap position of all modes of operation.	143
Figure 5.12	CVR factors in terms kW, kWh, INR/\$ under Mode-2, and Mode-3.	144
Figure 5.13	Lowest voltage profile at node 114a and compensated Qsupport	147
Figure 5.14	Active power losses and inverter losses profile due to PV1 active power reduction	147
Figure 5.15	Active power losses and inverter losses profile due to PV1 and PV2 both active power reduction	148
Figure 6.1	Time horizon-based model predictive control	156
Figure 6.2	Illustration of model predictive control	157
Figure 6.3	Active and reactive power capability of EV inverter	160
Figure 6.4	Flowchart of MP-VVO execution in STSC	167
Figure 6.5	Implementation of the proposed coordinated scheme	169
Figure 6.6	Modified IEEE 34 bus distribution system	170
Figure 6.7	EV load profiles	170
Figure 6.8	Forecasted load and solar irradiance	171
Figure 6.9	Grid price over a day	172
Figure 6.10	Lowest voltage under (a) case 1 and case 2 (b) case 3 and case 4	176
Figure 6.11	Power demand and CVR savings under (a) case 1 and case 2, and (b) case 3 and case 4.	177
Figure 6.12	Reactive power support from PV/EV smart inverter under (a) case 2 and (b) case 4.	178
Figure 6.13	Lowest voltage profile and compensated VAR support from PV inverters	180
Figure 6.14	Lowest voltage profile and compensated VAR support from PV and EV inverters.	180
Figure 6.15	Schematic of RTDS (both software and hardware)	182
Figure 6.16	Lowest voltage profile without and with droop controllers.	183

Figure 6.17	PV inverter reactive power compensation without and with droop controls	183
Figure 6.18	Lowest voltage profile with PV and EV inverters VAR support	184
Figure 6.19	Figure 6.19. Compensated VAR support from PV2 and EV inverter at node 890	185
Figure 7.1	Multi-timescale horizon	190
Figure 7.2	Schematic of event-driven predictive framework	191
Figure 7.3	Adaptive Volt/VAR droop characteristics	197
Figure 7.4	Framework of real-time co-simulation platform	199
Figure 7.5	Coordinated three-layer hierarchical dispatching structure	202
Figure 7.6	Implementation flowchart of the proposed methodology in real-time	203
Figure 7.7	Modified IEEE 123-node distribution test feeder	206
Figure 7.8	Real and forecasted load demand profile for a day	207
Figure 7.9	Real and forecasted solar irradiation profile for a day	207
Figure 7.10	Active power demand and percentage CVR power savings	211
Figure 7.11	Lowest feeder voltage profile at Node 114a without control, conventional droop controller, and adaptive droop controllers.	213
Figure 7.12	Per phase additional reactive power compensation from PV inverters	213
Figure 7.13	Figure 7.13 Voltage at PV3 node No control, with conventional droop and with adaptive droop control	214