

LIST OF FIGURES

Figure No.	Caption	Page No.
Figure 2.1	Various basic loading modes in fracture mechanics (a) Opening mode (b) Sliding mode (c) Tearing mode	17
Figure 2.2	Coordinate system at a crack tip region	19
Figure 2.3	Crack tip opening displacement	25
Figure 2.4	Comparison of plane stress and plane strain plastic zone boundaries	29
Figure 3.1	Reference and deformed configurations	54
Figure 4.1	The typical definition of the hardening-softening-hardening flow stress function with the transition strains denoted by ϵ_1 and ϵ_2 and the slope of the three piece wise linear functions given by h_1 , h_2 and h_3 , respectively	71
Figure 5.1	The condensation of internal node in quadrilateral element comprised of four crossed constant strain triangular elements	82
Figure 5.2	Triangular finite element	83
Figure 5.3	Geometry used in the finite element simulation of small scale yielding with K-field boundary conditions; a) Full geometry and b) Portion of the geometry showing the crack tip.	86
Figure 5.4	Triangular finite element and it's representation in the local coordinate system	88
Figure 5.5	The variation of hardness function $g(\epsilon_p)$ with plastic strain ϵ_p . a) material B ($h_2 = h_3 = 5.0$) and material C ($h_2 = h_3 = 1.0$), b) material E ($h_2 = -3.90$, $h_3 = 15.0$) and material G	92

$$(h_2 = -3.90, h_3 = 15.0, \varepsilon_2 = 5.0)$$

Figure 6.1	Cyclic loading used in present fatigue crack simulation	98
Figure 6.1A	Typical mesh used in the finite element simulation (near tip mesh)	99
Figure 6.2	Crack-tip opening displacement $\delta_t (= b/b_0 - 1)$ versus applied J -integral, J_{app} in material B; a) 22 x 54 quadrilateral mesh, b) 22 x 64 quadrilateral mesh, c) 22 x 74 quadrilateral mesh	100-101
Figure 6.3	Plastic strain distribution for plastically compressible solid, material B, $\alpha_p = 0.28$, a) 22 x 54 quadrilateral mesh, b) 22 x 64 quadrilateral mesh, c) 22 x 74 quadrilateral mesh	101-102
Figure 6.4	Stress distribution for a growing crack in material B, plastically incompressible, applied J -integral, $J_{app}/(\sigma_0 b_0) = 2.25$	103
Figure 6.5	Curves of crack-tip opening displacement $(b/b_0 - 1)$ versus the applied J -integral, J_{app} for plastically incompressible and compressible hardening solid, a) Material B. b) Material C	104
Figure 6.6	Curves of crack-tip opening displacement $(b/b_0 - 1)$ versus the applied J -integral, J_{app} for plastically incompressible and compressible solids. a) Material E. b) Material G	105
Figure 6.7	Distribution of plastic strain, ε_p , for material B with $J_{app}/(\sigma_0 b_0) = 2.25$ a) Plastically incompressible solid, $\alpha_p = 0.333333$. b) Plastically compressible solid, $\alpha_p = 0.28$	108
Figure 6.8	Distribution of plastic strain, ε_p , for material G with $J_{app}/(\sigma_0 b_0) = 2.25$ a) Plastically incompressible solid, $\alpha_p = 0.333333$. b) Plastically compressible solid, $\alpha_p = 0.28$	108

Figure 6.9	Field distributions in the crack tip vicinity for material B (a hardening material) with $\alpha_p = 0.28$ at $J_{app}/(\sigma_0 b_0) = 2.25$. a) Plastic strain, ε_p b) Hydrostatic stress, σ_h/σ_0	110
Figure 6.10	Strain distributions in the crack tip vicinity for material E at $J_{app}/(\sigma_0 b_0) = 2.25$. a) Distribution of ε_p for a plastically incompressible solid, $\alpha_p = 0.333333$. b) Distribution of ε_p for a plastically compressible solid, $\alpha_p = 0.28$. c) Distribution of ε_{vol} for a plastically compressible solid, $\alpha_p = 0.28$	111-112
Figure 6.11	Distributions of normalized hydrostatic stress σ_h/σ_0 in the crack tip vicinity for material E at $J_{app}/(\sigma_0 b_0) = 2.25$. a) Plastically incompressible solid, $\alpha_p = 0.333333$. b) Plastically compressible solid, $\alpha_p = 0.28$	113
Figure 6.12	Distributions of normalized effective stress measures in the crack tip vicinity for material E at $J_{app}/(\sigma_0 b_0) = 2.25$. a) σ_e/σ_0 for a plastically incompressible solid, $\alpha_p = 0.333333$. b) σ_e/σ_0 for a plastically compressible solid, $\alpha_p = 0.28$. c) σ_M/σ_0 for a plastically compressible solid, $\alpha_p = 0.28$	114-115
Figure 6.13	Distributions of plastic strain, ε_p in the crack tip vicinity for material G at $J_{app}/(\sigma_0 b_0) = 2.25$. a) Plastically incompressible solid, $\alpha_p = 0.333333$. b) Plastically compressible solid, $\alpha_p = 0.28$. c) Distribution of ε_{vol} for a plastically compressible solid, $\alpha_p = 0.28$	117-118
Figure 6.14	Distributions of normalized hydrostatic stress σ_h/σ_0 in the crack tip vicinity for material G at $J_{app}/(\sigma_0 b_0) = 2.25$. a) Plastically incompressible solid, $\alpha_p = 0.333333$. b) Plastically compressible solid, $\alpha_p = 0.28$	119-120
Figure 6.15	Distributions of normalized effective stress measures in the	121-122

crack tip vicinity for material G at $J_{app}/(\sigma_0 b_0) = 2.25$. a) σ_e/σ_0 for a plastically incompressible solid, $\alpha_p = 0.333333$. b) σ_e/σ_0 for a plastically compressible solid, $\alpha_p = 0.28$. c) σ_M/σ_0 for a plastically compressible solid, $\alpha_p = 0.28$

- Figure 6.16 Crack-tip opening displacement $\delta_t (= b/b_0 - 1)$ versus applied J -integral, J_{app} in material B with $K_{max} = 0.5$ and $K_{min} = 0$; a) Plastically incompressible solid b) Plastically compressible solid, $\alpha_p = 0.28$ (up to 10th cycle) 125
- Figure 6.17 Crack-tip opening displacement $\delta_t (= b/b_0 - 1)$ versus applied J -integral, J_{app} in material B with $K_{max} = 1.0$ and $K_{min} = 0$; a) Plastically incompressible solid b) Plastically compressible solid, $\alpha_p = 0.28$ (up to 10th cycle) 125
- Figure 6.18 Crack-tip opening displacement $\delta_t (= b/b_0 - 1)$ versus applied J -integral, J_{app} in material B with $K_{max} = 1.5$ and $K_{min} = 0.5$; a) Plastically incompressible solid b) Plastically compressible solid, $\alpha_p = 0.28$ (up to 10th cycle) 126
- Figure 6.19 Crack-tip opening displacement $\delta_t (= b/b_0 - 1)$ versus applied J -integral, J_{app} in material E with $K_{max} = 0.5$ and $K_{min} = 0$; a) Plastically incompressible solid b) Plastically compressible solid, $\alpha_p = 0.28$ (up to 10th cycle) 126
- Figure 6.20 Crack-tip opening displacement $\delta_t (= b/b_0 - 1)$ versus applied J -integral, J_{app} in material E with $K_{max} = 1.0$ and $K_{min} = 0$; a) Plastically incompressible solid b) Plastically compressible solid, $\alpha_p = 0.28$ (up to 10th cycle) 127
- Figure 6.21 Crack-tip opening displacement $\delta_t (= b/b_0 - 1)$ versus applied J -integral, J_{app} in material E with $K_{max} = 1.5$ and $K_{min} = 0.5$; a) Plastically incompressible solid b) Plastically compressible solid, $\alpha_p = 0.28$ (up to 10th cycle) 127

- Figure 6.22 Crack-tip opening displacement $\delta_t (= b/b_0 - 1)$ versus applied J -integral, J_{app} in material B with $K_{max} = 2.0$ and $K_{min} = 0$;
a) Plastically incompressible solid b) Plastically compressible solid, $\alpha_p = 0.28$, with overload, (up to 10th cycle) 128
- Figure 6.23 Crack-tip opening displacement $\delta_t (= b/b_0 - 1)$ versus applied J -integral, J_{app} in material E with $K_{max} = 2.0$ and $K_{min} = 0$;
a) Plastically incompressible solid b) Plastically compressible solid, $\alpha_p = 0.28$, with overload, (up to 10th cycle) 129
- Figure 6.24 Crack-tip deformations for plastically incompressible solid, material B, $K_{max} = 2.0$ and $K_{min} = 0$; a) At the end of loading phase, $K \rightarrow K_{max}$ b) At the end of unloading phase, $K \rightarrow K_{min}$ for 5th cycle 131
- Figure 6.25 Crack-tip deformations for plastically compressible solid, material B, $\alpha_p = 0.28$, $K_{max} = 2.0$ and $K_{min} = 0$; a) At the end of loading phase, $K \rightarrow K_{max}$ b) At the end of unloading phase, $K \rightarrow K_{min}$ for 5th cycle 132
- Figure 6.26 Crack-tip deformations for plastically incompressible solid, material E, $K_{max} = 2.0$ and $K_{min} = 0$; a) At the end of loading phase, $K \rightarrow K_{max}$ b) At the end of unloading phase, $K \rightarrow K_{min}$ for 5th cycle 133
- Figure 6.27 Crack-tip deformations for plastically compressible solid, material E, $\alpha_p = 0.28$, $K_{max} = 2.0$ and $K_{min} = 0$; a) At the end of loading phase, $K \rightarrow K_{max}$ b) At the end of unloading phase, $K \rightarrow K_{min}$ for 5th cycle 134
- Figure 6.28 Normalized crack extension $(\Delta a/b_0)$ versus normalized time (t/t_0) in plastically incompressible and compressible solids, 136-137

material B; a) $K_{\max} = 1.0$ and $K_{\min} = 0$ b) $K_{\max} = 2.0$ and $K_{\min} = 0$ c) $K_{\max} = 1.5$ and $K_{\min} = 0.5$ d) $K_{\max} = 2.0$ and $K_{\min} = 1.0$

- Figure 6.29 Normalized crack extension ($\Delta a/b_0$) versus normalized time (t/t_0) in plastically incompressible and compressible solids, material E; a) $K_{\max} = 1.0$ and $K_{\min} = 0$ b) $K_{\max} = 2.0$ and $K_{\min} = 0$ c) $K_{\max} = 1.5$ and $K_{\min} = 0.5$ d) $K_{\max} = 2.0$ and $K_{\min} = 1.0$ 137-138
- Figure 6.30 Normalized crack extension ($\Delta a/b_0$) versus normalized time (t/t_0) in plastically incompressible and compressible solids with overloading, material B; a) $K_{\max} = 1.0$ and $K_{\min} = 0$ b) $K_{\max} = 2.0$ and $K_{\min} = 0$ 139
- Figure 6.31 Normalized crack extension ($\Delta a/b_0$) versus normalized time (t/t_0) in plastically incompressible and compressible solids with overloading, material E; a) $K_{\max} = 1.0$ and $K_{\min} = 0$ b) $K_{\max} = 2.0$ and $K_{\min} = 0$ 139
- Figure 6.32 Fatigue crack growth da/dN versus ΔK for plastically compressible solids, $\alpha_p = 0.28$, (a) Material B and (b) Material E, (with $R=0$) at 5th cycle 140
- Figure 6.33 Distribution of plastic strain, for plastically incompressible solid, material B, $K_{\max} = 1.0$ and $K_{\min} = 0$; a) At the end of loading phase, $K \rightarrow K_{\max}$ b) At the end of unloading phase, $K \rightarrow K_{\min}$ for 10th cycle 142
- Figure 6.34 Distribution of plastic strain, for plastically compressible solid, material B, $\alpha_p = 0.28$, $K_{\max} = 1.0$ and $K_{\min} = 0$; a) At the end of loading phase, $K \rightarrow K_{\max}$ b) At the end of unloading 143

phase, $K \rightarrow K_{\min}$ for 10th cycle

- Figure 6.35 Distribution of plastic strain, for plastically incompressible solid, material E, $K_{\max} = 1.0$ and $K_{\min} = 0$; a) At the end of loading phase, $K \rightarrow K_{\max}$ b) At the end of unloading phase, $K \rightarrow K_{\min}$ for 10th cycle 143
- Figure 6.36 Distribution of Plastic strain, for plastically compressible solid, material E, $\alpha_p = 0.28$, $K_{\max} = 1.0$ and $K_{\min} = 0$; a) At the end of loading phase, $K \rightarrow K_{\max}$ b) At the end of unloading phase, $K \rightarrow K_{\min}$ for 10th cycle 144
- Figure 6.37 Distribution of plastic strain, for plastically incompressible solid, material B, $K_{\max} = 1.0$ and $K_{\min} = 0$; at the end of loading phase in 5th cycle a) With overload b) Without overload 145
- Figure 6.38 Distribution of plastic strain, for plastically compressible solid, material B, $\alpha_p = 0.28$, $K_{\max} = 1.0$ and $K_{\min} = 0$; at the end of loading phase in 5th cycle a) With overload b) Without overload 145
- Figure 6.39 Distribution of plastic strain, for plastically incompressible solid, material E, $K_{\max} = 1.0$ and $K_{\min} = 0$; at the end of loading phase in 5th cycle a) With overload b) Without overload 146
- Figure 6.40 Distribution of plastic strain, for plastically compressible solid, material E, $\alpha_p = 0.28$, $K_{\max} = 1.0$ and $K_{\min} = 0$; at the end of loading phase in 5th cycle a) With overload b) Without overload 146
- Figure 6.41 Plastic strain distribution for plastically compressible solid, material B, $\alpha_p = 0.28$, a) $K_{\max} = 0.5$ and $K_{\min} = 0$ b) $K_{\max} = 1.0$ and $K_{\min} = 0$ c) $K_{\max} = 1.5$ and $K_{\min} = 0.5$; at the end of loading phase for 10th cycle 148-149

Figure 6.42	Plastic strain distribution for plastically compressible solid, material E, $\alpha_p = 0.28$, a) $K_{\max} = 0.5$ and $K_{\min} = 0$ b) $K_{\max} = 1.0$ and $K_{\min} = 0$ c) $K_{\max} = 1.5$ and $K_{\min} = 0.5$; at the end of loading phase for 10 th cycle	149-150
Figure 6.43	Hydrostatic stress for plastically incompressible solid, material B, $K_{\max} = 1.0$ and $K_{\min} = 0$; a) At the end of loading phase b) At the end of unloading phase for 10 th cycle	152
Figure 6.44	Hydrostatic stress for plastically compressible solid, $\alpha_p = 0.28$, material B, $K_{\max} = 1.0$ and $K_{\min} = 0$; a) At the end of loading phase b) At the end of unloading phase for 10 th cycle	153
Figure 6.45	Hydrostatic stress for plastically incompressible solid, material E, $K_{\max} = 1.0$ and $K_{\min} = 0$; a) At the end of loading phase b) At the end of unloading phase for 10 th cycle	154
Figure 6.46	Hydrostatic stress for plastically compressible solid, $\alpha_p = 0.28$, material E, $K_{\max} = 1.0$ and $K_{\min} = 0$; a) At the end of loading phase b) At the end of unloading phase for 10 th cycle	155
Figure 6.47	Distributions of normalized effective stress measures for plastically compressible solid, $\alpha_p = 0.28$, material B, $K_{\max} = 1.0$ and $K_{\min} = 0$; a) At the end of loading phase b) At the end of unloading phase for 10 th cycle	156
Figure 6.48	Distributions of normalized effective stress measures for plastically compressible solid, $\alpha_p = 0.28$, material E, $K_{\max} = 1.0$ and $K_{\min} = 0$; a) At the end of loading phase b) At the end of unloading phase for 10 th cycle	157
Figure 6.49	Crack-tip opening displacement $\delta_t (= b/b_0 - 1)$ versus applied J -integral, J_{app} , $J_{\text{app}}/(\sigma_0 b_0) = 2.25$ a) Material B, b) Material	159-160

E, plastically incompressible and compressible conditions ($\alpha_p = \beta_p = 0.28$), c) Material E, plastically incompressible and compressible conditions ($\alpha_p = 0.28$ & $\beta_p = 0.20$)

- Figure 6.50 Distribution of accumulated plastic strain ϵ_p at the crack tip of material B, $J_{app}/(\sigma_0 b_0) = 2.25$. a) Plastically incompressible, b) Plastically compressible ($\alpha_p = \beta_p = 0.28$), c) plastically compressible ($\alpha_p = 0.28$ & $\beta_p = 0.20$) 161-162
- Figure 6.51 Distribution of accumulated plastic strain ϵ_p at the crack tip of material E, $J_{app}/(\sigma_0 b_0) = 2.25$. a) Plastically incompressible, b) Plastically compressible ($\alpha_p = \beta_p = 0.28$), c) plastically compressible ($\alpha_p = 0.28$ & $\beta_p = 0.20$) 163-164
- Figure 6.52 Distribution of volumetric strain ϵ_{vol} at the crack tip, $J_{app}/(\sigma_0 b_0) = 2.25$. material E a) $\alpha_p = 0.28$ & $\beta_p = 0.20$ b) $\alpha_p = \beta_p = 0.28$ 165
- Figure 6.53 Normalized hydrostatic stress distribution at the crack tip vicinity for material E, $J_{app}/(\sigma_0 b_0) = 2.25$. a) Plastically incompressible, b) Plastically compressible ($\alpha_p = \beta_p = 0.28$), c) Plastically compressible ($\alpha_p = 0.28$ & $\beta_p = 0.20$) 167-168
- Figure 6.54 Effective stress distribution at the crack tip vicinity for material E, $J_{app}/(\sigma_0 b_0) = 2.25$. a) Plastically compressible ($\alpha_p = \beta_p = 0.28$), b) Plastically compressible ($\alpha_p = 0.28$ & $\beta_p = 0.20$) 169