

## **Table of Contents**

|                             |              |
|-----------------------------|--------------|
| List of Figures.....        | <i>xiii</i>  |
| List of Tables .....        | <i>xvi</i>   |
| List of Abbreviations ..... | <i>xvii</i>  |
| Perface.....                | <i>xviii</i> |

### **Chapter 1 Introduction**

|  |           |
|--|-----------|
| 1.1 Energy Crisis and Global Warming.....                    | <b>1</b>  |
| 1.2 Historical Background.....                               | <b>3</b>  |
| 1.3 Types of fuel cells .....                                | <b>5</b>  |
| 1.3.1 Alkaline Fuel Cells .....                              | <b>5</b>  |
| 1.3.2 Phosphoric Acid Fuel Cells .....                       | <b>6</b>  |
| 1.3.3 Proton Exchange Membrane Fuel Cells .....              | <b>7</b>  |
| 1.3.4 Molten Carbonate Fuel Cells .....                      | <b>9</b>  |
| 1.3.5 Solid Oxide Fuel Cells.....                            | <b>10</b> |
| 1.4 SOFC Design .....  | <b>13</b> |
| 1.5 Key Challenges of SOFCs.....                             | <b>15</b> |
| 1.6 Fluorite Electrolytes.....                               | <b>16</b> |
| 1.6.1 Stablized ZrO <sub>2</sub> .....                       | <b>17</b> |
| 1.6.2 Doped Ceria .....                                      | <b>18</b> |
| 1.6.3 Bi <sub>2</sub> O <sub>3</sub> -based Electrolyte..... | <b>19</b> |
| 1.7 Perovskite Electrolyte .....                             | <b>20</b> |
| 1.7.1 LaGaO <sub>3</sub> based electrolyte .....             | <b>21</b> |
| 1.7.2 NBT based Electrolyte .....                            | <b>22</b> |
| 1.7.3 Other Electrolyte .....                                | <b>23</b> |
| 1.8 Scope of thesis.....                                     | <b>25</b> |
| References.....  | <b>26</b> |

### **Chapter 2**

|   |           |
|---|-----------|
| Experimental Techniques .....                   | <b>39</b> |
| 2.1 Overview .....                              | <b>39</b> |
| 2.2 Synthesis Technique.....                    | <b>39</b> |
| 2.2.1 Solid state reaction synthesis route..... | <b>39</b> |
| 2.2.2 Sol-Gel Auto Combustion Synthesis .....   | <b>40</b> |
| 2.2.3 Palletization .....                       | <b>41</b> |

|  |           |
|--|-----------|
| <b>2.3 Material Characterization Techniques .....</b>                          | <b>42</b> |
| <b>2.3.1 X-Ray Diffraction.....</b>  | <b>43</b> |
| <b>2.3.2 Phase Formation and Crystal Structure Studies by Powder XRD .....</b> | <b>44</b> |
| <b>2.3.3 Field Emission Scanning Electron Microscope .....</b>                 | <b>45</b> |
| <b>2.3.4 High-Resolution Transmission Electron Microscopy(HRTEM).....</b>      | <b>45</b> |
| <b>2.3.5 Energy Dispersive X-RAY Spectroscopy(EDX) .....</b>                   | <b>47</b> |
| <b>2.3.6 Thermogravimetric Analysis(TGA) .....</b>                             | <b>48</b> |
| <b>2.3.7 Differential Scanning Calorimetry (DSC).....</b>                      | <b>48</b> |
| <b>2.3.8 Raman Spectroscopy .....</b>  | <b>49</b> |
| <b>2.3.9 FTIR Spectroscopy .....</b>   | <b>50</b> |
| <b>2.3.10 Electrochemical Impedance Spectroscopy (EIS) .....</b>               | <b>50</b> |
| <b>2.3.11 Conductivity Measurement Using EIS .....</b>                         | <b>53</b> |
| <b>References.....</b>   | <b>54</b> |

### Chapter 3

|   |           |
|---|-----------|
| <b>KTaO<sub>3</sub> Based Perovskite material for Oxide Ion Electrolyte for SOFCs .....</b> | <b>55</b> |
| <b>3.1 Introduction.....</b>  | <b>55</b> |
| <b>3.2 Material Synthesis &amp; Characterization .....</b>                                  | <b>55</b> |
| <b>3.3 Thermal Study.....</b>   | <b>56</b> |
| <b>3.4 Crystal Structure Study.....</b>   | <b>58</b> |
| <b>3.5 SEM/EDX Study .....</b>  | <b>60</b> |
| <b>3.6 EIS Study .....</b>  | <b>61</b> |
| <b>3.7 Conclusion .....</b>   | <b>66</b> |
| <b>References.....</b>  | <b>67</b> |

### Chapter 4

|  |           |
|--|-----------|
| <b>Doped BaZrO<sub>3</sub> as oxide ion conductor.....</b> | <b>69</b> |
| <b>4.1 Introduction.....</b>                               | <b>69</b> |
| <b>4.2 Material Synthesis and Characterization .....</b>   | <b>70</b> |
| <b>4.3 Result and Discussion .....</b>                     | <b>71</b> |
| <b>4.3.1 XRD Study .....</b>                               | <b>71</b> |
| <b>4.3.2 Thermal Study.....</b>                            | <b>77</b> |
| <b>4.3.3 SEM Study .....</b>                               | <b>78</b> |
| <b>4.3.4 TEM Study.....</b>                                | <b>79</b> |

|                            |    |
|----------------------------|----|
| 4.3.5 Impedance Study..... | 81 |
| 4.4 Conclusion.....        | 86 |
| References.....            | 87 |

## Chapter 5

|   |     |
|---|-----|
| Study of SrTiO <sub>3</sub> based Pervoskite Material for developing superior oxide-ion electrolyte ..... | 89  |
| 5.1 Introduction.....   | 89  |
| 5.2 Material Synthesis and characterization .....   | 89  |
| 5.3 Crystal Structure Study.....  | 91  |
| 5.4 Thermal Study.....  | 94  |
| 5.5 SEM Study .....   | 95  |
| 5.6 Impedance Study.....  | 96  |
| 5.8 Conclusion .....  | 99  |
| References.....   | 100 |

## Chapter 6

|  |     |
|--|-----|
| Bi & Gd Co-Substituted Zirconia based Oxide Ion Conductor..... | 103 |
| 6.1 Introduction.....  | 103 |
| 6.2 Material Synthesis .....                                   | 105 |
| 6.3 Material Characterization.....                             | 105 |
| 6.4 Crystal Structure Analysis .....                           | 106 |
| 6.5 SEM/EDX Study .....  | 109 |
| 6.6 Raman Spectroscopy Analysis .....                          | 111 |
| 6.7 Impedance Study.....                                       | 112 |
| 6.8 Thermal Study.....   | 118 |
| 6.9 Conclusion .....   | 123 |
| References.....  | 125 |

## Chapter 7

|                                |     |
|--------------------------------|-----|
| Summary and Future Scope ..... | 131 |
| 7.1 Summary.....               | 131 |
| 7.2 Future Scope .....         | 134 |

## LIST OF FIGURES

| Figure No.         | Figure description  | Page No. |
|--------------------|---|----------|
| <b>Figure 1.1</b>  | Energy Consumption World Wide 2000 to 2018, with a forecast till 2050* (in extra joules)  | 1        |
| <b>Figure 1.2</b>  | Electricity Generation by Source  | 2        |
| <b>Figure 1.3</b>  | Comparison of efficiencies of conventional power generation & fuel cells.   | 3        |
| <b>Figure 1.4</b>  | Alkaline fuel cell  | 6        |
| <b>Figure 1.5</b>  | Phosphoric Acid & PEM fuel cell   | 9        |
| <b>Figure 1.6</b>  | Molten carbonate fuel cell  | 10       |
| <b>Figure 1.7</b>  | Solid Oxide Fuel Cell   | 13       |
| <b>Figure 1.8</b>  | Tubular Design of SOFCs   | 14       |
| <b>Figure 1.9</b>  | Planar Design of SOFCs  | 14       |
| <b>Figure 1.10</b> | Fluorite structure  | 16       |
| <b>Figure 1.11</b> | Perovskite Structure  | 20       |
| <b>Figure 2.1</b>  | Solid State Synthesis Route   | 40       |
| <b>Figure 2.2</b>  | Sol-Gel Auto Combustion   | 41       |
| <b>Figure 2.3</b>  | Pelletization Steps   | 42       |
| <b>Figure 2.4</b>  | Characterization techniques used  | 42       |
| <b>Figure 2.5</b>  | Demonstration for Bragg's Law   | 43       |
| <b>Figure 2.6</b>  | Interaction of electrons with sample  | 47       |
| <b>Figure 2.7</b>  | Nyquist Plot for ionic solids   | 52       |
| <b>Figure 2.8</b>  | Conductivity Test station   | 53       |
| <b>Figure 3.1</b>  | Thermogravimetric analysis (TGA) curve of $\text{KTa}_{0.4}\text{Ti}_{0.3}\text{Ge}_{0.3}\text{O}_{2.7}$  | 57       |
| <b>Figure 3.2</b>  | FT-IR spectra of $\text{KTa}_{0.4}\text{Ti}_{0.3}\text{Ge}_{0.3}\text{O}_{2.7}$   | 57       |
| <b>Figure 3.3</b>  | Powder XRD pattern (a) $\text{KTa}_{0.6}\text{Ti}_{0.4}\text{O}_{2.8}$ (b) $\text{KTa}_{0.6}\text{Ge}_{0.4}\text{O}_{2.8}$ and (c) $\text{KTa}_{0.4}\text{Ti}_{0.3}\text{Ge}_{0.3}\text{O}_{2.7}$                     | 59       |
| <b>Figure 3.4</b>  | Rietveld refined powder XRD profile of (a) $\text{KTa}_{0.6}\text{Ti}_{0.4}\text{O}_{2.8}$ (b) $\text{KTa}_{0.6}\text{Ge}_{0.4}\text{O}_{2.8}$ and (c) $\text{KTa}_{0.4}\text{Ti}_{0.3}\text{Ge}_{0.3}\text{O}_{2.7}$ | 60       |

|                      |   |       |
|----------------------|---|-------|
| <b>Figure 3.5</b>    | SEM image $\text{KTa}_{0.4}\text{Ti}_{0.3}\text{Ge}_{0.3}\text{O}_{2.7}$ (a) Powder (b) top view of the pellet (c) Cross-section of the pellets and (d) Image of EDX spectra  | 61    |
| <b>Figure 3.6</b>    | Arrhenius plot of (a) various compositions, (b) $\text{KTa}_{0.4}\text{Ti}_{0.3}\text{Ge}_{0.3}\text{O}_{2.7}$ in different mediums, (c) comparison of existing intermediate temperature Oxide-ion electrolytes in air  | 64-65 |
| <b>Figure 3.7</b>    | Cole-Cole plot of $\text{KTa}_{0.4}\text{Ti}_{0.3}\text{Ge}_{0.3}\text{O}_{2.7}$ at $600^\circ\text{C}$ . Inset shows the plot between 30 kHz to 20Hz frequencies.  | 65    |
| <b>Figure 3.8</b>    | The dielectric constant of $\text{KTa}_{0.4}\text{Ti}_{0.3}\text{Ge}_{0.3}\text{O}_{2.7}$ at different temperatures and frequencies.  | 66    |
| <b>Figure 4.1</b>    | Photograph of synthesized powder (off-white colour) & $\text{BaZrO}_3$  | 71    |
| <b>Figure 4.2</b>    | Powder XRD pattern (a) $\text{BaZrO}_3$ (b) $\text{Ba}_{0.9}\text{K}_{0.1}\text{Zr}_{0.9}\text{Ga}_{0.1}\text{O}_{2.9}$ (K10G10) (c) $\text{Ba}_{0.85}\text{K}_{0.15}\text{Zr}_{0.85}\text{Ga}_{0.15}\text{O}_{2.85}$ (K15G15) (d) $\text{Ba}_{0.8}\text{K}_{0.2}\text{Zr}_{0.8}\text{Ga}_{0.2}\text{O}_{2.8}$ (K20G20) (e) $\text{Ba}_{0.75}\text{K}_{0.25}\text{Zr}_{0.75}\text{Ga}_{0.25}\text{O}_{2.75}$ (K25G25)           | 72    |
| <b>Figure 3.3</b>    | Systematic peak shift of (011) plane of $\text{Ba}_{1-x}\text{K}_x\text{Zr}_{1-x}\text{Ga}_x\text{O}_{3-x}$ ( $x = 0, 0.1, 0.15, 0.2$ and $0.25$ ) samples with doping.   | 73    |
| <b>Figure 4.4(a)</b> | Rietveld refined powder XRD profile of $\text{Ba}_{0.9}\text{K}_{0.1}\text{Zr}_{0.9}\text{Ga}_{0.1}\text{O}_{2.9}$  | 74    |
| <b>Figure 4.4(b)</b> | Rietveld refined powder XRD profile of $\text{Ba}_{0.85}\text{K}_{0.15}\text{Zr}_{0.85}\text{Ga}_{0.15}\text{O}_{2.85}$   | 75    |
| <b>Figure 4.4(c)</b> | Rietveld refined powder XRD profile of $\text{Ba}_{0.8}\text{K}_{0.2}\text{Zr}_{0.8}\text{Ga}_{0.2}\text{O}_{2.8}$  | 75    |
| <b>Figure 4.4(d)</b> | Rietveld refined powder XRD profile of $\text{Ba}_{0.75}\text{K}_{0.25}\text{Zr}_{0.75}\text{Ga}_{0.25}\text{O}_{2.75}$   | 76    |
| <b>Figure 4.5</b>    | Thermogravimetric analysis (TGA) & DSC curve of $\text{Ba}_{0.8}\text{K}_{0.2}\text{Zr}_{0.8}\text{Ga}_{0.2}\text{O}_{2.8}$   | 78    |
| <b>Figure 4.6</b>    | SEM image $\text{Ba}_{0.8}\text{K}_{0.2}\text{Zr}_{0.8}\text{Ga}_{0.2}\text{O}_{2.8}$ (a) Powder (b) top view of the pellet (c) Cross-section of the pellets and (d) Image of EDX spectra   | 79    |
| <b>Figure 4.7</b>    | (a) & (b) TEM image Powder $\text{Ba}_{0.8}\text{K}_{0.2}\text{Zr}_{0.8}\text{Ga}_{0.2}\text{O}_{2.8}$ (c) SAED pattern from $\text{Ba}_{0.8}\text{K}_{0.2}\text{Zr}_{0.8}\text{Ga}_{0.2}\text{O}_{2.8}$ (d) HRTEM of $\text{Ba}_{0.8}\text{K}_{0.2}\text{Zr}_{0.8}\text{Ga}_{0.2}\text{O}_{2.8}$ Showing (011) planes (e) Elemental mapping of the $\text{Ba}_{0.8}\text{K}_{0.2}\text{Zr}_{0.8}\text{Ga}_{0.2}\text{O}_{2.8}$ | 80    |
| <b>Figure 4.8</b>    | Arrhenius plot for different composition of K and Ga substituted $\text{BaZrO}_3$ i.e. (i) $\text{Ba}_{0.9}\text{K}_{0.1}\text{Zr}_{0.9}\text{Ga}_{0.1}\text{O}_{2.9}$ (K10G10) (ii) $\text{Ba}_{0.85}\text{K}_{0.15}\text{Zr}_{0.85}\text{Ga}_{0.15}\text{O}_{2.85}$ (K15G15) (iii)  | 82    |

|                      |   |       |
|----------------------|---|-------|
|                      | $\text{Ba}_{0.8}\text{K}_{0.2}\text{Zr}_{0.8}\text{Ga}_{0.2}\text{O}_{2.8}$ (K20G20) (iv)<br>$\text{Ba}_{0.75}\text{K}_{0.25}\text{Zr}_{0.75}\text{Ga}_{0.25}\text{O}_{2.74}$ (K25G25)  |       |
| <b>Figure 4.9</b>    | Arrhenius plot of $\text{Ba}_{0.8}\text{K}_{0.2}\text{Zr}_{0.8}\text{Ga}_{0.2}\text{O}_{2.8}$ (BKGZO) in different medium   | 83    |
| <b>Figure 4.10</b>   | comparison of ionic conductivities of existing intermediate temperature Oxide-ion electrolytes in the air   | 83    |
| <b>Figure 4.11</b>   | Cole-Cole plot of $\text{Ba}_{0.8}\text{K}_{0.2}\text{Zr}_{0.8}\text{Ga}_{0.2}\text{O}_{2.8}$ at(a) 400°C (b) 500°C   | 85-86 |
| <b>Figure 5.1</b>    | Powder XRD pattern (a) $\text{SrTiO}_3$ (b) $\text{Sr}_{0.9}\text{K}_{0.1}\text{Ti}_{0.9}\text{Ga}_{0.1}\text{O}_{2.9}$ (SK10G10) (c) $\text{Sr}_{0.85}\text{K}_{0.15}\text{Ti}_{0.85}\text{Ga}_{0.15}\text{O}_{2.85}$ (SK15G15) (d) $\text{Sr}_{0.8}\text{K}_{0.2}\text{Ti}_{0.8}\text{Ga}_{0.2}\text{O}_{2.8}$ (SK20G20) (e) $\text{Sr}_{0.75}\text{K}_{0.25}\text{Ti}_{0.75}\text{Ga}_{0.25}\text{O}_{2.75}$ (SK25G25) | 91    |
| <b>Figure 5.2(a)</b> | Rietveld refined powder XRD profile of $\text{Sr}_{0.9}\text{K}_{0.1}\text{Ti}_{0.9}\text{Ga}_{0.1}\text{O}_{2.9}$  | 92    |
| <b>Figure 5.2(b)</b> | Rietveld refined powder XRD profile of $\text{Sr}_{0.8}\text{K}_{0.2}\text{Ti}_{0.8}\text{Ga}_{0.2}\text{O}_{2.8}$  | 92    |
| <b>Figure 5.3</b>    | Thermogravimetric analysis (TGA) of $\text{Sr}_{0.8}\text{K}_{0.2}\text{Ti}_{0.8}\text{Ga}_{0.2}\text{O}_{2.8}$   | 94    |
| <b>Figure 5.4</b>    | SEM image $\text{Sr}_{0.8}\text{K}_{0.2}\text{Ti}_{0.8}\text{Ga}_{0.2}\text{O}_{2.8}$ (a) Powder (b) pellet (c) EDX image of pallet   | 95    |
| <b>Figure 5.5</b>    | Arrhenius plot of Various compositions $\text{Sr}_{1-x}\text{K}_x\text{Ti}_{1-y}\text{Ga}_y\text{O}_{3-\delta}$   | 98    |
| <b>Figure 5.6</b>    | Comparison of ionic conductivities of existing intermediate Oxide-ion electrolytes in the air   | 98    |
| <b>Figure 6.1</b>    | Powder XRD pattern (i) $\text{Zr}_{0.6}\text{Bi}_{0.2}\text{Gd}_{0.2}\text{O}_{1.8}$ , (ii) $\text{Zr}_{0.6}\text{Bi}_{0.15}\text{Gd}_{0.25}\text{O}_{1.8}$ , (iii) $\text{Zr}_{0.65}\text{Bi}_{0.15}\text{Gd}_{0.2}\text{O}_{1.825}$ , (iv) $\text{Zr}_{0.7}\text{Bi}_{0.15}\text{Gd}_{0.15}\text{O}_{1.85}$ , and (v) $\text{Zr}_{0.6}\text{Bi}_{0.10}\text{Gd}_{0.30}\text{O}_{1.8}$                                   | 107   |
| <b>Figure 6.2</b>    | Rietveld refined powder XRD profile of (i) $\text{Zr}_{0.6}\text{Bi}_{0.2}\text{Gd}_{0.2}\text{O}_{1.8}$ (ii) $\text{Zr}_{0.6}\text{Bi}_{0.10}\text{Gd}_{0.30}\text{O}_{1.8}$   | 108   |
| <b>Figure 6.3</b>    | SEM image $\text{Zr}_{0.6}\text{Bi}_{0.2}\text{Gd}_{0.2}\text{O}_{1.8}$ (a) Powder (b) Top view of the pellet (c) Cross-section of the pallets and (d) EDX image of pallet  | 110   |
| <b>Figure 6.4</b>    | Vacancy mapping through Bi lone pair in cubic fluorite structure  | 111   |
| <b>Figure 6.5</b>    | Raman spectra of (a) monoclinic $\text{ZrO}_2$ and (b) Gd-Bi co-doped cubic Zirconia ( $\text{Zr}_{0.6}\text{Bi}_{0.2}\text{Gd}_{0.2}\text{O}_{1.8}$ )  | 112   |
| <b>Figure 6.6</b>    | Arrhenius plot of various compositions  | 115   |
| <b>Figure 6.7</b>    | Arrhenius plot of $\text{Zr}_{0.6}\text{Bi}_{0.2}\text{Gd}_{0.2}\text{O}_{1.8}$ (ZBGO) in different medium  | 116   |

|                    |   |     |
|--------------------|---|-----|
| <b>Figure 6.8</b>  | Cole-Cole plot of $Zr_{0.6}Bi_{0.2}Gd_{0.2}O_{1.8}$ at 500°C  | 116 |
| <b>Figure 6.9</b>  | Arrhenius plot of comparison of existing intermediate temperature Oxide-ion electrolytes in air                       | 117 |
| <b>Figure 6.10</b> | Powder XRD pattern of $Zr_{0.6}Bi_{0.2}Gd_{0.2}O_{1.8}$ heated in hydrogen atmosphere up 800°C during impedance study | 117 |
| <b>Figure 6.11</b> | TGA & DSC curves of $Zr_{0.6}Bi_{0.2}Gd_{0.2}O_{1.8}$ preheated at 120°C  | 119 |
| <b>Figure 6.12</b> | FT-IR spectra of $Zr_{0.6}Bi_{0.2}Gd_{0.2}O_{1.8}$ preheated at 120 °C  | 119 |
| <b>Figure 6.13</b> | Dielectric constant of $Zr_{0.6}Bi_{0.2}Gd_{0.2}O_{1.8}$ at different temperatures and frequencies                    | 121 |
| <b>Figure 6.14</b> | Dielectric loss of $Zr_{0.6}Bi_{0.2}Gd_{0.2}O_{1.8}$ at different temperatures and frequencies                        | 121 |

## LIST OF TABLES

---

| Table No. | Table description   | Page No. |
|-----------|---|----------|
| Table 1.1 | Comparison of different types of fuel cells   | 12       |
| Table 3.1 | Structural parameter of Ta and Ge doped $\text{KTaO}_3$   | 59       |
| Table 3.2 | $\text{O}^{2-}$ conductivity ( $\sigma$ ) of $\text{KTa}_{1-x-y}\text{Ti}_x\text{Ge}_y\text{O}_{3-\alpha}$ at different temperatures            | 63       |
| Table 4.1 | Structural parameter of K and Ga doped $\text{BaZrO}_3$   | 76       |
| Table 4.2 | $\text{O}^{2-}$ conductivity ( $\sigma$ ) of $\text{Ba}_{1-x}\text{K}_x\text{Zr}_{1-y}\text{Ga}_y\text{O}_{3-\delta}$ at different temperatures | 82       |
| Table 4.3 | Activation Energy of $\text{Ba}_{1-x}\text{K}_x\text{Zr}_{1-y}\text{Ga}_y\text{O}_{3-\delta}$   | 84       |
| Table 5.1 | Structural parameter of K and Ga doped $\text{SrTiO}_3$   | 93       |
| Table 5.2 | $\text{O}^{2-}$ conductivity ( $\sigma$ ) of $\text{Sr}_{1-x}\text{K}_x\text{Ta}_{1-y}\text{Ga}_y\text{O}_{3-\delta}$ at different temperatures | 97       |
| Table 6.1 | Structural parameter of Bi and Gd doped $\text{ZrO}_2$  | 109      |
| Table 6.2 | $\text{O}^{2-}$ conductivity ( $\sigma$ ) of $\text{Zr}_{1-x-y}\text{Bi}_x\text{Gd}_y\text{O}_{2-\delta}$ at different temperatures             | 113      |