

TABLE OF CONTENTS

Abstract	
Acknowledgement	
Table of Contents	
Index of Figures	
Index of tables	
Nomenclature	
CHAPTER 1 INTRODUCTION	1-10
CHAPTER 2 LITERATURE REVIEW AND OBJECTIVES	11-54
2.1 Literature Review	11
2.1.1 Microfluidic Fuel Cell Types/design	11
2.1.2 Microfluidic Fuel Cell Components	13
2.1.2.1 Electrode Materials	13
2.1.2.1.1 Anode Electrocatalysts	13
2.1.2.1.2 Cathode Electrocatalysts	15
2.1.2.2 Fuel, Oxidant, and Electrolytes	15
2.1.2.2.1 Fuel for Anode	15
2.1.2.2.2 Oxidant for Cathode	17
2.1.2.2.3 Electrolytes	19
2.1.3 Electrode Fabrication and Characterization	20
2.1.3.1 Anode Fabrication	20
2.1.3.2 Cathode Fabrication	21
2.1.3.2.1 Air Breathing Cathode	22
2.1.4 Electrode Characterizations	23
2.1.5 Half-cell Analyses	23

2.1.5.1	Anode Cyclic Voltammetry	38
2.1.5.2	Cathode Cyclic Voltammetry	43
2.1.6	Cell Performance	45
2.2	Objectives	53
CHAPTER 3	EXPERIMENTAL	55-68
3.1	Material	55
3.2	Experimental Setup	60
3.2.1	Air Breathing Microfluidic Fuel Cell	60
3.2.2	Half-Cell Studies	61
3.3	Method	63
3.3.1	Preparation of Carbon Cloth/Gas Diffusion Layer (GDL)	63
3.3.2	Electrode Preparation	64
3.3.2.1	Anode	64
3.3.2.2	Preparation of Air Breathing Cathode	64
3.3.2.3	SEM of Electrodes	65
3.3.2.4	Half-cell Analyses Using Potentiostat	66
3.3.3	Air Breathing Microfluidic Fuel Cell	66
3.3.4	Lifetime Analysis of the Microfluidic Fuel Cell	68
CHAPTER 4	MODEL DEVELOPMENT	69-92
4.1	Introduction	69
4.2	Activation Overpotentials	71
4.2.1	Methanol ($\eta_{a,act,MeOH}$)	71
4.2.2	Ethanol ($\eta_{a,act,EtOH}$)	74
4.2.3	Sodium Borohydride ($\eta_{a,act,NaBH_4}$)	76
4.3	Ohmic Over potential (η_{ohm})	79
4.4	Concentration Over potential	80
4.4.1	Anode	80

4.4.1.1 Methanol($\eta_{a,con,MeOH}$)	80
4.4.1.2 Ethanol ($\eta_{a,con,EtOH}$)	83
4.4.1.3 Sodium Borohydride ($\eta_{a,con,NaBH_4}$)	85
4.4.2 Cathode	87
4.5 Model Equation	90
4.5.1 Methanol	90
4.5.2 Ethanol	91
4.5.3 Sodium Borohydride	92
CHAPTER 5 RESULT AND DISCUSSION	93-150
5.1 Scanning Electron Microscope (SEM) of Electrodes	93
5.1.1 Blank Gas Diffusion Layer (GDL)	93
5.1.2 Anode Electrode	95
5.1.3 Cathode Electrode	97
5.2 Half-cell Study	99
5.2.1 Anode	100
5.2.1.1 Effect of Scan Rate	102
5.2.1.2 Effect of Fuel Concentration	105
5.2.1.3 Effect of Electrolyte Concentration	108
5.2.1.4 Effect of Electrocatalyst Loading	111
5.2.2 Cathode	114
5.2.2.1 Oxygen as Oxidant	114
5.2.2.2 Mixed Oxidant (H ₂ O ₂ combined with oxygen saturated solution)	116
5.3 Single Cell Study	117
5.3.1 Effect of Electrolyte Concentration at Anode Side	117
5.3.2 Effect of Electrolyte Concentration at Cathode Side	120
5.3.3 Effect of Fuel Concentration	123
5.3.4 Effect of Electrocatalyst Loading at Anode	126

5.3.5 Effect of Electrocatalyst Loading at Cathode	129
5.3.6 Effect of Electrocatalyst Type	132
5.3.7 Effect of Temperature	134
5.3.8 Effect of Gas Diffusion Layer (GDL) or Carbon Paper	137
5.3.9 Effect of Oxidant Type at Cathode	139
5.4 Life time Test of The Microfluidic Fuel Cell	140
5.5 Efficiency of The Air Breathing Microfluidic Fuel Cell	141
5.6 Model Prediction	144
5.6.1 Fuel Concentration	144
5.6.2 Temperature	146
5.6.3 Model Parameters	148
CHAPTER 6 CONCLUSIONS	151-160
6.1 Microfluidic Fuel Cell Components and Constructions	151
6.2 SEM and Half-cell Analyses	152
6.3 Fuel Cell Performance	154
6.4 Model Development and Prediction	157
6.5 Future Scope	158
Appendix A1	
Appendix A2	
References	

INDEX OF FIGURES

Figure 1.1	A schematic of a hydrogen-oxygen PEM fuel cell	2
Figure 1.2	Y-shape microfluidic fuel cell design	5
Figure 2.1	Three phase contact at air breathing cathode	22
Figure 2.2	Cyclic voltammograms of Pd-Sn/C, Pd-Ru-Sn/C and 40 wt% Pt-Ru/C (E-TEK Inc.) nanocatalysts in 0.5 M NaOH + 3 M ethanol at room temperature. Scan rate 50 mV/s 3rd cycle was used in this analysis	41
Figure 2.3	Cyclic voltammograms of Pt-NB/G, Pt-NB/C, commercial Pt/C modified GC and bulk Pt electrodes in Air-saturated 0.1 M KOH solution; Scan rate: 50 mV/s	44
Figure 3.1	Schematic of the experimental setup of an air breathing microfluidic fuel cell	61
Figure 3.2	Schematic of cyclic voltammetry setup for Single electrode studies	62
Figure 3.3	Three-electrode cell and notation for the different electrodes (Bard and Faulkner 2001)	63
Figure 3.4	Four layers composite of an air breathing cathode	65
Figure 3.5	Electrical circuit for measuring I-V characteristic curve data	67
Figure 4.1	Schematic presentation of methanol transportation at anode	81
Figure 4.2	Schematic of ethanol transportation at anode	83
Figure 4.3	Schematic of sodium borohydride transportation at anode	85

Figure 4.4	Schematic of O ₂ transport through cathode	90
Figure 5.1a	SEM of blank GDL (Toray TGP-H-60, Alfa Aesar)	94
Figure 5.1b	SEM of blank GDL (IIT (BHU) laboratory made	95
Figure 5.2a	SEM of Pt-Ru/CHSA (0.5 mg cm ⁻²)	96
Figure 5.2b	SEM of Pt-Ru/CHSA (1 mg cm ⁻²)	96
Figure 5.2c	SEM of Pt-Ru/CHSA (2 mg cm ⁻²)	97
Figure 5.3a	SEM of Pt/CHSA (0.5 mg cm ⁻²)	98
Figure 5.3b	SEM of Pt/CHSA (1 mg cm ⁻²)	98
Figure 5.3c	SEM of Pt/CHSA (2 mg cm ⁻²)	99
Figure 5.4a	Cyclic voltammetry for 0.5 M methanol in 1 M KOH at different scan rate on Pt-Ru/C _{HSA} anode at loading of 1 mg/cm ² ; Temperature 34 °C	103
Figure 5.4b	Cyclic voltammetry for 0.5 M ethanol in 1 M KOH at different scan rate on Pt-Ru/C _{HSA} anode at loading of 1 mg/cm ² ; Temperature 34 °C	103
Figure 5.4c	Cyclic voltammetry for 0.1 M NaBH ₄ in 1 M KOH at different scan rate on Pt/C _{HSA} anode at loading of 1 mg/cm ² ; Temperature 40 °C	104
Figure 5.5a	Cyclic voltammetry for different concentration of methanol in 1 M KOH as electrolyte at 50 mV/s scan rate on Pt-Ru/C _{HSA} anode of 1 mg/cm ² loading; Temperature 34 °C	106
Figure 5.5b	Cyclic voltammetry for different concentration of ethanol in 1 M KOH as electrolyte at 50 mV/s scan rate on Pt-Ru/C _{HSA} anode of	107

	1 mg/cm ² loading; Temperature 34 °C	
Figure 5.5c	Cyclic voltammetry for different concentration of NaBH ₄ in 1 M KOH as electrolyte at 50 mV/s scan rate on Pt/C _{HSA} anode of 1 mg/cm ² loading; Temperature 40 °C	107
Figure 5.6a	Cyclic voltammetry for 0.5 M methanol as fuel mixed with different concentration of KOH at 50 mV/s scan rate on Pt-Ru/C _{HSA} anode of 1 mg/cm ² loading; Temperature 34 °C	109
Figure 5.6b	Cyclic voltammetry for 0.5 M ethanol as fuel mixed with different concentration of KOH at 50 mV/s scan rate on Pt-Ru/C _{HSA} anode of 1 mg/cm ² loading; Temperature 34 °C	110
Figure 5.6c	Cyclic voltammetry for 0.1 M NaBH ₄ as fuel mixed with different concentration of KOH at 50 mV/s scan rate on Pt/C _{HSA} anode of 1 mg/cm ² loading; Temperature 40 °C	110
Figure 5.7a	Cyclic voltammetry for 0.5 M methanol in 1 M KOH as electrolyte at 50 mV/s scan rate using different anode loading of Pt-Ru/C _{HSA} ; Temperature 34 °C	112
Figure 5.7b	Cyclic voltammetry for 0.5 M ethanol in 1 M KOH as electrolyte at 50 mV/s scan rate using different anode loading of Pt-Ru/C _{HSA} ; Temperature 34 °C	113
Figure 5.7c	Cyclic voltammetry for 0.1 M NaBH ₄ in 1 M KOH as electrolyte at 50 mV/s scan rate using different anode loading of Pt/C _{HSA} ; Temperature 40 °C	113
Figure 5.8a	Cyclic voltammetry for Pt/C _{HSA} cathode at loading of 1 mg/cm ²	115

	and 10 mV/s scan rate using 1 M KOH in a nitrogen-saturated solution	
Figure 5.8b	Cyclic voltammetry for Pt/C _{HSA} cathode at loading of 1 mg/cm ² and 10 mV/s scan rate using 1 M KOH in an oxygen-saturated solution	115
Figure 5.9	Cyclic voltammetry for Pt/C _{HSA} cathode at loading of 1 mg/cm ² and 10 mV/s scan rate using 2 M H ₂ O ₂ mixed with 1 M KOH in an oxygen-saturated solution	116
Figure 5.10a	Current density vs. cell voltage and current density vs. power density curves for 0.5 M methanol mixed with different concentration of KOH at anode and fixed cathode electrolyte of 1 M KOH and air as an oxidant; Temperature 34 °C; Solid lines-polarization curves; Dotted lines-power density curves	119
Figure 5.10b	Current density vs. cell voltage and current density vs. power density curves for 0.5 M ethanol mixed with different concentration of KOH at anode and fixed cathode electrolyte of 1 M KOH and air as an oxidant; Temperature 34 °C; Solid lines-polarization curves; Dotted lines-power density curves	119
Figure 5.10c	Current density vs. cell voltage and current density vs. power density curves for 0.05 M NaBH ₄ mixed with different concentration of KOH at anode and fixed cathode electrolyte of 1 M KOH and air as an oxidant; Temperature 40 °C; Solid lines-polarization curves; Dotted lines-power density curves	120

Figure 5.11a	Current density vs. cell voltage and current density vs. power density curves for 0.5 M methanol and 0.5 M KOH as fuel using different concentration of KOH at cathode and air as oxidant; Temperature 34 °C; Solid lines-polarization curves; Dotted lines-power density curves	122
Figure 5.11b	Current density vs. cell voltage and current density vs. power density curves for 0.5 M ethanol and 0.5 M KOH as fuel using different concentration of KOH at cathode and air as oxidant; Temperature 34 °C; Solid lines-polarization curves; Dotted lines-power density curves	122
Figure 5.11c	Current density vs. cell voltage and current density vs. power density curves for 0.05 M NaBH ₄ and 1 M KOH as fuel using different concentration of KOH at cathode and air as oxidant; Temperature 40 °C; Solid lines-polarization curves; Dotted lines-power density curves.	123
Figure 5.12a	Current density vs. cell voltage and current density vs. power density curves for different concentration of methanol mixed with 1 M KOH as fuel using optimum concentration of electrolyte (1 M KOH) at cathode side and air as oxidant; Temperature 34 °C; Solid lines-polarization curves; Dotted lines-power density curves	125
Figure 5.12b	Current density vs. cell voltage and current density vs. power density curves for different concentration of ethanol mixed with	125

	1 M KOH as fuel using optimum concentration of electrolyte (1 M KOH) at cathode side and air as oxidant; Temperature 34 °C; Solid lines-polarization curves; Dotted lines-power density curves	
Figure 5.12c	Current density vs. cell voltage and current density vs. power density curves for different concentration of NaBH ₄ mixed with 1 M KOH as fuel using optimum concentration of electrolyte (1 M KOH) at cathode side and air as oxidant; Temperature 40 °C; Solid lines-polarization curves; Dotted lines-power density curves	126
Figure 5.13a	Current density vs. cell voltage and current density vs. power density curves for 0.5 M methanol mixed with 1 M KOH as electrolyte using different anode electrocatalyst loading of Pt-Ru/C _{HSA} and cathode at fixed loading of 1 mg/cm ² Pt/C _{HSA} ; Temperature 34 °C; Solid lines-polarization curves; Dotted lines-power density curves	128
Figure 5.13b	Current density vs. cell voltage and current density vs. power density curves for 0.5 M ethanol mixed with 1 M KOH as electrolyte using different anode electrocatalyst loading of Pt-Ru/C _{HSA} and cathode at fixed loading of 1 mg/cm ² Pt/C _{HSA} ; Temperature 34 °C; Solid lines-polarization curves; Dotted lines-power density curves	128
Figure 5.13c	Current density vs. cell voltage and current density vs. power	129

	density curves for 0.1 M NaBH ₄ mixed with 1 M KOH as electrolyte using different anode electrocatalyst loading of Pt/C _{HSA} and cathode at fixed loading of 0.5 mg/cm ² Pt/C _{HSA} ; Temperature 40 °C; Solid lines-polarization curves; Dotted lines-power density curves.	
Figure 5.14a	Current density vs. cell voltage and current density vs. power density curves for 0.5 M methanol mixed with 1 M KOH as electrolyte at different cathode electrocatalyst loading of Pt/C _{HSA} and anode at fixed loading of 1 mg/cm ² Pt-Ru/C _{HSA} ; Temperature 34 °C; Solid lines-polarization curves; Dotted lines-power density curves	130
Figure 5.14b	Current density vs. cell voltage and current density vs. power density curves for 0.5 M ethanol mixed with 1 M KOH as electrolyte at different cathode electrocatalyst loading of Pt/C _{HSA} and anode at fixed loading of 1 mg/cm ² Pt-Ru/C _{HSA} ; Temperature 34 °C; Solid lines-polarization curves; Dotted lines-power density curves	131
Figure 5.14c	Current density vs. cell voltage and current density vs. power density curves for 0.1 M NaBH ₄ mixed with 1 M KOH as electrolyte at different cathode electrocatalyst loading of Pt/C _{HSA} and anode at fixed loading of 1 mg/cm ² Pt/C _{HSA} ; Temperature 40 °C; Solid lines-polarization curves; Dotted lines-power density curves	131

Figure 5.15a	Current density vs. cell voltage and current density vs. power density curves for 0.5 M methanol mixed with 1 M KOH as electrolyte using different anode electrocatalyst at fixed cathode Pt/C _{HSA} ; Temperature 34 °C; Solid lines-polarization curves; Dotted lines-power density curves	133
Figure 5.15b	Current density vs. cell voltage and current density vs. power density curves for 0.5 M ethanol mixed with 1 M KOH as electrolyte using different anode electrocatalyst at fixed cathode Pt/C _{HSA} ; Temperature 34 °C; Solid lines-polarization curves; Dotted lines-power density curves	133
Figure 5.15c	Current density vs. cell voltage and current density vs. power density curves for 0.1 M NaBH ₄ mixed with 1 M KOH as electrolyte using different anode electrocatalyst at fixed cathode Pt/C _{HSA} ; Temperature 40 °C; Solid lines-polarization curves; Dotted lines-power density curves	134
Figure 5.16a	Current density vs. cell voltage and current density vs. power density curves using different temperatures of MFC for methanol concentration of 0.5 M mixed with 1 M KOH as electrolyte on Pt-Ru/C _{HSA} anode and Pt/C _{HSA} cathode at loading of 1 mg/cm ² ; Solid lines-polarization curves; Dotted lines-power density curves	136
Figure 5.16b	Current density vs. cell voltage and current density vs. power density curves using different temperatures of MFC for ethanol	136

	concentration of 0.5 M mixed with 1 M	
Figure 5.16c	Current density vs. cell voltage and current density vs. power density curves using different temperatures of MFC for NaBH ₄ concentration of 0.1 M mixed with 1 M KOH as electrolyte on Pt/C _{HSA} anode and cathode at loading of 1 mg/cm ² ; Solid lines-polarization curves; Dotted lines-power density curves	137
Figure 5.17	Current density vs. cell voltage and current density vs. power density curves using different Gas diffusion layers of MFC for methanol concentration of 0.5 M mixed with 1 M KOH as electrolyte on Pt-Ru/C _{HSA} anode and Pt/C _{HSA} cathode at loading of 1 mg/cm ² ; Solid lines-polarization curves; Dotted lines-power density curves	138
Figure 5.18	Current density vs. cell voltage and current density vs. power density curves for 0.5 M methanol mixed with 1 M KOH as fuel and 1 M KOH at cathode side mixed with different concentration of H ₂ O ₂ in presence of air; Temperature 34 °C; Solid lines-polarization curves; Dotted lines-power density curves	140
Figure 5.19	Life time or stability test of the microfluidic fuel cell using methanol, ethanol and sodium borohydride as fuel at constant load	141
Figure 5.20a	Current density vs. cell voltage characteristic for different methanol concentration; Temperature 34 °C	145
Figure 5.20b	Current density vs. cell voltage characteristic for different	145

	ethanol concentration; Temperature 34 °C	
Figure 5.20c	Current density vs. cell voltage characteristic for different NaBH ₄ concentration; Temperature 40 °C	146
Figure 5.21a	Current density vs. cell voltage characteristic at different cell temperatures for 0.5 M methanol concentration	147
Figure 5.21b	Current density vs. cell voltage characteristic at different cell temperatures for 0.5 M ethanol concentration	147
Figure 5.21c	Current density vs. cell voltage characteristic at different cell temperatures for 0.1 M NaBH ₄ concentration	148

INDEX OF TABLES

Table 2.1	Electrocatalyst fabrication for methanol electrooxidation at anode in alkaline condition and techniques used for analysis of the system	25
Table 2.2	Electrode-catalyst fabrication for ethanol electrooxidation at anode in alkaline condition and techniques used for analysis of the system	29
Table 2.3	Electrocatalyst fabrication for sodium borohydride electrooxidation at anode in alkaline condition and techniques used for analysis of the system	33
Table 2.4	Electrocatalyst fabrication for oxygen reduction at cathode in alkaline condition and techniques used for analysis of the system	35
Table 2.5	Performance of microfluidic fuel cell using methanol, ethanol and sodium borohydride as fuel in alkaline medium	47
Table 3.1	Properties of Electrocatalysts	55
Table 3.2	Typical properties of Carbon paper	57
Table 3.3	Ingredients of Nafion® solution (Grade: D-520)	58
Table 3.4	Properties of PTFE Dispersion (Sigma Aldrich, USA)	59
Table 3.5	Typical Properties of the fuels at 1.01 bar and 298 K	59
Table 5.1	Individual efficiencies, thermodynamic, η_r^{cell} , electrochemical, η_v , Faradic, η_F , fuel utilization, η_U , of microfluidic fuel cell at room temperature and atmospheric pressure (1 atm)	143

Table 5.2	Model parameters	149
------------------	------------------	-----