

TABLE OF CONTENTS

Contents	Page No.
Certificate	ii
Acknowledgment	v
Table of contents	vii
List of figures	xii
List of tables	xix
List of symbols	xxi
Abstract	xxv
1. Introduction	1-14
1.1 Background and Motivation	1
1.2 Thesis objectives	10
1.3 Novelty and contribution	11
1.4 Thesis structure	12
2. Literature Review	15-40
2.1 Introduction	15
2.2 Numerical studies	15
2.3 Experimental studies	33
2.4 Research gaps	39
3. Different regenerative evaporative cooling topologies	41-80
3.1 Introduction	41
3.2 Numerical Model and simulation	44
3.2.1 Mathematical model	46
3.2.2 Numerical method and performance parameters	49
3.2.3 Exergy analysis	51

3.2.4 Economic analysis	52
3.2.5 Environmental analysis	55
3.2.6 Sustainability analysis	55
3.2.7 Validation of simulation code	55
3.3 Results and discussion	56
3.3.1 Energetic comparison	57
3.3.2 Exergetic comparison	58
3.3.3 Economic comparison	60
3.3.4 Environmental and Sustainability comparison	61
3.3.5 Effect of water inlet conditions	62
3.3.6 Effect of extraction ratio	66
3.3.7 Effect of channel gap	70
3.3.8 Effect of inlet air flow rate	73
3.3.9 Effect of inlet wet-bulb temperature	77
3.4 Important findings	79
4. Performance enhancement of regenerative evaporative cooler	81-107
4.1 Introduction	81
4.2 Modeling and simulation	82
4.2.1 Correlations used for the surface modifications	84
4.2.2 Nanofluid and its thermophysical property	86
4.2.3 Performance parameters	88
4.2.4 Numerical solution and validation	89
4.3 Results and discussion	91
4.3.1 Hybrid nanofluid effect	92
4.3.2 Influence of dew point depression	96

4.3.3 Influence of inlet velocity	99
4.3.4 Influence of water flow rate	103
4.4 Important findings	106
5. Experimentation on dual-mode evaporative cooler	109-147
5.1 Introduction	109
5.2 Experimentation methodology	109
5.2.1 Fabrication of dual mode heat and mass exchanger	110
5.2.2 Experimental test setup and instrumentation	112
5.2.3 Experimental procedure	116
5.2.4 Evaluation of experimental performance parameter	117
5.2.5 Uncertainty analysis	120
5.3 Results and discussion	121
5.3.1 Effect of extraction ratio	122
5.3.2 Effect of inlet air velocity	126
5.3.3 Influence of air inlet conditions	129
5.3.4 Influence of water inlet temperature	136
5.3.5 Influence of water flow rate	139
5.3.6 Thermal comfort assessment	142
5.3.7 Techno-economic Usefulness	144
5.4 Important findings	145
6. Performance forecasting of dual mode evaporative cooler	149-202
6.1 Introduction	149
6.2 Numerical modeling and simulation	153
6.2.1 Governing equations	154
6.2.2 Boundary conditions	156

6.2.3 Numerical simulation	151
6.2.4 Performance parameters	157
6.2.5 Validation of simulation code	159
6.2.6 Comparison of both modes	160
6.3 Performance in Indian climatic conditions	162
6.3.1 Month-wise performance in composite climatic zone	166
6.3.2 Month-wise performance in hot and dry climatic zone	170
6.3.3 Month-wise performance in hot and humid climatic zone	172
6.4 Performance in Global climatic conditions	172
6.5 Performance assessment for Future climatic scenarios	183
6.5.1 Weather forecasting	184
6.5.2 Performance forecasting	188
6.6 Important findings	200
7. Conclusions and future scope	203-205
7.1 Conclusions	203
7.2 Future scope	205
References	207-216
List of Publications	217

LIST OF FIGURES

Fig. No.	Title	Page No.
Fig. 1.1	Global primary energy consumption	2
Fig. 1.2	Global energy-related emissions	4
Fig. 1.3	Direct Evaporative Cooling (DEC)	7
Fig. 1.4	Psychrometric representation of direct Evaporative Cooling	7
Fig. 1.5	Indirect Evaporative Cooling (IEC)	8
Fig. 1.6	Psychrometric representation of Indirect Evaporative Cooling (IEC)	8
Fig. 1.7	Regenerative Evaporative Cooling (REC)	9
Fig. 1.8	Psychrometric representation of Regenerative Evaporative Cooling (REC)	9
Fig. 3.1	Four configurations of regenerative parallel/counter flow evaporative cooler	42
Fig. 3.2	Four configurations of the regenerative cross-flow evaporative cooler	43
Fig. 3.3	Control volume of evaporative heat and mass exchanger	45
Fig. 3.4	Validation of numerical simulation with the experimental result (Ringvikul and Kumar, 2010)	56
Fig. 3.5	Exergy distribution graph of the configuration A (at the mean operating condition)	60
Fig. 3.6	Variation of cooling capacity with water flow rate for configuration A and H	64
Fig. 3.7	Variation of dew point effectiveness with water flow rate for configuration A and H	64

Fig. 3.8	Variation of COP with water flow rate for configuration A and H	65
Fig. 3.9	Variation of exergy efficiency with water flow rate for configuration A and H	65
Fig. 3.10	Variation of dew point effectiveness with water inlet temperature for configurations A to H	66
Fig. 3.11	Variation of dew point effectiveness and cooling capacity with an extraction ratio	68
Fig. 3.12	Variation of COP and exergy destruction with an extraction ratio	68
Fig. 3.13	Variation of exergy efficiency and specific total cost with an extraction ratio	69
Fig. 3.14	Variation of sustainability index and carbon emission with an extraction ratio	69
Fig. 3.15	Variation of dew point effectiveness and cooling capacity with channel gap	71
Fig. 3.16	Variation of COP and exergy destruction with channel gap	72
Fig. 3.17	Variation of exergy efficiency and specific total cost with channel gap	72
Fig. 3.18	Variation of sustainability index and carbon emission with channel gap	73
Fig. 3.19	Variation of dew point effectiveness and cooling capacity with primary air flow rate	75
Fig. 3.20	Variation of COP and exergy destruction with primary air flow rate	75

Fig. 3.21	Variation of exergy efficiency and specific total cost with the primary air flow rate	76
Fig. 3.22	Variation of sustainability index and carbon emission with the primary air flow rate	76
Fig. 3.23	Variation of dew point effectiveness and cooling capacity with inlet air wet bulb temperature	78
Fig. 3.24	Variation of COP and exergy destruction with inlet air wet bulb temperature	78
Fig. 3.25	Variation of sustainability index and specific total cost with inlet air wet bulb temperature	79
Fig. 4.1	Counter-flow regenerative evaporative cooler	83
Fig. 4.2	Modified surface profiles (capsule embossing, finned and corrugated surfaces)	83
Fig. 4.3	Line diagram for air pressure loss in regenerative evaporative cooler	86
Fig. 4.4	Validation of the present numerical model for flat plate	91
Fig. 4.5	Cooling capacity of REC with different hybrid nanofluids	93
Fig. 4.6	Dew point effectiveness of REC with different hybrid nanofluids	94
Fig. 4.7	COP of REC with different hybrid nanofluids	94
Fig. 4.8	Exergy efficiency of REC with different hybrid nanofluids	95
Fig. 4.9	Water consumption rate of REC with different hybrid nanofluids	95
Fig. 4.10	Effect of dew point depression on dew point effectiveness	97
Fig. 4.11	Effect of dew point depression on cooling capacity	97

Fig. 4.12	Effect of dew point depression on COP	98
Fig. 4.13	Effect of dew point depression on exergy efficiency	98
Fig. 4.14	Effect of dew point depression on the water consumption rate	99
Fig. 4.15	Effect of primary air inlet velocity on dew point effectiveness	100
Fig. 4.16	Effect of primary air inlet velocity on cooling capacity	101
Fig. 4.17	Effect of primary air inlet velocity on COP	101
Fig. 4.18	Effect of primary air inlet velocity on exergy efficiency	102
Fig. 4.19	Effect of primary air inlet velocity on the water consumption rate	102
Fig. 4.20	Effect of water flow rate on dew point effectiveness	104
Fig. 4.21	Effect of water flow rate on COP	104
Fig. 4.22	Effect of water flow rate on exergy efficiency	105
Fig. 5.1	Fabrication of heat and mass exchanger	111
Fig. 5.2	Layout of the experimental setup for dual mode device	115
Fig. 5.3	Photograph of the experimental setup for dual mode device	115
Fig. 5.4	Supply air temperature and cooling capacity variation with an extraction ratio	124
Fig. 5.5	Dew point effectiveness and COP variation with extraction ratio	124
Fig. 5.6	Variation of exergy destruction and sustainability index with extraction ratio	125
Fig. 5.7	Variation of exergy efficiency and specific cost with extraction ratio	125
Fig. 5.8	Supply air temperature and cooling capacity variation with inlet velocity	127

Fig. 5.9	Dew point effectiveness and COP variation with inlet velocity	128
Fig. 5.10	Exergy destruction and sustainability index variation with air inlet velocity	128
Fig. 5.11	Exergy efficiency and specific cost variation with air inlet velocity	129
Fig. 5.12	Supply air temperature variation with inlet velocity	132
Fig. 5.13	Cooling capacity variation with air inlet temperature	132
Fig. 5.14	Dew point effectiveness variation with inlet temperature	133
Fig. 5.15	COP variation with the inlet temperature	133
Fig. 5.16	Exergy destruction variation with air inlet temperature	134
Fig. 5.17	Sustainability index variation with air inlet temperature	134
Fig. 5.18	Exergy efficiency variation with air inlet temperature	135
Fig. 5.19	Specific cost variation with air inlet temperature	135
Fig. 5.20	Supply air temperature and cooling capacity variation with water temperature	137
Fig. 5.21	Dew point effectiveness and COP variation with the water temperature	138
Fig. 5.22	Exergy destruction and sustainability index variation with water inlet temperature	138
Fig. 5.23	Exergy efficiency and specific cost variation with water inlet temperature	139
Fig. 5.24	Supply air temperature and cooling capacity variation with water flow rate	140
Fig. 5.25	Dew point effectiveness and COP variation with the water flow rate	141

Fig. 5.26	Exergy destruction and sustainability index variation with the water flow rate	141
Fig. 5.27	Exergy ratio and specific cost variation with the water flow rate	142
Fig. 5.28	Psychrometric chart representation of supply air conditions with inlet air velocity, temperature, and specific humidity variations	143
Fig. 6.1	Proposed evaporative cooler in indirect regenerative mode (REC)	151
Fig. 6.2	Proposed evaporative cooler in direct mode (DEC)	151
Fig. 6.3	Flow processes in both DEC and REC modes on the psychrometric chart	152
Fig. 6.4	Schematic of direct and indirect mode heat and mass exchangers	154
Fig. 6.5	The computer model flow chart	157
Fig. 6.6	Validation of the experimental result	160
Fig. 6.7	Performance variation with a height of wet channel in DEC and REC mode	163
Fig. 6.8	Psychrometric chart showing REC mode results for Bhopal	167
Fig. 6.9	Psychrometric chart showing DEC mode results for Bhopal	168
Fig. 6.10	Psychrometric chart showing REC mode results for Lucknow	168
Fig. 6.11	Psychrometric chart showing DEC mode results for Lucknow	169
Fig. 6.12	Psychrometric chart showing REC mode results for Varanasi	169
Fig. 6.13	Psychrometric chart showing DEC mode results for Varanasi	170

Fig. 6.14	Psychrometric chart showing REC mode results for Ahmedabad	171
Fig. 6.15	Psychrometric chart showing DEC mode results for Ahmedabad	171
Fig. 6.16	Psychrometric chart showing REC mode results for Kolkata	173
Fig. 6.17	Psychrometric chart showing DEC mode results for Kolkata	173
Fig. 6.18	Dew point effectiveness of DEC modes of evaporative cooler	178
Fig. 6.19	Dew point effectiveness of REC modes of evaporative cooler	178
Fig. 6.20	Coefficient of performance of DEC modes of evaporative cooler	179
Fig. 6.21	Coefficient of performance of REC modes of evaporative cooler	179
Fig. 6.22	Month-wise variation of exergy efficiency in REC mode	180
Fig. 6.23	Month-wise variation of exergy efficiency in DEC mode	180
Fig. 6.24	Month-wise variation of specific total cost in REC mode	182
Fig. 6.25	Month-wise variation of specific total cost in DEC mode	182
Fig. 6.26	The forecasting of temperature for the Varanasi City	185
Fig. 6.27	The forecasting of relative humidity for the Varanasi City	186
Fig. 6.28	Monthly present and forecasted temperatures of the different city	187
Fig. 6.29	Monthly present and forecasted humidity of the different city	187
Fig. 6.30	Direct mode result of Varanasi city on the Psychrometric chart	190
Fig. 6.31	Regenerative mode result of Varanasi city on the Psychrometric chart	190

Fig. 6.32	Yearly hours of usability of the individual modes	195
Fig. 6.33	Monthly present and forecasted cooling capacity of different city in DEC mode	196
Fig. 6.34	Monthly present and forecasted cooling capacity of different city in REC mode	196
Fig. 6.35	Monthly present and forecasted effectiveness of different city in DEC mode	198
Fig. 6.36	Monthly present and forecasted effectiveness of different city in REC mode	198
Fig. 6.37	Monthly present and forecasted COP of different city in DEC mode	199
Fig. 6.38	Monthly present and forecasted COP of different city in REC mode	199

LIST OF TABLES

Table No.	Title	Page No.
Table 2.1	Summary of the different numerical studies on evaporative cooling	16
Table 2.2	Summary of the different experimental studies on evaporative cooling	33
Table 3.1	Boundary condition for all eight configurations of HMX	48
Table 3.2	The component capital cost of the HMX	53
Table 3.3	Specification of HMX and mean operating parameters	57
Table 3.4	The energetic comparison of the different configurations	58
Table 3.5	The specific exergy of the air at a different point in regenerative HMX	59
Table 3.6	The exergetic comparison of the different configurations	59
Table 3.7	The specific total cost of the different configurations at mean conditions	61
Table 3.8	The sustainability index of the different configurations at mean conditions	62
Table 4.1	Thermophysical properties of considered nanoparticles	88
Table 4.2	Comparison of simulated effectiveness with published experimental data	90
Table 4.3	Geometric and operating parameters (at mean conditions) of REC	91
Table 5.1	Specifications of dual-mode heat exchanger.	111
Table 5.2	Specifications of dual mode heat exchanger.	113
Table 5.3	The specification of the data logger	114
Table 5.4	Cost of the different component	120

Table 5.5	The maximum uncertainty of the measured and calculated parameters.	121
Table 5.6	Data of flow and humidity at a different point in the device at the reference state	122
Table 5.7	comparison between Vapor compression air – conditioning system and Dual mode evaporative coolers	145
Table 6.1	Electricity cost of countries in USD	159
Table 6.2	Summary of results of both modes of the proposed cooler for five cities in India	162
Table 6.3	Comparisons of results of both modes of evaporative cooler	164
Table 6.4	Results of dual-mode cooler for five cities of different climatic zones	176
Table 6.5	Geometric and operating parameters of evaporative HMX for forecasting	188
Table 6.6	Summary of results of both modes of the dual-mode cooler for the present (2019) scenario	192
Table 6.7	Summary of results of both modes of the dual-mode cooler for the future (for example, 2030) scenario	193
