

# Contents

---

---

<b>CERTIFICATE.....</b>	<b>ii</b>
<b>Acknowledgments .....</b>	<b>v</b>
<b>Abstract.....</b>	<b>ix</b>
<b>Contents .....</b>	<b>xiii</b>
<b>List of figures.....</b>	<b>xxiii</b>
<b>List of tables.....</b>	<b>xxxii</b>
<b>Abbreviations/symbols .....</b>	<b>xxxv</b>
<b>1. Introduction.....</b>	<b>1</b>
1.1. Tribology.....	1
1.1.1. Friction.....	1
1.1.2. Wear.....	2
1.1.3. Lubrication.....	2
1.2. Types of lubricants .....	3
1.2.1. Liquid lubricants .....	3
1.2.2. Grease (semi-solid lubricants) .....	4
1.2.3. Solid lubricants .....	4
1.3. Liquid lubricants .....	5
1.3.1. The function of liquid lubricants.....	6
1.4. Synthetic lubricants .....	8

1.4.1.	The requirement for synthetic lubricants .....	8
1.4.2.	An overview of synthetic base oils .....	9
1.4.3.	Tribology of synthetic base oils .....	11
1.4.4.	Role of additives in synthetic lubrication .....	12
1.5.	Summary of the chapter .....	13
<b>2.</b>	<b>Literature review .....</b>	<b>17</b>
2.1.	Background .....	17
2.2.	Polyalphaolefins (PAOs).....	18
2.2.1.	The synthesis process of PAOs.....	19
2.2.2.	Physical properties of PAOs .....	21
2.2.3.	Comparison of PAOs with petroleum-based mineral oils .....	21
2.2.4.	Advantages of PAOs.....	23
2.2.5.	Disadvantages of PAOs .....	25
2.2.6.	Recent developments .....	26
2.2.7.	Applications of PAOs .....	26
2.3.	Lubricant Additives.....	27
2.3.1.	Evolution of lubricant additive .....	29
2.3.2.	Nanoparticles as lubricant additive.....	30
2.3.3.	Classification of nanoparticles .....	31
2.3.3.1.	Metals-based nanoparticles.....	32
2.3.3.2.	Metal oxides nanoparticles .....	33

2.3.3.3.	Carbon-based nanoparticles.....	41
2.3.3.4.	Composite nanoparticles.....	45
2.3.3.5.	Rare earth compound-based nanoparticles.....	45
2.3.3.6.	Sulphides-based nanoparticles.....	45
2.3.3.7.	Other nanoparticles.....	46
2.4.	Tribological performance of PAOs-based nanolubricants.....	52
2.5.	Effect of nanoparticle parameters on tribological performance.....	58
2.5.1.	Effect of nanoparticle particle size.....	58
2.5.2.	Effect of nanoparticles concentration.....	59
2.5.3.	Effect of nanoparticles morphology.....	59
2.6.	The hypothesis of the lubrication mechanism of nanolubricant additives.....	59
2.6.1.	Rolling/ball bearing effect.....	60
2.6.2.	Mending effect.....	60
2.6.3.	Formation of the protective layer/tribo-film.....	61
2.6.4.	Polishing effect.....	61
2.7.	Optimization of process parameters.....	62
2.8.	Tribological performance of PAOs-based greases.....	63
2.9.	Formulation of the problem.....	66
2.9.1.	Problem identification.....	66
2.9.2.	Motivation.....	66
2.9.3.	Problem definition.....	66

2.9.4.	Objective of work .....	67
2.10.	Justification for selection of different nanoparticles .....	68
2.11.	Summary of the chapter.....	68
<b>3.</b>	<b>Materials and Experimentation details.....</b>	<b>71</b>
3.1.	Materials.....	71
3.1.1.	Base oils.....	71
3.1.2.	Lubricant additive .....	71
3.1.2.1.	COOH-functionalized multiwalled carbon nanotubes (MWCNTs).....	71
3.1.2.2.	Oleic acid-modified lanthanum trifluoride (LaF <sub>3</sub> ) nanoparticles .....	73
3.2.	Characterization of nanoadditives.....	74
3.2.1.	Transmission electron microscope (TEM).....	74
3.2.2.	X-ray diffractometer (XRD) .....	75
3.2.3.	Fourier transform infrared (FTIR) spectroscopy .....	75
3.2.4.	X-ray photoelectron spectroscopy (XPS) .....	75
3.3.	Formulation of nanolubricants .....	75
3.4.	Rheological investigation.....	76
3.5.	Tribological experimentation .....	76
3.5.1.	Four-ball tribometer .....	77
3.5.2.	High-frequency linear-oscillation tribometer (SRV 5).....	80
3.5.3.	Ball-on-disc tribometer .....	83
3.6.	Synthesis of PAO 100-based grease .....	84

3.7.	Characterization of grease .....	85
3.7.1.	Characterization of physicochemical properties of greases .....	86
3.7.1.1.	Consistency .....	86
3.7.1.2.	Drop point .....	88
3.7.2.	Characterization of tribological properties of grease using four-ball tester	88
3.8.	Characterization of worn surfaces .....	89
3.8.1.	Scanning electron microscope (SEM) and Energy-dispersive X-ray spectroscopy (EDS) .....	89
3.8.2.	X-ray photoelectron spectroscopy (XPS) .....	89
3.8.3.	Scanning probe microscope (SPM) .....	89
3.9.	Summary of the chapter .....	90
<b>4.</b>	<b>Tribological performance of various grades of PAOs with COOH-functionalized MWCNTs as an additive .....</b>	<b>93</b>
4.1.	Part-A: Tribological investigation of PAOs-based nanolubricants under fully flooded lubrication conditions using four-ball tribo-testing .....	93
4.1.1.	Structural and Morphological Attributes of COOH-Functionalized MWCNTs.....	94
4.1.2.	Tribological Performance of nanolubricants .....	96
4.1.2.1.	Antifriction behaviour of nanolubricants .....	96
4.1.2.2.	Anti-wear behaviour of nanolubricants .....	100
4.1.2.3.	Extreme pressure (EP) performance of nanolubricants .....	102
4.1.3.	The investigation of worn surfaces .....	104

4.1.4.	Proposed lubrication mechanism .....	114
4.2.	Part-B: Tribological investigation of PAOs-based and PPG based nanolubricants under starved lubrication conditions using SRV 5 tribo-test rig.....	115
4.2.1.	Tribological evaluation of high viscosity synthetic base oils (PAO 100 and PPG 2000) based nanolubricants .....	115
4.2.1.1.	Friction and wear response of nanolubricants .....	115
4.2.1.1.1.	Friction performance of nanolubricants .....	115
4.2.1.1.2.	Wear performance of nanolubricants .....	116
4.2.1.2.	Analysis of worn surfaces.....	117
4.2.1.2.1.	Analysis of worn surface of steel balls.....	117
4.2.1.2.2.	Worn surface analysis of disc.....	122
4.2.1.2.3.	EDS analysis of worn surfaces .....	123
4.2.1.3.	Proposed lubrication mechanisms .....	126
4.2.1.4.	Investigation of MWCNTs stability in base Oils .....	129
4.2.2.	Tribological evaluation of low viscosity synthetic base oils (PAO 4 and PAO 6) based nanolubricants.....	131
4.2.2.1.	Friction and wear response of nanolubricants .....	131
4.2.2.1.1.	Antifriction responses of nanolubricants .....	132
4.2.2.1.2.	Anti-wear responses of nanolubricants.....	134
4.2.2.2.	Worn surfaces analysis .....	135
4.2.2.2.1.	Worn surface analysis of steel balls .....	135
4.2.2.2.2.	Worn surface analysis of counterpart (disc) .....	142

4.2.2.2.3.	EDS analysis of worn surfaces .....	147
4.2.2.2.4.	XPS analysis of worn surfaces .....	150
4.2.2.3.	Dispersion analysis of MWCNTs in PAOs .....	152
4.2.2.4.	Rheological characterization of lubricants .....	154
4.3.	Summary of the chapter .....	156
<b>5.</b>	<b>Taguchi's optimization of various parameters for tribological performance of polyalphaolefins-based nanolubricants using ball-on-disc tribometer .....</b>	<b>161</b>
5.1.	Characterization of COOH-functionalized MWCNTs.....	161
5.2.	Design of experiment by Taguchi's method .....	161
5.3.	Tribological performance of nanolubricants .....	164
5.3.1.	Friction response of nanolubricants .....	164
5.3.1.1.	Taguchi's optimization for COF.....	164
5.3.1.2.	ANOVA analysis for COF .....	164
5.3.1.3.	Effect of control factor on COF.....	169
5.3.2.	Wear response of nanolubricants .....	178
5.3.2.1.	Taguchi's optimization and ANOVA analysis for specific wear rate (K).....	178
5.3.2.2.	Effect of control factors on specific wear rate (K) .....	179
5.3.3.	Confirmation test .....	180
5.4.	Dispersion stability analysis of nanolubricants.....	181
5.5.	Study on morphology and topography of worn surfaces .....	185
5.6.	Summary of the chapter .....	191

<b>6. Influence of oleic acid-treated LaF<sub>3</sub> nanoparticles as an additive on extreme pressure properties of various grades of polyalphaolefins using four-ball tribometer.....</b>	<b>195</b>
6.1. Characterization of oleic acid modified LaF <sub>3</sub> nanoparticles .....	195
6.2. Tribological performance of nanolubricants under EP conditions.....	199
6.2.1. EP properties of low viscosity PAOs-based nanolubricants (PAO 4 and PAO 6).....	199
6.2.2. EP properties of high viscosity PAOs-based nanolubricants (PAO 40 and PAO 100) .....	201
6.3. Analysis of worn surfaces .....	207
6.3.1. SEM analysis of worn surfaces.....	207
6.3.2. Surface topography analysis of worn steel balls by SPM.....	210
6.3.3. EDS analysis of worn surfaces .....	217
6.4. Dispersion stability analysis of nanolubricants.....	218
6.5. Rheological characterization of PAOs .....	221
6.6. Lubrication mechanism .....	223
6.7. Summary of the chapter .....	225
<b>7. Tribological evaluation of PAO 100 oil-based grease using four-ball tribometer.....</b>	<b>229</b>
7.1. Characterization of nanoadditives.....	229
7.2. Physicochemical properties of PAO 100 grease .....	229
7.3. Tribological performance of PAO 100 grease .....	233

7.3.1.	Antifriction performance of PAO 100 grease .....	233
7.3.2.	Anti-wear performance of PAO 100 grease.....	235
7.3.3.	Extreme pressure performance of PAO 100 grease .....	236
7.4.	Worn surface analysis .....	239
7.4.1.	Worn surface analysis by SEM.....	239
7.4.2.	Surface topographic analysis of worn surfaces by SPM.....	241
7.4.3.	EDS analysis of worn Surfaces.....	246
7.4.4.	XPS analysis of worn surfaces.....	247
7.5.	Summary of the chapter .....	251
<b>8.</b>	<b>Conclusions and scope for future work .....</b>	<b>255</b>
8.1.	Conclusions .....	255
8.1.1.	Conclusions on the tribological performance of various grades of PAO with COOH-functionalized MWCNTs as an additive .....	255
8.1.1.1.	Part-A: Conclusions on the tribological investigation of PAOs-based nanolubricants under fully flooded lubrication conditions using four-ball tribo- testing.....	255
8.1.1.2.	Part-B: Conclusions on the tribological investigation of PAOs-based and PPG based nanolubricants under starved lubrication conditions using SRV 5 tribo- test rig.....	257
8.1.1.2.1.	Conclusions on the tribological evaluation of high viscosity synthetic base oils (PAO 100 and PPG 2000) based nanolubricants .....	257
8.1.1.2.2.	Conclusions on the tribological evaluation of low viscosity synthetic base oils (PAO 4 and PAO 6) .....	258

8.1.2. Conclusions on Taguchi’s optimization of various parameters for tribological performance of polyalphaolefins-based nanolubricants .....	262
8.1.3. Conclusions on the influence of oleic acid-treated LaF <sub>3</sub> nanoparticles as an additive on extreme pressure properties of various grades of polyalphaolefins .....	263
8.1.4. Conclusions on tribological evaluation of PAO 100 oil-based grease .....	265
8.2. Overall general conclusions according to the problem definition.....	266
8.3. Scope for the future work.....	267
<b>References .....</b>	<b>269</b>
<b>Appendix–A .....</b>	<b>289</b>
<b>Appendix– B .....</b>	<b>295</b>
<b>Appendix– C .....</b>	<b>299</b>
<b>Appendix–D .....</b>	<b>307</b>
<b>Appendix–E .....</b>	<b>309</b>
<b>List of publications.....</b>	<b>311</b>

# List of figures

---

---

<b>Figure 1.1:</b> Classification of base oils on the basis of their origin.....	6
<b>Figure 2.1:</b> Molecular structure of 1-decene (PAO) components (a) monomer (b) dimer (c) trimer, and (d) tetramer .....	20
<b>Figure 2.2:</b> Manufacturing process of PAOs .....	21
<b>Figure 2.3:</b> The chronology of the evolution of lubricant additives [27] .....	30
<b>Figure 2.4:</b> Classification of nanoparticles based on their origin .....	32
<b>Figure 2.5:</b> Several possible lubrication mechanisms of nanoparticles as lubricants additives [111]. Reproduced with permission from Elsevier- Appendix E.....	62
<b>Figure 3.1:</b> Synthesis methodology of LaF <sub>3</sub> nanoparticles .....	74
<b>Figure 3.2:</b> Schematic diagram of the four-ball tribometer .....	79
<b>Figure 3.3:</b> The schematic diagram of (a) SRV 5 test rig (b) wear scar of ball and disc and quantification of various parameters.....	83
<b>Figure 4.1:</b> (a) XRD pattern, (b) FTIR spectra, and (c–e) HR-TEM micrographs of COOH-functionalized MWCNTs.....	95
<b>Figure 4.2:</b> (a) Variation in the diameter of MWCNTs, and (b) size and frequency distribution of additive.....	96
<b>Figure 4.3:</b> (a) Coefficient of friction as a function of test duration for various plain oil and with an optimum concentration of MWCNTs. The variation of average coefficient of friction with different concentrations of additive in (b) PAO 4 (c) PAO 6 (d) PAO 40 (e) PAO 100, and (f) percentage reduction in COF for different compositions of additive in the plain oils. (Applied load: 392 N and test duration: 60 min) .....	98
<b>Figure 4.4:</b> Influences of different concentrations of MWCNTs: (a)-(d) mean wear scar diameter of worn surfaces; (e)-(h) the mean wear volume; (I) the percentage reduction in	

WSD; and (j) MWV with different amounts of additive in PAO 4, PAO 6, PAO 40, and PAO 100. (Applied load: 392 N and test duration: 60 min) ..... 102

**Figure 4.5:** The SEM micrographs of wear scars of steel balls lubricated with (a, a<sub>1</sub>) plain PAO4; (b, b<sub>1</sub>) PAO 4 with 0.075 wt.% MWCNTs; (c, c<sub>1</sub>) plain PAO 6; (d, d<sub>1</sub>) PAO 6 with 0.075 wt.% MWCNTs; (e, e<sub>1</sub>) plain PAO 40; (f, f<sub>1</sub>) PAO 40 with 0.025 wt.% MWCNTs; (g, g<sub>1</sub>) plain PAO 100; (h, h<sub>1</sub>) PAO 100 with 0.1 wt.% MWCNTs. [ Note: - a, b, c, d, e, f, g, h: at 100X; and a<sub>1</sub>, b<sub>1</sub>, c<sub>1</sub>, d<sub>1</sub>, e<sub>1</sub>, f<sub>1</sub>, g<sub>1</sub>, h<sub>1</sub>: at 2000X]. (Applied load: 392 N and test duration: 60 min)..... 106

**Figure 4.6:** SPM roughness images of worn surfaces of steel balls, (a, a<sub>1</sub>) plain PAO 4; (b, b<sub>1</sub>) PAO 4 with 0.075 wt.% MWCNTs; (c, c<sub>1</sub>) plain PAO 6; (d, d<sub>1</sub>) PAO 6 with 0.075 wt.% MWCNTs; (e, e<sub>1</sub>) plain PAO 40; (f, f<sub>1</sub>) PAO 40 with 0.025 wt.% MWCNTs; (g, g<sub>1</sub>) plain PAO 100; (h, h<sub>1</sub>) PAO 100 with 0.1 wt.% MWCNTs. [ Note: - a, b, c, d, e, f, g, h: 2D view and a<sub>1</sub>, b<sub>1</sub>, c<sub>1</sub>, d<sub>1</sub>, e<sub>1</sub>, f<sub>1</sub>, g<sub>1</sub>, h<sub>1</sub>: 3 D view of worn surfaces]. (Applied load: 392 N and test duration: 60 min)..... 107

**Figure 4.7:** Linear roughness profile of worn surfaces measured in the 2D contact profilometer. (Applied load: 392 N and test duration: 60 min) ..... 108

**Figure 4.8:** The EDS spectra of wear scars of steel balls tested with (a, a<sub>1</sub>) plain PAO 4; (b, b<sub>1</sub>) PAO 4 with 0.075 wt.% MWCNTs; (c, c<sub>1</sub>) plain PAO 6; (d, d<sub>1</sub>) PAO 6 with 0.075 wt.% MWCNTs; (e, e<sub>1</sub>) plain PAO 40; (f, f<sub>1</sub>) PAO 40 with 0.025 wt.% MWCNTs; (g, g<sub>1</sub>) plain PAO 100; and (h) and (h<sub>1</sub>), PAO 100 with 0.1 wt.% MWCNTs. (Applied load: 392 N and test duration: 60 min) ..... 110

**Figure 4.9:** The flowchart represents the influences of MWCNTs on the tribological performance of different PAO oils ..... 111

**Figure 4.10:** Schematic diagram demonstrates the lubrication mechanism and role of MWCNTs..... 114

**Figure 4.11:** Variation of coefficient of friction (a) with different concentrations of additive in PAO 100, PPG 2000, (b) percentage reduction in COF (c) with test duration, (d) the variation of wear volume with different compositions of additive in both base oils, and (e) percentage reduction in WV. (Applied load: 300 N and test duration: 120 min)..... 118

**Figure 4.12:** SEM micrographs of wear scars of steel balls lubricated by (a, a<sub>1</sub>) plain PPG 2000; (b, b<sub>1</sub>) PPG 2000 with 0.025 wt.% MWCNTs; (c, c<sub>1</sub>) plain PAO 100, and (d, d<sub>1</sub>) PAO 100 with 0.05 wt.% MWCNTs [ Note: - a, b, c, d: at 100X; and a<sub>1</sub>, b<sub>1</sub>, c<sub>1</sub>, d<sub>1</sub>: at 1000X]. (Applied load: 300 N and test duration: 120 min) ..... 120

**Figure 4.13:** SPM pictures of worn surfaces of steel balls experimented with (a, a<sub>1</sub>) plain PPG 2000; (b, b<sub>1</sub>) PPG 2000 with 0.025 wt.% MWCNTs; (c, c<sub>1</sub>) plain PAO 100, and (d, d<sub>1</sub>) PAO 100 with 0.05 wt.% MWCNTs [ Note: - a, b, c, d: Top view and a<sub>1</sub>, b<sub>1</sub>, c<sub>1</sub>, d<sub>1</sub>: Three-dimensional view of worn surfaces]. (Applied load: 300 N and test duration: 120 min)..... 121

**Figure 4.14:** SEM images of wear scar of the steel disc after friction test (a, a<sub>1</sub>) plain PPG 2000; (b, b<sub>1</sub>) PPG 2000 with 0.025 wt.% MWCNTs; (c, c<sub>1</sub>) plain PAO 100, and (d, d<sub>1</sub>) PAO 100 with 0.05 wt.% MWCNTs [ Note: - a, b, c, d: at 100X; and a<sub>1</sub>, b<sub>1</sub>, c<sub>1</sub>, d<sub>1</sub>: at 500X] (Applied load: 300 N and test duration: 120 min) ..... 124

**Figure 4.15:** The cross-section profile of wear track of the disc lubricated with (a) plain PPG 2000 and PPG 2000 with 0.025 wt.% MWCNTs, and (b) plain PAO 100 and PAO 100 with 0.05 wt.% MWCNTs. (Applied load: 300 N and test duration: 120 min)..... 125

**Figure 4.16:** EDS spectra of wear scars of steel balls tested with (a, a<sub>1</sub>) plain PPG 2000; (b, b<sub>1</sub>) PPG 2000 with 0.025 wt.% MWCNTs; (c, c<sub>1</sub>) plain PAO 100, and (d, d<sub>1</sub>) PAO 100 with 0.05 wt.% MWCNTs. (Applied load: 300 N and test duration: 120 min)..... 128

**Figure 4.17:** Lubrication mechanisms with (a) plain base oil, and (b) base oil containing MWCNTs..... 129

**Figure 4.18:** Photographs of MWCNTs suspension stability at different time intervals, (a-d) PAO 100 and (e-h) PPG 2000 at room temperature ( $\sim 30\text{ }^{\circ}\text{C}$ ), and (i) demonstrates the role of the functional group in improving the dispersion stability in the base oils..... 130

**Figure 4.19:** The EP behavior of (a) PAO 4 and (b) PAO 6 as per ASTM D7421 ..... 131

**Figure 4.20:** (a) The average COF with variable concentration of MWCNTs in PAOs, change in (b) COF as a function of test duration, and (c) WV with varying doses of additive. (Applied load: 50 N for PAO 4 and 200 N for PAO 6-based nanolubricants and test duration: 120 min)..... 136

**Figure 4.21:** Worn surfaces of steel balls tested with (a, b) Plain PAO 4; (c, d) PAO 4 containing 0.025 wt.% MWCNTs; (e, f) Plain PAO 6, and (g, h) PAO 6 containing 0.05 wt.% MWCNTs. [ Note: - a, c, e, g: at 200X; and b, d, f, h: at 1000X] (Applied load: 50 N for PAO 4 and 200 N for PAO 6-based nanolubricants and test duration: 120 min) ..... 138

**Figure 4.22:** Topographic micrographs of steel balls lubricated by (a, b) plain PAO 4; (c, d) PAO 4 containing 0.025 wt.% MWCNTs; (e, f) Plain PAO 6, and (g, h) PAO 6 containing 0.05 wt.% MWCNTs. [ Note: - a, c, e, g: Top view and b, d, f, h: Three-dimensional view of worn surfaces] (Applied load: 50 N for PAO 4 and 200 N for PAO 6-based nanolubricants and test duration: 120 min)..... 139

**Figure 4.23:** Bearing area ratio curve and respective linear roughness profiles of steel balls tested with (a, b) Plain PAO 4; (c, d) PAO 4 containing 0.025 wt.% MWCNTs; (e, f) plain PAO 6 and (g, h) PAO 6 containing 0.05 wt.% MWCNTs. (Applied load: 50 N for PAO 4 and 200 N for PAO 6-based nanolubricants and test duration: 120 min)..... 143

**Figure 4.24:** SEM images of worn surfaces of disc in friction test lubricated with (a, b) Plain PAO 4; (c, d) PAO 4 containing 0.025 wt.% MWCNTs; (e, f) Plain PAO 6, and (g, h) PAO 6 containing 0.05 wt.% MWCNTs. [ Note: - a, c, e, g: at 60X; and b, d, f, h: at

500X] (Applied load: 50 N for PAO 4 and 200 N for PAO 6-based nanolubricants and test duration: 120 min)..... 146

**Figure 4.25:** The surface profile of wear track of the disc tested with (a) Plain PAO 4; (b) PAO 4 comprising 0.025 wt.% MWCNTs; (c) Plain PAO 6, and (d) PAO 6 containing 0.05 wt.% MWCNTs. (Applied load: 50 N for PAO 4 and 200 N for PAO 6-based nanolubricants and test duration: 120 min)..... 147

**Figure 4.26:** EDS spectrum of worn scars of steel balls lubricated by (a, b) Plain PAO 4; (c, d) PAO 4 containing 0.025 wt.% MWCNTs; (e, f) Plain PAO 6, and (g, h) PAO 6 comprising 0.05 wt.% MWCNTs. (Applied load: 50 N for PAO 4 and 200 N for PAO 6-based nanolubricants and test duration: 120 min)..... 149

**Figure 4.27:** XPS spectra of worn surface of (a) disc, and (b) ball lubricated by various lubricant compositions. (Applied load: 50 N for PAO 4 and 200 N for PAO 6-based nanolubricants and test duration: 120 min)..... 150

**Figure 4.28:** Deconvoluted XPS spectra of worn surface of disc lubricated by (a, b) PAO 4 containing 0.025 wt.% MWCNTs; (c, d) PAO 6 comprising 0.05 wt.% MWCNTs, and deconvoluted XPS spectra of wear scar of ball lubricated by (e, f) PAO 4 containing 0.025 wt.% MWCNTs; (g, h) PAO 6 with 0.05 wt.% MWCNTs. (Applied load: 50 N for PAO 4 and 200 N for PAO 6-based nanolubricants and test duration: 120 min)..... 151

**Figure 4.29:** The photograph demonstrates the dispersion stability of MWCNTs (a-d) PAO 4, and (e-h) PAO 6 at room temperature (~ 30 °C)..... 154

**Figure 4.30:** Rheological characterization of plain PAO 4, and PAO 6..... 156

**Figure 5.1:** Influences of control parameter on S/N ratio for (a) COF, and (b) specific wear rate (K)..... 167

**Figure 5.2:** Normal probability plot for (a) COF, and (b) specific wear rate (K)..... 171

<b>Figure 5.3:</b> Contour plot demonstrates the effect of interactions of control factors on COF .....	175
<b>Figure 5.4:</b> Variation in COF as a function of sliding distance for different operating conditions.....	177
<b>Figure 5.5:</b> Illustrates the contour plot to show the influence of interactions of control factors on the specific wear rate (K) .....	181
<b>Figure 5.6:</b> The photograph represents the dispersion stability of MWCNTs at room temperature (~ 30 °C) in different PAOs at different time interval .....	183
<b>Figure 5.7:</b> Illustrates the contribution of the functional group in the enhancement of suspension stability of MWCNTs in PAO oils .....	184
<b>Figure 5.8:</b> SEM micrographs of worn surfaces of steel ball tested with (a, a <sub>1</sub> ) pure PAO 4 at 50 N load and sliding velocity of 0.42 m/s; (b, b <sub>1</sub> ) PAO 4 with 0.075 wt.% MWCNTs at 80 N load and sliding velocity of 0.42 m/s; (c, c <sub>1</sub> ) pure PAO 6 at 80 N load and sliding velocity of 1.099 m/s; (d, d <sub>1</sub> ) PAO 6 with 0.05 wt.% MWCNTs at 80 N load and sliding velocity of 1.57 m/s; (e, e <sub>1</sub> ) pure PAO 40 at 100 N load and sliding velocity of 1.57 m/s; (f, f <sub>1</sub> ) PAO 40 with 0.075 wt.% MWCNTs at 50 N load and sliding velocity of 1.57 m/s..	187
<b>Figure 5.9:</b> SPM images of worn surfaces of steel ball experimented with (a, a <sub>1</sub> ) pure PAO 4 at 50 N load and sliding velocity of 0.42 m/s; (b, b <sub>1</sub> ) PAO 4 with 0.075 wt.% MWCNTs at 80 N load and sliding velocity of 0.42 m/s; (c, c <sub>1</sub> ) pure PAO 6 at 80 N load and sliding velocity of 1.099 m/s; (d, d <sub>1</sub> ) PAO 6 with 0.05 wt.% MWCNTs at 80 N load and sliding velocity of 1.57 m/s; (e, e <sub>1</sub> ) pure PAO 40 at 100 N load and sliding velocity of 1.57 m/s; (f, f <sub>1</sub> ) PAO 40 with 0.075 wt.% MWCNTs at 50 N load and sliding velocity of 1.57 m/s....	188
<b>Figure 5.10:</b> EDS spectra of wear scar of steel balls tested with (a, a <sub>1</sub> ) pure PAO 4 at 50 N load and sliding velocity of 0.42 m/s; (b, b <sub>1</sub> ) PAO 4 with 0.075 wt.% MWCNTs at 80 N	

load and sliding velocity of 0.42 m/s; (c, c<sub>1</sub>) pure PAO 6 at 80 N load and sliding velocity of 1.099 m/s; (d, d<sub>1</sub>) PAO 6 with 0.05 wt.% MWCNTs at 80 N load and sliding velocity of 1.57 m/s; (e, e<sub>1</sub>) pure PAO 40 at 100 N load and sliding velocity of 1.57 m/s; (f, f<sub>1</sub>) PAO 40 with 0.075 wt.% MWCNTs at 50 N load and sliding velocity of 1.57 m/s..... 190

**Figure 6.1:** (a) XRD pattern, (b) FTIR spectra, (c) FE-SEM micrograph, (d) HR-TEM image of LaF<sub>3</sub> nanoparticles, (e) variation in the diameter of LaF<sub>3</sub>, and (f) size and frequency distribution of nanoparticles ..... 198

**Figure 6.2:** (a) XPS survey spectra of LaF<sub>3</sub> nanoparticles, and corresponding deconvoluted XPS spectra of (b) C 1s, (c) La 3d, (d) F 1s, and (e) O 1s..... 199

**Figure 6.3:** Variation in the wear scar diameter of worn surfaces lubricated by (a) PAO 4, and (b) PAO 6-based nanolubricants with applied load .....203

**Figure 6.4:** Wear scar diameter as a function of applied load (a) PAO 40, and (b) PAO 100-based nanolubricants.....205

**Figure 6.5:** Worn surfaces of steel balls lubricated with (a, b) plain PAO 4; (c, d) PAO 4 containing 0.15 wt.% LaF<sub>3</sub>; (e, f) plain PAO 6, and (g, h) PAO 6 containing 0.15 wt.% LaF<sub>3</sub>. (Applied load: 785 N and test duration: 10 s) .....208

**Figure 6.6:** Worn surfaces of steel balls lubricated by (a, b) plain PAO 40; (c, d) PAO 40 containing 0.15 wt.% LaF<sub>3</sub>; (e, f) plain PAO 100; (g, h) PAO 100 containing 0.15 wt.% LaF<sub>3</sub>. (Applied load: 981 N and test duration: 10 s) .....209

**Figure 6.7:** Topographic micrographs of steel balls experimented with (a, b) plain PAO 4; (c, d) PAO 4 containing 0.15 wt.% LaF<sub>3</sub>; (e, f) plain PAO 6, and (g, h) PAO 6 containing 0.15 wt.% LaF<sub>3</sub> (Note: a, c, e, and g: top view and b, d, f, and h: three-dimensional view of worn surfaces). (Applied load: 785 N and test duration: 10 s) .....213

**Figure 6.8:** Topographic micrographs of steel balls experimented with (a, b) plain PAO 40; (c, d) PAO 40 containing 0.15 wt.% LaF<sub>3</sub>; (e, f) plain PAO 100, and (g, h) PAO 100

containing 0.15 wt.% LaF<sub>3</sub> (Note: a, c, e, and g: top view and b, d, f, and h: three-dimensional view of worn surfaces). (Applied load: 981 N and test duration: 10 s) .....214

**Figure 6.9:** Bearing area ratio (BAR) curves of steel balls lubricated with different lubricant compositions. (Applied load: 785 N for low viscosity PAOs and 981 N for high viscosity PAOs based nanolubricants, and test duration: 10 s) .....215

**Figure 6.10:** EDS spectrum of worn scars of steel balls lubricated with (a, b) plain PAO 4; (c, d) PAO 4 containing 0.15 wt.% LaF<sub>3</sub>; (e, f) plain PAO 6; (g, h) PAO 6 containing 0.15 wt.% LaF<sub>3</sub>; (i, j) plain PAO 40; (k, l) PAO 40 containing 0.15 wt.% LaF<sub>3</sub>, and (m, n) plain PAO 100, and (o, p) PAO 100 containing 0.15 wt.% LaF<sub>3</sub>. (Applied load: 785 N for low viscosity PAOs and 981 N for high viscosity PAOs based nanolubricants, and test duration: 10 s).....219

**Figure 6.11:** Photograph depicts the dispersion stability of LaF<sub>3</sub> at room temperature (~30°C) in (a-d) PAO 4; (e-h) PAO 6; (i-l) PAO 40, and (m-p) PAO 100 at different time interval .....220

**Figure 6.12:** Rheological characterization of plain PAO 4, PAO 6, PAO 40, and PAO 100 .....223

**Figure 7.1:** PAO 100 grease having a variable concentration of MWCNTs and LaF<sub>3</sub>: (a, f) 0.025 wt.%, (b, g) 0.05 wt.%, (c, h) 0.075 wt.%, (d, i) 0.1 wt.%, and (e, j) 0.15 wt.%...231

**Figure 7.2:** Variation in unworked and worked penetration depth of PAO grease with and without nanoadditives .....231

**Figure 7.3:** Variation in the drop point of PAO grease with and without nanoadditive.232

**Figure 7.4:** Variation in (a) average COF with variable concentration of MWCNTs and LaF<sub>3</sub> nanoparticles in PAO grease (b) COF as a function of test duration, and influence of varying concentrations of nanoadditive on (c) wear scar diameter and (d) the mean wear volume of worn surfaces. (Applied load: 392 N and test duration: 60 min) .....237

**Figure 7.5:** EP response of varied doses of MWCNTs and LaF<sub>3</sub> blended PAO grease .238

**Figure 7.6:** SEM micrographs of worn surfaces of steel balls lubricated with (a, b) PAO grease; (c, d) 0.05 wt.% MWCNTs doped grease; (e, f) 0.075 wt.% LaF<sub>3</sub> doped grease. (Applied load: 392 N and test duration: 60 min) .....240

**Figure 7.7:** Topographic micrographs of worn surfaces of steel balls lubricated with (a, b) PAO grease; (c, d) 0.05 wt.% MWCNTs doped grease; (e, f) 0.075 wt.% LaF<sub>3</sub> doped grease. (Note: a, c, and e: top view (2D) and b, d, and f: three-dimensional (3D) view of worn surfaces). (Applied load: 392 N and test duration: 60 min).....244

**Figure 7.8:** Bearing area ratio curves of steel balls lubricated with different grease compositions. (Applied load: 392 N and test duration: 60 min).....246

**Figure 7.9:** EDS spectrum of worn scars of steel balls lubricated by (a, b) PAO grease; (c, d) 0.05 wt.% MWCNTs doped grease; (e, f) 0.075 wt.% LaF<sub>3</sub> doped grease. (Applied load: 392 N and test duration: 60 min) .....248

**Figure 7.10:** XPS of worn surface of steel ball lubricated with various grease formulations. (Applied load: 392 N and test duration: 60 min) .....250

**Figure 7.11:** High-resolution XPS spectra showing typical elements on the worn surface of steel balls lubricated with (a, b, and c) PAO grease and (d) MWCNTs doped grease. (Applied load: 392 N and test duration: 60 min) .....251

**Figure 7.12:** High-resolution XPS spectra showing typical elements on the worn surface of steel balls lubricated with LaF<sub>3</sub> doped grease. (Applied load: 392 N and test duration: 60 min).....252

## List of tables

---

---

<b>Table 1.1:</b> Typical chemical structures of the most common synthetic base oils [1] .....	10
<b>Table 2.1:</b> American Petroleum Institute (API) classification of base stock [21] .....	19
<b>Table 2.2:</b> Physical properties of different grades of PAOs [24] .....	22
<b>Table 2.3:</b> Comparison of typical properties of PAOs with mineral and other synthetic oils [25] .....	24
<b>Table 2.4:</b> Physical attributes of a new class of PAO, i.e., SpectraSyn Ultra™ .....	27
<b>Table 2.5:</b> Application of different grades of PAOs in various areas [26] .....	28
<b>Table 2.6:</b> Summary of tribological performance of metals-based nanolubricants .....	34
<b>Table 2.7:</b> Summary of tribological performance of nanolubricants with metal oxides nanoparticles .....	37
<b>Table 2.8:</b> Summary of tribological performance of different base oils with carbon-based nanoparticles as an additive .....	42
<b>Table 2.9:</b> Summary of tribological performance of various types of nanoparticles as lubricant additives .....	47
<b>Table 2.10:</b> Summary of tribological performance of different grades of PAOs with various nanoparticles as an additive .....	53
<b>Table 2.11:</b> Summary of tribological performance of PAO-based greases with various nanoadditives .....	64
<b>Table 3.1:</b> Physical attributes of different base oils (Supplier's data) .....	72
<b>Table 3.2:</b> Properties of MWCNTs (Supplier's data) .....	72
<b>Table 3.3:</b> List of the analytical grade chemicals used in the preparation of LaF <sub>3</sub> nanoparticles .....	73
<b>Table 3.4:</b> Summary of test parameters as per ASTM standard .....	78
<b>Table 3.5:</b> Summary of test parameters as per ASTM D6425 .....	82

**Table 3.6:** Test conditions used for the determination of the grease consistency.....87

**Table 3.7:** Grades of grease classified according to NLGI (ASTM D217) .....87

**Table 4.1:** The summary of COF, WSD, and MWV for different lubricant compositions  
.....99

**Table 4.2:** The outline of EP response of different lubricant formulations ..... 103

**Table 4.3:** The summary of surface roughness of worn steel balls tested with various  
lubricant compositions ..... 108

**Table 4.4:** The summary of typical values of worn surfaces for the various composition of  
nanolubricants ..... 109

**Table 4.5:** The summary of MWCNTs compatibility with different grades of PAO oils  
..... 112

**Table 4.6:** The summary of surface roughness of worn steel balls tested with various  
lubricant formulations ..... 122

**Table 4.7:** The summary of the various characteristics of worn steel disc tested with  
different lubricants ..... 125

**Table 4.8:** The summary of typical values of elements present on the worn surfaces of disc  
lubricated with different lubricant compositions ..... 127

**Table 4.9:** Summary of frictional power loss at different concentrations of additives... 137

**Table 4.10:** Surface roughness parameter of worn steel balls tested various lubricant  
formulations ..... 144

**Table 4.11:** The elements present on the worn surfaces of disc lubricated with various  
lubricants ..... 148

**Table 5.1:** Experimental conditions (parameters and their levels)..... 163

**Table 5.2:** Matrix or designed experiments as per L<sub>18</sub> orthogonal array ..... 165

**Table 5.3:** Experimental layout and obtained results ..... 166

<b>Table 5.4:</b> Response table for S/N ratio for different parameters at different levels .....	168
<b>Table 5.5:</b> Analysis of variance (ANOVA) for coefficient of friction (COF; $\mu$ ) and specific wear rate (K) .....	170
<b>Table 5.6:</b> The summary of model for responses .....	172
<b>Table 5.7:</b> Mean response table for COF and K for various parameters at different levels (Note: Bold values shows the optimal levels of control factors) .....	174
<b>Table 5.8:</b> The summary of comparisons of predicted and confirmation test results .....	180
<b>Table 5.9:</b> The summary of surface roughness of worn steel balls test with various experimental conditions .....	189
<b>Table 6.1:</b> Summary of EP properties of PAO 4 and PAO 6 at different concentrations of LaF <sub>3</sub> nanoparticles .....	204
<b>Table 6.2:</b> Outline of EP properties of PAO 40 and PAO 100-based nanolubricants ....	206
<b>Table 6.3:</b> Surface roughness parameter of worn steel balls tested with various lubricant formulations .....	216
<b>Table 6.4:</b> Comparison of experimental viscosity of PAOs with supplier's data.....	225
<b>Table 7.1:</b> Summary of frictional power loss at different concentrations of MWCNTs and LaF <sub>3</sub> nanoparticles .....	238
<b>Table 7.2:</b> Surface roughness parameter of worn steel balls tested with various grease formulations .....	245
<b>Table 8.1:</b> Summary of overall comparative improvement in AF and AW performance of PAOs.....	261