

List of Figures

1.1	Solidification systems for (a) pure substance and (b) a binary substance.	2
1.2	Equilibrium phase diagram of binary eutectic system (A-B).	3
1.3	Two phase diagram	13
1.4	Multi phase diagram	15
1.5	Enthalpy as a function of temperature for (a) isothermal phase change (b) non-isothermal phase change.	26
2.1	Temperature distribution in b.c. of first kind (I).	50
2.2	Temperature distribution in b.c. of first kind, $Pd = 1.0$ (II).	50
2.3	Temperature distribution in b.c. of second kind, $Ki = 1.0$ (I).	51
2.4	Temperature distribution in b.c. of second kind $Ki = 1.0$, $Pd = 1.0$ (II)	51
2.5	Moving layer thickness (λ) for b.c. of first kind, $Ste = 1$ (I).	52
2.6	Moving layer thickness (λ) for b.c. of second kind, $Ste = 1$ (II).	52
2.7	Effect of Pd on moving layer thickness (λ) for b.c. of first kind, $Ste =$ 1 (II).	53
2.8	Effect of Pd on moving layer thickness (λ) for b.c. of first kind, $Ste =$ 1 (II).	53
2.9	Effect of Pd on moving layer thickness (λ) for b.c. of first kind, $Ste =$ 1 (I).	54
2.10	Effect of Pd on moving layer thickness (λ) for b.c. of second kind, $Ki = 1.0$, $Ste = 1$ (II).	54
2.11	Effect of Pd on moving layer thickness (λ) for b.c. of second kind, $Ki = 1.0$, $Ste = 1$ (II).	55

2.12	Effect of Pd on moving layer thickness (λ) for b.c. of second kind, $Ki = 1.0, Ste = 1$ (II).	55
2.13	Effect of Ki on moving layer thickness (λ) for b.c. of second kind, $Pd = 1.0, Ste = 1$	56
2.14	Effect of Ki on moving layer thickness (λ) for b.c. of second kind, $Pd =$ $1.0, Ste = 1$	56
2.15	Effect of Ki on moving layer thickness (λ) for b.c. of second kind, $Pd = 1.0, Ste = 1$	57
2.16	Effect of Stefan number on moving layer thickness (λ) for b.c. of first kind.	57
2.17	Effect of Stefan number on moving layer thickness (λ) for b.c. of second kind.	58
2.18	Effect of Stefan number on moving layer thickness (λ) for b.c. of third kind.	58
3.1	Compare the exact result of moving layer thickness (λ) with WGM.	72
3.2	Compare the exact result of dimensionless temperature distribution (θ) of phase 1 and phase 2 with WGM.	72
3.3	Dimensionless temperature distribution (θ) of phase 1 and phase (2).	73
3.4	Dimensionless temperature distribution (θ) of phase 1 and phase 2 (3).	73
3.5	Effect of density (ρ_{21}) on moving layer thickness (λ).	74
3.6	Effect of thermal conductivity (K_{12}) on moving layer thickness (λ).	74
3.7	Effect of specific heat coefficients (α_1, α_2) on moving layer thickness (λ) in case (2).	75
3.8	Effect of specific heat coefficients (α_1, α_2) on moving layer thickness (λ) in case (3).	75
3.9	Effect of thermal conductivity coefficients (β_1, β_2) on moving layer thickness (λ) in case (2).	76
3.10	Effect of thermal conductivity coefficients (β_1, β_2) on moving layer thickness (λ) in case (3).	76
3.11	Effect of Stefan no. (Ste) on moving layer thickness (λ).	77

4.1	Dimensionless temperature with dimensionless space x in stage I, $Pd_1 = 4, \eta_3 = 0.0277$	98
4.2	Dimensionless temperatures in mushy and liquid regions with dimensionless space x in stage II, $Pd_2 = 3.5891, \eta_2 = 0.0462, \lambda_2 = 0.0890, Fo_3 = 0.28$	98
4.3	Dimensionless temperatures with time Fo_2 in stage 2, $Pd_2 = 3.5891, \eta_2 = 0.0462, \lambda_2 = 0.0890$ (1).	99
4.4	Moving layer thickness (λ) with dimensionless time Fo_2	99
4.5	Solid fraction (f_s) in mushy zone with dimensionless space x in stage 2, $Fo_2 = 0.25$ (1).	100
4.6	Dimensionless temperatures in solid, mushy and liquid region with dimensionless Space x in stage 3 (1), $Pd_3 = 0.2177, \lambda_1 = 0.3193, \lambda_2 = 0.3931, Fo_3 = 5$	100
4.7	Dimensionless temperatures with time Fo_3 in stage 3 (1).	101
4.8	Moving layer thickness (λ_1, λ_2) with dimensionless time Fo_3 in stage 3 (1).	101
4.9	Solid fraction (f_s) in mushy region with dimensionless space x in stage 3 (1).	102
4.10	Dimensionless temperatures in mushy and liquid regions with dimensionless space x in stage 2 (2), $Pd_2 = 3.5891, \eta_2 = 0.0462, \lambda_2 = 0.0489, Fo_2 = 0.28$	102
4.11	Dimensionless temperatures with time Fo_2 in stage 2 (2), $Pd_2 = 3.5891, \eta_2 = 0.0462, \lambda_2 = 0.0489$	103
4.12	Moving layer thickness (λ_2) with dimensionless time Fo_2 in stage 2 (2).	103
4.13	Solid fraction (f_s) in mushy region with dimensionless space x in stage 2, $Fo_2 = 0.25$ (2).	104
4.14	Dimensionless temperatures in solid, mushy and liquid regions with dimensionless space x in stage III, $Pd_3 = 0.2177, \eta_1 = 0.002, \lambda_1 = 0.2573, \lambda_2 = 0.4729, Fo_3 = 5$	104

4.15	Dimensionless temperatures with time Fo_3 in stage 3 (2), $Pd_3 = 0.2177, \eta_1 = 0.002, \lambda_1 = 0.2573, \lambda_2 = 0.4729$	105
4.16	Moving layer thickness (λ_1, λ_2) with dimensionless time Fo_3 in stage 3 (2).	105
4.17	Solid fraction (f_s) in mushy zone with dimensionless space x in stage 3 (2), $Fo_3 = 22$	106
4.18	Effect of relaxation time on dimensionless temperatures θ_3 with dimensionless time Fo_1 in liquid region.	106
4.19	Effect of relaxation time on dimensionless temperatures θ_2 with dimensionless space x in mushy region.	107
4.20	Effect of relaxation time on dimensionless temperatures θ_1 with time Fo_3 in solid region.	107
5.1	Residual obtained from differential equation in first kind b.c. at $Fo = 5$ (II).	120
5.2	Residual obtained from boundary condition defined in first kind b.c. at $Fo = 5$ (II).	120
5.3	Residual obtained from differential equation in second kind b.c. at $y = Fo = 0.5, Ki = Pd = 0.01$ (II).	121
5.4	Residual obtained from boundary condition defined in second kind b.c. at $y = \lambda = 0.5, Ki = Pd = 0.01$ (II).	121
5.5	Residual obtained from boundary condition defined at $y = \lambda$ in second kind b.c., $y = \lambda = Fo = Pd = 0.5$ (II).	122
5.6	Residual obtained from boundary condition defined at $y = \lambda$ in second kind b.c., $y = \lambda = Fo = Ki = 0.5$ (II).	122
5.7	Residual obtained from differential equation in third kind b.c. at $Fo = 5$ (II).	123
5.8	Residual obtained from boundary condition in third kind b.c. at $\lambda = 0.5, Fo = 5$ (II).	123
5.9	Moving layer thickness $\lambda(Fo)$ with dimensionless time Fo (I). . . .	124
5.10	Moving layer thickness $\lambda(Fo)$ with dimensionless time Fo (II). . . .	124

5.11	Effect of Pd on moving layer thickness $\lambda(Fo)$ with dimensionless time $Fo, x = 1, Ki = 0.25$ (I).	125
5.12	Effect of Pd on moving layer thickness $\lambda(Fo)$ with dimensionless time $Fo, x = 2/3, Ki = 0.25$ (II).	125
5.13	Effect of Ki on moving layer thickness $\lambda(Fo)$ with dimensionless time $Fo, x = 1, Pd = 0.25$ (I).	126
5.14	Effect of Ki on moving layer thickness $\lambda(Fo)$ with dimensionless time $Fo, x = 2/3, Pd = 0.25$ (II).	126
5.15	Effect of Bi on moving layer thickness $\lambda(Fo)$ with dimensionless time Fo in third kind b.c. at $x = 1$ (I).	127
5.16	Effect of Bi on moving layer thickness $\lambda(Fo)$ with dimensionless time Fo in third kind b.c. at $x = 2/3$ (II).	127
5.17	Dimensionless temperature θ in first kind b.c. at $x = 1$ (I).	128
5.18	Dimensionless temperature θ in second kind b.c. at $x = 1$ (I).	128
5.19	Dimensionless temperature θ in third kind b.c. at $x = 1$ (I).	129
5.20	Dimensionless temperature θ in first kind b.c. (II).	129
5.21	Dimensionless temperature θ in second kind b.c. (II).	130
5.22	Dimensionless temperature θ in third kind b.c. (II).	130