

---

**LIST OF FIGURES**

<b>Figure 1.1</b>	Schematic of alkaline direct alcohol fuel cell	3
<b>Figure 2.1</b>	Cyclic voltammograms for 1 M methanol, ethanol and isopropanol oxidation on Pt/C and Pt-Ru/C nanocatalyst in 0.5 M KOH. Scan rate: 10 mV/s	22
<b>Figure 2.2</b>	The CV curves of ORR on Pt wire electrode in 1 M KOH solutions saturated with nitrogen and oxygen at temperature of 25 °C. Scan rate: 40 mV/s	24
<b>Figure 2.3</b>	Possible transport mechanism of OH <sup>-</sup> ions in alkaline membrane (Grew and Chiu, 2010)	31
<b>Figure 2.4</b>	Some important polymers for membrane electrolyte synthesis (a) Polychloropropene (b) Polyethylene oxide (c) Polybenzimidazole (PBI) (d) Polyvinyl alcohol (PVA) (e) Chitosan (CS) and (f) Polyepichlorhydrine (PECH)	32
<b>Figure 2.5</b>	The crosslinking mechanism of PVA with glutaraldehyde	35
<b>Figure 3.1</b>	Schematic of cyclic voltammetry setup for single electrode studies	55
<b>Figure 3.2</b>	Schematic of direct alcohol fuel cell setup	56
<b>Figure 3.3</b>	Two probe through plane setup for measuring membrane conductivity	61
<b>Figure 3.4</b>	Electrical circuit diagram for recording current-voltage data	65

---

<b>Figure 4.1a</b>	Electrochemical impedance spectra (EIS) for the pristine PVA membrane doped with various molar KOH solution at a temperature of 30 °C.	72
<b>Figure 4.1b</b>	Electrochemical impedance spectra (EIS) for the physical crosslinked PVA membrane doped with various molar KOH solution at a temperature of 30 °C.	73
<b>Figure 4.2a</b>	SEM image of the surface of pristine PVA membrane	75
<b>Figure 4.2b</b>	SEM image of the surface of physically crosslinked PVA membrane	75
<b>Figure 4.2c</b>	SEM image of the surface of physically crosslinked PVA membrane doped with 6 M KOH	76
<b>Figure 4.2d</b>	SEM-EDX image of cross section of physically crosslinked PVA membrane without KOH doping	76
<b>Figure 4.2e</b>	SEM-EDX image of cross section of physically crosslinked PVA membrane, doped with 6 M KOH	77
<b>Figure 4.3</b>	XRD spectra of the (a) pristine PVA membrane (b) physically crosslinked PVA membrane and (c) physically crosslinked PVA membrane, 6 M KOH doped	78
<b>Figure 4.4</b>	FTIR spectrum of the (a) pristine PVA membrane (b) physically crosslinked PVA membrane and (c) physically crosslinked PVA membrane, 6 M KOH doped	79
<b>Figure 4.5</b>	The stress-strain curves of pristine PVA membrane and the physically crosslinked PVA membrane	80
<b>Figure 4.6a</b>	SEM of the blank GDL	81
<b>Figure 4.6b</b>	SEM of 0.5 mg/cm <sup>2</sup> Pt-Ru/C anode	81

---

<b>Figure 4.6c</b>	SEM of 1 mg/cm <sup>2</sup> Pt-Ru/C anode	82
<b>Figure 4.6d</b>	SEM of 1.5 mg/cm <sup>2</sup> Pt-Ru/C anode	82
<b>Figure 4.7a</b>	SEM of 0.5 mg/cm <sup>2</sup> Pt/C <sub>HSA</sub> cathode	83
<b>Figure 4.7b</b>	SEM of 1 mg/cm <sup>2</sup> Pt/C <sub>HSA</sub> cathode	84
<b>Figure 4.7c</b>	SEM of 1.5 mg/cm <sup>2</sup> Pt/C <sub>HSA</sub> cathode	84
<b>Figure 4.8a</b>	Cyclic voltammetry for Pt-Ru/C anode at different scan rates using 1 M methanol solution mixed with 0.5 M KOH solution; Temperature: 30 °C	86
<b>Figure 4.8b</b>	Cyclic voltammetry for Pt-Ru/C anode at different scan rates using 1 M ethanol solution mixed with 0.5 M KOH solution; Temperature: 30 °C	87
<b>Figure 4.9a</b>	Cyclic voltammetry for different loading of Pt-Ru/C anode electrocatalyst using 1 M methanol solution mixed with 0.5 M KOH solution at scan rate of 100 mV/s; Temperature: 30 °C	89
<b>Figure 4.9b</b>	Cyclic voltammetry for different loading of Pt-Ru/C anode electrocatalysts using 1 M ethanol solution mixed with 0.5 M KOH solution at scan rate of 100 mV/s; Temperature: 30 °C	90
<b>Figure 4.10a</b>	Cyclic voltammetry for Pt-Ru/C anode using different concentration of methanol mixed with 0.5 M KOH solution at scan rate of 100 mV/s; Temperature: 30 °C	91
<b>Figure 4.10b</b>	Cyclic voltammetry for Pt-Ru/C anode using different concentration of ethanol mixed with 0.5 M KOH solution at scan rate of 100 mV/s; Temperature: 30 °C	92

---

<b>Figure 4.11a</b>	Cyclic voltammetry for Pt-Ru/C anode using different concentration of KOH mixed with 3 M methanol solution at scan rate of 100 mV/s; Temperature: 30 °C	94
<b>Figure 4.11b</b>	Cyclic voltammetry for Pt-Ru/C anode using different concentration of KOH mixed with 2 M ethanol solution at scan rate of 100 mV/s; Temperature: 30 °C	95
<b>Figure 4.12</b>	Cyclic voltammetry for Pt-Ru/C anode at fixed electrocatalyst loading of 1 mg/cm <sup>2</sup> using fixed KOH concentration of 0.5 M at different molar ratios of methanol to ethanol at scan rate of 100 mV/s; Temperature: 30 °C. MeOH-Methanol, EtOH-Ethanol	96
<b>Figure 4.13a</b>	Cyclic voltammetry for Pt/C <sub>HSA</sub> cathode loading of 1 mg/cm <sup>2</sup> and 100 mV/s scan rate using 1 M KOH purged with nitrogen; Temperature: 30 °C	98
<b>Figure 4.13b</b>	Cyclic voltammetry for Pt/C <sub>HSA</sub> cathode loading of 1 mg/cm <sup>2</sup> and 100 mV/s scan rate using 1 M KOH oxygen saturated solution; Temperature: 30 °C	98
<b>Figure 4.14a</b>	Current density vs. cell voltage and current density vs. power density characteristics for physical crosslinked PVA membrane doped with different molar KOH solution using 2 M methanol mixed with 6 M KOH at a temperature of 30 °C; Dotted line - power density curves; Solid line-polarization curves	101

- 
- Figure 4.14b** Current density vs. cell voltage and current density vs. power density characteristics for physical crosslinked PVA membranes doped with different molar KOH solution using 2 M ethanol mixed with 1 M KOH at a temperature of 30 °C; Dotted line-power density curves; Solid line-polarization curves 101
- Figure 4.15a** Current density vs. cell voltage and current density vs. power density characteristics using fixed 1 M KOH and different methanol concentration using O<sub>2</sub> as oxidant at a temperature of 30 °C; Dotted line-power density curves; Solid line-polarization curves 103
- Figure 4.15b** Current density vs. cell voltage and current density vs. power density characteristics using fixed 1 M KOH and different ethanol concentration using O<sub>2</sub> as oxidant at a temperature of 30 °C; Dotted line-power density curves; Solid line-polarization curves 104
- Figure 4.16a** Current density vs. cell voltage and current density vs. power density characteristics for fixed 2 M methanol and different KOH using O<sub>2</sub> as oxidant at a temperature of 30 °C; Dotted line-power density curves; Solid line-polarization curves 105
- Figure 4.16b** Current density vs. cell voltage and current density vs. power density characteristics for fixed 2 M ethanol and different KOH using O<sub>2</sub> as oxidant at a temperature of 30 °C; Dotted line-power density curves; Solid line-polarization curves 106

- 
- Figure 4.17a** Current density vs. cell voltage and current density vs. power density characteristics for different anode loading using 2 M methanol mixed with 6 M KOH at a temperature of 30 °C; Dotted line-power density curves; Solid line-polarization curves 108
- Figure 4.17b** Current density vs. cell voltage and current density vs. power density characteristics for different anode loading using 2 M ethanol mixed with 1 M KOH at a temperature of 30 °C; Dotted line-power density curves; Solid line-polarization curves 109
- Figure 4.18a** Current density vs. cell voltage and current density vs. power density characteristics for different cathode loading using 2 M methanol mixed with 6 M KOH at a temperature of 30 °C; Dotted line-power density curves; Solid line-polarization curves 110
- Figure 4.18b** Current density vs. cell voltage and current density vs. power density characteristics for different cathode loading using 2 M ethanol mixed with 1 M KOH at a temperature of 30 °C; Dotted line-power density curves; Solid line-polarization curves 111
- Figure 4.19a** Current density versus cell voltage and current density versus power density characteristics using different anode electrocatalyst for 2 M methanol mixed with 6 M KOH at a temperature of 30 °C; Dotted line-power density curves; Solid line-polarization curves 113

- 
- Figure 4.19b** Current density versus cell voltage and current density versus power density characteristics using different anode electrocatalyst for 2 M ethanol mixed with 1 M KOH at a temperature of 30 °C; Dotted line-power density curves; Solid line-polarization curves 113
- Figure 4.20a** Current density vs. cell voltage and current density vs. power density characteristics for 2 M methanol mixed with 6 M KOH at various temperatures; Dotted line -power density curves; Solid line-polarization curves 115
- Figure 4.20b** Current density vs. cell voltage and current density vs power density characteristics for 2 M ethanol mixed with 1 M KOH at various temperatures; Dotted line -power density curves; Solid line-polarization curves 116
- Figure 4.21a** Current density versus cell voltage and current density versus power density characteristics using oxygen and air for 2 M methanol mixed with 6 M KOH at a temperature of 30 °C; Dotted line -power density curves; Solid line-polarization curves 117
- Figure 4.21b** Current density versus cell voltage and current density versus power density using characteristics oxygen and air for 2 M ethanol mixed with 1 M KOH at a temperature of 30 °C; Dotted line -power density curves; Solid line-polarization curves 118

---

<b>Figure 4.22a</b>	Current density vs. cell voltage and current density vs. power density characteristics for pristine and physical crosslinked PVA membrane using 2 M methanol mixed with 6 M KOH at a temperature of 30 °C; Dotted line-power density curves; Solid line-polarization curves	120
<b>Figure 4.22b</b>	Current density vs. cell voltage and current density vs. power density characteristics for pristine and physical crosslinked PVA membrane using 2 M ethanol mixed with 1 M KOH at a temperature of 30 °C; Dotted line-power density curves; Solid line-polarization curves	120
<b>Figure 4.23</b>	Current density vs. cell voltage and current density vs. power density characteristics for different molar ratios of methanol to ethanol using O <sub>2</sub> as oxidant at a temperature of 30 °C; MeOH-Methanol, EtOH-Ethanol; Dotted line-power density curves; Solid line-polarization curves	121
<b>Figure 4.24</b>	Stability test of the DAFC using methanol or ethanol or their mixture as fuel at constant load at a temperature of 30 °C; MeOH-Methanol, EtOH-Ethanol	123
<b>Figure 4.25a</b>	Electrochemical impedance spectra (EIS), for PVA membrane crosslinked with 1 wt % GA and doped with various molar KOH solution at a temperature of 30 °C	128
<b>Figure 4.25b</b>	Electrochemical impedance spectra (EIS), for PVA membrane crosslinked with 2 wt % GA and doped with various molar KOH solution at a temperature of 30 °C	129

---

<b>Figure 4.25c</b>	Electrochemical impedance spectra (EIS), for PVA membrane crosslinked with 2.5 wt % GA and doped with various molar KOH solution at a temperature of 30 °C	129
<b>Figure 4.25d</b>	Electrochemical impedance spectra (EIS), for PVA membrane crosslinked with 3 wt % GA and doped with various molar KOH solution at a temperature of 30 °C	130
<b>Figure 4.26a</b>	SEM image of the surface of pristine PVA	133
<b>Figure 4.26b</b>	SEM image of the surface of crosslinked with 2 wt % GA PVA membrane	133
<b>Figure 4.26c</b>	SEM images of the surface of crosslinked with 2.5 wt % GA PVA membrane	134
<b>Figure 4.26d</b>	SEM images of the surface of crosslinked with 3 wt % GA PVA membrane	134
<b>Figure 4.26e</b>	SEM images of the surface of crosslinked with 2.5 wt % GA, doped with 6 M KOH PVA membrane	135
<b>Figure 4.26f</b>	SEM-EDX image of cross section of PVA membrane crosslinked with 2.5 wt % GA without KOH	135
<b>Figure 4.26g</b>	SEM-EDX image of cross section of PVA membrane crosslinked with 2.5 wt % GA, doped with 6 M KOH	136
<b>Figure 4.27</b>	XRD spectra of the (a) pristine PVA membrane (b) 2 wt % GA crosslinked PVA membrane (c) 2.5 wt % GA crosslinked PVA membrane (d) 2.5 wt % GA crosslinked, 6 M KOH doped PVA membrane and (e) 3 wt % GA crosslinked PVA membrane	137

- 
- Figure 4.28** FTIR spectrum of the (a) pristine PVA membrane (b) 2 wt % GA crosslinked PVA membrane (c) 2.5 wt % GA crosslinked PVA membrane (d) 2.5 wt % GA crosslinked, 6 M KOH doped PVA membrane and (e) 3 wt % GA crosslinked PVA membrane 138
- Figure 4.29** The stress-strain curves of pristine PVA membrane and the crosslinked PVA membrane (2.5 wt % GA) 139
- Figure 4.30a** Current density vs. cell voltage and current density vs. power density characteristics for PVA membranes crosslinked with different glutaraldehyde (GA) concentration using 3 M methanol mixed with 6 M KOH at a temperature of 30 °C; Dotted line-power density curves; Solid line-polarization curves 141
- Figure 4.30b** Current density vs. cell voltage and current density vs. power density characteristics for PVA membranes crosslinked with different glutaraldehyde (GA) concentration using 2 M ethanol mixed with 1 M KOH at a temperature of 30 °C; Dotted line-power density curves; Solid line-polarization curves 142
- Figure 4.31a** Current density vs. cell voltage and current density vs. power density characteristics for PVA membranes doped with different molar KOH solution using 3 M methanol mixed with 6 M KOH at a temperature of 30 °C; Dotted line-power density curves; Solid line-polarization curves 145

- 
- Figure 4.31b** Current density vs. cell voltage and current density vs. power density characteristics for PVA membranes doped with different molar KOH solution using 2 M ethanol mixed with 1 M KOH at a temperature of 30 °C; Dotted line-power density curves; Solid line-polarization curves 145
- Figure 4.32a** Current density vs. cell voltage and current density vs. power density characteristics for different methanol concentration using fixed 0.5 M KOH at a temperature of 30 °C; Dotted line-power density curves; Solid line-polarization curves 148
- Figure 4.32b** Current density vs. cell voltage and current density vs. power density characteristics for different ethanol concentration using fixed 0.5 M KOH at a temperature of 30 °C; Dotted line-power density curves; Solid line-polarization curves 148
- Figure 4.33a** Current density vs. cell voltage and current density vs. power density characteristics for different KOH concentration using fixed 3 M methanol at a temperature of 30 °C; Dotted line-power density curves; Solid line-polarization curves 150
- Figure 4.33b** Current density vs. cell voltage and current density vs. power density characteristics for different KOH concentration using fixed 2 M ethanol and at a temperature of 30 °C; Dotted line-power density curves; Solid line-polarization curves 151

- 
- Figure 4.34a** Current density vs. cell voltage and current density vs. power density characteristics for different anode loading using 3 M methanol mixed with 6 M KOH at a temperature of 30 °C; Dotted line-power density curves; Solid line-polarization curves 153
- Figure 4.34b** Current density vs. cell voltage and current density vs. power density characteristics for different anode loading using 2 M ethanol mixed with 1 M KOH at a temperature of 30 °C; Dotted line-power density curves; Solid line-polarization curves 154
- Figure 4.35a** Current density vs. cell voltage and current density vs. power density characteristics for different cathode loading using 3 M methanol mixed with 6 M KOH at a temperature of 30 °C; Dotted line-power density curves; Solid line-polarization curves 155
- Figure 4.35b** Current density vs. cell voltage and current density vs. power density characteristics for different cathode loading using 2 M ethanol mixed with 1 M KOH at a temperature of 30 °C; Dotted line-power density curves; Solid line-polarization curves 156
- Figure 4.36a** Current density vs. cell voltage and current density vs. power density characteristics for different anode electrocatalyst using 3 M methanol mixed with 6 M KOH at a temperature of 30 °C; Dotted line-power density curves; Solid line-polarization curves 158

- 
- Figure 4.36b** Current density vs. cell voltage and current density vs. power density characteristics for different anode electrocatalyst using 2 M ethanol mixed with 1 M KOH at a temperature of 30 °C; Dotted line-power density curves; Solid line-polarization curves 158
- Figure 4.37a** Current density vs. cell voltage and current density vs. power density characteristics at various temperatures for 3 M methanol mixed with 6 M KOH; Dotted line-power density curves; Solid line-polarization curves 160
- Figure 4.37b** Current density vs. cell voltage and current density vs. power density characteristics at various temperatures for 2 M ethanol mixed with 1 M KOH; Dotted line -power density curves; Solid line-polarization curves 161
- Figure 4.38a** Current density vs. cell voltage and current density vs. power density characteristics for oxygen and air using 3 M methanol mixed with 6 M KOH at a temperature of 30 °C; Dotted line-power density curves; Solid line-polarization curves 162
- Figure 4.38b** Current density vs. cell voltage and current density vs. power density characteristics for oxygen and air using 2 M ethanol mixed with 1 M KOH at a temperature of 30 °C; Dotted line-power density curves; Solid line-polarization curves 163

- Figure 4.39a** Current density vs. cell voltage and current density vs. power density characteristics for pristine and chemical crosslinked (2.5 wt % GA) PVA membrane using 3 M methanol mixed with 6 M KOH at a temperature of 30 °C; Dotted line-power density curves; Solid line-polarization curves 164
- Figure 4.39b** Current density vs. cell voltage and current density vs. power density characteristics for pristine and chemical crosslinked (2.5 wt % GA) PVA membrane using 2 M ethanol mixed with 1 M KOH at a temperature of 30 °C; Dotted line-power density curves; Solid line-polarization curves 165
- Figure 4.40** Current density vs. cell voltage and current density vs. power density characteristics for different molar ratios of methanol to ethanol at a temperature of 30 °C; MeOH-Methanol, EtOH-Ethanol; Dotted line-power density curves; Solid line-polarization curves 166
- Figure 4.41** Stability test of the DAFC using 3 M methanol mixed with 6 M KOH or 2 M ethanol mixed with 1 M KOH or methanol-ethanol mixture mixed with 0.5 M KOH at constant load at a temperature of 30 °C; MeOH-Methanol, EtOH-Ethanol 167