

LIST OF FIGURES

Fig. 1.1. Basic parameters on which damage depends.	1
Fig. 1.2. Structure health monitoring system.....	4
Fig. 1.3. Main categories of NDT methods for SHM.....	5
Fig. 1.4 Elements of structural health monitoring.....	6
Fig. 1.5. Flow chart of structural health monitoring.....	7
Fig. 2.1. Schematic diagram of nerve cell	26
Fig. 2.2. Basic working of artificial neural network.....	27
Fig. 3.1. Block diagram of different fiber optics sensor technologies.....	35
Fig. 3.2. Co-ordinate axis position for fiber curve.....	43
Fig. 3.3. Schematic showing working of discrete wavelet transform.....	53
Fig. 4.1. Advantages of aluminum as a structural material	57
Fig. 4.2. Schematic of sample notch location ratio.....	60
Fig. 4.3. Actual photograph of the sample with a notch.....	61
Fig. 4.4. Actual photograph of samples for FOS testing	61
Fig. 4.5. Schematic diagram of the sample used in diffuse wave analysis.....	62
Fig. 4.6. Samples used in diffuse wave based SHM.....	63
Fig. 4.7. Major equipment's used in FOS based testing	65
Fig. 4.8. Additional equipment's used in diffuse wave based testing	66
Fig. 4.9. Complete experimental setup for FOS testing.....	67
Fig. 4.10. Experimental setup used in diffuse wave analysis	68
Fig. 5.1(a). Different error comparison of Levenberg-Marquardt and Bayesian Regularization algorithms (root mean square error).....	77
Fig. 5.1(b). Different error comparison of Levenberg-Marquardt and Bayesian Regularization algorithms (mean square error)	77
Fig. 5.1(c). Different error comparison of Levenberg-Marquardt and Bayesian Regularization algorithms (mean relative error).....	77
Fig. 5.1(d). Different error comparison of Levenberg-Marquardt and Bayesian Regularization algorithms (mean absolute error)	77
Fig. 5.2(a). Regression histogram showing variation in sample type at different loads(Training R-value histogram).....	78

Fig. 5.2(b). Regression histogram showing variation in sample type at different loads (Testing R-value histogram)	78
Fig. 5.3. Schematic of neural network architecture for strain detection.....	79
Fig. 5.4(a). Comparative results of strain gauge and finite element modelling (Strain value comparison at different loads).....	81
Fig. 5.4(b). Comparative results of strain gauge and finite element modelling (Relative mean strain gauge error histogram).	81
Fig. 5.5(a). Comparative results of analytical solution and finite element modelling(Strain value comparison at different loads).....	81
Fig. 5.5(b). Comparative results of analytical solution and finite element modelling(Relative mean strain gauge error histogram).	81
Fig. 5.6(a). Comparative results of neural network model and finite element modelling(Strain value comparison at different loads).....	81
Fig. 5.6(b). Comparative results of neural network model and finite element modelling(Relative mean strain gauge error histogram)..	81
Fig. 5.7(a). Results of k-fold analysis at different k values (Root mean square error using LM algorithm)	84
Fig. 5.7(b). Results of k-fold analysis at different k values (Root mean square error using BR algorithm).....	84
Fig. 5.7(c). Results of k-fold analysis at different k values (Regression analysis using LM algorithm).....	84
Fig. 5.7(d). Results of k-fold analysis at different k values (Regression analysis using BR algorithm)	84
Fig. 5.8. Schematic representation of the neural network model	85
Fig. 5.9(a). Mean square error plots of data set of different samples at different loadings>Loading at 2N)	88
Fig. 5.9(b). Mean square error plots of data set of different samples at different loadings>Loading at 4N)	88
Fig. 5.9(c). Mean square error plots of data set of different samples at different loadings>Loading at 6N)	88
Fig. 5.9(d). Mean square error plots of data set of different samples at different loadings>Loading at 8N)	88
Fig. 5.9(e). Mean square error plots of data set of different samples at different loadings>Loading at 10N)	88

Fig. 5.10(a). Strain comparison obtained from different methods (Sample A).....	89
Fig. 5.10(b). Strain comparison obtained from different methods (Sample B).....	89
Fig. 5.10(c). Strain comparison obtained from different methods (Sample C).....	89
Fig. 5.10(d). Strain comparison obtained from different methods (Sample D).....	89
Fig. 5.11. Schematic representation of the neural network model.	90
Fig. 5.12(a). Comparison of k-fold analysis at different k values (Root mean square error).	92
Fig. 5.12(b). Comparison of k-fold analysis at different k values (Regression analysis).	92
Fig. 5.13(a). Sequential k-fold analysis at different phase (Root mean square error)...	93
Fig. 5.13(b). Sequential k-fold analysis at different phase (Regression analysis).....	93
Fig. 6.1(a). Comparative plots of approximate coefficients of open and constrained boundary conditions @ 2MHz (Sensor 1)	98
Fig. 6.1(b). Comparative plots of approximate coefficients of open and constrained boundary conditions @ 2MHz (Sensor 2)	98
Fig. 6.1(c). Comparative plots of approximate coefficients of open and constrained boundary conditions @ 2MHz (Sensor 3)	98
Fig. 6.1(d). Comparative plots of approximate coefficients of open and constrained boundary conditions @ 2MHz (Sensor 4)	98
Fig. 6.2(a). Comparative plots of approximate coefficients of open and constrained boundary conditions @ 2.5MHz (Sensor 1).	99
Fig. 6.2(b). Comparative plots of approximate coefficients of open and constrained boundary conditions @ 2.5MHz (Sensor 2).	99
Fig. 6.2(c). Comparative plots of approximate coefficients of open and constrained boundary conditions @ 2.5MHz (Sensor 3).	99
Fig. 6.2(d). Comparative plots of approximate coefficients of open and constrained boundary conditions @ 2.5MHz (Sensor 4).	99
Fig. 6.3(a). Comparative plots of approximate coefficients of open and constrained boundary conditions @ 3MHz (Sensor 1).	100
Fig. 6.3(b). Comparative plots of approximate coefficients of open and constrained boundary conditions @ 3MHz (Sensor 2).	100
Fig. 6.3(c). Comparative plots of approximate coefficients of open and constrained boundary conditions @ 3MHz (Sensor 3).	100

Fig. 6.3(d). Comparative plots of approximate coefficients of open and constrained boundary conditions @ 3MHz (Sensor 4).	100
Fig. 6.4. Schematic of neural network architecture.	102
Fig. 6.5(a). Mean square error plots of different sensor @ 2MHz (Sensor 1).....	105
Fig. 6.5(b). Mean square error plots of different sensor @ 2MHz (Sensor 2).	105
Fig. 6.5(c). Mean square error plots of different sensor @ 2MHz (Sensor 3).....	105
Fig. 6.5(d). Mean square error plots of different sensor @ 2MHz (Sensor 4).	105
Fig. 6.6(a). Mean square error plots of different sensor @ 2.5MHz (Sensor 1).....	106
Fig. 6.6(b). Mean square error plots of different sensor @ 2.5MHz (Sensor 2).....	106
Fig. 6.6(c). Mean square error plots of different sensor @ 2.5MHz (Sensor 3).....	106
Fig. 6.6(d). Mean square error plots of different sensor @ 2.5MHz (Sensor 4).....	106
Fig. 6.7(a). Mean square error plots of different sensor @ 3MHz (Sensor 1).....	107
Fig. 6.7(b). Mean square error plots of different sensor @ 3MHz (Sensor 2).	107
Fig. 6.7(c). Mean square error plots of different sensor @ 3MHz (Sensor 3).....	107
Fig. 6.7(d). Mean square error plots of different sensor @ 3MHz (Sensor 4).	107
Fig. 6.8(a). Comparison of ANN based output to the target values @ 2MHz excitation.....	108
Fig. 6.8(a). Comparison of ANN based output to the target values @ 2.5MHz excitation.....	108
Fig. 6.8(a). Comparison of ANN based output to the target values @ 3MHz excitation.....	108
Fig. 6.9(a). Variation of residual energy @ 2MHz (Sensor Location 1).....	116
Fig. 6.9(b). Variation of residual energy @ 2MHz (Sensor Location 2).....	116
Fig. 6.9(c). Variation of residual energy @ 2MHz (Sensor Location 3).....	116
Fig. 6.9(d). Variation of residual energy @ 2MHz (Sensor Location 4).....	116
Fig. 6.10(a). Variation of residual energy @ 2.5MHz(Sensor Location 1).....	117
Fig. 6.10(b). Variation of residual energy @ 2.5MHz(Sensor Location 2).....	117
Fig. 6.10(c). Variation of residual energy @ 2.5MHz(Sensor Location 3).....	117
Fig. 6.10(d). Variation of residual energy @ 2.5MHz(Sensor Location 4).....	117
Fig. 6.11(a). Variation of residual energy @ 3MHz(Sensor Location 1).....	118
Fig. 6.11(b). Variation of residual energy @ 3MHz(Sensor Location 2).....	118
Fig. 6.11(c). Variation of residual energy @ 3MHz(Sensor Location 3).....	118
Fig. 6.11(d). Variation of residual energy @ 3MHz(Sensor Location 4).....	118