
CONTENTS

	PAGE No.
List of Abbreviations	I-III
List of Figures	IV-X
List of Tables and Schemes	XI-XII
Preface	XIII-XV

Chapter 1

1. Introduction	1-57
1.1 Tribology	1
1.1.1. Friction	1
1.1.2. Wear	2
1.1.3. Lubrication	3
1.2. Lubricants	5
1.2.1. Liquid Lubricants	6
1.2.2. Semi-solid Lubricants	7
1.2.3. Solid Lubricants	7
1.2.4. Gaseous Lubricants	8
1.3. Lubricant Additives	8
1.3.1. Conventional Additives	8
1.3.2. Nanoadditives	10
1.3.2.1. Quantum Dots and their Functionalization	11
1.3.2.2. Nanoparticles	12
1.3.2.3. Nanosheets	14
1.3.2.4. Nanospheres	25
1.4. Statement of the Problem	27
1.5. Aims and Objectives	28
1.6. References	31

Chapter 2

2. Experimental Methods	58-65
2.1. Instrumentation Used for Characterization of the Synthesized Additives	58
2.2. Antiwear Testing	59
2.2.1. Base oil	59
2.2.2. Specification of Steel Ball Bearing	59
2.2.3. Test Methodology	59
2.3. Tribological Parameters relevant to the present study	61
2.3.1. Mean wear scar diameter (MWD)	61
2.3.2. Mean wear volume (MWV)	61
2.3.3. Wear rate	62
2.3.4. Coefficient of Friction (μ)	63
2.3.5. Analysis of Worn Surface	63
2.3.6. Frictional Power Loss (P)	63

Chapter 3

3. Ternary Composite of Methionine Functionalized Graphene Oxide, Lanthanum-Doped Yttria Nanoparticles, and Molybdenum Disulfide Nanosheets for Thin-Film Lubrication	66-109
3.1. Introduction	66
3.2. Experimental Section	69
3.2.1. Materials	69
3.2.2. Syntheses of nano-additives	69
3.2.2.1. Synthesis of yttria and 7% lanthanum-doped yttria nanoparticles	69
3.2.2.2. Synthesis of MoS ₂ nanosheets	69
3.2.2.3. Preparation of binary composite, lanthanum-doped Y ₂ O ₃ nanoparticles, and MoS ₂ nanosheets	70
3.2.2.4. Preparation of graphene oxide (GO) and methionine functionalized reduced	

graphene oxide (M-rGO)	70
3.2.2.5. Preparation of ternary composite (La-Y ₂ O ₃)-MoS ₂ -(M-rGO)	72
3.2.3. Tribological tests	72
3.3. Results and Discussion	73
3.3.1. Techniques adopted to characterize the nano additives	73
3.3.2. Assessment of tribological behavior of nano additives in paraffin oil	82
3.3.2.1. Determination Stability	82
3.3.2.2. Evaluation of Optimized concentration of the additives	84
3.3.2.3. Friction and wear modifying the behavior of the additives	84
3.3.2.4. Load Bearing Capacity	89
3.3.2.5. Worn surface Morphological studies	90
3.3.2.6. Characterization of the tribochemical film	93
3.3.2.7. Tribo-chemistry and mechanism of lubrication	96
3.4. Conclusions	97
3.5. References	99

Chapter 4

4. Hetero lamellar Bi₂Se₃/Bi₂WO₆ and Bi₂Se₃/N-doped Bi₂WO₆ Nanosheet Composites as Potential Antifriction and Antiwear Agents	110-148
--	----------------

4.1. Introduction	110
4.2. Experimental section	113
4.2.1. Materials	113
4.2.2. Preparation of Nano-Additives	113
4.2.2.1. Preparation of lamellar Bi ₂ Se ₃ nanosheets	113
4.2.2.2. Preparation of bismuth tungstate nanosheets (Bi ₂ WO ₆)	114
4.2.2.3. Preparation of N-Bi ₂ WO ₆ nanosheets	114
4.2.2.4. Preparation of Bi ₂ Se ₃ /Bi ₂ WO ₆ hybrid nanosheets	115
4.2.2.5. Preparation of Bi ₂ Se ₃ /N-Bi ₂ WO ₆ hybrid nanosheets	115

4.2.3. Sample preparation	115
4.3. Results and Discussion	116
4.3.1 Microstructure and Morphology of the Synthesized Additives	116
4.3.2. Tribological characteristics of the additives	123
4.3.2.1. Determination of Stability of Nanofluids	123
4.3.2.2. Assessment of Optimal Additive Concentration	124
4.3.2.3 Antiwear and antifriction properties	126
4.3.2.4. Load-carrying ability	127
4.3.2.5. Frictional power loss	128
4.3.2.6. Wear Scar Surface	129
4.3.2.7. XPS Analysis of Tribofilm	133
4.3.2.8. Tentative lubrication mechanism	135
4.4. Conclusions	136
4.5. References	138

Chapter 5

5. The Wear and Friction Behavior of NiO Nanosphere/Cobalt-Doped MnV₂O₆ Nanosheet Nanocomposite	149 - 184
5.1. Introduction	149
5.2. Experimental Section	152
5.2.1. Materials	152
5.2.2. Syntheses of nano additives	152
5.2.2.1. Synthesis of pure manganese vanadate (MnV ₂ O ₆) and Co-doped MnV ₂ O ₆ nanosheets	152
5.2.2.2. Synthesis of MOF-derived NiO nanospheres	153
5.2.2.3. Preparation of binary nanocomposite, NiO/C-MVO	153
5.2.2.4. Sample preparation	154
5.3. Results and Discussion	155
5.3.1. Techniques adopted to characterize the nano additives MVO, C-MVO, NiO, and the hybrid NiO/C-MVO	155

5.3.2. Assessment of tribological behavior of nano additives in paraffin oil	161
5.3.2.1. Dispersion stability	161
5.3.2.2. Evaluation of Optimized concentration of the additives	162
5.3.2.3. Friction and wear modifying the behavior of the additives	164
5.3.2.4. Load bearing capacity	164
5.3.2.5. Frictional Power Loss	166
5.3.3. Worn surface Morphological studies	167
5.3.4. XPS Analysis of Tribofilm	171
5.3.5. Tentative lubrication mechanism	173
5.4. Conclusions	174
5.5. References	176
Summary	185-192
List of Publications	193-197

List of Notations, Symbols, and Abbreviations

μ	Coefficient of friction
P	Frictional Power loss
AFM	Atomic force microscopy
ASTM	American standard of testing machine
BDC	1,4- Benzene dicarboxylic acid
CTAB	Cetyltrimethylammoniumbromide
C-MVO	Cobalt doped manganese vanadate
CNMs	Carbon nanomaterials
CCO	Calcium doped Ceria
CNTs	Carbon nanotubes
COF	Coefficient of friction
CQDs	Carbon quantum dots
CS	Carbon spheres
DLC	Diamond-like carbon
EDS	Energy Dispersive X-ray Spectrometry
FE-SEM	Field emission-scanning electron microscopy

FTIR	Fourier transforms infrared spectroscopy
GO	Graphene oxide
GQDs	Graphene quantum dots
MEMS	Micro-electro-mechanical systems
MCs	Metal Chalcogenides
MoS₂	Molybdenum disulfide
MWD	Mean wear scar diameter
MWV	Mean wear scar volume
NEMS	nanoelectro-mechanical systems
NPs	Nanoparticles
NTs	Nanotubes
PO	Paraffin Oil
PEG	Polyethylene glycol

PO	Paraffin oil
QDs	Quantum dots
rGO	Reduced graphene oxide
SDS	Sodium dodecyl sulfate
SEM	Scanning electron microscopy
TEA	Triethylamine
TEM	Transmission electron microscopy
UV-Vis	Ultraviolet visible Spectroscopy
VSe₂	Vanadium diselenide
WS₂	Tungsten disulfide
XPS	X-ray Photoelectron Spectroscopy
ZDDP	Zinc dialkyl dithiophosphate
ZIF	Zeolitic imidazolic framework
ZnO	Zinc oxide

LIST OF FIGURES

Figure No.	Description	Page No.
1.1	Stribeck curve illustrating the relationship between the COF and Bearing parameter (viscosity, speed, and load variables) in a lubricated sliding system	4
1.2	Various types of nanosheets	14
1.3	Potential applications of graphene across various fields	16
1.4	Synthesis of graphite oxide, graphene oxide, and graphene from graphite	17
1.5	An illustrative diagram depicting the reaction and mechanism of hydrazine-mediated reduction of GO	18
2.1	Four-ball tester machine	45
3.1	FT-IR spectra of the GO and M-rGO.	56
3.2	HR-SEM images of (a) Y_2O_3 , (b) $La-Y_2O_3$, (c) MoS_2 , (d) $(La-Y_2O_3)-MoS_2$ (e) M-rGO, (f) $(La-Y_2O_3)-MoS_2-(M-rGO)$ and (g) EDX spectrum of $(La-Y_2O_3)-MoS_2-(M-rGO)$.	59
3.3	EDX spectrum of $(La-Y_2O_3)-MoS_2$	60
3.4	TEM images of (a) Y_2O_3 , (b) $La-Y_2O_3$, (c) MoS_2 , (d) M-rGO, (e) $(La-Y_2O_3)-MoS_2$, (f) $(La-Y_2O_3)-MoS_2-(M-rGO)$ and HR-TEM images of (c ₁) MoS_2 , (d ₁) M-rGO and (f ₁) $(La-Y_2O_3)-MoS_2-(M-rGO)$	61

3.5	(a) The particle size histogram for Y_2O_3 and $La-Y_2O_3$ nanoparticles obtained from TEM studies, (b) XRD patterns of as-prepared nano additive	63
3.6	Raman spectra of (a) $La-Y_2O_3$, (b) MoS_2 , (c) ternary composite ($La-Y_2O_3$)- MoS_2 -(M-rGO) (inset showing spectra of M-rGO)	65
3.7	Survey spectrum (a) and deconvoluted XPS images of ($La-Y_2O_3$)- MoS_2 -(M-rGO) nanocomposite: (b) C 1s, (c) O 1s, (d) N 1s, (e) S 2p, (f) Mo 3d, (g) Y 3d and (h) La 3d spectra.	67
3.8	(a) Dispersion stabilities of base oil containing Y_2O_3 , MoS_2 , M-rGO, $La-Y_2O_3$, ($La-Y_2O_3$)- MoS_2 and ($La-Y_2O_3$)- MoS_2 -(M-rGO) studied by UV-vis spectrophotometry (inset showing the decrease in absorbance of 278 nm band against time) and (b) Optical photographs of (1) plain PO, and PO with dispersed nano additives (2) Y_2O_3 , (3) MoS_2 , (4) M-rGO, (5) $La-Y_2O_3$, (6) ($La-Y_2O_3$)- MoS_2 , and (7) ($La-Y_2O_3$)- MoS_2 -(M-rGO) at zero time and after 48 hours	69
3.9	(a) Variation of mean wear scar diameter for the paraffin oil as a function of additive concentration at 392 N applied load for 60 min duration (b) mean wear scar diameter and the average coefficient of friction (c) coefficient of friction as a function of sliding time (d) variation of mean wear volume with sliding time for paraffin oil without (given in inset) and with 0.2% w/v of different nano additives for 1.5 h test duration	72

3.10	Determination of running-in wear rate by varying mean wear volume with time (h) for paraffin oil containing (0.2% w/v) nano additives at 392 N applied load	73
3.11	Determination of steady-state wear rate by varying mean wear volume with time (h) for paraffin oil containing (0.2% w/v) nano additives at 392 N applied load	73
3.12	Variation of frictional torque as a function of stepwise loading and time for PO in the absence and presence of different nano additives: sliding speed, 600 rpm; temperature, 75 °C; concentration of additives, 0.2% w/v	74
3.13	(a) SEM micrographs (inset: full view of wear scar at 100X, wear scar surface at 2.00 KX magnification) of the worn steel surface lubricated with paraffin oil with and without different nano additives (0.2% w/v) for 60 min test duration at 392 N applied load (b) EDX spectra of worn surface lubricated with PO blended with 0.2%w/v (La-Y ₂ O ₃)-MoS ₂ -(M-rGO) nanohybrid at 392 N applied load	76
3.14	2D and 3D AFM images of the worn steel surface lubricated with blank paraffin oil (PO) and blends of PO with 0.2% w/v nano additives at 392 N applied load: (a) paraffin oil, (b) Y ₂ O ₃ , (c) MoS ₂ , (d) M-rGO, (e) La-Y ₂ O ₃ , (f) (La-Y ₂ O ₃)-MoS ₂ , and (g) (La- Y ₂ O ₃)-MoS ₂ -(M-rGO)	77
3.15	XPS spectra of the worn surface lubricated with (La-Y ₂ O ₃)-MoS ₂ -(M-rGO) nanocomposite: (a) C 1s, (b) O 1s, (c) N 1s, (d) S 2p, (e) Mo 3d, (f) Y 3d, (g) La 3d spectra and (h) Fe 2p spectra.	79

4.1	(a) XRD patterns and (b) IR spectra of Bi_2Se_3 , Bi_2WO_6 , $\text{N-Bi}_2\text{WO}_6$, $\text{Bi}_2\text{Se}_3/\text{Bi}_2\text{WO}_6$, and $\text{Bi}_2\text{Se}_3/\text{N-Bi}_2\text{WO}_6$	103
4.2	HR-SEM images of (a) Bi_2Se_3 , (b) Bi_2WO_6 , (c) $\text{N-Bi}_2\text{WO}_6$, (d) $\text{Bi}_2\text{Se}_3/\text{Bi}_2\text{WO}_6$, (e) $\text{Bi}_2\text{Se}_3/\text{N-Bi}_2\text{WO}_6$ and (f) EDX spectrum of $\text{Bi}_2\text{Se}_3/\text{N-Bi}_2\text{WO}_6$	104
4.3	EDX spectrum of, (a) Bi_2Se_3 , (b) Bi_2WO_6 , (c) $\text{N-Bi}_2\text{WO}_6$ and (d) $\text{Bi}_2\text{Se}_3/\text{Bi}_2\text{WO}_6$	105
4.4	TEM snapshots of (a) Bi_2Se_3 , (b) Bi_2WO_6 , (c) $\text{N-Bi}_2\text{WO}_6$, (d) $\text{Bi}_2\text{Se}_3/\text{Bi}_2\text{WO}_6$ (e) $\text{Bi}_2\text{Se}_3/\text{N-Bi}_2\text{WO}_6$ and HR-TEM photographs of $\text{Bi}_2\text{Se}_3(a_1)$, $\text{Bi}_2\text{WO}_6(b_1)$, $\text{N-Bi}_2\text{WO}_6(c_1)$, $\text{Bi}_2\text{Se}_3/\text{Bi}_2\text{WO}_6(d_1)$, and $\text{Bi}_2\text{Se}_3/\text{N-Bi}_2\text{WO}_6(e_1)$. SAED patterns of the additives in the insets of Figures a_1 , b_1 , c_1 , d_1 , and e_1	106
4.5	Deconvoluted core-level XPS spectra of $\text{Bi}_2\text{Se}_3/\text{N-Bi}_2\text{WO}_6$ nanocomposite: (a) Bi 4f, (b) Se 3d, (c) N 1s, (d) O 1s, and (e) W 4f	108
4.6	(a) Dispersion stabilities of base lube containing Bi_2Se_3 , Bi_2WO_6 , $\text{N-Bi}_2\text{WO}_6$, $\text{Bi}_2\text{Se}_3/\text{Bi}_2\text{WO}_6$, and $\text{Bi}_2\text{Se}_3/\text{N-Bi}_2\text{WO}_6$ using UV-vis spectrophotometry, (b) Photographs of the admixtures from the day 1-3	109
4.7	(a) Variation of MWD against the concentrations of various additives (b) COF against sliding time (c) average coefficient of friction and the MWD in the format of bar diagram (d) frictional torque vs. load and time for plain PO and with different additives under ASTM D5183 standards	111

4.8	Variation of coefficient of friction (COF) vs. additive concentration	114
4.9	(a)-(f) SEM micrographs of the depleted surfaces lubricated with plain PO and blended additives (0.05% w/v) at 2.00 KX magnification following the ASTM D4172 norms, inset discerning wear scar surface at a higher magnification of 100 KX (g) EDX spectrum of wear track lubricated with Bi ₂ Se ₃ /N-Bi ₂ WO ₆ .	117
4.10	EDX spectrum of wear track of steel surface lubricated with (a) Bi ₂ Se ₃ , (b) Bi ₂ WO ₆ , (c) N-Bi ₂ WO ₆ , and (d) Bi ₂ Se ₃ /Bi ₂ WO ₆	118
4.11	3D and 2D AFM images of the wear track lubricated with PO and its admixtures (0.05% w/v) after ASTM D4172 test, (a) PO, (b) Bi ₂ Se ₃ , (c) Bi ₂ WO ₆ , (d) N-Bi ₂ WO ₆ , (e) Bi ₂ Se ₃ /Bi ₂ WO ₆ and (f) Bi ₂ Se ₃ /N-Bi ₂ WO ₆ .	119
4.12	Deconvoluted XPS of the tribofilm generated on the wear track in the presence of PO blended with Bi ₂ Se ₃ /N-Bi ₂ WO ₆ after ASTM D4172 test (a) Bi 4f (b) Se 3d (c) N 1s (d) O 1s (e) W 4f and (f) Fe 2p.	122
4.13	The diagrammatic representation of the proposed lubricating mechanism	123
5.1	(a) XRD patterns and (b) IR spectra of MVO, C-MVO, NiO, and NiO/C-MVO	156
5.2	HR-SEM photographs of (a) MVO, (b) C-MVO, (c) NiO (d) NiO/C-MVO, and (e) EDX spectrum of NiO/C-MVO	157
5.3	EDX spectrum of, (a) MVO, (b) C-MVO, and (c) NiO	158

5.4	TEM photographs of (a) MVO, (b) C-MVO, (c) NiO, (d) NiO/C-MVO, and HR-TEM photographs of MVO (a ₁), C-MVO (b ₁), NiO (c ₁), and NiO/C-MVO (d ₁) with SAED patterns in the insets (a ₁ , b ₁ , c ₁ , and d ₁)	159
5.5	Deconvoluted XP spectra of NiO/C-MVO (a) Co 2p, (b) Mn 2p, (c) V 2p, (d) Ni 2p, and (e) O 1s	160
5.6	(a) Dispersion stabilities of base lube containing MVO, C-MVO, NiO, and NiO/C-MVO using UV-vis spectrophotometry, (b) Photographs of the admixtures from the day 1-3	162
5.7	(a) MWD vs additive concentration, (b) COF vs sliding time, (c) MWD and COF in the pattern of bar diagram, and (d) Frictional torque against time and load	165
5.8	Variation of coefficient of friction (COF) vs. additive concentration	166
5.9	(a)-(e) SEM optical photographs of the wear track surfaces of different admixtures at 2.0 K X amplification, wear scar surfaces in the inset at 100 K X (f) EDX spectrum of wear track surfaces lubricated with NiO/C-MVO	168
5.10	EDX spectrum of wear track of steel surface lubricated with (a) MVO, (b) C-MVO, and (d) NiO	169
5.11	2D and 3D AFM snapshots of the wear track in the presence of PO and its blends at the optimal concentration (0.05% w/v) (a) PO, (b) MVO, (c) NiO (d) C-MVO, and (e) NiO/C-MVO	170

5.12	Deconvoluted XPS of the tribofilm generated on the wear track in the presence of PO blended with NiO/C-MVO after ASTM D4172 test (a) Co 2p, (b) Mn 2p, (c) V 2p, (d) O 1s (e) Ni 2p and (f) Fe 2p	172
5.13	The diagrammatic representation of the proposed lubricating mechanism	174

LIST OF TABLES

Table No.	Description	Page No.
3.1	Surface roughness parameters obtained from the digital processing software of AFM (Nanosurf-basic Scan-2) for different additives after the antiwear test	78
4.1	Cutbacks in frictional power for individual additives in paraffin oil at the optimized concentration, 0.050 % (w/v).	115
4.2	Surface roughness parameters obtained from the digital processing software of AFM (Nanosurf-basic Scan-2) for different additives after the antiwear test.	120
5.1	Cutbacks in frictional power for individual additives in paraffin oil at the optimized concentration, 0.050 % (w/v).	167
5.2	Surface roughness parameters obtained from the digital processing software of AFM (Nanosurf-basic Scan-2) for different additives after the antiwear test.	171

LIST OF SCHEMES

Scheme No.	Description	Page No.
3.1	Illustration of synthesis of ternary nanohybrid (La-Y ₂ O ₃)-MoS ₂ -(M-rGO)	57
4.1	Schematic presentation for the preparation of Bi ₂ Se ₃ /N-Bi ₂ WO ₆	100
5.1	Schematic representation illustrating the procedure for NiO/C-MVO fabrication	154