

Contents

Certificate	i
Declaration by the Candidate	iii
Copyright Transfer Certificate	v
Acknowledgments.....	ix
Contents.....	xiii
List of Figures.....	xix
List of Tables	xxix
List of Symbols and Abbreviations.....	xxxii
Preface	xxxvii
CHAPTER 1: Introduction.....	1
1.1 Global Energy Demand.....	1
1.2 Solar Energy.....	3
1.3 Solar Cells: An Overview	5
1.3.1 The absorption of incident photons.....	6
1.3.2 The generation of photo-generated charge carriers (electron-hole pairs)	7
1.3.3 The transportation of these photogenerated charge carriers.....	7
1.3.4 The collection of photo-generated charge carriers.....	8
1.4 Characteristics of Solar Cells	8
1.4.1 The I-V (Current-Voltage) Characteristics.....	9
1.4.2 Open-Circuit Voltage	10
1.4.3 Short-Circuit Current (I_{sc}).....	11
1.4.4 Maximum Power Output (P_{max}).....	12
1.4.5 Fill Factor (FF)	12
1.4.6 Power Conversion Efficiency (PCE)	13
1.5 Generations of Solar Cell.....	14

1.6	Perovskite (3D and 2D) Crystal Structure: An Overview	15
1.7	Perovskite Solar Cells.....	18
1.7.1	Stability Issues	20
1.7.2	Current-Voltage (I-V) Hysteresis	23
1.8	Comparison of Cesium Lead Bromide (CsPbBr_3) Material with the Hybrid and All-Inorganic Perovskite Materials	25
1.9	The objective of current research	30
	CHAPTER 2: Materials and Methods	33
2.1	Overview.....	33
2.2	Synthesis of Compounds:	34
2.2.1	Specification of the Materials.....	34
2.2.2	Cold Sintering Method via Solid State Reaction Method (SSR).....	35
2.2.3	Thin Films Synthesis.....	37
2.3	Characterization Techniques (Measuring Equipment and Experiment Analysis Techniques)	40
2.3.1	X-Ray Diffraction (XRD)	40
2.3.2	Differential Scanning Calorimetry (DSC).....	42
2.3.3	X-Ray Photoelectron Spectroscopy (XPS).....	44
2.3.4	Scanning Electron Microscope (SEM).....	46
2.3.5	Raman Spectroscopy.....	47
2.3.6	Ultra-Violet Visible (UV-Vis) Spectroscopy	49
2.3.7	Photoluminescence (PL) Spectroscopy.....	51
2.4	Electrical Properties.....	52
2.4.1	Current-Voltage ($I-V$).....	52
2.4.2	Impedance Spectroscopic Technique.....	54
2.5	Analysis Techniques.....	58
2.5.1	Rietveld Refinement Technique	58
2.5.2	Process of Analyzing the Obtained Data.....	59

2.6	Conduction Mechanisms	60
2.6.1	Space Charge Limited Current (SCLC)	60
2.6.2	Poole-Frenkel.....	61
CHAPTER 3: Compositional Degradation with Br Content in Cesium Lead Halide CsPbBr_xI_{3-x}.....		65
3.1	Introduction	65
3.2	Experimental details	65
3.3	Results and Discussion	67
3.3.1	X-ray Diffraction and microstructural studies	67
3.3.2	Thermodynamics.....	77
3.3.3	Optical Properties.....	79
3.3.4	XPS Studies	81
3.3.5	Electrical Studies.....	84
3.3.6	Current (<i>I</i>)-Voltage (<i>V</i>) Studies	85
3.4	Conclusion.....	89
CHAPTER 4: Thermo-Optical Correlation for Room Temperature Synthesis: Cold Sintered Lead Halides		93
4.1	Introduction	93
4.2	Experimental Procedure.....	94
Synthesis of the CsPbX₃ (X = I and Br) and Analysis of the Results		95
4.3	Results and Discussion	95
4.3.1	Thermodynamics.....	95
4.3.2	X-ray diffraction	96
4.3.3	Raman Spectroscopy	99
4.3.4	Microstructural Studies	101
4.3.5	X-ray Photoelectron Spectroscopy (XPS) studies	101
4.3.6	Band gap using UV Visible	103
4.3.7	Urbach Energy	106

4.3.8	Structure- optical correlation	107
4.3.9	Thermo-optical correlation.....	108
4.3.10	Stability	108
4.3.11	Comparative (on the basis of synthesis techniques) of structural and optical properties.....	111
	Non-Linear Conduction Mechanism in Perovskite Halide CsPbI₃	113
4.4	Results and Discussion	113
4.4.1	Electrical Characterization (AC Conductivity Studies)	113
4.4.2	Relative Permittivity Analysis.....	118
4.4.3	Electrical Modulus	120
4.5	Conclusion	124
	CHAPTER 5: Hysteric Photo-Conduction and Negative Differential Resistance in Cesium Lead Bromide.....	129
5.1	Introduction.....	129
5.2	Experimental procedure.....	130
5.3	Results and Analysis.....	132
5.3.1	Observation of I-V hysteresis	132
5.3.2	Photo-conduction.....	136
5.3.3	Ion dynamics.....	138
5.3.4	Thermionic emission.....	142
5.4	Conclusion	144
	CHAPTER 6: Comparative Study of Perovskite and Ruddlesden Popper (RP) for Lead (Pb) and Lead-free Halides	147
6.1	Introduction.....	147
6.2	Experimental Procedure.....	147
6.3	Results and Discussion	148
6.3.1	Structural Studies.....	148
6.3.2	Current-Voltage Hysteresis Studies.....	149

6.3.3	Optical Properties.....	156
6.4	Conclusion.....	158
	CHAPTER 7: Thin Films and Devices for Perovskite Solar cells	163
7.1	Introduction	163
7.2	Methodology	163
7.3	Results and Discussion	167
7.4	Conclusion.....	173
	CHAPTER 8: Conclusions and Future Scopes	177
8.1	Conclusion of the Present Investigation	177
8.2	Future Scope.....	181
	References.....	183
	List of Publications.....	199

LIST OF FIGURES

		Page No.
Chapter I	Introduction	
Fig. 1.1	(a) Energy consumption by energy sources from 2010 to 2050. (b) Represents the total energy consumption in selected countries and regions from 1990-2050	3
Fig. 1.2	Depicts the solar radiation spectrum.	4
Fig. 1.3	(a) Depicts the structure of a solar cell and (b) represents an architect of a solar cell	5
Fig. 1.4	Represents the solar cell equivalent circuit model	9
Fig. 1.5	Schematic diagram of I-V peculiarities of a solar cell in dark and light	10
Fig. 1.6	(a) Represents the open-circuit voltage and (b) shows the short-circuit current equivalent circuits	11
Fig. 1.7	Schematic diagram of Fill Factor (FF) for a solar cell	12
Fig. 1.8	Represents the generations of the solar cell	14
Fig. 1.9	Represents the crystal structure of the perovskite and Ruddlesden-Popper materials	16
Fig. 1.10	Depicts the Ruddlesden-Popper (RP) perovskite crystal structure with increasing 'n' values	17
Fig. 1.11	(a) and (b) represents year-wise publications worldwide and publications by Indian authors	18
Fig. 1.12	Power conversion efficiency trend with different technologies from NREL map	20
Fig. 1.13	(a) Represents photodecomposition and thermal degradation processes of MAPbI ₃ . (b) Extrinsic and intrinsic factors (c) CsPbI ₃ phases	22
Fig. 1.14	(a) The stability of the perovskite by the surrounding condition with the crystal structure of the perovskites (Fig.(b)). (c) Normalized PCE vs Time (h) spectra for	27

	perovskite solar cell devices. (d) Degradation of CsPbI _{3-x} Br _x thin films exposed to ambient condition. (e) Photo-stability of CsPbBr ₃ and MAPbBr ₃ perovskites. (f) Depicts the relative absorbance vs aging time	
Fig. 1.15	(a) Represents the power conversion efficiency of tin (Sn)-based with organic and Sn-Pb mixed perovskite solar cells. (b) Cyclic degradation mechanism of tin iodide (SnI ₄) in ambient condition	28
Fig. 1.16	Overview of CsSnBr ₃ perovskite material properties	29
Fig. 1.17	Overview of CsPbBr ₃ perovskite material properties	29
Chapter II	Methods and Materials	
Fig. 2.1	Flow chart of cold sintering method for synthesizing the perovskite samples	36
Fig. 2.2	Yellow precipitate of lead iodide	37
Fig. 2.3	Image of the thin-film process by the spin coating system	38
Fig. 2.4	Schematic diagram of Pulsed Laser Deposition and experimental setup	39
Fig. 2.5	Two parallel incident X-rays reflected from crystalline planes	41
Fig. 2.6	X-ray diffractometer (Rigaku Miniflex, Japan), CIF IIT (BHU)	42
Fig. 2.7	The working principle (left) and the experimental setup of DSC (right), CIF IIT (BHU)	43
Fig. 2.8	Depicts the mechanism of XPS spectroscopy and experimental setup for the XPS measurement	45
Fig. 2.9	Schematic diagram of the SEM working principle	46
Fig. 2.10	Experimental set-up of DXRxi Raman measurement. (Banasthali University, Rajasthan) (b) Schematic representation of the principle of Raman spectroscopy	48
Fig. 2.11	Experimental setup of JASCO V-770 UV-Vis spectrometer	49

Fig. 2.12	Principle of Photoluminescence spectroscopy (PL) and setup of the 450W Illuminator model FL-1039A/40A spectrometer	51
Fig. 2.13	An experimental setup of a solar simulator with a Keithley source meter	53
Fig. 2.14	Solid-state reaction synthesis of investigated samples by using mortar pestle	56
Fig. 2.15	(a) Represents the experimental setup of a computer-controlled automatic impedance analyzer with sample holder and furnace. (b) Solartron 1260 A impedance analyzer	57
Fig. 2.16	J-V characteristic of SCLC	61
Chapter III	Compositional Degradation with Br Content in Cesium Lead Halide CsPbBr_xI_{3-x}	
Fig. 3.1	XRD patterns for CsPbBr _x I _{3-x} (x= 0.0 - 3.0 in steps of 0.5) samples at room temperature	67
Fig. 3.2	Double phase refinement of CsPbI ₃	71
Fig. 3.3	Rietveld refinement of XRD patterns of CsPbBr _x I _{3-x} (x= 0.0, 0.5, 1.0, and 3.0) samples.61	72
Fig. 3.4	(a) Comparison of XRD patterns of $1.5 \leq x < 3.0$ with standard JCPDS files and (b) The indexing of every peak with various phases such as PbBr ₂ , PbI ₂ , CsPbBr ₃ in the monoclinic and orthorhombic phases etc. for $1.5 \leq x < 3.0$	74
Fig. 3.5	(a, b) Variation of lattice parameters 'a', 'c', with x (c) variation of dislocation density and microstrain with x and (d) Structure of CsPbI ₃ and CsPbBr ₃ plotted with Diamond using cif file obtained from Rietveld refinement	74
Fig. 3.6	SEM micrographs of CsPbBr _x I _{3-x} (x= 0.0, 0.5, 1.0, 1.5 and 3.0) samples. Circle A and B show grain boundary rupturing (degradation)	76
Fig. 3.7	Variation of I content obtained from EDX and grain size analyzed from grain size histograms of CsPbBr _x I _{3-x} (x= 0.0 - 3.0 in steps of 0.5) systems	76
Fig. 3.8	(a) Variation of ($\Delta Q/\Delta m$) with temperature (b) Variation of (ΔG) with temperature (c) Variation of (C_v) with	78

	temperature (d) Schottky Anomaly variation for CsPbBr _x I _{3-x} (x= 0.0, 0.5, 1.0, and 3.0) systems	
Fig. 3.9	The change in Gibbs free energy (ΔG) and entropy (ΔS) with temperature and showing Little change in the entropy of these compounds indicates that the samples are thermodynamically stable at room temperature	78
Fig. 3.10	(a) Absorbance spectra for CsPbBr _x I _{3-x} (x= 0.0 to 3.0 at the step of 0.5) samples (b) Differential absorbance showing peaks at the band edges (c) Tauc plot for CsPbBr _x I _{3-x} (x= 0.0 to 3.0 at the step of 0.5) samples (d) Energy band gap at two indicated band edges (I and II) for CsPbBr _x I _{3-x} (x= 0.0, 0.5, 1.0, 1.5, and 3.0) samples	80
Fig. 3.11	Wide range XPS spectrum of CsPbBr _x I _{3-x} (x= 0.0, 0.5, 1.0, 1.5 and 3.0) systems	81
Fig. 3.12	XPS spectra with peak fitting of CsPbBr _x I _{3-x} (x=0.0, 0.5, 1.0, 1.5, and 3.0) corresponding to (a) Cs 3d; and(b) Pb 4f	82
Fig. 3.13	XPS spectra with peak fitting of CsPbBr _x I _{3-x} (x=0.0, 0.5, 1.0, 1.5, and 3.0) corresponding to (a) I 3d (b) Br 3d and (c) O (2p)	83
Fig. 3.14	Impedance and Modulus Nyquist plots for CsPbBr _x I _{3-x} (x=0.5 and 1.5) showing grain disintegration	84
Fig. 3.15	Current (I) - voltage (V) curves for CsPbBr _x I _{3-x} (x = 0.0, 0.5, 1.0, 1.5, and 3.0) samples	85
Fig. 3.16	Current (I) - voltage (V) curves for CsPbBr _x I _{3-x} (x= 0.0 - 3.0 in steps of 0.5) samples. Inset shows compositional variation of ratio of photocurrent to the dark current at 5V	85
Fig. 3.17	Deviation of Vegard's law for CsPbBr _x I _{3-x} (x= 0.0 - 3.0 in steps of 0.5) samples	87
Fig. 3.18	(a) Activation energy of CsPbBr _x I _{3-x} (x= 0.0 to 3.0 at the steps of 0.5). (b) Variation of $\ln(\Delta G)$ vs $1000/T$ for x = 0.0 and 3.0	87
Fig. 3.19	(a) Raman spectra of CsPbBr _x I _{3-x} (x= 0.0 to 3.0 at the steps of 0.5). (b) Area of peaks corresponding to metal-O and metal-OH bond in O XPS spectra	88
Chapter IV	Thermo-Optical Correlation for Room Temperature Synthesis: Cold Sintered Lead Halides	

Fig. 4.1	(a, b) Variation of specific heat (C_V) (insets show variation of $(\Delta Q/\Delta m)$) and (c, d) Variation of change in Gibbs free energy (ΔG) and entropy (ΔS) with temperature for CsPbBr ₃ and CsPbI ₃ , respectively	95
Fig. 4.2	Room temperature indexed X-ray diffractograms showing the single phase formation for CsPbBr ₃ and CsPbI ₃ , respectively. Most intense peak is highlighted in gray rectangle to show change in the XRD pattern with replacement of Br with I	97
Fig. 4.3	Rietveld refinement of XRD with the evaluated parameters for CsPbBr ₃ and CsPbI ₃ , respectively	99
Fig. 4.4	De-convoluted Raman spectra of CsPbBr ₃ and CsPbI ₃ showing the number of modes in agreement with the Pnma symmetry according to Bilbao crystallographic server	100
Fig. 4.5	SEM micrographs of CsPbBr ₃ and CsPbI ₃ samples	101
Fig. 4.6	Wide range XPS spectrum for the confirmation of oxidation states of different ions	102
Fig. 4.7	De-convoluted elemental XPS spectrum along with the spin orbit interaction for CsPbBr ₃ and CsPbI ₃	103
Fig. 4.8	Optical absorption spectra for CsPbBr ₃ and CsPbI ₃ , a strong absorbance edge at 555 nm is observed for CsPbBr ₃ while, on the other hand, for CsPbI ₃ two absorbance edges at 501 nm and 543 nm are observed, (b) direct band gap energy estimation from Tauc relation for CsPbBr ₃ and CsPbI ₃ , respectively	104
Fig. 4.9	Direct allowed transitions in CsPbBr ₃ and CsPbI ₃	105
Fig. 4.10	Plot of $\ln(\alpha)$ versus $h\nu$ (eV) for Urbach energy	106
Fig. 4.11	The comparative normalized XRD patterns in case of (a) CsPbBr ₃ , (b) CsPbI ₃ . The comparative UV absorption spectra in case of (c) CsPbBr ₃ , (b) CsPbI ₃ . (between 0 day (i.e., freshly prepared sample) and after, 100 days (i.e., aged sample))	109
Fig. 4.12	Current (I) -Voltage (V) plot in different light exposure (Dark, room light and AM 1.5 G Sun light) along with current degradation with time (0 h -3.0 h) in AM 1.5 G Sun light	110

Fig. 4.13	Variation of $\log \sigma$ with $\log \nu$ at 84 °C, 114°C, 133°C and 155°C for CsPbI ₃ . The red lines are fitted lines using JPL with goodness fits ($\langle r^2 \rangle \geq 0.96$)	115
Fig. 4.14	Arrhenius plots using dc conductivity with temperature for grain and grain-boundary and goodness fits ($\langle r^2 \rangle \geq 0.98$)	116
Fig. 4.15	(a) Variation of $\log \sigma_{dc}$ with $\log \nu_h$ for grain (b) Variation of $\log \sigma_{dc}$ with $\log \nu_h$ for grain- boundary	116
Fig. 4.16	Variation of exponent with temperature for grain and grain-boundary	117
Fig. 4.17	Variation of ϵ' and ϵ'' (real and imaginary parts of permittivity, respectively) are plotted with the temperature at 10 kHz, 100 kHz, and 1MHz frequencies	119
Fig. 4.18	Shows the fitting of the Modulus Nyquist plots over the temperature range from 84 °C to 153 °C and goodness fits ($\langle r^2 \rangle \geq 0.96$)	120
Fig. 4.19	(a) Shows the Modulus Nyquist plot at 153 °C and (b) Arrhenius plots showing the variation of $\ln(\tau)$ vs $1000/T$ and goodness fits ($\langle r^2 \rangle \geq 0.98$)	121
Fig. 4.20	Bode plots of permittivity (ϵ) with temperature and fitting with Cole- Davidson equation and goodness fits ($\langle r^2 \rangle \geq 0.98$).	123
Chapter V	Hysteric Photo-Conduction and Negative Differential Resistance in Cesium Lead Bromide	
Fig. 5.1	I-V characteristics with the different scan rates of CsPbBr ₃ synthesized via Cold sintering technique (6-month-old sample)	131
Fig. 5.2	(a) Experimental setup for I–V measurements showing the light and sample alignment in air (not in an inert atmosphere). (b) Time scale for the measurement of I–V characteristics. Just after dark and room light measurements, solar simulator was switched on and then continuously, the sample was illuminated for 3 h. (c) Observation of I–V hysteresis in CsPbBr ₃ with an illumination of AM 1.5 G Sun light taken at time intervals as line marked with an arrow on the light intensity and the time plot (right bottom corner). On the time scale, the origin is the start of illumination of the Sun light on the sample surface and (d) shows variation in the hysteresis area with the voltage in dark, room light (RL)	132

and with a continuous illumination of AM 1.5 G Sun light (at a few intervals of time, 0 h, 0.5 h, 1.0 h, 1.5 h, 2.0 h, and 3.0 h)

- Fig. 5.3** (a) Variation of extracted parameters “n” and “k” (lines are to guide only) from fitting $J = kE^n$ for both forward scan (FS) and reverse scan (RS) shown in the inset and (b) the variation of conductivity with an electric field for CsPbBr₃ in dark, room light (RL) and with a continuous illumination of AM 1.5 G Sun light (at a few intervals of time, 0 h, 0.5 h, 1.0 h, 1.5 h, 2.0 h, and 3.0 h) **134**
- Fig. 5.4** (a) The σ -E curves for dark and just illuminated (b)-(d) variation of σ_p , σ_0 , and E_0 parameters with illumination time. The negative time scale represents dark current and room light current **136**
- Fig. 5.5** (a) With the bias electric field (from the bottom to top: 0 V, 2 V, and 5 V), the photo generated current in a discharge mode after triggering by a 5 V pulse for 50 s. The inset shows a linear variation of the photo generated current with the electric field. (b) Absorption co-efficient and photoluminescence emission spectra with different excitation energies **137**
- Fig. 5.6** (a) Jonscher power fitting log-log σ (conductivity)- ν (frequency) isotherms for the temperature range 301–421 K in regimes I (low frequency regime) and II (high frequency regime). (b) Arrhenius plot of dc conductivity extracted, for regimes I and II. (c) Log-log σ_{dc} (dc conductivity)- ν_h (hopping frequency) plots. (d)-(f) Ghosh scaling for regime II in the temperature range 301–421 K, regime II in the temperature range 351–421 K and regime I in the temperature range 351–421 K. (g) Temperature variation of exponent extracted from the Jonscher fitting. (h) Imaginary impedance and the modulus bode plot and (i) Mott plots for two regimes I and II **139**
- Fig. 5.7** (a) Fitted impedance Nyquist plot at 301 K (inset) comparative impedance Nyquist plots on a log scale at temperatures 301 K and 426 K. (b) Fitted impedance Nyquist plot at 426 K with an equivalent circuit in the inset. (c) Variation of the circuit element with the parallel resistance R2 and (d) α , exponent of the constant phase element Q1 for the volume (grain, g) barrier (grain boundary, gb) **140**

Fig. 5.8	(a) Density of state ($\partial_E \sigma_d$) variation with the field and (b) the variation of a relative dielectric constant of RS with FS and (c) Frenkel–Poole fitting for just illuminated photo-current voltage variation	142
Chapter VI	Comparative study of perovskite and Ruddlesden-Popper of lead (Pb) and lead-free halides	
Fig. 6.1	(a and b) represents the XRD patterns for CsPbBr ₃ , CsSnBr ₃ , Cs ₂ PbBr ₄ , and Cs ₂ SnBr ₄ , respectively	148
Fig. 6.2	Observation of current density with electric field in perovskite (CsPbBr ₃ and CsSnBr ₃) and Ruddlesden-Popper (Cs ₂ PbBr ₄ and Cs ₂ SnBr ₄) materials with an illumination of AM 1.5 G Sunlight	149
Fig. 6.3	FS and RS fitted from $J=KE^n$ for CsPbBr ₃ and Cs ₂ PbBr ₄ in dark light and with the illumination of AM 1.5 G Sunlight (at a few intervals of time, 0h, 0.5h, 1h, 1.5h, 2h, 2.5h, 3.0h)	150
Fig. 6.4	FS and RS fitted from $J=KE^n$ for CsSnBr ₃ (zoomed images of current density on the right side of Fig. a) and Cs ₂ SnBr ₄ in dark light and with the illumination of AM 1.5 G Sunlight (at a few intervals of time, 0h, 0.5h, 1h, 1.5h, 2h, 2.5h, 3.0h)	151
Fig. 6.5	Variation of (σ -E) for CsPbBr ₃ and Cs ₂ PbBr ₄ in dark light and with the illumination of AM 1.5 G Sunlight (at a few intervals of time, 0h, 0.5h, 1h, 1.5h, 2h, 2.5h, 3.0h)	152
Fig. 6.6	Variation of (σ -E) for CsSnBr ₃ (zoomed images of conductivity are indicated by the arrow sign on the right side of Fig. a) and Cs ₂ SnBr ₄ in dark light and with the illumination of AM 1.5 G Sunlight (at a few intervals of time, 0h, 0.5h, 1h, 1.5h, 2h, 2.5h, 3.0h)	152
Fig. 6.7	Variation of photoconductivity (just illuminated) and dark conductivity for CsPbBr ₃ and CsSnBr ₃ samples	153
Fig. 6.8	Variation of extracted parameter 'n' from fitting $J=KE^n$ for FS and RS	154
Fig. 6.9	Photoresponse current vs time with the bias electric field	155
Fig. 6.10	Optical absorption spectra for CsPbBr ₃ , Cs ₂ PbBr ₄ , CsSnBr ₃ , and Cs ₂ SnBr ₄ samples (b) direct band gap energy calculation from Tauc relation (c) Plot of $\ln(\alpha)$ versus $h\nu$ (eV) for	156

	Urbach energy (E_u) (d) Variation of $h\nu$ (eV) verses Urbach energy (E_u)	
Fig. 6.11	Represents the ratio of $\epsilon_{RS}/\epsilon_{FS}$ with time in the continuous exposure of AM 1.5 G Sunlight	158
Chapter VII Thin Films and Devices for Perovskite Solar Cells		
Fig. 7.1	The morphology being optimized in FEM simulations	164
Fig. 7.2	The Mesh structure (triangular) being optimized in FEM simulations	164
Fig. 7.3	CsPbBr ₃ and CsSnBr ₃ thin films and devices by PLD techniques at room temperature with the I-V measurements	166
Fig. 7.4	Variation of absorbance for TiO ₂ /CsPbBr ₃ heterostructure in the wavelength range (0.01- 1.4 μ m) inset (i) nearly 100% absorption is obtained for 700 nm thickness for CsPbBr ₃ and 70 nm thickness of TiO ₂ (ii) Surface electric field distribution in visible region for 300nm thickness of CsPbBr ₃	167
Fig. 7.5	Variation of absorbance for TiO ₂ /CsSnBr ₃ heterostructure in the wavelength range (0.01- 1.4 μ m) inset (i) nearly 80% absorption is obtained for 200 nm thickness for CsSnBr ₃ and 20 nm thickness of TiO ₂ (ii) Surface electric field distribution in visible region for 300 nm thickness of CsSnBr ₃	168
Fig. 7.6	(a)Variation of absorbance for CuO/CsPbBr ₃ heterostructure with thickness in the wavelength range (0.01- 1.4 μ m) (b) 98% absorption is obtained for 150 nm – 750 nm thickness for CsPbBr ₃ and 50 nm – 250 nm thickness of CuO (b inset) Surface electric field distribution in visible region for 300 nm thickness of CsPbBr ₃	169
Fig. 7.7	(a) Variation of absorbance for CuO/ CsSnBr ₃ heterostructure with thickness in the wavelength range (0.01- 1.4 μ m) (b) 98% absorption is obtained for 150 nm – 750 nm thickness for CsSnBr ₃ and 50 nm – 250 nm thickness of CuO (b inset) Surface electric field distribution in visible region for 300 nm thickness of CsSnBr ₃	170
Fig. 7.8	(a) XRD patterns of CsPbBr ₃ powder and their thin film. (b) Absorbance spectra of CsPbBr ₃ thin films and device. Band gap plot in insets. (c) Photoluminescence spectrum	171

LIST OF TABLES

		Page No.
Chapter II	Methods and Materials	
Table 2.1	Details of the raw materials	34
Chapter III	Compositional Degradation with Br Content in Cesium Lead Halide CsPbBr_xI_{3-x}	
Table 3.1	Shows the fitting parameters with single phase for CsPbBr _x I _{3-x} (x= 0.0, 0.5, 1.0, and 3.0) samples	68
Table 3.2	Shows the fitting parameters with double phase for CsPbBr _x I _{3-x} (x= 0.0, 0.5, and 1.0) and single phase of x=3.0 samples	69
Table 3.3	The percentage of phases obtained from XRD and ratio of intensity	73
Chapter IV	Thermo-Optical Correlation for Room Temperature Synthesis: Cold Sintered Lead Halides	
Table 4.1	Lattice parameters and fitting parameters for the studied samples	98
Table 4.2	Comparative (on the basis of synthesis techniques) of structural and optical properties	111
Chapter VII	Thin Films and Devices for Perovskite Solar Cells	
Table 7.1	ITO/PEDOT:PSS/polyTPD/CH ₃ NH ₃ PbI ₃ /PCBM60/Au at different perovskite thicknesses	172