
CONTENTS

	PAGE No
List of Abbreviations	I-III
List of Figures	IV-XI
List of Tables and Schemes	XII-XIII
Preface	XIV-XVI

Chapter

1. Introduction	1-52
------------------------	-------------

1.1. Tribology	1
1.1.1. Friction	1
1.1.2. Wear	2
1.1.3. Lubrication	4
1.2. Lubricants	7
1.2.1. Liquid Lubricants	7
1.2.2. Semi-solid Lubricants	8
1.2.3. Solid Lubricants	9
1.2.4. Gaseous Lubricants	9
1.3. Lubricant Additives	10
1.3.1. Inorganic/Organic Compounds as Conventional Additives	10
1.3.2. Nanoadditives	13
1.3.2.1. Quantum Dots and their Functionalization	14
1.3.2.2. Nanoparticles	15
1.3.2.3. Nanorods	17
1.3.2.4. Nanotubes	17
1.3.2.5. Nanosheets	18
1.4. Statement of the Problem	26
1.5. Aims and Objectives	27
1.6. References	29

2. Experimental	53-58
------------------------	--------------

2.1. Instrumentation Used for Characterization of the Synthesized Additives	53
2.2. Antiwear Testing	54
2.2.1. Base oil	54
2.2.2. Parameter of Steel Ball Bearing	54
2.2.3. Test Procedure	54
2.3. Tribological Parameters	56
2.3.1. Mean wear scar diameter (MWD)	56
2.3.2. Coefficient of Friction (μ)	56
2.3.3. Analysis of Worn Surface	56
2.4. Frictional Power Loss (P)	57

3. Enhancement of Triboactivity of Nanolamellar Graphitic-C₃N₄ by N-Doped ZnO Nanorods	59-91
---	--------------

3.1. Introduction	59
3.2. Experimental Section	61
3.2.1. Materials	61
3.2.2. Synthesis of Additives	61
3.2.2.1. Preparation of N-doped ZnO nanorods	61
3.2.2.2. Preparation of g-C ₃ N ₄ nanosheets	62
3.2.2.3. Preparation of Hybrid N-ZnO/g-C ₃ N ₄	62
3.2.3. Sample Preparation	63
3.3. Results and Discussion	63

3.3.1. Structural and morphological studies of N-doped ZnO, g-C ₃ N ₄ , and the hybrid N-doped ZnO/g-C ₃ N ₄	63
3.3.2. Tribological Properties	69
3.3.2.1. Determination of Stability of Nanofluids	69
3.3.2.2. Optimization of concentration of the additives	70
3.3.2.3. Antiwear and Anti-friction Properties	71
3.3.2.4. Load Bearing Capacity	73
3.3.2.5. Frictional Power Loss	73
3.3.3. Morphological Studies of the Worn Surface	74
3.3.4. Analysis of Tribofilm by XPS	78
3.3.5. Proposed Mechanism of Lubrication	79
3.4. Conclusions	81
3.5. References	83

4. The superior performance of ultrathin metal organic framework nanosheets for antiwear and antifriction testing **92-117**

4.1. Introduction	92
4.2 Experimental Section	94
4.2.1. Synthesis of additives	94
4.2.1.1. Synthesis of ultrathin Mn-MOF nanosheets/Mn-MOF (U)	94
4.2.1.2. Synthesis of bulk Mn-MOF/Mn-MOF (B)	94
4.2.2. Sample Preparation	95
4.3. Results and Discussion	95
4.3.1 Synthesis and Characterization of the MOFs	95
4.3.2. Evaluation of tribological properties of Mn-MOF (U) and Mn-MOF (B)	100
4.3.2.1. Dispersion stability	100

4.3.2.2. Evaluation of Optimized concentration of the additives	101
4.3.2.3 Antiwear and antifriction properties of the additives	102
4.3.2.4. Load bearing test	104
4.3.2.5. Frictional power loss	104
4.3.3. Morphological studies of the worn surface	105
4.4. Conclusions	108
4.5. References	110

5. Reinforcement of nanoporous lanthanum-doped zinc borate by vanadium selenide nanosheets for improved tribological activity	118-150
--	----------------

5.1. Introduction	118
5.2. Experimental Section	121
5.2.1. Preparation of additives	121
5.2.1.1. Preparation of nanoporous zinc borate and La-doped zinc borate	121
5.2.1.2. Preparation of VSe ₂ nanosheets	121
5.2.1.3. Preparation of VSe ₂ reinforced porous La-doped zinc borate	122
5.2.2. Sample preparation	123
5.3. Results and Discussion	123
5.3.1. Morphological investigation of ZB, LZB, VSe ₂ , and the LZB/VSe ₂	123
5.3.2. Tribological behavior of the additives	128
5.3.2.1. Dispersion Stability of Additives in Base lube	128
5.3.2.2. Concentration Optimization	129
5.3.2.3. Antiwear and Anti-friction Properties	131
5.3.2.4. Load-carrying ability	131
5.3.2.5. Frictional Power Loss	133
5.3.3. Morphological Characteristics of Wear Scar Surface	134
5.3.3.1. Characterization of Tribofilm by XPS	138

5.3.3.2. Suggested Mechanism of Lubrication	139
5.4. Conclusions	141
5.5. References	143

6. Lamellar Ni-Mn-Based Bimetallic-Organic Frameworks Reinforced by Molybdenum-Doped Bismuth Vanadate Nanorods for Advancing Tribological Activity **151-183**

6.1. Introduction	151
6.2. Experimental Section	153
6.2.1. Preparation of Nanoadditives	153
6.2.1.1. Synthesis of Bismuth Vanadate and Mo-doped Bismuth Vanadate Nanorods	153
6.2.1.2. Preparation of Ni/Mn-MOF Nanosheets	154
6.2.1.3. Preparation of nanocomposite MBV/NMF	154
6.2.2. Sample preparation	155
6.3. Results and Discussion	155
6.3.1. Characterization and Morphological study of BiVO ₄ , Mo-doped BiVO ₄ , Ni/Mn-MOF and the hybrid MBV/NMF	155
6.3.2. Tribological Characteristics	162
6.3.2.1. Evaluation of Dispersion Stability of Nano additives	162
6.3.2.2. Concentration Optimization of the Additives	163
6.3.2.3. Anti-friction and Antiwear Properties	164
6.3.2.4. Load-bearing Capacity	165
6.3.2.5. Frictional Power Loss	166
6.3.3. Morphological Attributes of Wear Track	167
6.3.3.1. Investigation of Tribofilm by XPS	171
6.3.4. Proposed Lubrication Mechanism	172
6.4. Conclusions	173
6.5. References	175
Summary	184-189
List of Publications	190-194