


CERTIFICATE

It is certified that the work contained in this thesis titled “Novel Intelligent Signal Processing Approaches for Performance Enhancement of Gas Sensor Nodes Suitable for Near Real-Time Resource-Constrained Scenarios” by Shiv Nath Chaudhri has been carried out under my supervision and that this work has not been submitted elsewhere for a degree.

It is further certified that the student has fulfilled all the requirements of Comprehensive, Candidacy and SOTA.


20/07/2022

Signature of Supervisor

(Dr. N. S. Rajput)


20.07.22

Signature of Head of Department

(Prof. V. N. Mishra)

“SEAL OF THE DEPARTMENT”
आचार्य व विभागाध्यक्ष/PROFESSOR & HEAD
इलेक्ट्रॉनिकी अभियांत्रिकी विभाग/Department of Electronics Engineering
भारतीय प्रौद्योगिकी संस्थान (का.हि.वि.)/Indian Institute of Technology (BHU)
वाराणसी/Varanasi-221005 (INVT)
20/8

DECLARATION BY THE CANDIDATE

I, **Shiv Nath Chaudhri**, certify that the work embodied in this thesis is my own bonafide work and carried out by me under the supervision of **Dr. N. S. Rajput** from “25/07/2017” to “20/07/2022”, at the *Department of Electronics Engineering*, Indian Institute of Technology (BHU), Varanasi. The matter embodied in this thesis has not been submitted for the award of any other degree/diploma. I declare that I have faithfully acknowledged and given credits to the research workers wherever their works have been cited in my work in this thesis. I further declare that I have not willfully copied any other’s work, paragraphs, text, data, results, etc., reported in journals, books, magazines, reports, dissertations, theses, etc., or available at websites and have not included them in this thesis and have not cited as my own work.

Date: 20/07/2022

Place: IIT (BHU), Varanasi


Signature of the Student

(Shiv Nath Chaudhri)

CERTIFICATE BY THE SUPERVISOR

It is certified that the above statement made by the student is correct to the best of my knowledge.


Dr. N. S. Rajput

Supervisor

Department of Electronics Engineering

IIT (BHU), Varanasi

COPYRIGHT TRANSFER CERTIFICATE

Title of the Thesis: Novel Intelligent Signal Processing Approaches
for Performance Enhancement of Gas Sensor
Nodes Suitable for Near Real-Time Resource-
Constrained Scenarios

Name of the Student: Shiv Nath Chaudhri

Copyright Transfer

The undersigned hereby assigns to the Indian Institute of Technology (Banaras Hindu University), Varanasi all rights under copyright that may exist in and for the above thesis submitted for the award of the "Doctor of Philosophy."

Date: 20/08/2022
Place: IIT (BHU), Varanasi


(Shiv Nath Chaudhri)

Note: However, the author may reproduce or authorize others to reproduce material extracted verbatim from the thesis or derivative of the thesis for author's personal use provided that the source and the Institute's copyright notice are indicated.

Acknowledgements

I want to express my immense gratitude to my supervisor Dr. N. S. Rajput, for accepting me as his student and allowing me to be his Ph.D. Scholar. His support and guidance inspired me to work hard during my work. I have learned so much from my eminent supervisor that will enlighten me throughout my life. I am also grateful to his family members for sacrificing their family-time when we (me and my supervisor) were working 24/7 to finish the Ph.D. associated targets within the stipulated time. Also, I thank my research performance evaluation committee (RPEC) members, Dr. K. Sarawadekar and Dr. H. P. Gupta, for their encouragement and insightful comments. I also would like to express my gratitude to Prof. K. P. Singh and Prof. V. N. Mishra (HoD) for their kind cooperation and encouragement during my M.Tech. & Ph.D. journey at IIT (BHU), Varanasi. I am also thankful to Prof. Dr. Dharmendra Singh (IIT Roorkee) for being an inspiration in the area of remote sensing. I want to express my special thanks to Dr. Saeed Hamood Alsamhi and Dr. Ashutosh Mishra for their valuable assistance in knowing the insight of Ph.D. I also thank Dr. Gaurav Modanwal for making me aware of LaTeX. I am thankful to my research colleagues working at NCC Lab, Mr. Sumit Srivastava, Mr. Kanak Kumar, Mr. Dharmendra Kumar, and all my colleagues from other Labs for providing a friendly environment at the IIT (BHU) Campus. My special thanks and sincere appreciations also go to all office staff members of the department for their kind cooperation.

I am indebted to my father, Mr. Brij Lal Chaudhri, and mother, Mrs. Shiv Devi, whose blessings and their trust in me, helped me attain this position. I also appreciate my wife, Mrs. Nancy Chaudhri, for her continuous support, patience, and unconditional love especially during the periods of my tryst with various research phases and to keep me confident. I want to express my gratitude to my father-in-law Mr. Ramveer Chaudhri and mother-in-law Mrs. Ramsanehi Chaudhri for their persistent pray for my success. Also, I sincerely thank all my well-wishers.

Finally, and above all, I thank Baba Kashi Vishwanath for giving me the strength and courage to complete this doctoral work.

Date:

Shiv Nath Chaudhri

Dedicated

to

Almighty Baba Kashi Vishwanath

&

The Holy City
Kashi/Banaras/Varanasi

Contents

List of Figures	xvii
List of Tables	xxi
Abbreviations	xxiii
Preface	xxvii
1 Introduction and Literature Survey	1
1.1 The Historical Background	1
1.1.1 The Etymology of Word ‘Gas’	1
1.1.2 The Evolution of Gas Detectors	2
1.1.3 Gas Chromatography-Mass Spectrometry (GC-MS)	3
1.2 Introduction	4
1.2.1 Gas Sensors	5
1.2.2 Gas Sensor Array	9
1.2.3 Electronic Noses (e-Noses)	10
1.2.4 Applications of e-Noses	10
1.3 Literature Survey	13
1.4 Pattern Recognition Techniques Used in e-Nose Systems	20
1.4.1 Principal Component Analysis	20
1.4.2 Probability-Based Techniques	21
1.4.3 Cluster Analysis-Based Techniques	22
1.4.4 Discriminant Analysis-Based Techniques	22
1.4.5 Nearest Neighbor-Based Techniques	22
1.4.6 Genetic Algorithms	23
1.4.7 Decision Tree-Based Techniques	23
1.4.8 Support Vector Machine (SVM)	24
1.4.9 Ensemble Techniques	24
1.4.10 Artificial Neural Networks (ANNs)	25

1.5 Observed Research Gaps from Literature	
Survey	26
1.6 Problem Statements	27
1.7 Outline of the Thesis	29
1.8 Conclusion	31
2 Materials, Methods, and Technology Background	33
2.1 Materials	33
2.1.1 Metal Oxide Semiconductors	34
2.1.2 Working of MOX Gas Sensors	34
2.1.3 Responses of MOX Gas Sensors	35
2.1.4 Steady-State and Sampled Dynamic/Transient Responses	36
2.1.5 Dataset-1	38
2.1.6 Dataset-2	39
2.1.7 Dataset-3	39
2.1.8 Dataset-4	41
2.2 Methods	42
2.2.1 Artificial Neural Networks (ANN)	42
2.2.2 ANN Compatibility with Array Response Modalities	45
2.3 Technology Background	46
2.3.1 A General Architecture of 2D-CNN	48
2.3.2 Motivation for Using 2D-CNN for Gas Classification	49
2.4 Conclusion	51
3 Multidimensional Multiconvolution-Based Feature Extraction Approach for Drift Tolerant Robust Classifier for Gases/Odors	53
3.1 Abstract	53
3.2 Introduction	54
3.3 Corresponding Gas Sensor Array and Data	60
3.4 Design & Training of DTRC	63
3.5 Results	67
3.6 Discussion	71
3.7 Conclusion	73
4 A Novel Principal Component-Based Virtual Sensor Approach for Efficient Classification of Gases/Odors	75
4.1 Abstract	75
4.2 Introduction	76
4.3 Methodology	80
4.3.1 Characteristics of Gas Sensor Array Responses	80
4.3.2 Upscaling Through Virtual Sensor Responses	82
4.3.3 Techniques for Virtual Sensor Responses	83

4.3.4	Zero and Non-Zero Padding	84
4.3.5	Mathematical Ground of Principal Component Analysis	86
4.3.6	Mirror Mosaicking	87
4.3.7	Architecture of Used 2D Convolutional Neural Network	88
4.4	Gas Sensor Array Responses	90
4.4.1	Dataset-1	91
4.4.2	Dataset-2	92
4.4.3	PCA Visualization for Dataset-1 and Dataset-2	93
4.4.4	Step-wise Description of Approach Implementation	95
4.5	Results and Discussion	95
4.6	Conclusion	99
5	Zero-Padding and Spatial Augmentation-Based Gas Sensor Node Optimization Approach in Resource-Constrained 6G-IoT Paradigm	101
5.1	Abstract	101
5.2	Introduction	102
5.2.1	Motivation and Utilities for Presented Work	107
5.3	Description of Used Dataset	109
5.4	Gas Sensor Systems for Resource-Constrained 6G-IoT Applications	110
5.5	About Simpler 2D-CNN	113
5.6	Virtual Gas Sensors and Zero-Padding	115
5.7	Contextual Outline of Spatial Augmentation	116
5.8	Experimental Cases for Baseline, Scenario 1, and Scenario 2	119
5.9	Results	121
5.9.1	Experiment 1: Baseline (While Classifying and Quantifying the Considered Gases/Odors Using Responses of All Four Physical Gas Sensor Elements)	121
5.9.2	Experiment 2: Scenario 1 (While Classifying and Quantifying the Considered Gases/Odors Using Responses of Three Physical Gas Sensor Elements & One Virtual Sensor Element)	123
5.9.3	Experiment 3: Scenario 2 (While Classifying and Quantifying the Considered Gases/Odors Using Responses of Two Physical Gas Sensor Elements & Two Virtual Sensor Elements)	125
5.10	Discussion	126
5.11	Conclusion	128
6	Conclusions and Future Scopes	131
6.1	Conclusions	131

6.2 Future Scopes	133
References	135
Author's Publications	165

List of Figures

1.1	Jean-Baptiste Van Helmont: The Etymologist of Word “Gas” (Source: CurioKids - Jean-Baptiste Van Helmont)	2
1.2	Early Means for Gas Detection in Coal Mines (Credits: Wikipedia)	3
1.3	Human Sensory Panels for Olfactory Assessment	4
1.4	Schematic Blocks of GC–MS Instrument	5
1.5	Schematic Circuit for Catalytic Gas Sensor	6
1.6	Circuitry of Electrochemical Gas Sensor	7
1.7	Schematic of NDIR (Non-Dispersive Infrared) Gas Sensor	8
1.8	Mass Sensitive QCM Gas Sensor	8
1.9	Schematic of Metal Oxide Semiconductor (MOX) Gas Sensor	9
1.10	A Schematic Diagram of Gas Sensor Array	10
1.11	An Analogous Schematic Representation of Electronic Nose Principle	11
1.12	A Schematic Picture of Gas Sensing Applications	12
1.13	Advanced Gas Sensing Materials	14
1.14	Gas Sensor Technologies	15
1.15	MOX Gas Sensor Circuit	16
1.16	Three Basic Building Blocks of e-Nose	17
2.1	Response of a MOX (TGS2610) Gas Sensor for Ethylene at 125 ppm	36
2.2	Steady-State and Transient Regions of Sensor Array Responses Captured for Carbon Monoxide and Ethylene	37
2.3	A General Architecture of Artificial Neural Network	43
2.4	Perceptron Architecture	44
2.5	A Simplest Architecture of 2D-CNN	48
2.6	2D Convolution Operation	49
2.7	2D Max-Pooling Operation	49
2.8	2D-CNN for Image Classification	50
3.1	Three Stages of A Model Nose	55
3.2	The End-to-End Hybrid Convolutional Neural Network (CNN) Architecture of Drift Tolerant Robust Classifier (DTRC)	59

3.3	A Pictorial Representation of Extracted Salient Features from Raw Data → (a) Raw response of MOX gas sensor for Acetaldehyde at 30ppmv concentration. The graph shows three phases: baseline, injection phase, and recovery phase. (b)-(d) exponential moving average of injection phase for $\alpha = 0.1, 0.01, 0.001$. (e)-(g) exponential moving average of recovery phase for $\alpha = 0.1, 0.01, 0.001$.	62
3.4	Differential Performance of DTRC <i>w.r.t.</i> Vergara et al. (2012)	69
3.5	Performance Comparison of DTRC <i>w.r.t.</i> State-of-The-Art Methods Under Setting-1	70
3.6	Performance Comparison of DTRC <i>w.r.t.</i> State-of-The-Art Methods Under Setting-2	71
4.1	(a) AI-Based Intelligent Gas-Sensing (IGS) System, (b) AI-Based IGS System Utilizing Hybrid Analysis Space	78
4.2	Response Characteristics of MOX-Based Gas Sensing Element During Exposure of Analyte (Gas/Odor)	81
4.3	The Explained Role of Virtual Sensor Responses	83
4.4	Graphical Notion of Principal Component Analysis: PCA orthonormalizes the data along with rotated axes.	87
4.5	Mirror Mosaicking Utilizing: (a) Zero-Padding Based Virtual Sensor Responses, (b) Non-Zero Virtual Sensor Responses	89
4.6	2D-CNN Architectures (a) A General Representation, (b) Simplified for Classification of Gases/Odors	90
4.7	3D Cluster Representation for: (a) UPPER : Dataset-1, (b) LOWER Dataset-2.	94
4.8	Step-wise Flowchart for Approach Implementation	96
5.1	A schematic block diagrams of an electronic nose; (a) using traditional ANN which are too complex due to usage of only fully connected layers resulting in a large number of trainable parameters; (b) using the proposed sensor array optimization approach suitable for resource-constrained 6G-IoT scenarios incorporating a simpler 2D-CNN which results in less trainable parameters due to usage of convolutional layers than traditional ANN.	111
5.2	Percentage of Change in Resistance of Gas Sensor Element Vs. Percent Concentration of Considered Gas/Odor \forall the characteristics of four gas sensing elements of gas sensor array <i>w.r.t.</i> four hazardous gases/odors, viz., acetone, carbon tetrachloride, ethyl methyl ketone, and xylene.	112
5.3	(a) The general architecture of 2D-CNN consisting of convolution and pooling layers, (b) Customized 2D-CNN for gas sensor node optimization well-suited for resource-constrained 6G-IoT applications.	114

5.4	Augmentation procedure of four-element data vectors for (a) Baseline: Unoptimized gas sensor array, (b) Scenario 1: The removal of most redundant physical gas sensor element, (c) Scenario 2: The removal of two most redundant physical gas sensor elements.	118
5.5	Sample-wise quantification performance for test samples in terms of actual vs predicted percent concentration during best observation of Baseline, Scenario 1, and Scenario 2 experiments.	123
5.6	Sample-wise classification performance for test samples in terms of actual vs predicted targets during Baseline, Scenario 1, and Scenario 2 experiments.	124
5.7	Quantification MSEs in Baseline, Scenario 1 / Case 3, and Scenario 2 / Case 6 experiments.	127
5.8	Approximated power requirement distribution in gas sensor node: (a) UPPER : before optimization, (b) LOWER after optimization. . . .	129

List of Tables

1.1	Pre-processing Functions on Sensor Data.	18
2.1	Related Content of Dataset-1.	40
2.2	Related Content of Dataset-2 (1/2).	41
2.3	Related Content of Dataset-2 (2/2).	41
3.1	Batch-wise Distribution of Samples for Considered Gases/Odors	61
3.2	Concentration Ranges for Considered Gases/Odors	61
3.3	Month IDs Corresponding to Batch ID	61
3.4	Types of Gas Sensor Elements Used in Gas Sensor Array	63
3.5	Input and Output Shapes Through 1D, 2D, and 3D Blocks	66
3.6	Batch-wise Classification Accuracy Obtained by DTRC for 20% Samples of Individual Batches	68
3.7	Batch-wise Classification Accuracy Obtained by DTRC for Subsequent Batches	68
3.8	A Layer-wise Comparison of Some State-of-The-Art CNN Architectures Used for Gas Classification	72
4.1	Intermediate Steps in Data Vector Conversion Process	80
4.2	Parameters Used by Simpler 2D-CNN	91
4.3	Details of 16 Gas Sensor Elements <i>w.r.t.</i> Dataset-2	93
4.4	Gases/Odors' Classification Performances While Using Zero and Non-Zero Virtual Sensor Responses	97
5.1	Performance Metrics for Baseline, Scenario 1, and Scenario 2 Experiments	122

Abbreviations

1D	One Dimensional
2D	Two Dimensional
3D	Three Dimensional
6G	6th Generation of Wireless Communication Technology
6G-IoT	6G driven Internet of Things
<i>ace</i>	Acetone
AddNet	Additive Neural Network
AI	Artificial Intelligence
ANN	Artificial Neural Network
BPNN	Back Propagation Neural Network
CA	Cluster Analysis
<i>car</i>	Carbon Tetrachloride
<i>CdS</i>	Cadmium Sulphide
CNN	Convolutional Neural Network
CO	Carbon Mono-Oxide
CPS	Cyber-Physical System
CS	Copmressed Sensing
DA	Discriminant Analysis
DCNN	Deep Convolutional Neural Network
DFA	Discriminant Function Analysis
DiscGAN	Discriminator of Generative Adversarial Network
DL	Deep Learning

DRCA	D omain R egularized C omponent A nalysis
DTRC	D rift T olerant R obust C lassifier
ELM	E xtrême L earning M achine
EMA	E xponential M oving A verage
<i>emk</i>	Ethyl-Methyl Ketone
e-Nose	E lectronic N ose
GA	G enetic A lgorithm
GC	G as C hromatography
GC-MS	G as C hromatography - M ass S pectrometry
GMM	G aussian M ixture M odel
GSS	G as- S ensing S ystem
HCA	H ierarchical C luster A nalysis
IGS	I ntelligent G as- S ensing S ystem
IoT	I nternet of T hings
JDA	J oint D istribution A daptation
kNN	k N earest N eighbor
LDA	L inear D iscriminant A nalysis
LEL	L ower E xplosive L imit
MDA	M ultiple D iscriminant A nalysis
ML	M achine L earning
MLP	M ulti- L ayer P erceptron
<i>MoO</i>	Molybdenum Oxide
MOS	M etal O xide S emiconductor
MOX	M etal O xide
MS	M ass S pectrometry
MSE	M ean S quared E rror
OCA	O verall C lassification A ccuracy
PC	P ricipal C omponent
PCA	P ricipal C omponent A nalysis

PPM	P arts P er M illion
QCM	Q uartz C rystal M icrobalance
QoS	Q uality of S ervice
RBF	R adial B asis F unction
RF	R andom F orest
SAW	S urface W ave A coustic
SGD	S tochastic G radient D escent
<i>SnO₂</i>	Tin Oxide
SoC	S ystem on C hip
SVM	S upport V ector M achine
TGS	T aguchi G as S ensor
VGS	V irtual G as S ensor
VOC	V olatile O rganic C ompound
WSN	W ireless S ensor N etwork
<i>xyl</i>	Xylene
<i>ZnO</i>	Zinc Oxide

PREFACE

Artificial neural networks (ANNs) have been used for classification, quantification, and drift corrections for decades. While applying ANNs and traditional pattern recognition techniques, additional statistical algorithms are necessary for data pre-processing and compensating for the drift. Due to such multistage off-line statistical procedures, these methods are not suitable for real-time applications. Hence, we have developed an end-to-end hybrid CNN architecture called a “Drift Tolerant Robust Classifier (DTRC),” suitable for real-time real-field applications. It can automatically extract salient multidimensional features from the drifted raw sensor array responses capable of efficiently classifying the gases/odors. While classifying with such extracted features, DTRC also curtails the drift impacts and outperforms the various state-of-the-art peers. The DTRC comprises three blocks performing one-, two-, and three-dimensional (1D, 2D, and 3D) operations. DTRC does not use any additional statistical algorithm to compensate for the drift, making it compatible with real-time applications. A publicly available benchmark drifted-dataset has been used to prove the efficacy of DTRC.

Moreover, real-time applications requiring high accuracy to detect and estimate hazardous gases/odors are too challenging to implement with traditional approaches. Therefore, researchers have started to use CNNs for developing efficient e-Noses. However, the generalization has not been discussed so far to apply CNNs for gas classification independent of types of gas sensor array responses. Recently, authors have applied CNNs to classify the gases/odors using only dynamic responses without discussing the same for static responses. The popular 2D-CNN performs better when operating on 2D input data of optimal size with suitable kernels. Hence, we have proposed a novel approach by utilizing 2D-CNN for gas classification using steady-state responses of the gas sensor array. In this regard, the operational data vectors are augmented with the synergy of mirror mosaicking and padding of virtual

sensor responses, which are obtained from the principal components. The experimental results have been demonstrated on two different datasets that have been upscaled with this approach to provide the desired outcomes. Using such an approach, we are the first to utilize a principal component-based hybrid and upscaled dataset. An e-Nose utilizing our proposed policy has achieved 100 percent correct classification for the considered set of unknown test samples which were not used during training and validation of the networks over the considered gases/odors.

Further, the sensor nodes should be ultra-power-efficient and compatible with Artificial Intelligence (AI) models in 6G-IoT ecosystems. The challenge arises whenever the sensor node is required to be deployed in a resource-constrained environment since AI models require high computational capacity due to inherent complex architecture. We have, hence, discussed how a gas sensor node can be optimized to be power-efficient; and how we can obtain high performance using the synergy of an optimized sensor node and a lightweight CNN. A gas sensor node consists of an array of non-selective gas sensors chosen randomly without intuition about the optimal number of sensors to use, causing redundancy. Consequently, the gas sensor nodes can be optimized by removing the redundant physical gas sensor elements that leads to the reduction in power consumption of the gas sensor node. While the deteriorated performance by this removal is compensated using a CNN incorporating zero-padding and spatial augmentation. The experimentation with this approach has been demonstrated to classify and quantify the four hazardous gases. The performance of the unoptimized gas sensor array has been taken as a “baseline” to compare the performance of the optimized gas sensor array. This approach reduced the power consumption of the gas sensor array to half. At the same time, classification and quantification were achieved with 100 percent accuracy, and a very low mean squared error (MSE). Consequently, our power-efficient optimization and lightweight CNN pave the way to deploy gas sensor nodes in the resource-constrained 6G-IoT paradigm. It is also suitable for edge intelligence reducing the computational complexity on edge.

Thus, this thesis presents certain well interrogated Sensor Data Processing Approaches for Performance Enhancement of Gas Sensor Nodes operating in Resource-Constrained Scenarios, explaining advanced learning concepts for gas sensing applications. The six chapters of this dissertation provide information about the subject area, from historical background to future scopes to develop advanced data analytics-based high-performance gas sensing systems using modern approaches.

Chapter 1: presents the introduction and literature survey, starting from the very primitive historical context.

Chapter 2: presents details about MOX gas sensors and their response modalities, including the background of ANN and CNN for gas/odor classification.

Chapter 3: presents a novel hybrid CNN architecture DTRC capable of classifying gases/odors, even without additional drift-correction algorithms.

Chapter 4: presents a novel scheme of padding that enables CNNs even operable on steady-state responses.

Chapter 5: presents a novel approach for gas sensor node optimization suitable for resource-constrained paradigms.

Chapter 6: concludes the dissertation with the highlights of presented works and future scopes.

