

# CONTENTS

<i>Contents</i>	xiii-xv
<i>List of Figures</i>	xvii-xxvi
<i>List of Tables</i>	xxvii
<i>List of Abbreviations</i>	xxix-xxx
<i>List of Symbols</i>	xxxi-xxxii
<i>Preface</i>	xxxiii-xxxv
<b>Chapter 1</b>	<b>Page No.</b>
<b>Introduction and Scope of the Thesis</b>	01-52
1.1 Introduction	01
1.2 MOSFET Scaling and Moore's Law	02
1.3 Adverse Effects of Scaling on Subthreshold Characteristics of MOSFETs	04
1.4 Introduction to Tunnel Field Effect Transistor (TFET)	08
1.4.1 Working Principle of TFET	11
1.4.2 Band-to-Band Tunneling Current in TFETs	13
1.5 Possible Techniques for Performance Improvements of TFETs	16
1.5.1 Gate Engineering Techniques	17
1.5.2 Source Pocket Engineering	19
1.5.3 Vertically Grown TFET Structure	21
1.5.4 Band Gap Engineering Techniques	22
1.5.5 Gate-Dielectric Engineering	27
1.6 Circuit level Performance Using TFETs	29
1.7 Review of Some State-of-the-Art Research Works on TFETs	34
1.7.1 Review of Some Experimental Research Works on TFETs	34
1.7.2 Review of Some Simulations and Modelling works on TFET	37
1.7.3 Review of Some TFETs Based Circuits	39
1.8 Summary of the Literature Review: Motivation behind the Present Thesis	46
1.9 Scopes of the Thesis	49

## Chapter 2

### **Effect of Source Pocket Engineering on Device Level Performance of GaSb/Si Heterojunction Vertical TFET** 53-87

2.1	Introduction	53
2.2	TCAD Simulation Framework	55
2.2.1	Proposed Vertical TFET Architectural Specifications	55
2.2.2	Possible Fabrication Steps to Realize the proposed TFET	56
2.2.3	TCAD Simulation Methodology	59
2.2.3.1	Description of Various Models used in the Simulations	60
2.2.3.2	Models Calibration	63
2.3	Results and Discussion	64
2.3.1	DC Performance Analysis	64
2.3.2	Temperature Reliability Analysis	66
2.3.3	Analog/RF Performance Evaluation	67
2.4	SPE GaSb/Si HJ VTFET Verses SPE All-Si VTFET: Performance Comparison	74
2.5	Conclusion	86

## Chapter 3

### **Effect of Gate Oxide Stacking on the Electrical Performance Characteristics of Source Pocket Engineered GaSb/Si Heterojunction Vertical TFETs** 89-108

3.1	Introduction	89
3.2	Proposed structures and TCAD Simulation Details	90
3.2.1	Proposed Device Structures	90
3.2.2	Possible Fabrication Steps to Realize Proposed TFETs Structures	93
3.2.3	Simulation Methodology	96
3.3	Results and Discussion	97
3.3.1	DC Performance Analysis	97
3.3.2	RF Performance Analysis	101
3.4	Conclusion	107

## Chapter 4

### **Impact of Gate Oxide Stacking on the Performance of Source Pocket Engineered GaSb/Si Heterojunction Vertical TFET Based 8T SRAM Cell** 109-124

4.1	Introduction	109
4.2	Device to Circuit Level Framework for Implementation of 8T SRAM	111

Using Presented VTFETs	
4.3 Results and Discussion	114
4.3.1 Read Stability	114
4.3.2 Write Ability	116
4.3.3 Read Delay	118
4.3.4 Write Delay	120
4.4 Conclusion	123

## **Chapter 5**

### **SPE GaSb/Si VTFET Versus SPE Ge/Si VTFET: Performance Comparison at Device and Circuit Levels** 125-142

5.1 Introduction	125
5.2 Device and Circuit Level Simulation Methodology with Device Design Parameters	126
5.3 Results and Discussion	130
5.3.1 Device Level Performance Analysis	130
5.3.2 Circuit Level Performance Analysis	136
5.3.2.1 Digital Logic Inverter Performance Analysis	136
5.3.2.2 8T SRAM Performance Analysis	138
5.4 Conclusion	142

## **Chapter 6**

### **Conclusion and Future Scope** 143-146

6.1 Summary of Major Findings of the Thesis	143
6.2 Future Scope of Work	145

<i>References</i>	147-161
<i>Author's Relevant Publications</i>	163-164



## LIST OF FIGURES

---

<b>Fig. 1.1:</b>	The ITRS roadmap of transistor development [Internet resource (IR1)]	2
<b>Fig. 1.2:</b>	Variation of power density against gate length scaling of MOS device [42]	5
<b>Fig. 1.3:</b>	Variation of drain current against gate-to-source voltage of MOS device [Internet resource (IR2)]	6
<b>Fig. 1.4:</b>	Variation of supply voltage and threshold voltage against technology generation [50]	7
<b>Fig. 1.5(a):</b>	2-D cross-sections view of MOSFET	10
<b>Fig. 1.5(b):</b>	2-D cross-sections view of TFET	10
<b>Fig. 1.6(a):</b>	The current conduction mechanism of MOSFET	10
<b>Fig. 1.6(b):</b>	The current conduction mechanism of TFET	10
<b>Fig. 1.7(a):</b>	Conventional structure of n-TFET	11
<b>Fig. 1.7(b):</b>	Conventional structure of p-TFET	11
<b>Fig. 1.8(a):</b>	Energy band distribution of a typical TFET under OFF-state	12
<b>Fig. 1.8(b):</b>	Energy band distribution of a typical TFET under ON-state	12
<b>Fig. 1.9(a):</b>	The ON-state energy band diagram for a typical TFET	13
<b>Fig. 1.9(b):</b>	The triangular potential barrier for a typical TFET	13
<b>Fig. 1.10(a):</b>	Transfer characteristics for Ideal device, Bulk MOSFET and Tunnel FET [34]	16
<b>Fig. 1.10(b):</b>	Comparison of the energy consumption per cycle with respect to supply voltage for TFET and MOSFET having same $I_{ON}/I_{OFF}$ ratio [89].	16
<b>Fig. 1.11(a):</b>	Double-Gate TFET Structure	18
<b>Fig. 1.11(b):</b>	Tri-gate TFET Structure	18
<b>Fig. 1.11(c):</b>	Quadruple Gate TFET Structure	18

<b>Fig. 1.11(d):</b>	Cylindrical Gate TFET Structure	<b>18</b>
<b>Fig. 1.12 (a):</b>	Source pocket Engineered tunnel field effect transistor with Vertical process flow technique [83]	<b>20</b>
<b>Fig. 1.12(b):</b>	Source pocket Engineered tunnel field effect transistor with Lateral process flow technique [78]	<b>20</b>
<b>Fig. 1.13(a):</b>	Schematic view vertically grown TFET with rectangular geometry [126]	<b>22</b>
<b>Fig. 1.13(b):</b>	Schematic view vertically grown TFET gate all around or cylindrical geometry [81]	<b>22</b>
<b>Fig. 1.14(a):</b>	Type-I or straddling gap heterojunction [46].	<b>24</b>
<b>Fig. 1.14(b):</b>	Type-II or staggered gap heterojunction [46].	<b>24</b>
<b>Fig. 1.14(c):</b>	Type-III or broken-gap heterojunction [46].	<b>24</b>
<b>Fig. 1.15(a):</b>	Cross sectional view of heterojunction double gate TFET based on low-band gap materials (source) and Si (channel)	<b>27</b>
<b>Fig. 1.15(b):</b>	Cross sectional view of heterojunction double gate TFET based on compound semiconductor (source)- compound semiconductor (channel)	<b>27</b>
<b>Fig. 1.16(a):</b>	Cross sectional views of Double Gate TFET structure with Lateral Stacked Gate (high- $k$ /low- $k$ )	<b>28</b>
<b>Fig. 1.16(b):</b>	Cross sectional views of Double Gate TFET structure with Vertical Stacked Gate (low- $k$ /high- $k$ )	<b>28</b>
<b>Fig. 1.17(a):</b>	Comparison of output characteristics for TFET [82]	<b>30</b>
<b>Fig. 1.17(b):</b>	Comparison of output characteristics for MOSFET [82]	<b>30</b>
<b>Fig. 1.18(a):</b>	Comparison between gate to drain capacitance ( $C_{gd}$ ) with different gate to source bias ( $V_{gs}$ ) of MOSFET [66]	<b>31</b>
<b>Fig. 1.18(b):</b>	Comparison between gate to drain capacitance ( $C_{gd}$ ) with different gate to source bias ( $V_{gs}$ ) of TFET [66]	<b>31</b>
<b>Fig. 1.19(a):</b>	Enhanced capacitive loading in TFET because of two times increase in Miller capacitance [101]	<b>32</b>
<b>Fig. 1.19(b):</b>	Overshoot and undershoot caused due to capacitive loading [101]	<b>32</b>
<b>Fig. 1.20(a):</b>	Schematic of 6T SRAM designed with TFETs having inward access transistors	<b>33</b>
<b>Fig. 1.20(b):</b>	Schematic of 6T SRAM designed with TFETs having outward access transistors (O-6T)	<b>33</b>
<b>Fig. 1.21(a)</b>	Homogeneous gate oxide VTFET based on the literature review	<b>39</b>

<b>Fig. 1.21(b)</b>	Vertical gate oxide stacked VTFET based on the literature review	<b>39</b>
<b>Fig. 1.21(c)</b>	Lateral gate oxide stacked VTFET based on the literature review	<b>39</b>
<b>Fig 2.1(a):</b>	Schematic diagram of GaSb/Si heterojunction vertical TFET without source pocket (GaSb/Si HJ VTFET)	<b>56</b>
<b>Fig. 2.1(b):</b>	Schematic diagram of GaSb/Si heterojunction vertical TFET with source pocket (SPE GaSb/Si HJ V-TFET)	<b>56</b>
<b>Fig. 2.1(c):</b>	Cross section view of GaSb/Si HJ VTFET	<b>56</b>
<b>Fig. 2.1(d):</b>	Cross section view of GaSb/Si HJ VTFET	<b>56</b>
<b>Fig. 2.2(a)</b>	Starting with a silicon (Si) substrate	<b>58</b>
<b>Fig. 2.2(b)</b>	Growth of silicon drain and channel region on the silicon substrate using molecular beam epitaxy (MBE) or low-pressure chemical vapor deposition (LPCVD)	<b>58</b>
<b>Fig. 2.2(c)</b>	Growth of GaSb source pocket and source region on silicon channel using metalloorganic vapor phase epitaxy (MOVPE)	<b>58</b>
<b>Fig. 2.2(d)</b>	Hard mask (HM) oxide deposition on top of the source for digital etching to form form width of the vertical TFET with specific dimension	<b>58</b>
<b>Fig. 2.2(e)</b>	Digital etching	<b>58</b>
<b>Fig. 2.2(f)</b>	Deposition of gate oxide layer ( $\text{Al}_2\text{O}_3$ ) using atomic layer deposition (ALD) technique	<b>58</b>
<b>Fig. 2.2(g)</b>	Gate length definition along with etching out oxide layer at unwanted place. Hard mask oxide can be removed after etching	<b>58</b>
<b>Fig. 2.2(h)</b>	Gate metal with desired work function deposition to form gate contact	<b>58</b>
<b>Fig. 2.2(i)</b>	Source and drain metal deposition to form source and drain contacts	<b>58</b>
<b>Fig. 2.3(a):</b>	Calibration of used models in SILVACO ATLAS <sup>TM</sup> 3D TCAD tool: comparison of simulation results of $I_{\text{DS}}-V_{\text{GS}}$ in linear-linear scale with experimental results of a Ge source based VTFET [119]	<b>64</b>
<b>Fig. 2.3(b):</b>	Calibration of used models in SILVACO ATLAS <sup>TM</sup> 3D TCAD tool: comparison of simulation results of $I_{\text{DS}}-V_{\text{GS}}$ in log-linear scale with experimental results of a Ge source based VTFET [119]	<b>64</b>
<b>Fig. 2.4(a):</b>	Energy band distribution of GaSb/Si HJ VTFET in OFF-state as well as in ON-state	<b>65</b>
<b>Fig. 2.4(b):</b>	Energy band distribution of SPE GaSb/Si HJ VTFET in OFF-state as well as in ON-state.	<b>65</b>
<b>Fig. 2.5(a):</b>	Transfer characteristics of GaSb/Si HJ VTFET and SPE GaSb/Si HJ VTFET	<b>66</b>

<b>Fig. 2.5(b):</b>	Output characteristics of GaSb/Si HJ VTFET and SPE GaSb/Si HJ VTFET.	<b>66</b>
<b>Fig. 2.6(a):</b>	Comparative plot of SS with respect to temperature for GaSb/Si HJ VTFET and SPE GaSb/Si HJ VTFET.	<b>67</b>
<b>Fig. 2.6(b):</b>	Comparative plot of $I_{ON}/I_{OFF}$ ratio with respect to temperature for GaSb/Si HJ VTFET and SPE GaSb/Si HJ VTFET.	<b>67</b>
<b>Fig. 2.7(a):</b>	Transconductance ( $g_m$ ) comparison of GaSb/Si HJ VTFET and SPE GaSb/Si HJ VTFET	<b>68</b>
<b>Fig. 2.7(b):</b>	Output conductance ( $g_d$ ) comparison of GaSb/Si HJ VTFET and SPE GaSb/Si HJ VTFET	<b>68</b>
<b>Fig. 2.8(a):</b>	Comparative plot of gate to drain capacitance ( $C_{gd}$ ) with respect to gate to source voltage ( $V_{GS}$ ) for GaSb/Si HJ VTFET and SPE GaSb/Si HJ VTFET	<b>69</b>
<b>Fig. 2.8(b):</b>	Comparative plot of gate to source capacitance ( $C_{gs}$ ) with respect to gate to source voltage ( $V_{GS}$ ) for GaSb/Si HJ VTFET and SPE GaSb/Si HJ VTFET	<b>69</b>
<b>Fig. 2.9(a):</b>	Comparative plot of $f_T$ with respect to gate to source voltage ( $V_{GS}$ ) for GaSb/Si HJ VTFET and SPE GaSb/Si HJ VTFET	<b>70</b>
<b>Fig. 2.9(b):</b>	Comparative plot of GBP with respect to gate to source voltage ( $V_{GS}$ ) of GaSb/Si HJ VTFET and SPE GaSb/Si HJ VTFET	<b>70</b>
<b>Fig. 2.10(a):</b>	Comparative plot of $f_{max}$ for GaSb/Si HJ VTFET and SPE GaSb/Si HJ VTFET	<b>71</b>
<b>Fig. 2.10(b):</b>	Comparative plot of transit time for GaSb/Si HJ VTFET and SPE GaSb/Si HJ VTFET	<b>71</b>
<b>Fig. 2.11(a):</b>	Comparative plot of TGF with respect to gate to source voltage ( $V_{GS}$ ) for GaSb/Si HJ VTFET and SPE GaSb/Si HJ VTFET	<b>72</b>
<b>Fig. 2.11(b):</b>	Comparative plot of TFP with respect to gate to source voltage ( $V_{GS}$ ) of GaSb/Si HJ VTFET and SPE GaSb/Si HJ VTFET.	<b>72</b>
<b>Fig. 2.12(a):</b>	Schematic diagram of source pocket engineered all-Si vertical TFET (SPE All-Si VTFET)	<b>75</b>
<b>Fig. 2.12(b):</b>	Schematic diagram of source pocket engineered GaSb/Si heterojunction vertical TFET (SPE GaSb/Si HJ VTFET)	<b>75</b>
<b>Fig. 2.12(c):</b>	Cross sectional view of SPE All-Si VTFET	<b>75</b>
<b>Fig. 2.12(d):</b>	Cross sectional view of SPE GaSb/Si HJ VTFET	<b>75</b>
<b>Fig. 2.13(a):</b>	OFF-state energy band diagram of SPE All-Si VTFET and SPE GaSb/Si HJ VTFET	<b>77</b>
<b>Fig. 2.13(b):</b>	ON-state energy band diagram of SPE All-Si VTFET and SPE	<b>77</b>

	GaSb/Si HJ VTFET	
<b>Fig. 2.14(a):</b>	Comparison of transfer characteristics for SPE All-Si VTFET and SPE GaSb/Si HJ VTFET	<b>78</b>
<b>Fig. 2.14(b):</b>	Comparison of output characteristics for SPE All-Si VTFET and SPE GaSb/Si HJ VTFET	<b>78</b>
<b>Fig. 2.15(a):</b>	Comparison of SS for SPE All-Si VTFET and SPE GaSb/Si HJ VTFET with respect to temperature varying from 250 K to 450 K.	<b>80</b>
<b>Fig. 2.15(b):</b>	Comparison of $I_{ON}/I_{OFF}$ ratio for SPE All-Si VTFET and SPE GaSb/Si HJ VTFET with respect to temperature varying from 250 K to 450 K.	<b>80</b>
<b>Fig. 2.16(a):</b>	Comparison of transconductance for SPE All-Si VTFET and SPE GaSb/Si HJ VTFET	<b>81</b>
<b>Fig. 2.16(b):</b>	Comparison of output conductance for SPE All-Si VTFET and SPE GaSb/Si HJ VTFET	<b>81</b>
<b>Fig. 2.17(a):</b>	Comparison of gate to drain intrinsic capacitance ( $C_{gd}$ ) for SPE All-Si VTFET and GaSb/Si VTFET WP.	<b>82</b>
<b>Fig. 2.17(b):</b>	Comparison of gate to source intrinsic capacitance ( $C_{gs}$ ) for SPE All-Si VTFET and GaSb/Si VTFET WP.	<b>82</b>
<b>Fig. 2.18(a):</b>	Comparison of cut-off frequency ( $f_T$ ) for SPE All-Si VTFET and SPE GaSb/Si HJ VTFET.	<b>83</b>
<b>Fig. 2.18(b):</b>	Comparison of maximum frequency of oscillation ( $f_{max}$ ) for SPE All-Si VTFET and SPE GaSb/Si HJ VTFET.	<b>83</b>
<b>Fig. 2.19(a):</b>	Comparison of gain bandwidth product (GBP) for SPE All-Si VTFET and SPE GaSb/Si HJ VTFET.	<b>84</b>
<b>Fig. 2.19(b):</b>	Comparison of transit time of SPE All-Si VTFET and SPE GaSb/Si HJ VTFET.	<b>84</b>
<b>Fig. 2.20(a):</b>	Comparative plot of TGF with respect to gate to source voltage ( $V_{GS}$ ) for SPE All-Si VTFET and SPE GaSb/Si HJ VTFET.	<b>84</b>
<b>Fig. 2.20(b):</b>	Comparative plot of TFP with respect to gate to source voltage ( $V_{GS}$ ) for SPE All-Si VTFET and SPE GaSb/Si HJ VTFET.	<b>84</b>
<b>Fig. 3.1(a):</b>	Schematic representation of source pocket engineered GaSb/Si heterojunction vertical TFET without gate oxide stacking (SPE GaSb/Si HJ VTFET)	<b>91</b>
<b>Fig. 3.1(b):</b>	Schematic representation of source pocket engineered GaSb/Si heterojunction vertical TFET with vertical gate oxide stacking (SPE GaSb/Si HJ VTFET with VS)	<b>91</b>

<b>Fig. 3.1(c):</b>	Schematic representation of source pocket engineered GaSb/Si heterojunction vertical TFET with lateral gate oxide stacking (SPE GaSb/Si HJ VTFET with LS)	<b>91</b>
<b>Fig. 3.1(d):</b>	Cross section view of SPE GaSb/Si HJ VTFET	<b>91</b>
<b>Fig. 3.1(e):</b>	Cross section view of SPE GaSb/Si HJ VTFET with VS	<b>91</b>
<b>Fig. 3.1(f):</b>	Cross section view of SPE GaSb/Si HJ VTFET with LS	<b>91</b>
<b>Fig. 3.2(a)</b>	Fabrication steps of GaSb/Si heterojunction vertical TFET with source pocket with vertical gate oxide stacked structure (SPE GaSb/Si HJ VTFET with VS) in 2D view starting with a silicon (Si) substrate	<b>94</b>
<b>Fig. 3.2(b)</b>	growth of silicon in drain and channel region on the silicon substrate using molecular beam epitaxy (MBE) or low-pressure chemical vapor deposition (LPCVD)	<b>94</b>
<b>Fig. 3.2(c)</b>	growth of GaSb source pocket and source region on silicon channel using metalloorganic vapor phase epitaxy (MOVPE)	<b>94</b>
<b>Fig. 3.2(d)</b>	Hard mask (HM) oxide deposition on top of the source for digital etching to form width of the vertical TFET with specific dimension	<b>94</b>
<b>Fig. 3.2(e)</b>	Digital etching	<b>94</b>
<b>Fig. 3.2(f)</b>	Deposition of gate oxide layer ( $\text{Al}_2\text{O}_3$ ) using atomic layer deposition (ALD) technique	<b>94</b>
<b>Fig. 3.2(g)</b>	Deposition of gate oxide layer ( $\text{HfO}_2$ ) using atomic layer deposition technique to form vertical gate stacked structure	<b>94</b>
<b>Fig. 3.2(h)</b>	Gate length definition along with etching out oxide layer at unwanted place. Hard mask oxide can be removed after etching	<b>94</b>
<b>Fig. 3.2(i)</b>	Gate metal with desired work function deposition to form gate contact. Source and drain metal deposition to form source and drain contact	<b>94</b>
<b>Fig. 3.3(a)</b>	Fabrication steps of GaSb/Si heterojunction vertical TFET with source pocket with lateral gate oxide stacked structure (SPE GaSb/Si HJ VTFET with LS) in 2D view starting with a silicon (Si) substrate	<b>95</b>
<b>Fig. 3.3(b)</b>	Growth of silicon in drain and channel region on the silicon substrate using molecular beam epitaxy (MBE) or low-pressure chemical vapor deposition (LPCVD)	<b>95</b>
<b>Fig. 3.3(c)</b>	Growth of GaSb source pocket and source region on silicon channel using metalloorganic vapor phase epitaxy (MOVPE)	<b>95</b>

<b>Fig. 3.3(d)</b>	Hard mask (HM) oxide deposition on top of the source for digital etching to form width of the vertical TFET with specific dimension	<b>95</b>
<b>Fig. 3.3(e)</b>	Digital etching	<b>95</b>
<b>Fig. 3.3(f)</b>	Deposition of gate oxide layer ( $\text{Al}_2\text{O}_3$ ) using atomic layer deposition (ALD) technique	<b>95</b>
<b>Fig. 3.3(g)</b>	Deposition of gate oxide layer ( $\text{HfO}_2$ ) using atomic layer deposition technique to form lateral gate stacked structure	<b>95</b>
<b>Fig. 3.3(h)</b>	Etching out $\text{HfO}_2$ oxide layer at unwanted place to form lateral gate stacked structure. Hard mask oxide can be removed after etching	<b>95</b>
<b>Fig. 3.3(i)</b>	Gate metal with desired work function deposition to form gate contact. Source and drain metal deposition to form source and drain contact	<b>95</b>
<b>Fig. 3.4(a):</b>	Comparison of surface potential in ON-state for SPE GaSb/Si HJ VTFET, SPE GaSb/Si HJ VTFET with VS, and SPE GaSb/Si HJ VTFET with LS	<b>98</b>
<b>Fig. 3.4(b):</b>	Comparison of electric field in ON-state for SPE GaSb/Si HJ VTFET, SPE GaSb/Si HJ VTFET with VS, and SPE GaSb/Si HJ VTFET with LS.	<b>98</b>
<b>Fig. 3.5(a):</b>	Comparison of energy band distribution in OFF-state for SPE GaSb/Si HJ VTFET, SPE GaSb/Si HJ VTFET with VS, and SPE GaSb/Si HJ VTFET with LS.	<b>99</b>
<b>Fig. 3.5(b):</b>	Comparison of energy band distribution ON-state for SPE GaSb/Si HJ VTFET, SPE GaSb/Si HJ VTFET with VS, and SPE GaSb/Si HJ VTFET with LS.	<b>99</b>
<b>Fig. 3.6(a):</b>	Comparison of transfer characteristics for SPE GaSb/Si HJ VTFET, SPE GaSb/Si HJ VTFET with VS, and SPE GaSb/Si HJ VTFET with LS.	<b>100</b>
<b>Fig. 3.6(b):</b>	Comparison of output characteristics for SPE GaSb/Si HJ VTFET, SPE GaSb/Si HJ VTFET with VS, and SPE GaSb/Si HJ VTFET with LS.	<b>100</b>
<b>Fig. 3.7(a):</b>	Comparison of sub-threshold swing (SS) for SPE GaSb/Si HJ VTFET, SPE GaSb/Si HJ VTFET with VS, and SPE GaSb/Si HJ VTFET with LS.	<b>101</b>
<b>Fig. 3.7(b):</b>	Comparison of $I_{\text{ON}}/I_{\text{OFF}}$ ratio for SPE GaSb/Si HJ VTFET, SPE GaSb/Si HJ VTFET with VS, and SPE GaSb/Si HJ VTFET with LS.	<b>101</b>
<b>Fig. 3.8(a):</b>	Comparison of transconductance characteristics for SPE GaSb/Si HJ VTFET, SPE GaSb/Si HJ VTFET with VS, and SPE GaSb/Si HJ VTFET with LS	<b>102</b>
<b>Fig. 3.8(b):</b>	Comparison of output conductance characteristics ( $g_a$ ) for SPE GaSb/Si HJ VTFET, SPE GaSb/Si HJ VTFET with VS, and SPE	<b>102</b>

	GaSb/Si HJ VTFET with LS	
<b>Fig. 3.9(a):</b>	Comparative plot of intrinsic gate-drain capacitance ( $C_{gd}$ ) for SPE GaSb/Si HJ VTFET, SPE GaSb/Si HJ VTFET with VS, and SPE GaSb/Si HJ VTFET with LS	<b>103</b>
<b>Fig. 3.9(b):</b>	Comparative plot of intrinsic gate-source capacitance ( $C_{gs}$ ) for SPE GaSb/Si HJ VTFET, SPE GaSb/Si HJ VTFET with VS, and SPE GaSb/Si HJ VTFET with LS	<b>103</b>
<b>Fig. 3.10(a):</b>	Comparative plot of cut-off frequency ( $f_T$ ) for SPE GaSb/Si HJ VTFET, SPE GaSb/Si HJ VTFET with VS, and SPE GaSb/Si HJ VTFET with LS	<b>104</b>
<b>Fig. 3.10(b):</b>	Comparative plot of GBP for SPE GaSb/Si HJ VTFET, SPE GaSb/Si HJ VTFET with VS, and SPE GaSb/Si HJ VTFET with LS	<b>104</b>
<b>Fig. 3.11(a):</b>	Comparative plot of TGF for SPE GaSb/Si HJ VTFET, SPE GaSb/Si HJ VTFET with VS, and SPE GaSb/Si HJ VTFET with LS.	<b>106</b>
<b>Fig. 3.11(b):</b>	Comparative plot of TFP for SPE GaSb/Si HJ VTFET, SPE GaSb/Si HJ VTFET with VS, and SPE GaSb/Si HJ VTFET with LS.	<b>106</b>
<b>Fig. 4.1(a):</b>	Schematic of 6T SRAM cell designed with TFETs with inward access transistors (I-6T)	<b>110</b>
<b>Fig. 4.1(b):</b>	Schematic of 6T SRAM cell designed with TFETs with outward access transistors (O-6T).	<b>110</b>
<b>Fig. 4.2:</b>	Schematic of 8T SRAM designed with presented VTFETs	<b>112</b>
<b>Fig. 4.3:</b>	Device (SILVACO ATLAS™ 3-D TCAD tool) to circuit (CADENCE Virtuoso tool) simulation framework	<b>113</b>
<b>Fig. 4.4:</b>	Comparison of $I_d$ - $V_g$ characteristics of a source pocket engineered GaSb/Si heterojunction vertical TFET (SPE GaSb/Si HJ VTFET) between Verilog-A model prediction (symbol) and TCAD simulations (solid line) at $V_{DS}= 1.0$ V.	<b>114</b>
<b>Fig. 4.5:</b>	Read static noise margin (RSNM) calculation for SPE GaSb/Si HJ VTFET, SPE GaSb/Si HJ VTFET with VS, SPE GaSb/Si HJ VTFET with LS at 0.6 V supply voltage	<b>115</b>
<b>Fig. 4.6(a):</b>	Comparative plot of read SNM (RSNM) for SPE GaSb/Si HJ VTFET, SPE GaSb/Si HJ VTFET with VS, and SPE GaSb/Si HJ VTFET with LS;	<b>116</b>
<b>Fig. 4.6(b):</b>	Comparative plot of read SNM (RSNM) for SPE GaSb/Si HJ VTFET with LS with other reported 8T SRAM based on TFET.	<b>116</b>
<b>Fig. 4.7:</b>	Write margin (WM) calculation for SPE GaSb/Si HJ VTFET, SPE GaSb/Si HJ VTFET with VS, SPE GaSb/Si HJ VTFET with LS at	<b>117</b>

	0.6 V supply voltage	
<b>Fig. 4.8(a):</b>	Comparative plot of write margin (WM) for SPE GaSb/Si HJ VTFET, SPE GaSb/Si HJ VTFET with VS, and SPE GaSb/Si HJ VTFET with LS	<b>118</b>
<b>Fig. 4.8(b):</b>	Comparative plot of write margin (WM) for SPE GaSb/Si HJ VTFET with LS with other reported 8T SRAM based on TFET	<b>118</b>
<b>Fig. 4.9(a):</b>	Comparison of read delay for SPE GaSb/Si HJ VTFET, SPE GaSb/Si HJ VTFET with VS, and SPE GaSb/Si HJ VTFET with LS	<b>119</b>
<b>Fig. 4.9(b):</b>	Comparison of read delay of SPE GaSb/Si HJ VTFET with LS with other reported 8T SRAM based on TFET	<b>119</b>
<b>Fig. 4.10(a):</b>	Comparative plot for write delay of SPE GaSb/Si HJ VTFET, SPE GaSb/Si HJ VTFET with VS, and SPE GaSb/Si HJ VTFET with LS	<b>121</b>
<b>Fig. 4.10(b):</b>	Comparative plot of write delay for SPE GaSb/Si HJ VTFET with LS with other reported 8T SRAM based on TFET	<b>121</b>
<b>Fig. 5.1(a):</b>	Schematic representation of SPE Ge/Si HJ VTFET	<b>127</b>
<b>Fig. 5.1(b):</b>	Schematic representation of SPE GaSb/Si HJ VTFET	<b>127</b>
<b>Fig. 5.1(c):</b>	Cross-sectional view of SPE Ge/Si HJ VTFET	<b>127</b>
<b>Fig. 5.1(d):</b>	Cross-sectional view of SPE GaSb/Si HJ VTFET	<b>127</b>
<b>Fig. 5.2(a):</b>	Schematic view of the inverter designed using presented VTFETs	<b>129</b>
<b>Fig. 5.2(b):</b>	Schematic view of 8T SRAM designed with presented VTFETs	<b>129</b>
<b>Fig. 5.3(a):</b>	OFF-state energy band distribution of SPE GaSb/Si HJ VTFET and SPE Ge/Si HJ VTFET	<b>131</b>
<b>Fig. 5.3(b):</b>	ON-state energy band distribution of SPE GaSb/Si HJ VTFET and SPE Ge/Si HJ VTFET	<b>131</b>
<b>Fig. 5.4(a):</b>	Comparative plot of Transfer characteristics for SPE GaSb/Si HJ VTFET and SPE Ge/Si HJ VTFET	<b>132</b>
<b>Fig. 5.4(b):</b>	Comparative plot of Transconductance ( $g_m$ ) for SPE GaSb/Si HJ VTFET and SPE Ge/Si HJ VTFET	<b>132</b>
<b>Fig. 5.5(a):</b>	Comparative plot of intrinsic gate to drain capacitance ( $C_{gd}$ ) for SPE GaSb/Si HJ VTFET and SPE Ge/Si HJ VTFET	<b>134</b>
<b>Fig. 5.5(b):</b>	Comparative plot of intrinsic gate to source capacitance ( $C_{gs}$ ) for SPE GaSb/Si HJ VTFET and SPE Ge/Si HJ VTFET	<b>134</b>
<b>Fig. 5.6(a):</b>	Comparative plot of cut-off frequency for SPE GaSb/Si HJ VTFET and SPE Ge/Si HJ VTFET	<b>135</b>
<b>Fig. 5.6(b):</b>	Comparative plot of Transconductance generation factor (TGF) for	<b>135</b>

SPE GaSb/Si HJ VTFET and SPE Ge/Si HJ VTFET		
<b>Fig. 5.7(a):</b>	Butterfly curve to calculate static noise margin (SNM) of the inverter based on SPE GaSb/Si HJ VTFET	<b>137</b>
<b>Fig. 5.7(b):</b>	Butterfly curve to calculate static noise margin (SNM) of the inverter based on SPE Ge/Si HJ VTFET	<b>137</b>
<b>Fig. 5.8(a):</b>	Comparative plot of inverter transient response for SPE GaSb/Si HJ VTFET	<b>138</b>
<b>Fig. 5.8(b):</b>	Comparative plot of inverter transient response for SPE Ge/Si HJ VTFET	<b>138</b>
<b>Fig. 5.9(a):</b>	Comparative plot of read static noise margin (RSNM) for SPE Ge/Si HJ VTFET and SPE GaSb/Si HJ VTFET	<b>140</b>
<b>Fig. 5.9(b):</b>	Comparative plot of write margin for SPE Ge/Si HJ VTFET and SPE GaSb/Si HJ VTFET	<b>140</b>
<b>Fig. 5.10(a):</b>	Comparative plot of read delay for SPE Ge/Si HJ VTFET and SPE GaSb/Si HJ VTFET	<b>141</b>
<b>Fig. 5.10(b):</b>	Comparative plot of write delay for SPE Ge/Si HJ VTFET and SPE GaSb/Si HJ VTFET	<b>141</b>

## LIST OF TABLES

---

<b>Table 1.1:</b>	Different Parameters of the used Materials for Heterojunctions in TFETs	<b>25</b>
<b>Table 1.2:</b>	TFETs Based Circuit Level Simulations	<b>43</b>
<b>Table 2.1:</b>	Different Parameters of the Proposed GaSb/Si Heterojunction Vertical TFET	<b>57</b>
<b>Table 2.2:</b>	Comparison of Different DC/RF Parameters of the Proposed Heterojunction Vertical TFETs with some References	<b>73</b>
<b>Table 2.3:</b>	Device Parameters with Optimized Value for the Presented Vertical TFETs	<b>76</b>
<b>Table 2.4:</b>	Comparison of Device Level Performance Parameters for the Presented VTFETs	<b>85</b>
<b>Table 3.1:</b>	Device Design Parameters of the Source Pocket Engineered GaSb/Si Heterojunction Vertical TFETs with and Without Gate Oxide Stacking	<b>92</b>
<b>Table 3.2:</b>	Different Analog/RF Performance Parameters Comparison of the Presented GaSb/Si Vertical TFETs With Lateral, Vertical and Homogeneous Gate Oxide Stacking	<b>107</b>
<b>Table 4.1:</b>	Comparison of Different 8T SRAM Performance Parameters of SPE GaSb/Si HJ VTFET, SPE GaSb/Si HJ VTFET with VS, and SPE GaSb/Si HJ VTFET with LS	<b>122</b>
<b>Table 5.1:</b>	Device Design Parameters of the SPE GaSb/Si HJ VTFET And SPE Ge/Si HJ VTFET	<b>128</b>
<b>Table 5.2:</b>	Different DC Parameters of the VTFETs Under Study	<b>133</b>

