
List of Figures

Figure No.	Caption of Figures	Page No.
Fig. 1.1:	Geometry of microstrip patch antenna.	3
Fig. 1.2:	Inverted-F antenna geometry.	5
Fig. 1.3:	Basic layout of the planar inverted-F antenna.	6
Fig. 1.4:	Schematic of planar inverted-F antenna.	7
Fig. 1.5:	Quarter wavelength monopole antenna.	9
Fig. 3.1:	The configuration of the proposed antenna with fabricated prototype.	35
Fig. 3.2:	Detail dimensions of the proposed antenna.	35
Fig. 3.3:	Variation of reflection coefficient with frequency for different configurations.	36
Fig. 3.4:	Variation of reflection coefficient with frequency for l_1 .	39
Fig. 3.5:	Variation of reflection coefficient with frequency for l_3 .	39
Fig. 3.6:	Variation of reflection coefficient with frequency for l_4 .	40
Fig. 3.7:	Variation of reflection coefficient with frequency for x .	40
Fig. 3.8:	Variation of reflection coefficient with frequency for w_f .	42
Fig. 3.9:	Variation of reflection coefficient with frequency for h .	42
Fig. 3.10:	Variation of reflection coefficient with frequency for width w_s .	43
Fig. 3.11:	Variation of reflection coefficient with frequency for width w_2 .	43
Fig. 3.12:	Variation of reflection coefficient with frequency for width w_4 .	44
Fig. 3.13:	Variation of reflection coefficient with frequency for width w .	44
Fig. 3.14:	Variation of reflection coefficient of the proposed antenna.	45
Fig. 3.15:	Surface current distributions of proposed antenna at different frequencies.	47
Fig. 3.16:	The radiation patterns of proposed antenna at different frequencies.	48

Fig. 3.17:	Variation of peak realized gain and total radiation efficiency.	49
Fig. 3.18:	Antenna in mobile environment.	50
Fig. 3.19:	Effect of mobile environment on S-parameters.	51
Fig. 4.1:	Configuration of proposed antenna, (a) Configuration along with fabricated prototype and (b) Detail dimensions of the antenna element.	54
Fig. 4.2:	Effect of different configuration on reflection coefficient	55
Fig. 4.3:	Variation of reflection coefficient with frequency for length L_1 .	58
Fig. 4.4:	Variation of reflection coefficient with frequency for width W_2 .	58
Fig. 4.5:	Variation of reflection coefficient with frequency for width W_3 .	59
Fig. 4.6:	Variation of reflection coefficient with frequency for width W_4 .	59
Fig. 4.7:	Variation of reflection coefficient with frequency for X .	60
Fig. 4.8:	Variation of reflection coefficient with frequency for length l_s .	60
Fig. 4.9:	Simulated and measured reflection coefficient of the proposed antenna.	61
Fig. 4.10:	Surface current distributions at different frequencies.	63
Fig. 4.11:	Measured radiation patterns at different frequencies.	64
Fig. 4.12:	Variation of measured peak realized gain and calculated total radiation efficiency with frequency.	65
Fig. 4.13:	Antenna in mobile environment.	66
Fig. 4.14:	Effect of mobile environment on S-parameters.	67
Fig. 5.1:	(a) Front and rear view of the proposed antenna, (b) Details of front side radiating element (c) Details of rear side parasitic meandered strip.	71
Fig. 5.2:	The variation of the reflection coefficient with frequency for different configurations during evolution.	72
Fig. 5.3:	Simulated and measured reflection coefficient	74

Fig. 5.4:	Variation of the reflection coefficient with shape parameter ‘ s ’.	76
Fig. 5.5:	Variation of the reflection coefficient with shape parameter ‘ L_{s2} ’.	76
Fig. 5.6:	Variation of the reflection coefficient with shape parameter ‘ M_y ’.	77
Fig. 5.7:	Variation of the reflection coefficient with shape parameter ‘ d ’.	77
Fig. 5.8:	Vector surface current distribution at different frequencies.	79
Fig. 5.9:	Simulated and measured radiation patterns.	80
Fig. 5.10:	Variation of peak realized gain and total efficiency with frequency.	81
Fig. 5.11:	Antenna in mobile environment	82
Fig. 5.12:	Effect of mobile environment on S -parameters.	82
Fig. 6.1:	Model and antenna position (a) SAM head and PDA hand (Talk mode) (b) PDA hand (Data mode) (c) Dual hand (Read mode).	85
Fig. 6.2:	Variation of S -parameters of Antenna 1 in user proximity; (a) Antenna at top position, (b) Antenna at bottom position.	87
Fig. 6.3:	Variation of S -parameters of Antenna 2 in user proximity; (a) Antenna at top position, (b) Antenna at bottom position.	88
Fig. 6.4:	Variation of S -parameters of Antenna 3 in user proximity; (a) Antenna at top position, (b) Antenna at bottom position.	89
Fig. 6.5:	Variation of peak realized gain of Antenna 1 in user proximity; (a) Antenna at top position, (b) Antenna at bottom position.	91
Fig. 6.6:	Variation of peak realized gain of Antenna 2 in user proximity; (a) Antenna at top position, (b) Antenna at bottom position.	92
Fig. 6.7:	Variation of peak realized gain of Antenna 3 in user proximity; (a) When antenna at top position, (b) When antenna at bottom position.	93
Fig. 6.8:	Variation of total radiation efficiency of Antenna 1 in user	94

- proximity; (a) Antenna at top position, (b) Antenna at bottom position.
- Fig. 6.9:** Variation of total radiation efficiency of Antenna 2 in user proximity; (a) Antenna at top position, (b) Antenna at bottom position. **95**
- Fig. 6.10:** Variation of total radiation efficiency of Antenna 3 in user proximity; (a) Antenna at top position, (b) Antenna at bottom position. **96**