

References

- [1] E. I. Administration, “International Energy outlook”, Sept. 2019
- [2] <https://www.eia.gov/outlooks/ieo/pdf/ieo2019.pdf>
- [3] F. MAacdonald, “Renewable Energy Officially Just Overtook Fossil Fuels”, <https://www.sciencealert.com/renewable-energy-officially-just-overtook-fossil-fuels>.
- [4] G. Masson and I. Kaizuka, “ Trends in photovoltaics Applications”, IEA PVPS,2019; https://iea-pvps.org/wp-content/uploads/2020/11/IEA_PVPS_Trends_Report_2020-1.pdf
- [5] C. S. Solanki, Solar Photovoltaics: *Fundamentals, Technologies and Applications*. PHI Learning Pvt. Ltd., 2015.
- [6] H. Lee, J. Suk, H. Kim, J. Kim, J. Song, D.S. Jeong, J.K. Park, W.M. Kim, D.K. Lee, K. J. Choi, B.K Ju, T.S. Lee, I. kim, “*Enhanced efficiency of crystalline Si solar cells based on kerfless-thin wafers with nanohole arrays*”, *Nat. Sci Rep* 8, 3504 (2018), doi:- 10.1038/s41598-018-21381-2.
- [7] J. Shin, J. Park, N. Park, “A method to recycle silicon wafer from end-of-life photovoltaic module and solar panels by using recycled silicon wafers”, *Sol. Energy Mater. Sol. Cells*, 162 (2017), doi:- 10.1016/j.solmat.2016.12.038.
- [8] M.Woodhouse, B. Smith, A. Ramdas, R. Margolis. “Crystalline Silicon Photovoltaic Module Manufacturing Costs and Sustainable Pricing: 1H 2018 Benchmark and Cost Reduction Road Map”, *Nat. Rene. Energy Lab.*, <https://www.nrel.gov/docs/fy19osti/72134.pdf>.
- [9] M.M. ;Lunardi, J.P.A.Gaitan, J.I. Bilbao, R.Corkish, "A review of recycling processes for photovoltaic modules." *Solar Panels and Photovoltaic Materials* (2018), doi:- 10.5772/intechopen.74390
- [10] A. Kumar and S. N. Melkote, “Diamond Wire Sawing of Solar Silicon Wafers: A Sustainable Manufacturing Alternative to Loose Abrasive Slurry Sawing”,*Proc. Manufac.*, 21 (2018), doi:- 10.1016/j.promfg.2018.02.156
- [11] R. Santbergen and R. J. C Zolingen, “The absorption factor of crystalline silicon PV cells: A numerical and experimental study”, *Sol. Energy Mater. Sol. Cells* 92 (2008), doi:- <https://doi.org/10.1016/j.solmat.2007.10.005>.
- [12] B. Hoex, J. Schmidt, R.Bock, “Excellent passivation of highly doped p-type Si surface by the negative-charge-dielectric Al₂O₃”, *Appl. Phys. lett.*, 91 (2007) doi:- 10.1063/1.2784168.
- [13] M. Z. M. Rahman and S. I. Khan, “Advances in surface passivation of c-Si solar cell”, *Mater. Renew. Sustain. Energy*, 1 (2012) doi:- <https://doi.org/10.1007/s40243-012-0001-y>.
- [14] S. Morawiec, M.J. Mendes, F. Priolo, I. Crupi, “Plasmonic nanostructures for light trapping in thin-film solar cells”, *Mat. Sci. Sem. Process.* 92 (2019) doi:- 10.1016/j.mssp.2018.04.035.
- [15] H. D. Omar, M.R. Hashim, M.Z. Pakhuruddin, “Ray tracing of inverted pyramids for light trapping in thin crystalline silicon for solar cells”, *Optik* 219 (2020) doi:- 10.1016/j.ijleo.2020.165279.
- [16] X. Sheng, L.Z. Broderick, L.C. Kimerling, “Photonic crystal structures for light trapping in thin-film Si solar cells: Modelling, process and optimizations”, 314 (2014) doi:- 10.1016/j.optcom.2013.07.085.
- [17] W. Shockley and H. J. Queisser, “Detailed Balance Limit of Efficiency of pn Junction Solar Cells”, *J. Appl. Phys.* 510 (1961),doi:- <https://doi.org/10.1063/1.1736034>
- [18] Edition N 2018 International Technology Roadmap for Roadmap for Photovoltaic-Results 2017 including maturity report 2018 *Ninth Ed.*
- [19] S. W. Glunz , F. Feldmann, “ SiO₂ surface passivation layers- a key technology for silicon solar cells”, *Sol. Energy Mater. Sol. Cells*,185 (2018) doi:-10.1016/j.solmat.2018.04.029.

- [20] R. S. Bonilla, B. Hoex, P. Hamer, p.R. Wilshaw, “Dielectric surface passivation for silicon solar cells: A review”, *Phys. status solidi A* 214 (2017) doi:- 10.1002/pssa.201700293.
- [21] F. Lin, B. Hoex, Y.H. Koh, J.J Lin, A.G. Aberle, “Low-temperature Surface Passivation of Moderately Doped Crystalline Silicon by Atomic-layer-deposited Hafnium Oxide Film”, *Energy Proc.*, 15 (2012) doi:- 10.1016/j.egypro.2012.02.010
- [22] A. B. Gougam, B. Rajab, A.B. Afif, “Investigation of c-Si surface passivation using thermal ALD deposited HfO₂ films”, *Mat. Sci. Sem. Proc.*, 95 (2019) doi:- <https://doi.org/10.1016/j.mssp.2019.02.012>
- [23] J. Schmidt, A. Merkle, R. Brendel, B. Hoex, M.C.M. Van.de Sanden, W.M.M. Kessels, “surface passivation of high-efficiency solar cells by atomic-layer- deposited Al₂O₃ ”, *Prog. Photov.*, 16 (2008) doi:- 10.1002/pip.823.
- [24] F. Werner, W. Stals, R. Gortzen, B. Veith, R. Brendel, J. Schmdit, “High-rate atomic layer deposition of Al₂O₃ for the surface passivation of Si solar cells”, *Eng. Procedia*, 8 (2011) doi:- 10.1016/j.egypro.2011.06.140.
- [25] X. M. Song, M. Gao, Z.G. Huang, B.C. Han, Y.Z. Wan, Q.Y. Lei, Z.Q. Ma, “Interface properties of ITO/n-Si heterojunction solar cell: Quantum tunnelling, passivation and hole selective contacts”, *Sol. Energy*, 173 (2018) doi:- 10.1016/j.solener.2018.07.083
- [26] M. Rudzikas, A. Setkus, M. Stange, J. Ulbikas, A. ulyashin , “Simple interference based colorization of Si based solar cells and panels with ITO/SiNx:H double layer antireflective coatings”, *Sol. Energy*, 207 (2020) doi:- <https://doi.org/10.1016/j.solener.2020.06.091>.
- [27] X. Cheng , E.S. Marstein, H. Haug, M.D. Sabatino, “Double layers of ultrathin a-Si:H and SiNx for surface passivation of n-type crystalline Si wafer”, *Energy Proc.*, 92 (2016) doi:- 10.1016/j.egypro.2016.07.094.
- [28] E. Kim, Y. Cho, A. Sohn, D.W. Kim, H.H. Park, J.Kim, “Surface photovoltage characterizations of Si nanopillar arrays for verifying field-effect passivation using a SiNx layer”, *Curr. Appl. Phy.* 16 (2016) doi:- 10.1016/j.cap.2015.11.006.
- [29] H. Huang, C. Modanese, S. Sun, G. Gastrow, J. Wang, T.P. Pasanen, S. Li, L.Wang, Y. Bao, Z. Zhu, S. Sneek, H. Savin, “Effective passivation of p⁺ and n⁺ emitters using SiO₂/Al₂O₃/SiNx stacks: Surface passivation mechanisms and application to industrial p-PERT bifacial Si solar cells”, *Sol. Energy Mater. Sol. Cells*, 186 (2018) doi:- 10.1016/j.solmat.2018.07.007.
- [30] S. Li, N. Yang, X. Yuan, C. Liu, X. Ye, H.Li, “Hydrogen induced interface passivation in atomic layer deposited Al₂O₃ films and Al₂O₃/SiO₂ stacks”, *Mat. Sci. Sem. Process.*, 83 (2018) doi:- 10.1016/j.mssp.2018.04.031
- [31] P. K Hurley, K. Cherkaoui, S.Mcdonwell, G. Hughes, A.W. Groenland, “Characterization and passivation of interface defects in (100)-Si/SiO₂/HfO₂/TiN gate stacks”, *Micro. Elect. Reliab.*, 47(2007) doi:- 10.1016/j.microrel.2006.09.030.
- [32] J. Benick, K. Zimmermann, J. Spiegelman, M. Hermle, S. W. Glunz, “ Rear side passivation of PERC-type solar cells by wet oxides grown from purified steam”, *Prog. Photov.: Res. Appl.*, 19 (2011) doi:- 10.1002/pip.1020.
- [33] M. L. Reed, J.D. Plummer, “Chemistry of Si-SiO₂ interface trap annealing”, *J. Appl. Phys.* 63 (1988) doi:- 10.1063/1.340317.
- [34] W. D. Eades, R.M. Swanson, “Calculation of surface generation and recombination velocities at the Si-SiO₂ interface”, *J. Appl. Phys.*, 58 (1985) doi:- 10.1063/1.335562.
- [35] M. J Kerr, A. Cuevas, “Recombination at the interface between silicon and stoichiometric plasma silicon nitride”, *Sem. Sci. Tech.* 17 (2002), doi:- 10.1088/0268-1242/17/2/314/

- [36] O. Schultz, A. Mette, M. Hermle, S.W. Glunz, “Thermal oxidation for crystalline solar cells exceeding 19% efficiency applying industrially feasible process technology”, *Prog. Photov* 16 (2008) doi:- 10.1002/pip.814.
- [37] G. Santana , A.M.Acevedo, “Optimization of PECVD SiNx:H films for silicon solar cells”, *Sol. Energy Mater. Sol. Cells*, 60 (2000) doi:- 10.1016/S0927-0248(99)00078-1
- [38] S. Dauwe, L. Mittelstadt, A. Metz, R. Hezel, “Experimental evidence of parasitic shunting in silicon nitride rear surface passivated solar cells”, *Prog. Photov.*, 10 (2002), doi:- 10.1002/pip.420.
- [39] M. I. Bertoni, S. Hudelson, B.K. Newman, D.P. Fenning, “Influence of defect type on hydrogen passivation efficiency in multicrystalline silicon solar cells”, *Prog. Photov.*, 19 (2011) doi:- <https://doi.org/10.1002/pip.1008>.
- [40] W. Warren, J. Kanicki, J. Robertson, E.H. Poindexter, P.J.McWnorter, “Electron paramagnetic resonance investigation of charge trapping centres in amorphous silicon nitride films”, *J. Appl. Phys.* 74 (1993)doi:- 10.1063/1.355315
- [41] H. Mackel, R. Ludemann, “ Detailed study of the composition of the hydrogen generated SiNx layers for high-quality silicon surface passivation”, *J. Appl. Phys.* 92 (2002) doi:- <https://doi.org/10.1063/1.1495529>.
- [42] J. Benick, A. Richter, M. Hermle, S.W.Glunz, “Thermal stability of the Al₂O₃ passivation on p-type silicon surfaces for solar cell applications”, *Phys. Status Solidi RRL*, 3 (2009) doi:- 10.1002/pssr.200903209
- [43] G. Dingemans, P. Engelhart, R. Seguin, W.M.M.Kessels , “Comparison between Al₂O₃ surface passivation films deposited with thermal ALD, plasma ALD and PECVD”, 35th IEEE PVSC, Honolulu, Hawaii (2010)doi:- 10.1109/PVSC.2010.5614508
- [44] H. Hang, J. Lv, Y. Bao, R. Xuan, S. Sun, S. Sneek, J. Zhao, “20.8% industrial PERC solar cell: ALD Al₂O₃ rear surface passivation, efficiency loss mechanisms analysis and roadmap to 24%”, *Sol. Energy Mater. Sol. Cells*, 161 (2017) doi:- 10.1016/j.solmat.2016.11.018
- [45] J. Benick, B. Hoex, M.C.M Van de Sande, S.W.Glunz, “High efficiency n- type Si solar cells on Al₂O₃- passivated boron emitters” *Appl. Phys. Lett.* 92 (2008)doi:- 10.1063/1.2945287
- [46] A M. Green, "The path to 25% silicon solar cell efficiency: History of silicon cell evolution." *Progress in Photovoltaics: Research and Applications* 17.3 (2009): 183-189.doi:- 10.1002/pip.892.
- [47] A. Morato, B. Vermany, H. Goverde, E. Cornagli, “Electrical characterization of ALD Al₂O₃-HfO₂ and PECVD Al₂O₃ passivation layers for p-type CZ-silicon PERC solar cells”, In *Photovoltaic Specialists Conference (PVSC) 2012* 38th IEEE (2012) doi:- 10.1109/PVSC.2012.6317790
- [48] H. Geng , T. Lin, A.J. Letha, H.L.Hwang, F.A. Kyznetsov, V.V. kaichev, “Advanced passivation techniques for Si solar cells with high –K dielectric materials”, *Appl. Phys. Lett.* 105 (2014) doi:- <https://doi.org/10.1063/1.4896619>
- [49] A. S. Foster, F.L. Gejo, A.L. Shluger, R.M. Nieminen, “Vacancy and interstitial defects in hafnia”, *Phys. Rev. B*, 65 (2002) doi:- 10.1103/PhysRevB.65.174117
- [50] J. L. Gavartin, G. Bersuker, B.H. Lee, “Negative oxygen vacancies in HfO₂ as charge traps in high-k stacks”, *Appl. Phys. Lett.* 89 (2006) doi:- 10.1063/1.2236466.
- [51] D. k. Simon, P.M. Jordan, I. Dirnstofer, F. Benner, C. Richter, T. Mikolajick, “Symmetrical Al₂O₃-based passivation layers for p- and n- type silicon”, *Sol. Energy Mater. Sol. Cells*, 131 (2014) doi:- 10.1016/j.solmat.2014.06.005.
- [52] B. W. H Van de loo, H.C.M. Knoop, G. Dingemans, G.J.M. Janssen, M.W.P.E. Lamers, I.G. Romijn, A.W. Weeber, W.M.M. Kessels, “ Zero charge SiO₂/Al₂O₃ stacks for the simultaneous passivation of n⁺ and p⁺ doped silicon surface by atomic layer deposition” 143 (2015)”, *Sol. Energy Mater. Sol. Cells*, doi:- 10.1016/j.solmat.2015.07.040.

- [53] Y. Liu, P. Stradins, H. Deng, J. Luo, S.H. Wei, "Suppress carrier recombination by introducing defects: The case of Si solar cell", *Appl. Phys. Lett.* 108 (2016) doi:- 10.1063/1.4939628.
- [54] R. Williams, "Becquerel photovoltaic effect in binary compounds" *J. Chem. Phys.* 32 (1960) doi:- <https://doi.org/10.1063/1.1730950>
- [55] H. N. Draper. "Effect of light on the electric conductivity of Selenium", *Nat.* 7 (1873) doi:- <https://doi.org/10.1038/007340e0>.
- [56] D. M. Chapin, C.S. Fuller, G.L. Pearson, "A new silicon p-n junction photocell for converting solar radiation into electrical power", *J. Appl. Phys.* 25 (1954) doi:- 10.1063/1.1721711.
- [57] G. Pearson, "P V founders award luncheon", in conference Record, 18th IEEE Photov. Specialists Conf. Las Vegas, IEEE New York (1985).
- [58] M. A Green, "Silicon solar cells: Evolution, high-efficiency design and efficiency enhancements", *Sem. Sci. Tech.* 8 (1993) doi:- <http://iopscience.iop.org/0268-1242/8/1/001>
- [59] J. Mandelkorn, C. McAfee, J. Kesperis, L. Schwartz, W. Pharo, "Fabrication and characterization of phosphorous-diffused silicon solar cells" *J. Elect. Chem. Soc.* 109 (1962).
- [60] M. A Green, "The path to 25% silicon solar cell efficiency: History of silicon cell evolution", *Prog. Photovolt: Res. Appl.*, 17 (2009) doi:- 10.1002/pip.892.
- [61] B. Du, R. Yang, Y. He, F. Wang, S.Huang, "Nondestructive inspection, testing and evaluation for Si-based, thin film and multi-junction solar cells: An overview" *Ren. Sus. Energ. Rev.* 78 (2017) doi:- 10.1016/j.rser.2017.05.017.
- [62] J. Ramanujam, D.M. Bishop, T.K.Todorov, O. Gunawan, J. Rath, R. Nekovei, E. Argeian,, "Flexible CIGS, CdTe and a-Si:H based thin film solar cells: A review", *Prog. Mat. Sci.*, 110 (2020) doi:- <https://doi.org/10.1016/j.pmatsci.2019.100619>
- [63] H. S. Kim, K.B. Yoon, "Preparation and characterization of CdS and PbS quantum dots in Zeolite Y and their applications for nonlinear optical materials and solar cell", *Cord. Chem. Rev.* 263 (2014) doi:- <https://doi.org/10.1016/j.ccr.2013.12.001>
- [64] S. Essig, K.B. Yoon, S. Ward, M.A. Steiner, D.J. Friedman, J.F. Geisz, P. Stradins, D.L. Young, "Progress towards a 30% efficient GaInP/Si Tandem Solar cell", *Energy Proc.* 77 (2015) doi:- <https://doi.org/10.1016/j.egypro.2015.07.066>
- [65] X. Liu, H. Chem, S. Tan, "Overview of high-efficiency organic photovoltaic materials and devices", *Ren. Sust. Ener. Rev.* 52 (2015) doi:- <https://doi.org/10.1016/j.rser.2015.08.032>
- [66] W. Qi, X. Zhou, J. Li, J. Cheng, Y. Li, M.J. Ko, Y. Zhao, X. Zhang, "Inorganic material passivation of defects towards efficient perovskite solar cells", *Science Bull.* 65 (23)(2020) doi:- 10.1016/j.scib.2020.07.017.
- [67] M. Wright, A. uddin, "Organic-Inorganic hybrid solar cells: A comparative review", *Sol. Energy Mater. Sol. Cells*, 107 (2012) doi:- <https://doi.org/10.1016/j.solmat.2012.07.006>.
- [68] M. K. Assadi, S. Bakhoda, R. Saidur, H. Hanaei, "Recent progress in perovskite solar cells", *Ren. Sust. Ener. Rev.*, 81 (2018) doi:- <https://doi.org/10.1016/j.rser.2017.06.088>.
- [69] V.V. Tyagi, N.A.A. Rahim, N. A Rahim, J.A Selvaraj, "Progress in solar PV technology: Research and achievement", *Ren. and Sust. Energy Rev.*, 20 (2013) doi:- 10.1016/j.rser.2012.09.028.
- [70] M. Zalas, B. Gierczyk, M. Klein, K. Siuzdak, T. Pedzinski, T. Luczak, "Synthesis of a novel dinuclear ruthenium polypyridine dye for dye-sensitized solar cell application", *Polyhedron* 67 (2014) doi:- 10.1016/j.poly.2013.09.023.
- [71] B. Pandit, B.R. Gautam, T.P. Basel, Z.V. Vardeny, "Correlation between ultrafast transient photo modulation spectroscopy and organic photovoltaic solar cell efficiency based on RR-P3HT/PCBM blends", *Org. Elect.* 15 (2014) doi:- 10.1016/j.orgel.2014.03.021.

- [72] H. Beygi, S.A. Sajjadi, A. Babakhani, J.F. Young, F.C.J.M. Vanveggel, "Air exposure oxidation and photo oxidation of solution-phase treated PbS quantum dot thin films and solar cells", *Sol. Energy Mater. Sol. Cells*, 203 (2019) doi:- 10.1016/j.solmat.2019.110163.
- [73] J. W. Xiao, S. Ma, S. Yu, C. Zhou, P. Liu, Y. Chen, H. Zhou, Y. Li, Q. Chen, "ligand engineering on CdTe quantum dots in perovskite solar cells for suppressed hysteresis" *Nano Energ.* 46 (2018) doi:- 10.1016/j.nanoen.2018.01.035.
- [74] J. Su, D.P. Chen, C.J. Lin, "Growth of large CH₃NH₃PbX₃ (X= I, Br) single crystals in solution", *J. Crys. Growth* 422 (2015) doi:- 10.1016/j.jcrysgro.2015.04.029.
- [75] M. A. Green, "Crystalline and thin-film silicon solar cells: State of the art and future potential", *Sol. Energy* 74 (2003) doi:- 10.1016/S0038-092X(03)00187-7.
- [76] J. Zhao, A. Wang, M.A. Green, "19.8% efficient 'honeycomb' textured multicrystalline and 24.4% monocrystalline silicon solar cells", *Appl. Phys. Lett.* 73 (1998) doi:- 10.1063/1.122345.
- [77] G. Dingemans, "Nanolayer surface passivation scheme for silicon solar cells", Tilburg: PhD Thesis (2011) doi:- 10.6100/IR719798.
- [78] R. Ren ,Z. Zhong "Enhanced light absorption of silicon solar cell with dielectric nanostructured back reflector", 417 (2018) doi:- 10.1016/j.optcom.2018.02.051.
- [79] J. Yan,X. Liu, C. Ma, Y. Huang, G. Yang, "All- Dielectric materials and related nanophotonic applications", *Mat. Sci. Engg. R:Report* 141 (2020) doi:- 10.1016/j.mser.2020.100563.
- [80] C. Wu, K. Wang, M. Batmunkh, A.S.R. Bati, D. Yang, Y. Jiang, Y. Hou, J.G. Shapter, S. Priya, "Multifunctional nanostructured materials for next generation photovoltaics", *Nano Energy* 70 (2020) doi:- 10.1016/j.nanoen.2020.104480.
- [81] B. Kumaragurubaran , S. Anandhi, "Reduction of Reflection losses in solar cell using Anti-reflective coating" *Int. Conference ICCPEIC Chennai* (2014) doi:- 10.1109/ICCPEIC.2014.6915357.
- [82] H. Ghosh, S. Mitra, H. Saha, S.K. Datta, C. Banerjee, "Argon plasma treatment of silicon nitride (SiN_x) for improved antireflection coating on c-Si solar cells", *Mat. Sci. Engg.:B* 215 (2017) doi: <https://doi.org/10.1016/j.mseb.2016.11.003>
- [83] M. F stuckings ,A. W. Blakers, "A study of shading and resistive loss from the fingers of encapsulated solar cells", *Sol. Energy Mater. Sol. Cells*, 59 (1999) doi:- [https://doi.org/10.1016/S0927-0248\(99\)00024-0](https://doi.org/10.1016/S0927-0248(99)00024-0)
- [84] Z. Xi, D. Yang, W. Dan, C. Jun, X. Li, D. Que, "Investigation of texturization for monocrystalline silicon solar cells with different kind of alkaline" *Ren. Energy* 29 (2004) doi:- 10.1016/j.renene.2004.03.003.
- [85] E. Vazsonyia, D. Yang, W. Dan, C. Jun, X. Li, D. Que, "Improved anisotropic etching process for industrial texturing of silicon solar cells" *Sol. Energy Mater. Sol. Cells*, 57 (1999) doi:- 10.1016/S0927-0248(98)00180-9
- [86] P. K. Basu, R.M. Pujahari, H. Kaur, D. Singh, D. Varandani, B.R. Mehta, "Impact of surface roughness on the electrical parameters of industrial high efficiency NaOH-NaOCl textured multicrystalline silicon solar cell", *Sol. Energy* 84 (2010) doi:- 10.1016/j.solener.2010.06.001
- [87] M. Ju , M. Gunasekaran, K. Kim, K. Han, I. Moon, K. Lee, S. Han, T. Kwon, D. Kyung, J. Yi , "A new vapour texturing method formulticrystalline silicon solar cell applications" *Mat. Sci. Engg.:B* 153 (2008), doi:- <https://doi.org/10.1016/j.mseb.2008.10.030>
- [88] F. Chen, L. Wang, "light trapping design in silicon-based solar cells "In solar cells-silicon wafer-based technologies, Book chapter, (2011) doi:- 10.5772/20962.

- [89] C. Xiong, R. Yao, K. Gen, “Two low reflectance of triple-layer broadband antireflecting coating for silicon solar cells” IEEE International Conference on Solid-State and Integrated Circuit Technology (2010) doi:- 10.1109/ICSICT.2010.5667867.
- [90] K. H. Yang, J. Y. Yang, “The analysis of light trapping and internal quantum efficiency of a solar cell with DBR back reflector”, Sol. Energy 83 (2009) doi:- <https://doi.org/10.1016/j.solener.2009.08.003>.
- [91] Y. Zhang, C. K. Lim, Z. Dai, G. Yu, J.W. Haus, H. Zhang, P.N. Prasad, “Photonics and optoelectronics using nano-structured hybrid perovskite media and their optical cavities” Phys. reports 795 (2019) doi:- 10.1016/j.physrep.2019.01.005.
- [92] D. Sammito, P.Zilio, G. Zacco, J. Janusonis, F. Romanato, “Light trapping properties of metallic gratings on wafer-based silicon solar cells”, Nano Energy 2 (2013) doi:- 10.1016/j.nanoen.2012.10.008.
- [93] D. Derkacs, S.H. Lim,, “Improved performance of amorphous silicon solar cells via scattering from surface Plasmon polaritons in near by metallic nanoparticles”, Appl. Phys. Lett. 89 (2006) doi:- <https://doi.org/10.1063/1.2336629>
- [94] K. R. Catchpole, A. Polman, “Design principles for particles plasmons enhanced solar cells” Appl. Phys. Lett. 93 (2008) doi:- 10.1063/1.3021072
- [95] E. Moulin, J. Sukmanowski, P. Luo, R. Carius, F.X. Royer, H. Stiebig, “Improved light absorption in thin-film silicon solar cell by integration of silver nanoparticles” J. Non-Cryst. Sol. 354 (2008) doi:- 10.1016/j.jnoncrysol.2007.09.031.
- [96] B. Dale, Rudenberg, “ Photovoltaic conversion-high efficiency silicon solar cells:” Transitron Electronic Corporation, Reprinted from 14th annual proceedings, Sol. Energy 5 (1961) doi:- 10.1016/0038-092X(61)90076-7.
- [97] U. Gangopadhyay, S.K. Dutta, H. Saha, “Texturization and light trapping in silicon solar cells” Nova science Pub. (2009).
- [98] M. F Abdullah, H. Naser, N. Asim, S. Ahmadi, B. Yatim, K. sopian, “Research and development efforts on texturization to reduce the optical uses at front surface of silicon solar cell”, Renew. Sus. Energy Rev. 66 (2016) doi:- 10.1016/j.rser.2016.07.065
- [99] I. Zubel, “Silicon anisotropic etching in alkaline solutions III: On the possibility of spatial structures for forming in the course of Si(100) anisotropic etching in KOH and KOH+ IPA solutions” Sens. Act. A: Phys. 84 (2000) doi:- [https://doi.org/10.1016/S0924-4247\(99\)00347-7](https://doi.org/10.1016/S0924-4247(99)00347-7).
- [100] X. Liu, P.R. Coxon, M. Peters, B. Hoex, J.M. Cole, D.J. Fray, “Black Silicon: fabrication methods, properties and solar energy applications”, Energy Environ. Sci. 7 (2014) doi:- 10.1039/C4EE01152J
- [101] C. Wu, C.H. Crouch, L. Zhao, J.E. Carey, “Near-unity below-band-gap absorption by microstructured silicon”, Appl. Phys. Lett. 60 (2001) doi:- 10.1063/1.1358846
- [102] M. Halbwax, T. Sarnet, ph. Delaporte, m. Sentis, H. Etienne, F. Torregrosa, V. Vervisch, I. Perichaud, S. Martinuzzi, “Micro and nano-structuration of silicon by femtosecond laser: Application to silicon photovoltaic cells fabrication”, Thin Sol. Film 516 (2008) doi:- 10.1016/j.tsf.2007.12.117.
- [103] Y. T. Lu, A. R. Barron, “Anti-reflection layers fabricated by a one-step copper-assisted chemical etching with inverted pyramidal structures intermediate between texturing and nanopore-type black silicon” J. Mater. Chem. A 30 (2014) doi:- 10.1039/C4TA02006E.
- [104] Y. Zhang, N. Stokes, B. Jia, S. Fan, M. Gu, “Towards ultra-thin plasmonic silicon wafer solar cells with minimized efficiency loss”, Nat. Sci. Reports 4939 (2014) doi:- 10.1038/srep04939.
- [105] H. A. Atwar, A. Polmam, “Plasmonics for improved photovoltaic devices”, Nat. Mater. 9 (2010) doi:- <https://doi.org/10.1038/nmat2629>.

- [106] P. Spinelli, V.E. Ferry, J.V. de Groep, C.V. Lara, M.A. Verschuuren, r.E.I. Schropp, H.A. Atwater, A. Polman “Plasmonic light trapping in thin-film Si solar cells”, *J. Optics* 14 (2012) doi:- 10.1088/2040-8978/14/2/024002
- [107] F. Monticone and A. Alu, “Metamaterials and plasmonics: From nanoparticles to nanoantenna arrays, metasurfaces, and metamaterials”, *Chin. Phys. B* 23 (2014) doi:- 10.1088/1674-1056/23/4/047809.
- [108] A. Boltasseva, H. A. Atwater, “low-loss plasmonic metamaterials”, *Mat. Sci.* 21 (2011) doi:- 10.1126/science.1198258.
- [109] M. Kanehara, H. Koike, T. Y. Oshinaga, T. Teranishi, “Indium tin oxide nanoparticles with compositionally tunable surface plasmon resonance frequencies in the near IR region” *J. Am. Chem. Soc.* 131 (2009) doi:- <https://doi.org/10.1021/ja9064415>.
- [110] Z. Ouyang, S. Pillai, F. Beck, O. Kunz, S. Varlamov, K.R. Catchpole, P. Campbell, M.A. Green, “Effective light trapping in polycrystalline silicon thin-film solar cells by means of rear localized surface plasmon” *Appl. Phys. Lett.* 96 (2010) doi:-10.1063/1.3460288.
- [111] S. Das, A. Kundu, H. Saha, S.K. Datta, “Effect of embedding silica nanoparticles and voids in the performance of c-Si solar cells” *J. Renewable Sustainable Energy* 5 (2013) doi:- 10.1063/1.4807618.
- [112] M. R. Foreman, F. Vollmer, “Theory of resonance shifts of whispering gallery modes by arbitrary plasmonic nanoparticles” *New J. Physics* 15 (2013) doi:- 10.1088/1367-2630/15/8/083006.
- [113] D. J. Barber I. C. Freestone, “An investigation of the origin of the colour of the lycurgus cup by analytical transmission electron microscopy” 32 (1990) doi:- 10.1111/j.1475-4754.1990.tb01079x.
- [114] C. Zhang, Y. Xu, J. liu, J. Li, J. Xiang, H. Li, I. Li, Q. Dai, S. lan, A.E. Miroshnichenko, “Lighting up silicon nanoparticles with Mie resonances”, *Nat. Commun.* 9 (2018) doi:- 10.1038/s41467-018-05394-z.
- [115] <https://www.cntraveler.com/activities/london/st-pauls-cathedral>.
- [116] J. Gallium, D.M. Callahan, J.N. Munday, H.A. Atwater, “Arsenide Solar Cell Absorption Enhancement Using Whispering Gallery Modes of Dielectric Nanospheres” *IEEE J. Photovolt.* 2 (2012) doi:-10.1109/JPHOTOV.2011.2180512
- [117] E. Sachs, D. Harvey, R. Janoch, A. Anselmo, D. Miller, J.I. Hanoka, “string ribbon growth via the mesa crucible; multiple ribbons, inherent flatness stability and low materials and power consumption” 14th Workshop on Crystalline Silicon Solar Cells & Modules: Materials and Processes (1997).
- [118] R. L Wallace, J.I. Hanoka, S. Narasimha, S. Karma, A. Rohatgi, “Thin silicon string ribbon for high efficiency polycrystalline solar cells” In 26th photovoltaic solar conference, Anaheim (1997).
- [119] R. Niepelt, J. Hensen, V. steckenreiter, R. Brendel, S.K. Schroder, “Kerfless exfoliated thin crystalline Si wafers with Al metallization layers for solar cells” *J. Mat. Research* 30 (2015) doi:- 10.1557/jmr.2015.309.
- [120] K. Reinhardt, W. Kern, “Handbook of Semiconductor Wafer Cleaning Technology, New Jersey: Noyes” New Jersey: Noyes Publications (1993)
- [121] W. Kern, D. A. Puotinen, “Cleaning solutions based on hydrogen peroxide for use in silicon semiconductor technology” *RCA Rev.* 31 (1970).
- [123] Gudmundsson, Jon Tomas. "Physics and technology of magnetron sputtering discharges." *Plasma Sources Science and Technology* 29.11 (2020): 113001.

- [124] M. A. Green, A. Ho-Baillie, and H. J. Snaith, "The emergence of perovskite solar cells," *Nature Photonics*, vol. 8, no. 7, pp. 506–514, 2014.
- [125] Q. Yu, Y. Wang, Z. Yi, N. Zu, J. Zhang, M. Zhang, and P. Wang, "High-Efficiency dye-sensitized solar Cells: The influence of lithium ions on Exciton Dissociation, Charge recombination, and Surface States," *ACS Nano*, vol. 4, no. 10, pp. 6032–6038, 2010.
- [126] Q. Wang, Y. Xie, F. Soltani-Kordshuli, and M. Eslamian, "Progress in emerging solution-processed thin film solar cells – part I: Polymer solar cells," *Renewable and Sustainable Energy Reviews*, vol. 56, pp. 347–361, 2016.
- [127] M. Wright, A. Uddin, "Organic-inorganic hybrid solar cells: A comparative review", *Solar Energy Mat. Solar cells*, Vol. 107, pp. 87-111, 2012.
- [128] M. Lozac'h, S. Nunomura, H. Sai, and K. Matsubara, "Passivation property of ULTRATHIN SiOx:H / a-Si:H stack layers for solar cell applications," *Solar Energy Materials and Solar Cells*, vol. 185, pp. 8–15, 2018.
- [129] G. Limodio, G. Yang, H. Ge, P. Procel, Y. De Groot, L. Mazzarella, O. Isabella, and M. Zeman, "Front and rear contact si solar cells combining high and low thermal budget si passivating contacts," *Solar Energy Materials and Solar Cells*, vol. 194, pp. 28–35, 2019.
- [130] A. Inglese, J. Lindroos, and H. Savin, "Accelerated light-induced degradation for detecting copper contamination in p-type silicon," *Applied Physics Letters*, vol. 107, no. 5, p. 052101, 2015.
- [131] D. J. Curtin and R. L. Statler, "Review of radiation damage to silicon solar cells," *IEEE Transactions on Aerospace and Electronic Systems*, vol. AES-11, no. 4, pp. 499–513, 1975
- [132] H. Hashigami, Y. Itakura, and T. Saitoh, "Effect of illumination conditions on Czochralski-grown silicon solar cell degradation," *Journal of Applied Physics*, vol. 93, no. 7, pp. 4240–4245, 2003.
- [133] Y. Tsunomura, Y. Yoshimine, M. Taguchi, T. Baba, T. Kinoshita, H. Kanno, H. Sakata, E. Maruyama, and M. Tanaka, "Twenty-two percent efficiency HIT solar cell," *Solar Energy Materials and Solar Cells*, vol. 93, no. 6-7, pp. 670–673, 2009.
- [134] S. Nordmann, B. Berghoff, A. Hessel, B. Zielinsk, J. John, S. Starschich, and J. Knoch, "Record-high Solar-to-hydrogen conversion efficiency based on a monolithic All-silicon TRIPLE-JUNCTION IBC solar cell," *Solar Energy Materials and Solar Cells*, vol. 191, pp. 422–426, 2019.
- [135] P. Hamer, C. Chan, R. S. Bonilla, B. Hallam, G. Bourret-Sicotte, K. A. Collett, S. Wenham, and P. R. Wilshaw, "Hydrogen induced contact resistance in PERC solar cells," *Solar Energy Materials and Solar Cells*, vol. 184, pp. 91–97, 2018.
- [136] W. Shockley and H. J. Queisser, "Detailed balance limit of efficiency of p-n junction solar cells," *Journal of Applied Physics*, vol. 32, no. 3, pp. 510–519, 1961
- [137] A. B. Roy, A. Dhar, M. Choudhuri, S. Das, S. M. Hossain, and A. Kundu, "Black silicon solar cell: Analysis optimization and evolution towards a thinner and flexible future," *Nanotechnology*, vol. 27, no. 30, p. 305302, 2016.
- [138] L. Wang, J. Han, A. Lochtefeld, A. Gerger, M. Carroll, D. Stryker, S. Bengtson, M. Curtin, H. Li, Y. Yao, D. Lin, J. Ji, A. Lennon, R. Opila, A. Barnett, "16.8% Efficient ultra-thin silicon solar cells on steel," 28th European Photovoltaic Solar Energy Conference and Exhibition, France, pp.2641 – 2644, 2013.
- [139] I. Kuzma-Filipek, F. Dross, K. Baert, J.L. Hernandez, S. Singh, K.V. Nieuwenhuysen, J. Poortmans, ">16% thin-film epitaxial silicon solar cells on 70-cm² area with 30- μ m active layer, porous silicon back reflector, and Cu-based top-contact metallization," *Progress in Photovoltaics: Research and Applications*, vol. 20, no. 3, pp. 350–355, 2012.

- [140] M. Moslehi, P. Kapur, J. Kramer, V. Rana, S. Scutter, A. Deshpande, “Worldrecord, 20.6% efficiency 156mm_156mm full-square solar cells using low-cost kerfless ultrathin epitaxial silicon and porous silicon lift-off technology for industry leading high-performance smart PV modules,” PV Asia Pacific Conference (APVIA/PVAP), Oct 2012
- [141] <https://www.greentechmedia.com/articles/read/crystal-solar-vapor-to-wafer-to-cut-solar-costs#gs.r3z9xz>
- [142] <http://www.amberwave.com>.
- [143] S. Saha, E. U. Onyegam, D. Sarkar, M. M. Hilali, R. A. Rao, L. Mathew, D. Jawarani, D. Xu, R. S. Smith, U. K. Das, J. G. Fossum, and S. K. Banerjee, “Exfoliated $\sim 25\mu\text{m}$ Si Foil for Solar Cells with Improved Light-Trapping,” MRS Proceedings, vol. 1493, pp. 51–58, 2013.
- [144] M. M. Hilali, S. Saha, E. Onyegam, R. Rao, L. Mathew, and S. K. Banerjee, “Light trapping In Ultrathin 25 Mm EXFOLIATED Si solar cells,” Applied Optics, vol. 53, no. 27, p. 6140, 2014.
- [145] H.-S. Lee, J. Suk, H. Kim, J. Kim, J. Song, D. S. Jeong, J.-K. Park, W. M. Kim, D.-K. Lee, K. J. Choi, B.-K. Ju, T. S. Lee, and I. Kim, “Enhanced efficiency of crystalline si solar cells based on kerfless-thin wafers with nanohole arrays,” Scientific Reports, vol. 8, no. 1, 2018.
- [146] J.H. Petermann, D. Zielke, J. Schmidt, F. Haase, E.G. Rojas, R. Brendel, “19%-efficient and 43 μm -thick crystalline Si solar cell from layer transfer using porous silicon,” Progress in Photovoltaics: Research and Applications, Vol. 20, pp. 1-5, 2012.
- [147] Y. Yao, E. Brueckner, L. Li, and R. Nuzzo, “Fabrication and assembly of ultrathin high-efficiency silicon solar microcells integrating electrical passivation and anti-reflection coatings,” Energy & Environmental Science, vol. 6, no. 10, p. 3071, 2013.
- [148] M. C. Carotta, M. Merli, L. Passari, D. Palmeri, G. Martinelli, and R. Van Steenwinkel, “Effect of thickness and surface treatment on silicon water reflectance,” Solar Energy Materials and Solar Cells, vol. 27, no. 3, pp. 265–272, 1992.
- [149] D. Thorp, P. Campbell, and S. R. Wenham, “Conformal films for light-trapping in thin silicon solar cells,” Progress in Photovoltaics: Research and Applications, vol. 4, no. 3, pp. 205–224, 1996.
- [150] G. Das, S. Mandal, S. Dhar, P. B. Bhargav, C. Banerjee, S. Mukhopadhyay, and A. K. Barua, “Synthesis of ito nanoparticles at room temperature using plasma treatment process and use it as back reflector in a-Si flexible solar cell,” Surfaces and Interfaces, vol. 7, pp. 83–86, 2017.
- [151] R. M. Swanson, S. K. Beckwith, R. A. Crane, W. D. Eades, Young Hoon Kwark, R. A. Sinton, and S. E. Swirhun, “Point-contact silicon solar cells,” IEEE Transactions on Electron Devices, vol. 31, no. 5, pp. 661–664, 1984.
- [152] D. Das and L. Karmakar, “Further optimization of Ito films at the melting point of Sn and configuration Of OHMIC contact at the c-si/ito interface,” Applied Surface Science, vol. 481, pp. 16–24, 2019.
- [153] A. H. Le, V. A. Dao, D. P. Pham, S. Kim, S. Dutta, C. P. Thi Nguyen, Y. Lee, Y. Kim, and J. Yi, “Damage to PASSIVATION contact in silicon heterojunction solar cells by ITO SPUTTERING under various Plasma EXCITATION MODES,” Solar Energy Materials and Solar Cells, vol. 192, pp. 36–43, 2019.
- [154] H. Guo, K. Zhang, X. Jia, C. Ma, N. Yuan, and J. Ding, “Effect of ITO film deposition conditions ON Ito and CdS films of semiconductor solar cells,” Optik, vol. 140, pp. 322–330, 2017.
- [155] J. W. Wang, F. F. Luo, G. X. Ouyang, and Y. Shi, “Magnetic, optical and electrical properties of ito thin FILMS implanted by cobalt ions,” Nuclear Instruments and Methods in Physics

- Research Section B: Beam Interactions with Materials and Atoms, vol. 450, pp. 234–238, 2019.
- [156] H. Kobayashi, T. Ishida, Y. Nakato, and H. Tsubomura, “Mechanism of carrier transport in highly efficient solar cells having indium tin oxide/si junctions,” *Journal of Applied Physics*, vol. 69, no. 3, pp. 1736–1743, 1991.
- [157] F. Djeflal, H. Ferhati, A. Benhaya, and A. Bendjerad, “Effects of annealing temperature and its intermediate Thin-layer on electrical PROPERTIES OF Au/p-Si STRUCTURE deposited by Rf magnetron sputtering,” *Superlattices and Microstructures*, vol. 128, pp. 382–391, 2019.
- [158] Ferhati, F. Djeflal, and A. Benhaya, “Optimized high-performance ITO/Ag/ITO multilayer Transparent ELECTRODE deposited by Rf magnetron sputtering,” *Superlattices and Microstructures*, vol. 129, pp. 176–184, 2019.
- [159] K. P. Sabin, G. Srinivas, H. D. Shashikala, A. Dey, N. Sridhara, A. Kumar Sharma, and H. C. Barshilia, “Highly transparent and CONDUCTING ITO/Ag/ITO Multilayer thin films On FEP substrates for flexible electronics applications,” *Solar Energy Materials and Solar Cells*, vol. 172, pp. 277–284, 2017.
- [160] Y. Tawada, M. Kondo, H. Okamoto, Y. Hamakawa, “Hydrogenated amorphous silicon carbide as a window material for high efficiency a-Si solar cells”, *Sol. Energy Mater.*, 6 (1982) 299-315.
- [161] G. Das, S. Mandal, S. Dhar, S. Bose, J. R. Sharma, S. Mukhopadhyay, C. Banerjee, A. K. Barua, “Development of Improved n- μ c-SiOx:H Films and Its Innovative Application in Silicon-Based Single Junction Thin Film Solar Cells”, *IEEE J. Photovolt.*, 7 (2017) 892 – 899 doi: 10.1109/JPHOTOV.2017.2655721.
- [162] J-H Yang, S. Y. Myong, K S. Lim, “Improvement of Light Trapping in a-Si:H-Based Solar Cells by Inserting a ZnO/LiF Double Interlayer”, *IEEE Elect. Dev. Letters*, 35 (2014) 102 – 104 doi: 10.1109/LED.2013.2287885.
- [163] H. Keppner, J. Meier, P. Torres, D. Fischer and A. Shah, “Microcrystalline silicon and micromorph tandem solar cells”, *Applied Physics A*, 69 (1999) 169–177 doi: 10.1007/s003399900065.
- [164] M. Boccard, M. Despeisse, J. Escarre, X. Niquille, G. Bugnon, S. Hänni, M. Bonnet-Eymard, F. Meillaud, C. Ballif, “High-Stable-Efficiency Tandem Thin-Film Silicon Solar Cell With Low-Refractive-Index Silicon-Oxide Interlayer”, *IEEE J. Photovolt.*, 46 (2014) 1368 – 1373 doi: 10.1109/JPHOTOV.2014.2357495.
- [165] W. K. Metzger, S. Grover, D. Lu, E. Colegrove, J. Moseley, C. L. Perkins, X. Li, R. Mallick, W. Zhang, R. Malik, J. Kephart, C.-S. Jiang, D. Kuciauskas, D. S. Albin, M. M. Al-Jassim, G. Xiong & M. Gloeckler, “Exceeding 20% efficiency with in situ group V doping in polycrystalline CdTe solar cells”, *Nat. Energy*, 4 (2019) 837–845 doi: 10.1038/s41560-019-0446-7.
- [166] R. Kamada, T. Yagioka, S. Adachi, A. Handa, K. F. Tai, T. Kato, “H. Sugimoto, New world record Cu(In,Ga)(Se,S)₂ thin film solar cell efficiency beyond 22%”, *IEEE 43rd Photovoltaic Specialists Conf. (PVSC)*, Portland, (2016) 1287-129 doi: 10.1109/PVSC.2016.7749822.
- [167] Q. Qian Chu, B. Ding, J. Peng, H. Shen, X. Li, Y. Liu, C-X. Li, C-J. Li, G-J. Yang, T. P. White, K. R. Catchpole, “Highly stable carbon-based perovskite solar cell with a record efficiency of over 18% via hole transport engineering”, *J. Mat. Sci. & Technol.*, 35 (2019) 987-993 doi: 10.1016/j.jmst.2018.12.025.
- [168] <https://www.ise.fraunhofer.de/content/dam/ise/de/documents/publications/studies/Photovoltaics-Report.pdf>.

- [169] M. Chapin, C. S. Fuller, G. L. Pearson, "A New Silicon p-n Junction Photocell for Converting Solar Radiation into Electrical Power", *J. Appl. Phys.*, 25 (1954) 676-677 doi: 10.1063/1.1721711.
- [170] M. Sheorana, A. Upadhyaya, A. Rohatgi, "Bulk lifetime and efficiency enhancement due to gettering and hydrogenation of defects during cast multicrystalline silicon solar cell fabrication", *Sol.-State Electr.*, 52 (2008) 612-617 doi: 10.1016/j.sse.2007.10.001.
- [171] S. M. Joshi, U.M. Gösele, T. Y. Tan, "Improvement of minority carrier diffusion length in Si by Al gettering", *J. Appl. Phys.*, 77 (1995) 3858-3863 doi: 10.1063/1.358563.
- [172] Z-W. Peng, T. Buck, L. J. Koduvelikulathu, V. D. Mihailetschi, R. Kopecek, "Industrial Screen-Printed n-PERT-RJ Solar Cells: Efficiencies Beyond 22% and Open-Circuit Voltages Approaching 700 mV", *IEEE J. Photovolt.*, 9 (2019) 1166 – 1174 doi: 10.1109/JPHOTOV.2019.2919117.
- [173] K. Chan, B. Hekmatshoartabari, T. H. Ning, "Shallow junction photovoltaic devices" United States Patent, US9105770B2, 2015.
- [174] S. Narasimha, A. Rohatgi, A.W. Weeber, "An optimized rapid aluminium back surface field technique for silicon solar cells", *IEEE Trans. Elect. Devices*, 46 (1999) 1363 – 1370 doi: 10.1109/16.772477.
- [175] X. Yan, E-C. Wanga, N. Chen, L. Zhang, X. Gong, X. Zhang, S. Duttgupta, "Investigation of phosphorus diffused back surface field (BSF) in bifacial nFAB solar cells", *Sol. Energy*, 179 (2018) 335-342 doi: 10.1016/j.solener.2018.12.052.
- [176] P. Campbell, M. A. Green, "High performance light trapping textures for monocrystalline silicon solar cells", *Sol. Energy Mater. Sol. Cells*, 65 369-375 (2001) doi:10.1016/S0927-0248.
- [177] A. S. Kale, W. Nemeth, H. Guthrey, M. Page, M. A. Jassim, D. L. Young, S. Agarwal, P. Stradins, "Modifications of Textured Silicon Surface Morphology and Its Effect on Poly-Si/SiO_x Contact Passivation for Silicon Solar Cells", *IEEE J. Photovolt.*, 9 (2019) 1513 – 1521 doi:10.1109/JPHOTOV.2019.2937230.
- [178] B. Kumar, T. B. Pandian, E. Sreerkan, S. Narayanan, "Benefit of dual layer silicon nitride anti-reflection coating", *Conference Record of the Thirty-first IEEE Photovoltaic Specialists Conference*, 2005., Lake Buena Vista, FL, USA, (2005) 1205-1028, doi: 10.1109/PVSC.2005.1488355.
- [179] Z. N. Adamian, A. P. Hakhoyan, V. M. Aroutiounian, R. S. Barseghian, K. Touryan, "Investigations of solar cells with porous silicon as antireflection layer", *Sol. Energy Mater. Sol. Cells*, 64 (2000) 347-351 doi: 10.1016/S0927-0248.
- [180] A.G. Aberle, "Surface passivation of crystalline silicon solar cells: a review *Prog. Photovolt.*": *Res. and Appl.*, 8 (2000) 473-487 doi: 10.1002/1099-159X.
- [181] A. Rohatgi, P. Doshi, J. Moschner, T. Lauinger, A.G. Aberle, D.S. Ruby, "Comprehensive study of rapid, low-cost silicon surface passivation technologies", *IEEE Trans. Electron Devices*, 47 (2000) 987 – 993 doi: 10.1109/16.841230.
- [182] Y. F. Zhuang, S. H. Zhong, X. J. Liang, H. J. Kang, Z. P. Li, W. Z. Shen, "Application of SiO₂ passivation technique in mass production of silicon solar cells", *Sol. Energy Mater. Solar Cells*, 193 (2019) 379-386 doi: 10.1016/j.solmat.2019.01.038.
- [183] Y-J. Huang, Y.-C. Chen, C.-Y. Yu, C.-P. Sun, C.-H. Lin, "Evaluation of Graphene Oxide as the Passivation Layer for Si Solar Cells", 2019 IEEE 46th Photovoltaic Specialists Conference (PVSC), Chicago, IL, USA, pp. (2019) 1906-1908 doi:10.1109/PVSC40753.2019.8980656.

- [184] T. G. Allen, J. Bullock, X. Yang, A. Javey, S.D.Wolf, “Passivating contacts for crystalline silicon solar cells”, *Nature Energy*, 4 (2019) 914–928doi: org/10.1038/s41560-019-0463-6.
- [185] W. Shockley, Hans J. Queisser, “Detailed Balance Limit of Efficiency of p-n Junction Solar Cells”, *J. App. Phys.*, 32 (1961) 514-519 doi: 10.1063/1.1736034.
- [186] Y. Lv, Y.F. Zhuang, W.J. Wang, W.W. Wei, J. Sheng, S. Zhang, W.Z. Shen, “Towards high-efficiency industrial p-type mono-like Si PERC solar cells”, *Sol. Energy Mater. Solar Cells*, 204 (2019) 1-7doi: 10.1016/j.solmat.2019.110202.
- [187] J. Benick, B. Steinhauser, R. Müller, J. Bartsch, M. Kamp, A. Mondon, A. Richter, M. Hermle, S. Glunz, “High efficiency n-type PERT and PERL solar cells”, 2014 IEEE 40th Photovoltaic Specialist Conference (PVSC), Denver, CO,(2014) 3637-3640doi: 10.1109/PVSC.2014.6924895.
- [188] M. Taguchi, A. Yano, S. Tohoda, K. Matsuyama, Y. Nakamura, T. Nishiwaki, K. Fujita, E. Maruyama, “24.7% Record Efficiency HIT Solar Cell on Thin Silicon Wafer”, *IEEE J. Photovolt.*,4 (2014) 96-99doi: 10.1109/JPHOTOV.2013.2282737.
- [189] K. Masuko, M. Shigematsu, T. Hashiguchi, D. Fujishima, M. Kai, N. Yoshimura, T. Yamaguchi, Y. I. chihashi, T. Mishima, N. Matsubara, T. Yamanishi, T. Takahama, M. Taguchi, E. Maruyama, S. Okamoto, “Achievement of More Than 25% Conversion Efficiency With Crystalline Silicon Heterojunction Solar Cell”, *IEEE J. Photovolt.*,4 (2014) 1433-1435doi: 10.1109/JPHOTOV.2014.2352151.
- [190] F. Feldmann, M. Bivour, C. Reichel, M. Hermle, S. W. Glunz, “Passivated rear contacts for high-efficiency n-type Si solar cells providing high interface passivation quality and excellent transport characteristics”, *Sol. Energy Mater. Sol. Cells*, 120 (2014) 270-274doi: 10.1016/j.solmat.2013.09.017.
- [191] Y. Tao, V. Upadhyaya, C.-W. Chen, A. Payne, E. Lori Chang, A. Upadhyaya, A. Rohatgi, “Large area tunnel oxide passivated rear contact n-type Si solar cells with 21.2% efficiency”, *Prog.Photovolt: Res. Appl.*,24 (2016) 830–835 doi: 10.1002/pip.2739.
- [192] U. Das, L. Zhang, S. Hegedus, “Processing Approaches and Challenges of Interdigitated Back Contact Si Solar Cells”, 2017 IEEE 44th Photovoltaic Specialist Conference (PVSC), Washington, DC, USA, (2017) 1761- 1764doi: 10.1109/PVSC.2017.8366709.
- [193] A. Tomasi, B. P. Salomon, Q. Jeangros, J. Haschke, G. Christmann, L. Barraud, A. Descoeurdes, J. P. Seif, S. Nicolay, M. Despeisse, S. D. Wolf, C. Ballif, “Simple processing of back-contacted silicon heterojunction solar cells using selective-area crystalline growth”, *Nature Energy*,2 (2017) 1-8doi: 10.1038/nenergy.2017.62.
- [194] K. Masuko, M. Shigematsu, T. Hashiguchi, D. Fujishima, M. Kai, N. Yoshimura, T. Yamaguchi, Y. Ichihashi, T. Mishima, N. Matsubara, T. Yamanishi, T. Takahama, M. Taguchi, E. Maruyama, S. Okamoto, “Achievement of More Than 25% Conversion Efficiency With Crystalline Silicon Heterojunction Solar Cell”, *IEEE J. Photovolt.*, 4 (2014) 1433 – 1435doi: 10.1109/JPHOTOV.2014.2352151.
- [195] K. Yoshikawa, H. Kawasaki, W. Yoshida, T. Irie, K. Konishi, K. Nakano, T. Uto, D. Adachi, M. Kanematsu, H. Uzu, K. Yamamoto, “Silicon heterojunction solar cell with interdigitated back contacts for a photoconversion efficiency over 26%”, *Nature Energy*, vol. 2 (2017)1-8doi: 10.1038/nenergy.2017.32.
- [196] A. Louwen, W. van Sark, R. Schropp, André Faaij, “A cost roadmap for silicon heterojunction solar cells, *Sol. Energy Mater. Sol. Cells*”, 147 (2016) 295 – 314doi: 10.1016/j.solmat.2015.12.026.
- [197] Z. Liu, S. E. Sofia, H. S. Laine, M. Woodhouse, S. Wiegold, I. M. Peters, T. Buonassisi, “Revisiting thin silicon for photovoltaics: a technoeconomic perspective”, *Energy Environ. Sci.*, vol. 13, pp. 12-23, oct.2020,doi: 10.1039/C9EE02452B.

- [198] Y. Hirayama, H. Inoue, K. Matsuyama, Y. Tsunomura, “The Study of Improving the Conversion Efficiency and Reducing the Thickness of the HIT Solar Cell”, *Mater. Res. Soc. Symp. Proc.*, 1288 (2011) 1-6doi: Mrsf10-1288-g06-09, 10.1557/opl.2011.240.
- [199] M. Taguchi, A. Yano, S. Tohoda, K. Matsuyama, Y. Nakamura, T. Nishiwaki, K. Fujita, E. Maruyama, “24.7% Record Efficiency HIT Solar Cell on Thin Silicon Wafer” *IEEE J. Photovolt.*, 4 (2014) 96 – 99doi: 10.1109/JPHOTOV.2013.2282737.
- [200] H. Sai, T. Matsui, “Challenges and prospects of very thin (<50 μm) crystalline silicon solar cells”, 2019 26th International Workshop on Active-Matrix Flat panel Displays and Devices (AM-FPD), Kyoto, Japan (2019) 1-2doi: 10.23919/AM-FPD.2019.8830583.
- [201] H. Sai, T. Oku, Y. Sato, M. Tanbe, T. Matsui, K. Matsubara, “Potential of very thin and high efficiency silicon heterojunction solar cells”, *Prog. Photovolt.*, 27 (2019) 1061-1070 doi: <https://doi.org/10.1002/pip.3181>.
- [202] P. Balaji, W.J. Dauksher, S.G. Bowden, A. Augusto, “Improving surface passivation on very thin substrate for high efficiency silicon heterojunction solar cell”, 216 (2020) 11075-11083doi: <https://doi.org/10.1016/j.solmat.2020.110715>.
- [203] A. K. Dikshit, N. C. Mandal, S. Bose, N. Mukherjee, P. Chakrabarti, “Optimization of back ITO layer as the sandwiched reflector for exploiting longer wavelength lights in thin and flexible (30 μm) single junction c-Si solar cells”, *Sol. Energy* 193 (2019) 293–302doi: 10.1016/j.solener.2019.09.017
- [204] H. Sai, T. Oku, Y. Sato, M. Tanabe, T. Matsui, K. Matsubara, “Potential of very thin and high efficiency silicon heterojunction solar cells”, *Prog. Photovolt.; Research and Application* 27 (2019) 1061–1070doi: 10.1002/pip.3181.
- [205] Y. Kim, S. Jung, M. Ju, K. Ryu, J. Park, H. Choi, D. Yang, Y. Lee, J. Yi, “Effect of rear surface polishing to the performance of thin crystalline silicon solar cells”, *Sol. Energy*, 85b(2011) 1085-1090doi: 10.1016/j.solener.2011.03.001.
- [206] C. Y. Kung, C. H. Yang, C. W. Huang, S. Y. Lein, W. Z. Zhu, H. J. Lin, X. Y. Zhang, “Performance Improvement of high efficiency mono-crystalline silicon solar cells by modifying rear-side morphology”, *Appl. Sci.*, 7 (2017) 2-6 doi: 10.3390/app7040410.
- [207] M. Kanehara, H. Koike, T. Yoshinaga, T. Teranishi, “Indium Tin Oxide Nanoparticles with Compositionally Tunable Surface Plasmon Resonance Frequencies in the Near-IR Region”, *J. Am. Chem. Soc.*, 131 (2009) 17736 – 17737doi: 10.1021/ja9064415.
- [208] J. Muller, B. Rech, J. Springer, M. Vanecek, “TCO and light trapping in silicon thin film solar cells”, *Sol. Energy*, 77 (2004) 917 – 930doi: 10.1016/j.solener.2004.03.015.
- [209] S. Yang, S. Guo, D. Xu, H. Xue, H. Kou, and J. Wang, “Improved efficiency of dye-sensitized solar cells applied with F-doped TiO₂ electrodes,” *J. Fluor. Chem.* 150, 78–84 (2013)
- [210] R. Liu, Z. Sun, Y. Zhang, L. Xu, and N. Li, “Polyoxometalate-modified TiO₂ nanotube arrays photoanode materials for enhanced dye-sensitized solar cells,” *J. Phy. Chem. Sol.* 109, 64–69 (2017).
- [211] J. Chou, C. Chu, and Y. Liao, “Fabrication and photovoltaic properties of dye-sensitized solar cells modified by graphene oxide and magnetic bead,” *IEEE Elect. Dev. Lett.* 36, 711–713 (2015).
- [212] R. Osterbacka, A. Pivrikas, G. Juška, A. Poškus, H. Aarnio, G. Sliaužys, K. Genevičius, K. Arlauskas and N. S. Sariciftci, “Effect of 2-D delocalization on charge transport and recombination in bulk-heterojunction solar cells,” *IEEE J. Quant. Elect.* 16, 1738–1745 (2010).
- [213] S. Ganesan, S. Mehta, and D. Gupta, “Opto-electronics review fully printed organic solar cells – a review of techniques , challenges and their solutions,” *Opto-Elect. Rev.* 27. 298–320 (2019).

- [214] Z. Khezripour, F. F Mahani and A. Mokhtari “Double-sided TiO₂ nano-gratings for broadband performance enhancement of organic solar cells,” *J. Opt. Soc. Am. B* 35, 2478–2483 (2018).
- [215] H. Liu, W. Fu, B. Zong, L. Huang, B. Zhang S. Wang, Z. Guo, H. Bala, G. Sun, J. Cao and Z. Zhan, “A high stability, hole-conductor-free mixed organic cation pervoskite solar cells based on carbon counter electrode,” *Electrochim. Acta.* 266, 78–85 (2018).
- [216] M. Courel, T. Jiménez, A. Arce-plaza, D. Seuret-jiménez, and J. P. Morán-lázaro, “A theoretical study on Sb₂S₃ solar cells : The path to overcome the efficiency barrier of 8 %,” *Sol. Energy Mater. Sol. Cells.* 201 110123 (2019).
- [217] Y. Xu, C. Gao, S. Tang, J. Zhang, Y. Chen, Y. Zhu and Z. Hu, “Comprehensive understanding of TiCl₄ treatment on the compact TiO₂ layer in planar perovskite solar cells with efficiencies over 20 %,” *J. Alloy & Comp.* 787, 1082–1088 (2019).
- [218] D. Li, W. Sun, L. Shao, S. Wu, Z. Huang, X. Jin, Q. Zhang and Q. Li, “Tailoring solar energy spectrum for efficient organic/inorganic hybrid solar cells by up-conversion luminescence nanophosphors,” *Electrochim. Act.* 182, 416–423 (2015).
- [219] A. E. Kobryn, S. Gusarov, and K. Shankar, “Multiscale modeling of active layer of hybrid organic-inorganic solar cells for photovoltaic applications by means of density functional theory and integral equation theory of molecular liquids,” *J. Mol. Liq.* 289, 110997 (2019).
- [220] J. Duan, J. Wei, Q. Tang, and Q. Li, “Unveiling the interfacial charge extraction kinetics in inorganic perovskite solar cells with formamidinium lead halide (FAPbX₃) nanocrystals,” *Sol. Ener.* 195, 644–650 (2020).
- [221] A. Manjceevan and J. Bandara, “stacking of PbS/CdS/CdSe multi-layered quantum dots for the enhancement of solar cell efficiency by harvesting wide solar spectrum,” *Electrochim. Acta.* 271, 567–575 (2018).
- [222] X. Zhang, P. K. Santra, L. Tian, M. B. Johansson, H. Rensmo and E. M. J Johansson, “Highly Efficient flexible quantum-dot solar cells with improved electron extraction using MgZnO Nanocrystal,” *ACS Nano.* 11, 8478-8487 (2017).
- [223] R. Azmi, G. Seo, T. K. Ahn, and S. Jang, “High-efficiency air-stable colloidal Quantum dot solar cells based on a potassium-doped ZnO electron-accepting layer,” *ACS Appl. Mater. Interfaces* 10, 35244–35249 (2018).
- [224] A. Aissat and J. P. Vilot, “Optik development of In_xGa_{1-x}N / GaN axial multiple quantum well nanowire for solar cell applications,” *Opt. - Int. J. Light Electron Opt.* 163844 (2019).
- [225] T. S. Lay, Z. H. Lin, K. Y. Chuang, and T. E. Tzeng, “InGaAs quantum dots-in-a-well solar cells with anti-reflection coating,” *J. Cryst. Growth* 513, 6–9 (2019).
- [226] A. K. Dikshit, N. C. Mondal, S. Bose, and N. Mukherjee, “Optimization of back ITO layer as the sandwiched reflector for exploiting longer wavelength lights in thin and flexible (30 μm) single junction c-Si solar cells,” *Sol. Energy.* 193, 293–302 (2019).
- [227] A. B. Roy, S. Das, A. Kundu, C. Banerjee, and N. Mukherjee, “c-Si/n-ZnO-based flexible solar cells with silica nanoparticles as a light trapping metamaterial,” *Phys. Chem.* 19, 12838–12844 (2017).
- [228] J. H. Petermann, D. Zielke, J. Schmidt, F. Haase, E. G. Rojas, and R. Brendel, “19% efficient and 43 μm thick crystalline Si solar cell from layer transfer using porous silicon,” *Prog. Photovolt: Res. Appl.* 20, 1–5 (2012).
- [229] M. G. Mauk, “Thin Crystalline and Polycrystalline Silicon Solar Cells”, Elsevier, 2018.
- [230] W. Shockley and H. J. Queisser, “Detailed balance limit of efficiency of p-n junction solar cells,” *J. Appl. Phys.* 32, 510 (1961).

- [231] A. B. Roy, A. Dhar, M. Choudhuri, and S. Das, "Black silicon solar cell: analysis optimization and evolution towards a thinner and flexible future," *Nanotechnology* 27, 1–12 (2016).
- [232] H. Heidarzadeh, "Incident light management in a thin silicon solar cell using a two-dimensional grating according a Gaussian distribution," *Sol. Energy* 189, 457–463 (2019)
- [233] A. Abbasiyan, M. Noori, and H. Baghban, "Investigation of quasi-periodic structures to increase the efficiency of thin-film silicon solar cells: A comparative study," *Sol. Energy Mater. Sol. Cells* 202, 110129 (2019).
- [234] Q. Tang, H. Shen, H. Yao, K. Gao, J. Ge, and Y. Liu, "Investigation of optical and mechanical performance of inverted pyramid based ultrathin flexible c-Si solar cell for potential application on curved surface," *Appl. Surf. Sci.* 504, 144588 (2020)
- [235] M. Taguchi, A. Yano, S. Tohoda, K. Malsuyama, Y. Nakamura, T. Nishiwaki, K. Fujita and E. Maruyama, "24.7 % Record efficiency HIT solar cell on thin silicon solar wafer," *IEEE J. Photovoltaics* 4, 96–99 (2014).
- [236] X. Zeng, X. Wen, X. Sun, W. Liao, and Y. Wen, "Boron-doped zinc oxide thin films grown by metal organic chemical vapor deposition for bifacial a-Si:H/c-Si heterojunction solar cells," *Thin Solid Films* 605, 257–262 (2016).
- [237] . Zhao, A. Wang, and M. A. Green, "High-efficiency PERL and PERT silicon solar cells on FZ and MCZ substrates," *Sol. Energy Mater. Sol. Cells* 65, 429–435 (2001).
- [238] X. Yang, P. Zheng, Q. Bi, and K. Weber, "Silicon heterojunction solar cells with electron selective TiO_x contact," *Sol. Energy Mater. Sol. Cells* 150, 32–38 (2016).
- [239] P. Campbell and M. A. Green, "Light trapping properties of pyramidally textured surfaces" *J. Appl. Phys.* 62, 243 (1987).
- [240] S. Duttagupta, F. Ma, B. Hoex, T. Mueller and G. Aberle, "Optimised antireflection coatings using silicon nitride on textured silicon surfaces based on measurements and multi dimensional modelling," *Energy Proc.* 15, 78-83 (2012).
- [241] N. Feng, J. Michel, L. Zeng, J. Liu, C.Y Hong and L. C. Kimerling, "Design of highly efficient light-trapping structures for thin-film crystalline silicon solar cells," *IEEE Trans. Elect. Dev.* 54, 1926–1933 (2007).
- [242] C. Heine and R. H. Morf, "Submicrometer gratings for solar energy applications," *OSA App. Opt.* 34, 2476-2482 (1995).
- [243] J. M. Gee, "Optically enhanced absorption in thin silicon layer using photonic crystals," *IEEE Lett.* 150–153 (2002).
- [244] E. R. Martins, J. Li, Y. Liu, V. Depauw, Z. Chen, J. Zhou and E. R. Martins, "Deterministic quasi-random nanostructures for photon control," *Nat. Comm.* 3665, 1–7 (2013).
- [245] P. Bermel, C. Luo, L. Zeng, L. C. Kimerling, and J. D. Joannopoulos, "Improving thin-film crystalline silicon solar cell efficiencies with photonic crystals," *OSA Optic. Exp.* 15, 16986–17000 (2007).
- [246] P G. Brein, N. P. Kherani, A. Chutinam, G. A.Ozin, S. John, S. Zukotynski., "Silicon Photovoltaics Using Conducting Photonic Crystals Back-Reflectors," *Adv. Mater.* 1577–1582 (2008).
- [247] . Zhao, Y.H. Zuo, C.L. Zhou, H.L. Li, H.W. Diao and W.J. Wang "A highly efficient light-trapping structure for thin-film silicon solar cell," *Sol. Energy* 84, 110-115 (2010).
- [248] O. Isabella, S. Dobrovolskiy, G.kroon, M. Zeman "Design and application of dielectric distributed Bragg back reflector in thin-film silicon solar cell" *J. Non-Crys. Solid* 358, 2295-2298 (2012).
- [249] Y. L. Tsai, C. C Lin, H. Han, C. Chang, H. Chen, K. Chen, W. Lai, J Sheu, F. Lai, P. Yu and H. Kuo "Improving efficiency of InGaN/GaN multiple quantum well solar cells using CdS

- quantum dots and distributed Bragg reflectors,” *Sol. Energy Mater. Sol. Cells* 117, 531-536 (2013).
- [250] S. Banerjee, S. Mandal, S. Dhar, A. B. Roy and N. Mukherjee, “Nanomirror-Embedded Back Reflector Layer (BRL) for Advanced Light Management in Thin Silicon Solar Cells,” *Ind. Eng. Chem. Res.* 58(28), 12678-12686 (2019).
- [251] W. Chen, R. Liu, Q. Zeng, and L. Zhou, “Low cost multicrystalline bifacial PERC solar cells – Fabrication and thermal improvement,” *Sol. Energy* 184, 508–514 (2019).
- [252] N. Wöhrle, T. Fellmeth, J. Greulich, B. Bitnar, H. Neuhaus, P. Palinginis, R. Köhler and S. Rein, “Understanding the rear-side layout of p-doped bifacial PERC solar cells with simulation driven experiments,” *Energy Proc.* 124, 225–234 (2017).
- [253] F. Ye, Y. Li, X. Jia, H. Guo, X. Wang, and J. Ding, N. Yuan and Z. Peng, “Optimization of phosphorus dopant profile of industrial p-type mono PERC solar cells,” *Sol. Energy Mater. Sol. Cells.* 190, 30–36 (2019).
- [254] H. Huang, C. Modanese, S. Sun, G. Gastrow, J. Wang, T. P. Pasanen, S. Li, L. Wang, Y. Bao, Z. Zhu, S. Sneck and H. Savin, “Effective passivation of p⁺ and n⁺ emitters using SiO₂/Al₂O₃/SiN_x stacks: surface passivation mechanisms and application to industrial p-PERT bifacial solar cells,” *Sol. Energy Mater. Sol. Cells* 186, 356-364 (2018).
- [255] S. Li, N. Yang, X. Yuan, C. Liu, X. Ye and H. Li, “Hydrogen induced interface passivation in atomic layer deposition Al₂O₃ films and Al₂O₃/SiO₂ stacks,” *Mat. Sci. Sem. Proc.* 83, 171-174 (2018).
- [256] A. El amrani, I. Menous, L. Mahiou, R. Tadjine, A. Touati, A. Lefgoum, “Silicon nitride film for solar cells,” *Renew. Energy*, 33, 2289–2293(2008).
- [257] COMSOL Multiphysics™ v. 5.4 software used to perform simulation www.comsol.com.
- [258] J. Benick, K. Zimmermann, J. Spiegelman, M. Hermle, S.W. Glunz, “Rear side passivation of PERC-type solar cells by wet oxides grown from purified steam: Rear side passivation of PERC-type solar cells,” *Prog. Photovolt: Res. Appl.* 19 361–365 (2011).
- [259] R. S. Bonilla, B. Hoex, P. Hamer and P. R. Wilshaw, “Dielectric surface passivation for silicon solar cells: A review,” *Phys. Status Solidi A*, 214, 1700293 (1 – 30) (2017).
- [260] J. Panigrahi, V. Panwar, R. Singh and P. K. Singh, “Atomic layer deposited dielectric and/or semiconducting oxide bilayers for crystalline silicon surface passivation,” *Energy Proc.* 124, 302–306 (2017).
- [261] X. Y. Zhang, C. H. Hsu, S. Y. Lien, S. Y. Chen, W. Huang, C. H. Yang, C. Y. Kung, W. Z. Zhu, F. B. Xiong and X. G. Meng, “Surface Passivation of Silicon Using HfO₂ Thin Films Deposited by Remote Plasma Atomic Layer Deposition System,” *Nanoscale Res. Lett.* 12, 324 (1-7) (2017).
- [262] J. Gope, Vandanaa, N. Batra, J. Panigrahi, R. Singh, K. K. Maurya, R. Srivastava and P.K. Singh, “Silicon surface passivation using thin HfO₂ films by atomic layer deposition,” *Appl. Surf. Sci.* 357, 635 – 642 (2015).
- [263] J. Schmidt, A. Merkle, R. Brendel, B. Hoex, M. C. M. van de Sanden and W. M. M. Kessels, “Surface Passivation of High-efficiency Silicon Solar Cells by Atomic-layer-deposited Al₂O₃,” *Prog. Photovolt: Res. Appl.* 16, 461–466 (2008).
- [264] . Dullweber, R. Hesse, V. Bhosle and C. Dubé, “Ion-implanted PERC solar cells with Al₂O₃/SiN_x rear passivation,” *Energy Proc.* 38, 430–435 (2013).
- [265] H. Huang, J. Lv, Y. Bao, R. Xuan, S. Sun, S. Sneck, S. Li, C. Modanese, H. Savin, A. Wang and J. Zhao, “Data of ALD Al₂O₃ rear surface passivation, Al₂O₃ PERC cell performance, and cell efficiency loss mechanisms of Al₂O₃ PERC cell,” *Data Brief*, 11, 19 – 26 (2017).

- [266] F. Lin, B. Hoex, Y.H. Koh, J.J. Lin, A.G. Aberle, “Low-temperature Surface Passivation of Moderately Doped Crystalline Silicon by Atomic-layer-deposited Hafnium Oxide Films,” *Energy Procedia*. 15, 84–90 (2012).
- [267] M. Turek, “Current and illumination dependent series resistance of solar cells,” *J. Appl. Phys.* 115 144503 (2014).
- [268] T. Kuwabara, C. Iwata, T. Yamaguchi, K. Takahashi, “Mechanistic insights into UV-induced electron transfer from PCBM to titanium oxide in inverted-type organic thin film solar cells using A.C. impedance spectroscopy”, *A.C.S. Appl. Mater. Interfaces*, Vol. 2, no. 8, pp. 2254-2260, July 2010, doi: 10.1021/am100312v
- [269] K. Xu, Z. Zhang, Z. Zhang, “Structural and optical properties of silicon metal-oxide-semiconductor light-emitting devices”, *J. Nanophotonics*, Vol. 10, no. 1, pp. 1-10, Mar 2016, doi: 10.1117/1.JNP.10.016002.
- [270] Z. He, B. Xiao, F. Liu, H. Wu, Y. Yang, S. Xiao, C. Wang, T. P. Russell and Y. Cao, “Single-junction polymer solar cells with high efficiency and photovoltage,” *Nat. Photon*, Vol. 9, no. 3, pp. 174–179, Mar. 2015, doi:10.1038/nphoton.2015.6
- [271] S.-H Liao, H.-J. Jhuo, P.-N. Yeh, Y.-S. Cheng, Y.-L. Li, Y.-H. Lee, S. Sharma, S.-A. Chen, “Single junction inverted polymer solar cell reaching power conversion efficiency 10.31% by employing dual-doped zinc oxide nano-film as cathode interlayer”, *Nat. Sci. Rep.*, Vol. 4, no. 6813, pp. 1-7, Oct. 2014, doi:10.1038/srep06813.
- [272] A.K.K. Kyaw, X.W. Sun, C.Y. Jiang, G.Q. Lo, D.W. Zhao, D.L. Kwong, “An inverted organic solar cell employing a sol–gel derived ZnO electron selective layer and thermal evaporated MoO₃ hole selective layer”, *Appl. Phys. Lett.*, Vol. 93, no. 22, pp. 221107(1-3), Dec.2008, doi: <http://dx.doi.org/10.1063/1.3039076>.
- [273] H.M. Zuhir, I. Saad, A. Roystone, A. M. Khairul, B. Ghosh, N. Bolong, “Enhancing efficiency of organic solar cells by interfacial materials modification”, 2017 IEEE Regional Symposium on Micro and Nanoelectronics (R.S. M), pp. 159-162, Oct. 2017, doi: 10.1109/RSM.2017.8069154.
- [274] Y. Vaynzof, D. Kabra, L. Zhao, P. K. H. Ho, A. T.-S. Wee, R. H. Friend, “Improved photoinduced charge carriers separation in organic-inorganic hybrid photovoltaic devices”, *Appl. Phys. Lett.*, Vol. 97, no.3, pp. 033309(1-3), Jun. 2010, doi: <http://dx.doi.org/10.1063/1.3464973>.
- [275] C. G. Allen, D. J. Baker, T. M. Brenner, C. C. Weigand, J. M. Albin, K. X. Steirer, D. C. Olson, C. Ladam, D. S. Ginley, R. T. Collins, T. E. Furtak, “Alkyl Surface Treatments of Planar Zinc Oxide in Hybrid Organic/Inorganic Solar Cells”, *J. Phys. Chem. C.*, Vol. 116, no. 16, pp. 8872–8880, doi:10.1021/jp211692m
- [276] T. C. Monson, M. T. Lloyd, D. C. Olson, Y. J. Lee, J. W. P. Hsu, “Photocurrent enhancement in polythiophene- and alkanethiol-modified ZnO solar cells,” *Adv. Mater.*, Vol. 20, no. 24, pp. 4755-4759, Dec. 2008, doi: 10.1002/adma.200801082.
- [277] J. N. Sekine, C.-H. Chou, W. L. Kwan, Y. Yang, “ZnO nano-ridge structure and its application in inverted polymer solar cell”, *Org. Electron.*, Vol. 10, no. 8, pp. 1473–1477, Dec. 2009, doi:10.1016/j.orgel.2009.08.011.
- [278] H. Ma, H. L. Yip, F. Huang, A. K. Y. Jen, “Interface Engineering for Organic Electronics”, *Adv. Funct. Mater.*, Vol. 20, no. 9, pp. 1371–1388 May 2010, doi: 10.1002/adfm.200902236.
- [279] B. J. Richardson, X. Wang, A. Almutairi, Q. Yu, “High efficiency PTB7-based inverted organic photovoltaics on nano-ridged and planar zinc oxide electron transport layers”, *J. Mater. Chem. A*, Vol. 3, no. 10, pp. 5563-5571, Feb. 2015, doi: <https://doi.org/10.1039/C5TA00400D>.

- [280] L. Yang, H. Xu, H. Tian, S. Yin, F. Zhang, “Effect of cathode buffer layer on the stability of polymer bulk heterojunction solar cells”, *Sol. Energy Mater. Sol. Cells*, Vol. 94, no. 10, pp. 1831-1834, Oct. 2010, doi: <https://doi.org/10.1016/j.solmat.2010.05.043>.
- [281] H. Oh, J. Krantz, I. Litzov, T. Stubhan, L. Pinna, C.J. Brabec, “Comparison of various sol-gel derived metal oxide layers for inverted organic solar cells”, *Sol. Energy Mater. Sol. Cells*, Vol. 95, no. 8, pp. 2194–2199, Aug. 2011, doi: <https://doi.org/10.1016/j.solmat.2011.03.023>.
- [282] D.W. Zhao, S.T. Tan, L. Ke, P. Liu, A.K.K. Kyaw, X.W. Sun, G.Q. Lo, D.L. Kwong, “Optimization of an inverted organic solar cell”, *Sol. Energy Mater. Sol. Cells*, Vol. 94, no. 6, pp. 985–991, Jun. 2010, doi: <https://doi.org/10.1016/j.solmat.2010.02.010>.
- [283] Z. Tan, W. Zhang, Z. Zhang, D. Qian, Y. Huang, J. Hou, Y. Li, “High-performance inverted polymer solar cells with solution-processed titanium chelate as electron-collecting layer on ITO electrode”, *Adv. Mat.*, Vol. 24, no. 11, pp. 1476–1481, Mar. 2012, doi: 10.1002/adma.201104863.
- [284] Y. Sun, J.H. Seo, C.J. Takacs, J. Seifert, A.J. Heeger, “Inverted polymer solar cells integrated with a low-temperature-annealed sol-gel-derived ZnO Film as an electron transport layer”, *Adv. Mat.*, Vol. 23, no. 14, pp. 1679–1683, April 2011, doi: 10.1002/adma.201004301.
- [285] K. W. Wong, H. L. Yip, Y. Luo, K. Y. Wong, W. M. Lau “Blocking reactions between indium-tin oxide and poly (3,4-ethylene dioxythiophene): poly(styrene sulphonate) with a self-assembly monolayer”, *Appl. Phys. Lett.*, Vol. 80, no. 15, 2788–2790, April 2000, doi: <http://dx.doi.org/10.1063/1.1469220>.
- [286] S.Maity, C. T. Bhunia, P. P. Sahu, “Improvement in optical and structural properties of ZnO thin film through hexagonal nanopillar formation to improve the efficiency of a Si–ZnO heterojunction solar cell”, *J. Phy. D Appl. Phy*, Vol. 49, no. 20, pp. 1-9, April 2016, doi:10.1088/0022-3727/49/20/205104.
- [287] M. T. Dang, L. Hirsch, G. Wantz, “P3HT:PCBM, Best Seller in Polymer Photovoltaic Research”, *Adv. Mater.*, Vol. 23, no. 31, pp. 3597–3602, Aug. 2016, doi: 10.1002/adma.201100792.
- [288]] H.Jin, J. Olkkonen, M. Tuomikoski, P. Kopola, A. Maaninen, J. Hast, “Thickness dependence and solution-degradation effect in poly(3-hexylthiophene):phenyl-C61-butyric acid methyl ester based solar cells”, *Sol. Energy Mater. Sol. Cells*, Vol. 94, no. 3, pp. 465-470, Mar. 2010, doi: <https://doi.org/10.1016/j.solmat.2009.11.007>.
- [289] H. Chen, S. Hu, H. Zang, B. Hu, M. Dadmun, “Precise Structural Development and its Correlation to Function in Conjugated Polymer: Fullerene Thin Films by Controlled Solvent Annealing”, *Adv. Funct. Mater*, Vol. 23, no. 13, pp. 1701-1710, April 2013, doi: 10.1002/adfm.201202035.
- [290] W. Ma, C. Yang, X. Gong, K. Lee, A. J. Heeger, “Thermally Stable, Efficient Polymer Solar Cells with Nanoscale Control of the Interpenetrating Network Morphology”, *Adv. Funct. Mater*, Vol. 15, no. 10, pp. 1617-1622, Oct. 2005, doi: 10.1002/adfm.200500211.
- [291] T.Ivanovska, Z. Saponjic, M. Radoicic, L. Ortolani, V. Morandi, G. Ruani, "Improvement of Dye Solar Cell Efficiency by PhotoanodePosttreatment", *Int. J. Photoenergy*, Vol. 10, pp. 1-10, Jul. 2014, doi: <http://dx.doi.org/10.1155/2014/835760>.
- [292] S. H. Oh, S. J. Heo, J. S. Yang, H. J. Kim, “Effects of ZnO Nanoparticles on P3HT: PCBM Organic Solar Cells with DMF-Modulated PEDOT:PSS Buffer Layers”, *A.C.S. Appl. Mater. Interfaces*, Vol. 5, no. 22, pp. 11530–11534, Oct. 2013, doi: <https://doi.org/10.1021/am4046475>.
- [293] R. S. Kim, J. Zhu, J. H. Park, L. Li, Z. Yu, H. Shen, M. Xue, K. L. Wang, G. Park, T. J. Anderson, Q. Pei, “E-beam deposited Ag-nanoparticles plasmonic organic solar cell and its absorption enhancement analysis using FDTD-based cylindrical nano-particle optical

- model”, *Opt. Exp.*, Vol. 20, no. 12, pp. 12649-12657, May 2012, doi: <https://doi.org/10.1364/OE.20.012649>.
- [294] M. A. Sefunc, A. K. Okyay, H. V. Demir, “Plasmonic backcontact grating for P3HT:PCBM organic solar cells enabling strong optical absorption increased in all polarizations”, *Opt. Exp.*, Vol. 19, no. 15, pp. 14200-14209, Jul 2011, doi: <https://doi.org/10.1364/OE.19.014200>.
- [295] D. Chi, S. Qu, Z. Wang, Jizheng Wang, “High efficiency P3HT:PCBM solar cells with an inserted PCBM layer”, *J. Mater. Chem. C*, Vol. 2, no. 22, pp. 4383- 4387, Mar. 2014, doi: 10.1039/c4tc00003j.
- [296] J. P. Liu, K. L. Choy, Xiang-hui Hou, “Charge transport in flexible solar cells based on conjugated polymer and ZnO nanoparticulate thin films”, *J. Mater. Chem.*, Vol. 21, no. 6, pp. 1966–1969, Nov. 2010, doi: 10.1039/c0jm02184a.
- [297] S. H. Oh, S. J. Heo, J. S. Yang, H. J. Kim, “Effects of ZnO Nanoparticles on P3HT:PCBM Organic Solar Cells with DMF-Modulated PEDOT:PSS Buffer Layers”, *A.C.S. Appl. Mater. Interfaces*, Vol. 5, no. 22, pp. 11530–11534, Oct. 2013, doi: [dx.doi.org/10.1021/am4046475](https://doi.org/10.1021/am4046475).
- [298] M. Mirsafaei, A. H. Fallahpour, P. Lugli, H. G. Rubahn, J. Adam, M. Madsen, “The influence of electrical effects on device performance of organic solar cells with nano-structured electrodes”, *Nat. Sci. Rep.*, Vol. 7, no. 5300, doi:10.1038/s41598-017-05591-8.
- [299] C. J. Brabec, G. Zerza, G. Cerullo, S. D. Silvestri, S. Luzzati, J. C. Hummelen, S. Sariciftci, “Tracing photoinduced electron transfer process in conjugated polymer/fullerene bulk heterojunctions in real time”, *Chem. Phys. Lett.*, Vol. 340, no. 3–4, pp. 232-236, Jun. 2001, doi: [https://doi.org/10.1016/S0009-2614\(01\)00431-6](https://doi.org/10.1016/S0009-2614(01)00431-6).
- [300] M. O. Reese, A. M. Nardes, B. L. Rupert, R. E. Larsen, D. C. Olson, M. T. Lloyd, S. E. Shaheen, D. S. Ginley, G. Rumbles, Nikos Kopidakis, “Photoinduced degradation of polymer and polymer-fullerene active layers: Experiment and theory”, *Adv. Fun. Mat.*, Vol. 20, no. 20, pp. 3476-3483, Aug. 2010, doi: 10.1002/adfm.201001079.
- [301] A. Aguirre, S. C. J. Meskers, R. A. J. Janssen, H-J. Egelhaaf, “Formation of metastable charges as a first step in photo induced degradation in π -conjugated polymer:fullerene blends for photovoltaic applications”, *Org. Electron*, Vol. 12 no. 10, pp. 1657-1662, Oct. 2011, doi: 10.1016/j.orgel.2011.06.020.
- [302] .Lafalce, P. Togliola, J. E. Lewis, Xiaomei Jiang, “Photo annealing effect on p-doped inverted organic solar cell”, *J. Appl. Phys.*, Vol. 115, no. 24, Jun. 2014, doi: 10.1063/1.4883957.