

TABLE OF CONTENTS

Contents	Page No.
Certificate	ii
Acknowledgment	v
Table of contents	vii
List of figures	xi
List of tables	xxii
List of symbols	xxiv
Abstract	xxix
1. Introduction	1-12
1.1 General Background	1
1.2 Motivation for the Research	2
1.3 Thermal Energy Storage (TES) and its importance	2
1.3.1 Classification of Energy Storage	3
1.3.2 Application of various thermal energy storage	4
1.4 Phase Change Materials (PCMs)	5
1.5 Classification of PCMs	6
1.6 Nano-enhanced phase change materials (NEPCMs)	9
1.7 Classification of NEPCMs	10
1.8 Classification of PCMs/ NEPCMs based on temperature	10
1.9 Selection criteria of PCMs/NEPCMs	11
2. Literature Review	13-32
2.1 Mechanism of PCMs based TES system	13

2.2 Technique to enhance the thermal performance of the TES system	20
2.2.1 Foam-based PCMs in the TES system	20
2.2.2 Nano additives based PCMs in TES system	22
2.2.3 Improvement in TES system design	23
2.3 Mythology of TES system in waste heat recovery	25
2.4 Highlights	29
2.5 Research gap	30
2.6 The objective of present work	31
2.7 Structure of thesis	31
3. Energy and exergy comparison of organic PCMs based TES system integrated with IC engine	33-64
3.1 Experimental Analysis	33
3.1.1 Description of the experimental setup	33
3.2 Uncertainties analysis	44
3.3 Description and methodology for energy and exergy comparison of organic PCMs	45
3.4 Data Reduction	52
3.4.1. Charging Time of TES System	52
3.4.2. Discharging Time of TES System	53
3.4.3. Energy Analysis of TES System	55
3.4.4. Exergy Analysis of TES System	58
3.4.5. Validation of experimental results with theoretical estimations	61
3.5 Highlights of the results	62
4. Thermal performance of TES system with Al₂O₃ and CuO nano additives-organic PCMs based NEPCMs integrated with IC engine	65-102

4.1 Preparation method for nano-enhanced phase change materials	65
4.2 Procedures of the experiment	68
4.3 Thermal performance evaluation of the designed experimental setup	69
4.4 Comparison of nano additives in organic PCMs (CA, LA, PW & SA) based TES system integrated with IC engine	72
4.4.1 Effect of charging profile of nano additives-in organic PCMs based TES system	72
4.4.2 Thermal performance of TES system	83
4.4.3 Energy and Exergy Analysis of NEPCM Based TES System	95
4.5 Highlights	99
5. Thermophysical properties and thermal performance analysis of MWCNT based organic PCMS TES system using T-History method	101-138
5.1 About T-History Method	102
5.1.1 Procedure and types of equipment used in the T-History method	102
5.1.2 Equation used for T-History method	105
5.1.3 Solidification profile of PCM/NEPCMs	106
5.2 Variation in thermophysical properties of PCM/NEPCM	109
5.3 Thermal performance evaluation of TES system with MWCNT based organic PCMs	118
5.3.1 Data reduction	118
5.3.2 Variation in Charging profile and liquid fraction of PCM/NEPCM	120
5.3.3 Variation in dimensionless numbers of PCM/NEPCM	125

5.3.4 Variation in heat transfer coefficient PCM/NEPCM	132
5.3.5 Variation in the heat transfer rate of PCM/NEPCM	135
5.4 Highlights	138
6. Comparative studies of inline & staggered tube bundles based TES system integrated with engine exhaust for cabin heating	139-178
6.1 Theoretical study on inline and staggered types tube bundles based TES system	139
6.1.1 Design description of TES system and governing equations	140
6.1.2 Results and discussion	144
6.2 Thermal performance of inline and staggered tube bundles type TES system integrated with IC engine.	155
6.2.1 Detail of experiment setup and procedure	156
6.2.2 Data Reduction	159
6.3 Application of the waste heat recovery for cabin heating	171
6.4 Economic analysis of PCMs /NEPCMs based on TES system	173
6.6 Highlights	176
7. Conclusions and Future Scope	179-184
7.1 Conclusions	179
7.2 Future scope	183
References	185-195
List of Publications	196
Appendix	197-214

LIST OF FIGURES

Fig. No.	Title	Page No.
Fig. 1.1	An internal combustion engine's typical energy distribution	2
Fig. 1.2	Classification chart of thermal energy storage	4
Fig. 1.3	Classification chart of Nanoparticles	10
Fig. 3.1	The Engine test rig	35
Fig. 3.2	The concentric cylindrical type TES system	36
Fig. 3.3	Samples of CA, LA, PW, and SA PCMs	37
Fig. 3.4	The shell and tube heat exchanger	38
Fig. 3.5	The HTF Storage tank	40
Fig. 3.6	The magnetic drive pump	40
Fig. 3.7	The rotameter	41
Fig. 3.8	PT100 type thermocouple	42
Fig. 3.9	Digital data logger	42
Fig. 3.10	The schematic diagram of an experimental setup	47
Fig.3.11	Flow chart of Experimental procedure	47
Fig.3.12	Schematic diagram of the problem under consideration	48
Fig. 3.13	Charging time of CA PCM with the mass fraction	53
Fig. 3.14	Charging time of LA PCM with the mass fraction	53
Fig. 3.15	Charging time of PW PCM with the mass fraction	53
Fig. 3.16	Charging time of SA PCM with the mass fraction	53
Fig. 3.17	Discharging time of CA PCM with the mass fraction	54
Fig. 3.18	Discharging time of LA PCM with the mass fraction	54

Fig. 3.19	Discharging time of PW PCM with the mass fraction	54
Fig. 3.20	Discharging time of SA PCM with the mass fraction	54
Fig. 3.21	Variation in energy of storage medium	55
Fig. 3.22	Variation in the energy efficiency of charging	56
Fig. 3.23	Variation in the energy efficiency of the integrated system	56
Fig. 3.24	Variation in the energy saved	57
Fig. 3.25	Variation in exergy of storage medium	59
Fig. 3.26	Variation in the exergy efficiency of charging	59
Fig. 3.27	Variation in the exergy efficiency of the integrated system	60
Fig. 3.28	Variation in the exergy saved	60
Fig. 4.1	Preparation steps of nano-additives based NEPCM	66
Fig. 4.2	Samples of Al ₂ O ₃ and CuO based NEPCMs	66
Fig. 4.3	The diagram (front view) of the experiment setup	68
Fig. 4.4	The diagram of the thermal storage system	69
Fig. 4.5(a)	Charging profile of CA (axial direction)	73
Fig. 4.5(b)	Charging profile of CA (radial direction)	73
Fig. 4.5(c)	Charging profile of CA+Al ₂ O ₃ (axial direction)	73
Fig. 4.5(d)	Charging profile of CA+Al ₂ O ₃ (radial direction)	73
Fig. 4.5(e)	Charging profile of CA+CuO (axial direction)	74
Fig. 4.5(f)	Charging profile of CA+CuO (radial direction)	74
Fig. 4.5(g)	Charging profile of CA	74

Fig. 4.5(h)	Charging profile of CA+Al ₂ O ₃	74
Fig. 4.6(a)	Charging profile of LA (axial direction)	75
Fig. 4.6(b)	Charging profile of LA (radial direction)	75
Fig. 4.6(c)	Charging profile of LA+Al ₂ O ₃ (axial direction)	76
Fig. 4.6(d)	Charging profile of LA+Al ₂ O ₃ (radial direction)	76
Fig. 4.6(e)	Charging profile of LA+CuO (axial direction)	76
Fig. 4.6(f)	Charging profile of LA+CuO (radial direction)	76
Fig. 4.6(g)	Charging profile of LA	77
Fig. 4.6(h)	Charging profile of LA+Al ₂ O ₃	77
Fig. 4.7(a)	Charging profile of PW (axial direction)	78
Fig. 4.7(b)	Charging profile of PW (radial direction)	78
Fig. 4.7(c)	Charging profile of PW+Al ₂ O ₃ (axial direction)	79
Fig. 4.7(d)	Charging profile of PW+Al ₂ O ₃ (radial direction)	79
Fig. 4.7(e)	Charging profile of PW+CuO (axial direction)	79
Fig. 4.7(f)	Charging profile of PW+CuO (radial direction)	79
Fig. 4.7(g)	Charging profile of PW	80
Fig. 4.7(h)	Charging profile of PW+Al ₂ O ₃	80
Fig. 4.8(a)	Charging profile of SA (axial direction)	81
Fig. 4.8(b)	Charging profile of SA (radial direction)	81
Fig. 4.8(c)	Charging profile of SA+Al ₂ O ₃ (axial direction)	81
Fig. 4.8(d)	Charging profile of SA+Al ₂ O ₃ (radial direction)	81
Fig. 4.8(e)	Charging profile of SA+CuO(axial direction)	82
Fig. 4.8(f)	Charging profile of SA+CuO (radial direction)	82
Fig. 4.8(g)	Charging profile of SA	82

Fig. 4.8(h)	Charging profile of SA+CuO	82
Fig. 4.9(a)	Overall heat transfer coefficient of CA with nano additives	84
Fig. 4.9(b)	Overall heat transfer coefficient of LA with nano additives	84
Fig. 4.9(c)	Overall heat transfer coefficient of PW with nano additives	85
Fig. 4.9(d)	Overall heat transfer coefficient of SA with nano additives	86
Fig. 4.10(a)	Heat extraction rate of capric acid with nano additives	87
Fig. 4.10(b)	Heat extraction rate of lauric acid with nano additives	88
Fig. 4.10(c)	Heat extraction rate of paraffin wax with nano additives	88
Fig. 4.10(d)	Heat extraction rate of stearic acid with nano additives	89
Fig. 4.11(a)	Heat transfer rate of capric acid with nano additives	90
Fig. 4.11(b)	Heat transfer rate of lauric acid with nano additives	90
Fig. 4.11(c)	Heat transfer rate of paraffin wax with nano additives	91
Fig. 4.11(d)	Heat transfer rate of stearic acid with nano additives	92
Fig. 4.12(a)	Heat storage for capric acid with nano additives	93
Fig. 4.12(b)	Heat storage for lauric acid with nano additives	93
Fig. 4.12(c)	Heat storage for paraffin wax with nano additives	94
Fig. 4.12(d)	Heat storage for stearic acid with nano additives	94
Fig. 4.13	Variation of charging energy efficiency	96
Fig. 4.14	Variation of energy saved	96

Fig. 4.15	Variation of charging exergy efficiency	98
Fig. 4.16	Variation of exergy saved	98
Fig. 5.1	The schematic diagram of an experimental setup	103
Fig. 5.2	Samples of MWCNT based Capric acid NEPCM	104
Fig. 5.3(a)	Solidification profile of capric acid PCM/NEPCM	107
Fig. 5.3(b)	Solidification profile of lauric acid PCM/NEPCM	107
Fig. 5.3(c)	Solidification profile of paraffin wax PCM/NEPCM	108
Fig. 5.3(d)	Solidification profile of stearic acid PCM/NEPCM	108
Fig. 5.3(e)	Temperature of distilled water during the cooling process	109
Fig. 5.4(a)	Specific heat capacity of capric acid PCM/NEPCM	110
Fig. 5.4(b)	Specific heat capacity of lauric acid PCM/NEPCM	111
Fig. 5.4(c)	Specific heat capacity of paraffin wax PCM/NEPCM	111
Fig. 5.4(d)	Specific heat capacity of stearic acid PCM/NEPCM	112
Fig. 5.5(a)	Thermal conductivity capric acid PCM/NEPCM	113
Fig. 5.5(b)	Thermal conductivity lauric acid PCM/NEPCM	113
Fig. 5.5(c)	Thermal conductivity paraffin wax PCM/NEPCM	114
Fig. 5.5(d)	Thermal conductivity stearic acid PCM/NEPCM	114
Fig. 5.6(a)	Latent heat of capric acid PCM/NEPCM	115
Fig. 5.6(b)	Latent heat of lauric acid PCM/NEPCM	115
Fig. 5.6(c)	Latent heat of paraffin wax PCM/NEPCM	116
Fig. 5.6(d)	Latent heat of stearic acid PCM/NEPCM	116
Fig. 5.7(a)	Charging profile of capric acid PCM/NEPCM	120
Fig. 5.7(b)	Charging profile of lauric acid PCM/NEPCM	121

Fig. 5.7(c)	Charging profile of paraffin wax PCM/NEPCM	121
Fig. 5.7(d)	Charging profile of stearic acid PCM/NEPCM	122
Fig. 5.8(a)	Liquid fraction of capric acid PCM/NEPCM	123
Fig. 5.8(b)	Liquid fraction of lauric acid PCM/NEPCM	123
Fig. 5.8(c)	Liquid fraction of paraffin wax PCM/NEPCM	124
Fig. 5.8(d)	Liquid fraction of stearic acid PCM/NEPCM	124
Fig. 5.9(a)	Fourier Number of capric acid PCM/NEPCM	125
Fig. 5.9(b)	Fourier Number of lauric acid PCM/NEPCM	126
Fig. 5.9(c)	Fourier Number of paraffin wax PCM/NEPCM	126
Fig. 5.9(d)	Fourier Number of stearic acid PCM/NEPCM	127
Fig. 5.10(a)	Rayleigh Number of capric acid PCM/NEPCM	128
Fig. 5.10(b)	Rayleigh Number of lauric acid PCM/NEPCM	128
Fig. 5.10(c)	Rayleigh Number of paraffin wax PCM/NEPCM	129
Fig. 5.10(d)	Rayleigh Number of stearic acid PCM/NEPCM	129
Fig. 5.11(a)	Nusselt Number of capric acid PCM/NEPCM	130
Fig. 5.11(b)	Nusselt Number of lauric acid PCM/NEPCM	131
Fig. 5.11(c)	Nusselt Number of paraffin wax PCM/NEPCM	131
Fig. 5.11(d)	Nusselt Number of stearic acid PCM/NEPCM	132
Fig. 5.12(a)	Heat transfer coefficient of capric acid PCM/NEPCM	133
Fig. 5.12(b)	Heat transfer coefficient of lauric acid PCM/NEPCM	133
Fig. 5.12(c)	Heat transfer coefficient of paraffin wax PCM/NEPCM	134
Fig. 5.12(d)	Heat transfer coefficient of stearic acid PCM/NEPCM	134
Fig. 5.13(a)	Heat transfer rate of capric acid PCM/NEPCM	136
Fig. 5.13(b)	Heat transfer rate of lauric acid PCM/NEPCM	136

Fig. 5.13(c)	Heat transfer rate of paraffin wax PCM/NEPCM	137
Fig. 5.13(d)	Heat transfer rate of stearic acid PCM/NEPCM	137
Fig. 6.1(a)	Inline tube arrangement	140
Fig. 6.1(b)	Staggered tube arrangement	140
Fig. 6.2(a)	Variation in air outlet temperature with tube diameter(D) at $u=2\text{m/s}$ and $l=0.3\text{m}$ (inline tube arrangement)	145
Fig. 6.2(b)	Variation in air outlet temperature with tube(D) diameter at $u=2\text{m/s}$ & $l=0.3\text{m}$ (Staggered tube arrangement)	145
Fig. 6.3(a)	Variation in air outlet temperature with air velocity(u) at $D=0.0254\text{m}$ and $l=0.3\text{m}$ (inline tube arrangement)	145
Fig. 6.3(b)	Variation in air outlet temperature with air velocity(u) at $D=0.0254\text{m}$ & $l=0.3\text{m}$ (Staggered tube arrangement)	145
Fig. 6.4(a)	Variation in air outlet temperature with length of tube(l) at $D=0.0254\text{m}$ & $u=2\text{m/s}$ (inline tube arrangement)	146
Fig. 6.4(b)	Variation in air outlet temperature with length of tube(l) at $D=0.0254\text{m}$ & $u=2\text{m/s}$ (Staggered tube arrangement)	146
Fig. 6.5(a)	Variation in pressure drop (δp) with tube(D) diameter at $u=2\text{m/s}$ & $l=0.3\text{m}$ (Inline tube arrangement)	148
Fig. 6.5(b)	Variation in pressure drop (δp) with tube(D) diameter at $u=2\text{m/s}$ & $l=0.3\text{m}$ (staggered tube arrangement)	148

Fig. 6.6(a)	Variation in pressure drop (δp) with air velocity(u) at $D=0.0254\text{m}$ & $l=0.3\text{m}$ (Inline tube arrangement)	148
Fig. 6.6(b)	Variation in pressure drop (δp) with air velocity(u) at $D=0.0254\text{m}$ & $l=0.3\text{m}$ (staggered tube arrangement)	148
Fig. 6.7(a)	Variation in Nusselt and Reynolds number with tube(D) diameter at $u=2\text{m/s}$ & $l=0.3\text{m}$ (Inline tube arrangement)	150
Fig. 6.7(b)	Variation in Nusselt and Reynolds number with tube(D) diameter at $u=2\text{m/s}$ & $l=0.3\text{m}$ (staggered tube arrangement)	150
Fig. 6.8(a)	Variation in Nusselt and Reynolds number with air velocity(u) at $D=0.0254\text{m}$ & $l=0.3\text{m}$ (Inline tube arrangement)	150
Fig. 6.8(b)	Variation in Nusselt and Reynolds number with air velocity(u) at $D=0.0254\text{m}$ & $l=0.3\text{m}$ (staggered tube arrangement)	150
Fig. 6.9(a)	Variation in convective heat transfer coefficient with tube diameter(D) at $u=2\text{m/s}$ and $l=0.3\text{m}$ (inline tube arrangement)	152
Fig. 6.9(b)	Variation in convective heat transfer coefficient with tube diameter(D) at $u=2\text{m/s}$ and $l=0.3\text{m}$ (Staggered tube arrangement)	152
Fig. 6.10(a)	Variation in convective heat transfer coefficient with air velocity(u) at $D=0.0254\text{m}$ and $l=0.3\text{m}$ (inline tube)	152

Fig. 6.10(b)	Variation in convective heat transfer coefficient with air velocity(u) at $D=0.0254\text{m}$ and $l=0.3\text{m}$ (Staggered tube arrangement)	152
Fig. 6.11(a)	Variation in energy transfer rate with tube diameter(D) at $u=2\text{m/s}$ and $l=0.3\text{m}$ (inline tube arrangement)	154
Fig. 6.11(b)	Variation in energy transfer rate with tube(D) diameter at $u=2\text{m/s}$ & $l=0.3\text{m}$ (Staggered tube arrangement)	154
Fig. 6.12(a)	Variation in energy transfer rate with air velocity(u) at $D=0.0254\text{ m}$ and $l=0.3\text{ m}$ (inline tube arrangement)	154
Fig. 6.12(b)	Variation in energy transfer rate with air velocity(u) at $D=0.0254\text{ m}$ & $l=0.3\text{ m}$ (Staggered tube arrangement)	154
Fig. 6.13(a)	Variation in energy transfer rate with length of tube(l) at $D=0.0254\text{m}$ & $u=2\text{m/s}$ (inline tube arrangement)	155
Fig. 6.13(b)	Variation in energy transfer rate with length of tube(l) at $D=0.0254\text{m}$ & $u=2\text{m/s}$ (Staggered tube arrangement)	155
Fig. 6.14(a)	Front view of the Experimental setup	156
Fig. 6.14(b)	Side view of the Experimental setup	157
Fig. 6.15(a)	Inline tubes arrangement	157
Fig. 6.15(b)	Staggered tubes arrangement	157
Fig. 6.16(a)	LA+0.1% Al_2O_3 (liquid state)	158
Fig. 6.16(b)	PW+0.02% MWCNT (liquid state)	158
Fig. 6.16(c)	SA+0.1% CuO (liquid state)	158
Fig. 6.16(d)	LA+0.1% Al_2O_3 (solid state)	158
Fig. 6.16(e)	PW+0.02% MWCNT (solid state)	158

Fig. 6.16(f)	SA+0.1% CuO (solid state)	158
Fig. 6.17(a)	Lauric acid filled in inline TES system	160
Fig. 6.17(b)	Lauric acid filled in staggered TES system	160
Fig. 6.17(c)	Lauric acid with Al ₂ O ₃ filled in inline TES system	161
Fig. 6.17(d)	Lauric acid with Al ₂ O ₃ filled in staggered TES system	161
Fig. 6.18(a)	Paraffin wax filled in inline TES system	162
Fig. 6.18(b)	Paraffin wax filled in staggered TES system	162
Fig. 6.18(c)	Paraffin wax with MWCNT filled in inline TES system	162
Fig. 6.18(d)	Paraffin wax with MWCNT filled in staggered TES system	162
Fig. 6.19(a)	Stearic acid filled in inline TES system	163
Fig. 6.19(b)	Stearic acid filled in staggered TES system	163
Fig. 6.19(c)	Stearic acid with Al ₂ O ₃ filled in inline TES system	163
Fig. 6.19(d)	Stearic acid with Al ₂ O ₃ filled in staggered TES system	163
Fig. 6.20(a)	Lauric acid PCM/NEPCM based TES system	164
Fig. 6.20(b)	Paraffin wax PCM/NEPCM based TES system	164
Fig. 6.20(c)	Stearic acid PCM/NEPCM based TES system	165
Fig. 6.21(a)	Lauric acid filled in inline TES system	166
Fig. 6.21(b)	Lauric acid filled in staggered TES system	166
Fig. 6.21(c)	Lauric acid with Al ₂ O ₃ filled in inline TES system	167
Fig. 6.21(d)	Lauric acid with Al ₂ O ₃ filled in staggered TES system	167
Fig. 6.22(a)	Paraffin wax filled in inline TES system	167
Fig. 6.22(b)	Paraffin wax filled in staggered TES system	167
Fig. 6.22(c)	Paraffin wax with MWCNT filled in inline TES system	168
Fig. 6.22(d)	Paraffin wax with MWCNT filled in staggered TES system	168

Fig. 6.23(a)	Stearic acid filled in inline TES system	168
Fig. 6.23(b)	Stearic acid filled in staggered TES system	168
Fig. 6.23(c)	Stearic acid with Al ₂ O ₃ filled in inline TES system	169
Fig. 6.23(d)	Stearic acid with Al ₂ O ₃ filled in staggered TES system	169
Fig. 6.24(a)	Lauric acid PCM/NEPCM based TES system	170
Fig. 6.24(b)	Paraffin wax PCM/NEPCM based TES system	170
Fig. 6.24(c)	Stearic acid PCM/NEPCM based TES system	171
Fig. 6.25	Experiment apparatus with cabin attachment	172
Fig. 6.26(a)	Variation in cabin temperature at air velocity 2m/s	172
Fig. 6.26(b)	Variation in cabin temperature at air velocity 3m/s	172
Fig. 6.26(c)	Variation in-cabin temperature at air velocity 4m/s	173
Fig. 6.27	Payback duration of PCMs/NEPCMs based TES system	175

LIST OF TABLES

Table No.	Title	Page No.
Table 3.1	Specification of Diesel Engine	35
Table 3.2	Specification of Concentric cylindrical TES system	36
Table 3.3	Specification of shell and tube heat exchanger	39
Table 3.4	Specification of digital data logger	43
Table 3.5	Accuracy of Instruments	44
Table 3.6	Calculated maximum uncertainties	45
Table 3.7	Validation of experimental parameters	61
Table 4.1	Properties obtained by the Hot disk analyzer	67
Table 4.2	Energy density of PCMs/NEPCMs based TES system	95
Table 5.1	Specification of the experimental instruments	104
Table 5.2	Accuracy of Instruments	104
Table 5.3	Calculated maximum uncertainties	105
Table 5.4	Thermo-physical data obtained for 0.02% MWCNT based NEPCMs by T-history method and Hot disk analyzer	118
Table 6.1	The geometrical description of the TES system	141
Table 6.2	Specification of tubes used in TES systems	159
Table A.1	Organic PCMs with its thermo-physical	197
Table A.2	Inorganic PCMs with its thermo-physical	200
Table A.3	Eutectics PCMs with its thermo-physical	202
Table A.4	Nano-enhanced PCMs with its thermo-physical	205
Table B.1	The past literature on the inorganic PCM based of TES	208

	system	
Table B.2	Enhancement of thermophysical properties in NEPCM based TES system studied in the past literature	209
Table B.3	Enhancement of thermophysical properties in TES system by applying SWCNT/MWCNT based PCM studied in the past literature	211
Table B.4	Tubes bundles arrangement based TES system studied in the past literature	212
Table B.5	The past literature on the applications of the TES system	213
