

# Table of Contents

|   |              |
|---|--------------|
| <b>Table of Contents .....</b>  | <b>i</b>     |
| <b>Abstract.....</b>  | <b>v</b>     |
| <b>Acknowledgement .....</b>  | <b>xi</b>    |
| <b>List of Figures.....</b>   | <b>xv</b>    |
| <b>List of Tables .....</b>   | <b>xxiii</b> |
| <b>List of Acronyms .....</b>   | <b>xxiv</b>  |
| <b>Symbols Used.....</b>  | <b>xxvii</b> |
| <b>Chapter 1. Introduction.....</b>   | <b>1</b>     |
| 1.1 Background.....   | 1            |
| 1.2 Motivation .....  | 2            |
| 1.3 Literature Survey.....  | 7            |
| 1.3.1 Resonant Dual Active Bridge Converters for Optimal Battery Charging.....  | 7            |
| 1.3.2 Fractional Power Processor for Ultra-fast Charging.....   | 12           |
| 1.3.3 Inter-Operable Multi-Utility Charger with V2Aux, V2V and Fast charging<br>Capability.....   | 16           |
| 1.3.4 Quad-Operative Fractional Processor with Step Up/Down Capability for Wide<br>Voltage EV Charging Applications .....                 | 20           |
| 1.4 Challenges with the Existing System.....  | 22           |
| 1.5 Objective of the Thesis .....   | 25           |
| 1.6 Organization of the Thesis.....   | 26           |
| <b>Chapter 2. A Current-Driven Resonant Dual Active Bridge Converter with Dual Source<br/>Property for Optimal Battery Charging .....</b> | <b>29</b>    |
| 2.1 Introduction .....  | 29           |
| 2.2 The Proposed Optimal Battery Charger.....   | 31           |
| 2.2.1 Circuit Configuration.....  | 32           |
| 2.2.2 Modulation Strategy .....   | 33           |
| 2.2.3 Operation as Parallel Resonant Converter .....  | 34           |
| 2.3 Operation Principle and State Plane Analysis of the Proposed Charger.....   | 35           |
| 2.3.1 Intervals with State Plane Trajectory.....  | 36           |
| 2.3.1 Closed Form Solution of State Plane Analysis.....   | 42           |
| 2.4 Performance Analysis of Proposed Optimal Battery Charger .....  | 43           |
| 2.4.1 CC-CV Behavior: The M-J Characteristics of Proposed Charger .....   | 45           |
| 2.4.2 Charger Output in CC and CV Mode .....  | 45           |
| 2.5 Design of the converter.....  | 46           |

|   |   |           |
|---|---|-----------|
| 2.5.1   | Transformer Turn Ratio .....  | 46        |
| 2.5.2   | Design of Magnetics Component.....  | 46        |
| 2.5.1   | Selection of Input Capacitor .....  | 48        |
| 2.5.2   | Selection of Input Inductor .....   | 48        |
| 2.6   | Experimental Verification.....  | 49        |
| 2.6.1   | Steady State Performance of the Proposed Charger .....                                  | 50        |
| 2.6.2   | Soft Switching Performance .....  | 53        |
| 2.6.3   | Dynamic Performance of the Proposed Charger.....  | 55        |
| 2.6.4   | Transition from CC to CV Mode .....   | 57        |
| 2.6.5   | Cost Comparison with Existing Literature.....   | 59        |
| 2.7   | Conclusion .....  | 65        |
| <b>Chapter 3. A Current Driven Fractional Power Processor for Ultra-Fast Charging .....</b>   |   | <b>67</b> |
| 3.1   | Introduction.....   | 67        |
| 3.2   | The Concept of Fractional Power Processing .....  | 67        |
| 3.3   | The proposed FPP-based Current Driven Ultra-Fast Charger .....                          | 72        |
| 3.3.1   | Configuration of the Proposed Charger .....   | 70        |
| 3.3.2   | Operation of the Proposed Charger.....  | 70        |
| 3.3.3   | Current and Voltage Matrices of the Proposed Charger .....                              | 74        |
| 3.4   | Performance Analysis of Proposed Ultra-Fast Charger .....                               | 76        |
| 3.4.1   | Effect of Fractionality Ratio, K .....  | 76        |
| 3.4.2   | Effect of Phase Shift Control .....   | 78        |
| 3.4.3   | Effect of Fractionality on Component Selection and Loss Reduction .....                 | 80        |
| 3.4.4   | Effect of Fractionality on Charger Cost.....  | 80        |
| 3.4.5   | Simultaneous Charging and Vehicle Isolation Monitoring.....                             | 81        |
| 3.5   | Experimental Validation of Proposed Charger .....                                       | 82        |
| 3.5.1   | Steady State Behavior of the Proposed Charger .....                                     | 82        |
| 3.5.2   | Phase Control Behavior of the Proposed Charger.....                                     | 86        |
| 3.5.3   | Dynamic Response of the Converter .....   | 88        |
| 3.5.4   | Comparison with Full-Power Processing Charger.....                                      | 89        |
| 3.5.5   | Comparison with Other FPP Literature .....  | 92        |
| 3.6   | Conclusion .....  | 92        |
| <b>Chapter 4. Inter-Operable Multi-Utility Fast Charger with V2Aux and V2V Capability .95</b> |   |           |
| 4.1   | Introduction.....   | 95        |
| 4.2   | Proposed Interoperable Multi-utility Charger.....                                       | 97        |
| 4.2.1   | Circuit Configuration of Proposed Multi-Utility Charger.....                            | 97        |
| 4.2.2   | Working of the Proposed Charger in Each Mode .....                                      | 99        |
| 4.2.3   | Switching Strategy and Operating Principle of the Proposed Converter in each Mode ..... | 100       |

|   |  |            |
|---|--|------------|
| 4.3   | Performance Analysis of the Proposed Charger .....   | 105        |
| 4.3.1   | Performance as a Current Source and a Voltage Source .....   | 105        |
| 4.3.2   | Performance as a Fractional Power Processor .....  | 108        |
| 4.3.3   | Behavior with varying fractionality ratio, $K$ .....   | 108        |
| 4.4   | Design of the Proposed Charger .....   | 110        |
| 4.4.1   | Selection of switches .....  | 110        |
| 4.4.2   | Choice of transformer turn ratio .....   | 112        |
| 4.4.3   | Choice of resonant tank parameters.....  | 112        |
| 4.5   | Experimental Validation.....   | 113        |
| 4.5.1   | Performance Validation of FPP Fast Charging Mode .....   | 113        |
| 4.5.2   | Performance Validation of Charger in V2Aux mode .....  | 117        |
| 4.5.3   | Performance Validation of Charger in V2V mode .....  | 119        |
| 4.5.4   | Comparison and Discussion .....  | 122        |
| 4.6   | Conclusion.....  | 122        |
| <b>Chapter 5. Quad-Operative Fractional Processor for Wide Battery Voltage EV Charging Applications .....</b> |  | <b>125</b> |
| 5.1   | Introduction .....   | 125        |
| 5.2   | The Proposed Quad-Operative Fractional Processor for Wide Battery Voltage .....  | 126        |
| 5.2.1   | Circuit Configuration.....   | 128        |
| 5.3   | Operation and Analysis of the Proposed EV Charger .....  | 128        |
| 5.3.1   | Operation of Quad-Operational Charger in Buck Mode: Quadrant II ( $V_{bat} < V_{dc}$ , $I_{bat} > 0$ ) and Quadrant III ( $V_{bat} < V_{dc}$ , $I_{bat} < 0$ ) ..... | 137        |
| 5.3.1   | Operation of Quad-Operational Charger in Boost Mode Quadrant I ( $V_{bat} > V_{dc}$ , $I_{bat} > 0$ ) and Quadrant IV ( $V_{bat} > V_{dc}$ , $I_{bat} < 0$ ).....    | 133        |
| 5.4   | Verification.....  | 134        |
| 5.4.1   | Operation in Boost Mode, Forward Power Flow.....   | 134        |
| 5.4.2   | Operation in Buck Mode, Forward Power Flow.....  | 136        |
| 5.4.3   | Operation in Boost Mode, Reverse Power Flow .....  | 138        |
| 5.4.4   | Operation in Buck Mode, Reverse Power Flow .....   | 138        |
| 5.5   | Conclusion.....  | 139        |
| <b>Chapter 6. Conclusion and Scope of Future Work .....</b>   |  | <b>141</b> |
| 6.1   | Introduction .....   | 141        |
| 6.2   | Conclusion.....  | 142        |
| 6.3   | Scope of Future Work.....  | 144        |
| <b>Bibliography .....</b>   |  | <b>147</b> |
| <b>List of Publications.....</b>  |  | <b>159</b> |

