

CONTENTS

<i>List of Figures</i>	<i>xix</i>
<i>List of Tables</i>	<i>xxv</i>
<i>List of Abbreviations</i>	<i>xxvii</i>
<i>List of symbols</i>	<i>xxxi</i>
<i>Preface</i>	<i>xxxv</i>
CHAPTER 1: INTRODUCTION AND LITERATURE REVIEW.....	1
1.1 Introduction	1
1.2 Overview of High-Power Microwave Sources	3
1.2.1 Prime Power Supply	5
1.2.2 Pulse Power Supply	5
1.2.3 HPM Sources.....	7
1.2.4 Mode Convertor.....	8
1.2.5 Antenna.....	9
1.3 Overview of different HPM Sources.....	10
1.3.1 Relativistic Klystron Amplifier	12
1.3.2 Relativistic Magnetron	14
1.3.3 Virtual Cathode Oscillators (VCO or Vircator)	16
1.3.4 Magnetically Insulated Line Oscillator (MILO)	17
1.3.5 Reltron	20
1.3.6 Free Electron Laser.....	22
1.3.7 Relativistic Gyrotron Devices	23
1.4 Relativistic Backward Wave Oscillator (RBWO).....	24
1.4.1 Advantages of an RBWO	26
1.4.2 Applications of an RBWO.....	27
1.5 Literature Review of an RBWO.....	29
1.6 Problem Definition.....	34
1.7 Outline of the Thesis	35
1.8 Conclusion.....	39
CHAPTER 2: DESIGN INVESTIGATIONS AND PIC SIMULATION OF SIBGLE FREQUENCY RELATIVISTIC BACKWARD WAVE OSCILLATOR.....	43
2.1 Introduction	43
2.2 Operating Principle and Condition for Sustained Oscillation.....	45

2.3 Modeling of Sub-Assemblies	48
2.3.1 Annular Cathode	49
2.3.2 Reflector.....	50
2.3.3 Slow Wave Structure (SWS)	55
2.3.4 Tapered Waveguide Collector	57
2.3.5 Guiding Magnetic Field	58
2.4 Analytical Background of Relativistic BWO	589
2.4.1 Beam Power of thin annular electron beam.....	59
2.4.2 Dispersion Relation Sinusoidally Corrugated SWS	62
2.5 Simulation Results and Discussion.....	65
2.5.1 Cold Simulation	67
2.5.2 Particle-In-Cell (PIC) Simulation	68
2.6 Parametric Analysis and Discussion.....	70
2.6.1 Beam Voltage (V_b)	70
2.6.2 Corrugation Amplitude (r_0).....	71
2.6.3 Drift Length (L_{dr})	72
2.6.4 Magnetic Field (B)	73
2.7 Conclusion	74
CHAPTER 3: MODELLING OF RF PULSE SHORTENING CAUSES AND THEIR EFFECTS ON RBWO UNDER LOW GUIDING MAGNETIC FIELD	79
3.1 Introduction	79
3.2 Overview of Simulation Techniques in VED's.....	80
3.3 Design and Simulation of Non-Overmoded RBWO with RR.....	82
3.4 Simulation Study of RF Pulse Shortening.....	87
3.4.1 Modeling of various causes of RF pulse shortening.....	87
3.4.2 Simulation Study of Combined Causes of RF Pulse Shortening and their effects in RBWO Operation.....	92
3.5 Conclusion.....	98
CHAPTER 4: DESIGN AND SIMULATION INVESTIGATIONS OF S-BAND RBWO WITH SECTIONAL BRAGG REFLECTOR.....	103
4.1 Introduction	103
4.2 Bragg Reflector.....	105
4.2.1 Design Methodology.....	105
4.2.2 Coupling Coefficient and Power Reflection/Conversion Coefficient	1077

4.2.3 Cold analysis of Sectional BRAGG Structure.....	108
4.3 Slow Wave Structure (SWS).....	109
4.4 Modelling of PIC Simulation Results	110
4.5 Parametric Analysis	114
4.5.1 Effect on frequency and RF power with magnetic field.....	114
4.5.2 Effect on frequency and RF power with magnetic field.....	115
4.5.3 Effect on RF output power and frequency with Drift section-II	115
4.6 Conclusion.....	116
CHAPTER 5: DESIGN AND SIMULATION INVESTIGATIONS DUAL-BAND (S-AND C-	
BAND) RBWO WITH SECTIONAL SLOW-WAVE STRUCTURES	121
5.1 Introduction	121
5.2 Design of Dual-Band RBWO with Sectional SWS's	123
5.2.1 Sectional Slow-Wave Structures (SWS-I and -II).....	123
5.2.2 Rectangular Resonant Reflector (RR)	125
5.2.3 Drift Section-I.....	127
5.2.4 Drift Section-II	127
5.3 PIC Simulation of Dual Band RBWO	128
5.4 Parametric Analysis and Discussion	132
5.4.1 Effect on frequency generation and RF power by drift section-I and drift	
section-II (L_{dr1} and L_{dr2})	133
5.4.2 Effect on frequency and RF power by DC magnetic field	135
5.4.3 Effect on frequency and RF power by beam voltage	137
5.5 Conclusion.....	138
CHAPTER 6: DESIGN AND SIMULATION INVESTIGATIONS OF DUAL-BAND (S-AND C-	
BAND) RBWO WITH BRAGG REFLECTOR FOR DIRECT GENERATION OF GAUSSIAN	
PULSE.....	143
6.1 Introduction	143
6.2 Design Methodology of Bragg Reflector and Slow-Wave Structure.....	145
6.2.1 Design Methodology of BRAGG Structure	145
6.3 Slow Wave Structure (SWS).....	151
6.3.1 Design Methodology	151
6.3.2 Cold Dispersion Diagram of Slow Wave Structure	154
6.4 Cut-off Neck Reflector and Drift Sections.....	155
6.5 Tapered Waveguide Collector.....	155

6.6 PIC simulation of Dual band RBWO	158
6.7 Parametric Analysis	163
6.7.1 Effect on frequency and average RF output power with magnetic field.	163
6.8 Conclusion	164
CHAPTER 7: CONCLUSION AND FUTURE SCOPE	169
7.1 Conclusion	169
7.2 Limitations of the Present Work and Future Scope.....	169

LIST OF FIGURES

Figure 1.1: Application domain of HPM at a different frequency and Power level [3].	3
Figure 1.2: Block diagram of an HPM system [3].	4
Figure 1.3: Comparison of HPM sources and conventional microwave sources with respect to optimal impedance and voltage [3].	6
Figure 1.4: Generalized block diagram for linear beam microwave tubes.	9
Figure 1.5: 2D Schematic of HPM source relativistic klystron amplifier (RKA).	13
Figure 1.6: 2D Schematic of HPM source relativistic magnetron (RM).	15
Figure 1.7: 2D Schematic of HPM source virtual cathode oscillator (VCO).	17
Figure 1.8: 2D Schematic of HPM source MILO.	19
Figure 1.9: 2D Schematic of HPM source Reltron.	20
Figure 1.10: Schematic of a FEL with planer wiggler.	22
Figure 1.11: All types of Gyro devices [11].	23
Figure 1.12: 2D Schematic of HPM source RBWO.	25
Figure 1.13: Domains and trends of HPM DEW and EWF [6].	28
Figure 2.1: Schematic of RBWO with overmoded SWS and TRR.	45
Figure 2.2: Working principle for sustained oscillation.	46
Figure 2.3: The Brillouin diagram of the slow-Wave Structure.	48
Figure 2.4: Schematic of cut-off neck reflector.	51
Figure 2.5: Schematic of Cavity RR.	54
Figure 2.6: Schematic of Trapezoidal RR (TRR).	54
Figure 2.7: 2D Schematic of sinusoidal rippled wall SWS. of the sinusoidally corrugated.	57
Figure 2.8: 2D Schematic of a tapered collector.	58
Figure 2.9: A schematic picture of a dispersion relation of TM_{01} mode in infinitely long periodic structure. Two straight lines that intersect the cold structure dispersion curve correspond to Cerenkov and cyclotron beam modes.	58
Figure 2.10: The dependence of beam current on γb .	61
Figure 2.11: The dispersion curve of the beam mode line (1.2 MV) with the TM_{01} mode line.	65
Figure 2.12: Absolute electric field distribution in contour of a cold test, (a) RR and (b) TRR.	67

Figure 2.13: The simulation model of RBWO having an electron beam.....	68
Figure 2.14: RF output powers for the Overmoded RBWO with different reflectors. ..	68
Figure 2.15: (a) Frequency spectrum and (b) The time-frequency of the electric field. 69	
Figure 2.16: Fundamental TM_{01} mode electric field distribution of (a) vector and (b) contour plot.	69
Figure 2.17: Beam voltage depends on (a) RF output power and efficiency and (b) frequency.....	71
Figure 2.18: Influence of developed beam current on RF output power.	71
Figure 2.19: Influence of corrugation amplitude on (a) frequency and (b) RF output power with different periods.	72
Figure 2.20: RF output power and frequency w.r.t drift length.	72
Figure 2.21: RF output power and frequency w.r.t magnetic field.	73
Figure 3.1: 2D Model simulation structure of non-overmoded RBWO ($D/\lambda \approx 1.17$) with RR under guiding magnetic field ~ 0.22 T and DC input voltage 550 kV.	83
Figure 3.2: RF output power versus magnetic field for non-overmoded RBWO ($D/\lambda \approx 1.17$) for the DC input voltage 550 kV. The cyclotron resonances magnetic fields are found at $B_1 \approx 0.10$ T and $B_2 \approx 0.57$ T.	83
Figure 3.3: (a) RF output power and (b) FFT of the RF output signal of non-overmoded RBWO ($D/\lambda \approx 1.52$) with RR under guiding magnetic field of ~ 0.22 T.	84
Figure 3.4: RF output power versus magnetic field for overmoded RBWO ($D/\lambda \approx 1.52$) for the DC input voltage 550 kV. The cyclotron resonances magnetic fields are found at $B_1 \approx 0.07$ T and $B_2 \approx 0.49$ T.	86
Figure 3.5: 2D The Schematic of Trapezoidal Resonant Reflector (TRR).....	86
Figure 3.6: Dispersion curve for (a) non-overmoded RBWO and (b) overmoded RBWO showing TM_{01} mode line and beam mode line intersecting at ~ 3.7 GHz.	86
Figure 3.7: (a) Developed electron beam current ~ 5.9 kA, and (b) DC beam power (voltage*current) ~ 3.25 GW when the applied beam voltage is 550 kV.	87
Figure 3.8: Phase space plot of traversed electrons (at the end of SWS) in radial momentum at ~ 100 ns in (a) non-overmoded RBWO ($D/\lambda \approx 1.17$) with RR at $B = \sim 0.22$ T, (b) non-overmoded RBWO with TRR $B = \sim 0.22$ T, (c) overmoded RBWO ($D/\lambda \approx 1.52$) with RR at $B = \sim 0.19$ T, and (d) overmoded RBWO with TRR at $B = \sim 0.19$ T.	88
Figure 3.9: Phase space plot distribution showing combined influences of SEE (yellow color), HEE (blue color), PCHI (green color) at ~ 100 ns in (a) non-overmoded RBWO ($D/\lambda \approx 1.17$) with RR at $B = \sim 0.22$ T, (b) non-overmoded RBWO with TRR at $B = \sim 0.22$	

T, (c) overmoded RBWO with ($D/\lambda \approx 1.52$) RR at $B = \sim 0.19$ T, and (d) overmoded RBWO with TRR at $B = \sim 0.19$ T.	89
Figure 3.10: Variation of temperature at the collector conducting wall w.r.t to time for (a) non-overmoded SWS, and (b) overmoded SWS.	91
Figure 3.11: Contour plot of the RF electric field at ~ 100 ns in non-overmoded RBWO ($D/\lambda \approx 1.17$) with RR under the guiding magnetic field ~ 0.22 T.	93
Figure 3.12: Contour plot of the RF electric field at ~ 100 ns in non-overmoded RBWO ($D/\lambda \approx 1.17$) with TRR under the guiding magnetic field ~ 0.22 T.	93
Figure 3.13: Contour plot of the RF electric field at ~ 100 ns in an overmoded RBWO ($D/\lambda \approx 1.52$) with RR under the guiding magnetic field ~ 0.19 T.	93
Figure 3.14: Contour plot of the RF electric field at ~ 100 ns in an overmoded RBWO ($D/\lambda \approx 1.52$) with TRR under the guiding magnetic field ~ 0.19 T.	94
Figure 3.15: RF output power for all four configurations of RBWOs after including the combined causes of pulse shortening.	94
Figure 4.1: 2D Model of Dual-Band RBWO using Bragg Structure.	105
Figure 4.2: (a) 2D longitudinal cut view of Sectional Bragg Structure.	106
Figure 4.3: Reflection or conversion coefficient vs number of Bragg axial periods. ...	108
Figure 4.4: Dispersion diagram of Sectional Bragg reflector.	109
Figure 4.5: Dispersion Diagram of Bragg Structure.	110
Figure 4.6: 2D simulation configuration of the RBWO with sectional Bragg reflector and intense relativistic electron beam particles.	111
Figure 4.7: (a) DC beam voltage (550 kV) and (b) Developed electron beam current (~ 4.66 kA).	112
Figure 4.8: Instantaneous and average RF output power of the dual-band RBWO with sectional SWS's.	112
Figure 4.9: FFT of the generated HPM wave for RBWO with Sectional Bragg reflector.	113
Figure 4.10: Time-Frequency plot showing generation of frequency.	113
Figure 4.11: Contour plots for the generated mode for both bands at two different time instants.	113
Figure 4.12: Effect of guiding magnetic field on RF power and frequency.	114
Figure 4.13: Effect of beam voltage on RF power.	115
Figure 4.14: Effect of drift section length (L_{dr2}) on RF output power, and frequency.	115

Figure 5.1: 2D simulation configuration of the dual-band RBWO with sectional SWS and intense relativistic electron beam particles.....	125
Figure 5.2: Dispersion curve of TM_{01} mode and beam mode line of (a) SWS-I and (b) SWS-II.....	125
Figure 5.3: CST cold simulation model of the present dual-band RBWO	126
Figure 5.4: Reflection and transmission coefficients of (a) both RR and drift section-II are present, and (b) only drift section-II is present.	126
Figure 5.5: a) Applied beam voltage in b/w anode and cathode, and b) Developed beam current at the entrance of SWS-I of the present dual-band RBWO.	129
Figure 5.6: Instantaneous and average RF output power of the dual-band RBWO with sectional SWS's.....	129
Figure 5.7: Dual-band axial electric field variation vs time at the end of the simulation.	129
Figure 5.8: The Frequency spectrum of dual-band RBWO with sectional SWS's.....	130
Figure 5.9: Phase-space distribution of electron energy along the axial direction of sectional SWS's at (a) ~6 ns, (b) ~9.8 ns, (c) ~50 ns, and (d) ~100 ns of simulation time (SWS-I region from 250 mm to 500 mm, and SWS-II region from 520 mm to 700 mm).	131
Figure 5.10: Time-frequency spectrogram of the axial electric field (Fig. 5.7).....	132
Figure 5.11: Distribution of axial E-field in the present dual-band RBWO.	132
Figure 5.12: Effect of drift section-I length on (a) time-frequency spectrogram and (b) RF power.	134
Figure 5.13: Effect of drift section-II length on (a) time-frequency spectrogram and (b) RF power.	135
Figure 5.14: Effect of guiding magnetic field on (a) dual-band frequency generation and (b) RF power.....	136
Figure 5.15: Effect of beam voltage on a) dual-band frequency and (b) RF power. ...	137
Figure 6.1: 2D Model of Dual-Band RBWO using Bragg Structure.....	144
Figure 6.2: (a) 2D longitudinal cut view and (b) 3D model of Bragg Structure.....	146
Figure 6.3: Reflection or conversion coefficient Vs (a) Frequency for different N and (b) number of Bragg axial periods for different corrugation depth (R1).	146
Figure 6.4: (a) 3D View of Bragg reflector, and (b) 3D Cut view of Bragg reflector.	148

Figure 6.5: TM ₀₁ mode converted (reflected) from the end of Bragg reflector to TE ₁₁ mode to the end of Bragg reflector (S ₂ (TE ₁₁),2(TM ₀₁)), and the converted (reflected) TE ₁₁ mode penetration at the beginning of Bragg reflector (S ₁ (TE ₁₁),2(TM ₀₁)).	148
Figure 6.6: TM ₀₁ mode reflected from and to the end of Bragg reflector (S ₂ (TE ₀₁),2(TM ₀₁)), and TM ₀₁ mode penetration at the beginning of Bragg reflector (S ₁ (TE ₀₁),2(TM ₀₁)).	148
Figure 6.7: Mode pattern at the output port after mode conversion/reflection from TM ₀₁ at the output port (port 2), i.e., S ₂ (TE ₁₁),2(TM ₀₁).	149
Figure 6.8: Validation of reflection coefficient Vs number of Bragg axial periods using analytical and simulation techniques.	149
Figure 6.9: Dispersion diagram of Bragg structure.	150
Figure 6.10: 2D Schematic of sinusoidal rippled wall SWS.	151
Figure 6.11: (a) Dependence on beam current I _b on ω and (b) Dependence on beam current I _{scl} on V ₀ for different r _b /r ₀ .	154
Figure 6.12: Dispersion diagram for SWS in C-Band.	155
Figure 6.13: 2D schematic shows cathode, cut-off neck reflector and drift Section-1.	156
Figure 6.14: 2D schematic of drift Section-2 separating Bragg and slow wave structures.	156
Figure 6.15: 2D schematic of tapered collector section.	156
Figure 6.16: 2D Model simulation structure of Dual-band RBWO with Bragg reflector under guiding magnetic field 2.0 T and DC input voltage 550 kV.	159
Figure 6.17: Developed electron beam current.	159
Figure 6.18: Instantaneous RF output power.	160
Figure 6.19: Average RF output power with DC input voltage 550 kV.	160
Figure 6.20: FFT of the generated HPM wave for dual-band frequency.	161
Figure 6.21: Particle energy distribution with the function of axial direction at different instances of time.	162
Figure 6.22: Time-Frequency plot showing generation of dual-band frequencies.	162
Figure 6.23: Contour plots of the radial electric field showing linearly polarized TE ₁₁ generated mode shown at a different simulation time.	163
Figure 6.24: Effect of guiding magnetic field on (a) Dual-band frequency generation and (b) RF power.	164

LIST OF TABLES

Table 1.1: Classifications of HPM Sources	7
Table 1.2: Comparison of various experimentally tested HPM Sources	27
Table 2.1: Design Parameters of an S-band RBWO	66
Table 2.2: Comparison of proposed work with previous works.....	70
Table 3.1: Design Parameters for the four configurations of RBWOs.....	84
Table 3.2: Output parameters of all four configurations of RBWOs after Pulse shortening Analysis.....	97
Table 4.1: Design Parameters of Sectional Bragg Reflector.	108
Table 4.2: Design Parameters of SWS.....	110
Table 5.1: Structural Parameters of the Present Dual-Band RBWO.	128
Table 6.1: Optimized Design Parameters of Dual-Band RBWO using Bragg Reflector.	157