

REFERENCES

- [1] K. Vignarooban, X. Xu, A. Arvay, K. Hsu, and A. M. Kannan, “Heat transfer fluids for concentrating solar power systems – A review,” *Appl. Energy*, vol. 146, pp. 383–396, 2015, doi: 10.1016/j.apenergy.2015.01.125.
- [2] H. Benoit, L. Spreafico, D. Gauthier, and G. Flamant, “Review of heat transfer fluids in tube-receivers used in concentrating solar thermal systems: Properties and heat transfer coefficients,” *Renew. Sustain. Energy Rev.*, vol. 55, pp. 298–315, 2016, doi: 10.1016/j.rser.2015.10.059.
- [3] S. Akbarzadeh and M. S. Valipour, “Heat transfer enhancement in parabolic trough collectors: A comprehensive review,” *Renew. Sustain. Energy Rev.*, vol. 92, pp. 198–218, 2018, doi: 10.1016/j.rser.2018.04.093.
- [4] V. Pranesh, R. Velraj, S. Christopher, and V. Kumaresan, “A 50 year review of basic and applied research in compound parabolic concentrating solar thermal collector for domestic and industrial applications,” *Sol. Energy*, vol. 187, pp. 293–340, 2019, doi: 10.1016/j.solener.2019.04.056.
- [5] S. Kalogirou, “The potential of solar industrial process heat applications,” *Appl. Energy*, vol. 76, no. 4, pp. 337–361, 2003, doi: 10.1016/S0306-2619(02)00176-9.
- [6] P. Saini, J. Singh, and J. Sarkar, “Proposal and performance comparison of various solar-driven novel combined cooling, heating and power system topologies,” *Energy Convers. Manag.*, vol. 205, p. 112342, 2020, doi: 10.1016/j.enconman.2019.112342.
- [7] M. A. Haghghi, S. M. Pesteei, A. Chitsaz, and J. Hosseinpour, “Thermodynamic investigation of a new combined cooling, heating, and power (CCHP) system driven by parabolic trough solar collectors (PTSCs): A case study,” *Appl. Therm. Eng.*, vol. 163, p. 114329, 2019, doi: 10.1016/j.applthermaleng.2019.114329.
- [8] E. Bellos, C. Tzivanidis, and K. A. Antonopoulos, “A detailed working fluid

- investigation for solar parabolic trough collectors,” *Appl. Therm. Eng.*, vol. 114, pp. 374–386, 2017, doi: 10.1016/j.applthermaleng.2016.11.201.
- [9] E. Bellos and C. Tzivanidis, “Thermal analysis of parabolic trough collector operating with mono and hybrid nanofluids,” *Sustain. Energy Technol. Assessments*, vol. 26, pp. 105–115, 2018, doi: 10.1016/j.seta.2017.10.005.
- [10] X. Y. Tang, W. W. Yang, Y. Yang, Y. H. Jiao, and T. Zhang, “A design method for optimizing the secondary reflector of a parabolic trough solar concentrator to achieve uniform heat flux distribution,” *Energy*, vol. 229, p. 120749, 2021, doi: 10.1016/j.energy.2021.120749.
- [11] E. E. G. Rojas, J. S. R. Coimbra, and J. Telis-romero, “Thermophysical Properties of Cotton , Canola , Sunflower and Soybean Oils as a Function of Temperature,” *Int. J. Food Prop.*, vol. 16, pp. 1620–1629, 2013, doi: 10.1080/10942912.2011.604889.
- [12] O. O. Fasina and Z. Colley, “Viscosity and specific heat of vegetable oils as a function of temperature: 35°C to 180°C,” *Int. J. Food Prop.*, vol. 11, no. 4, pp. 738–746, 2008, doi: 10.1080/10942910701586273.
- [13] J. F. Hoffmann *et al.*, “Temperature dependence of thermophysical and rheological properties of seven vegetable oils in view of their use as heat transfer fluids in concentrated solar plants,” *Sol. Energy Mater. Sol. Cells*, vol. 178, pp. 129–138, 2018, doi: 10.1016/j.solmat.2017.12.037.
- [14] Y. Krishna, M. Faizal, R. Saidur, K. C. Ng, and N. Aslfattahi, “State-of-the-art heat transfer fluids for parabolic trough collector,” *Int. J. Heat Mass Transf.*, vol. 152, p. 119541, 2020, doi: 10.1016/j.ijheatmasstransfer.2020.119541.
- [15] A. Gomna, K. E. N. Tsoukpoe, and N. Le Pierrès, “Thermal stability of a vegetable oil-based thermal fluid at high temperature,” *African J. Sci. Technol. Innov. Dev.*, vol. 12, pp. 1–10, 2020, doi: 10.1080/20421338.2020.1732080.

- [16] A. K. Hussein, “Applications of nanotechnology to improve the performance of solar collectors - Recent advances and overview,” *Renew. Sustain. Energy Rev.*, vol. 62, pp. 767–792, 2016, doi: 10.1016/j.rser.2016.04.050.
- [17] A. K. Tiwari, V. Kumar, Z. Said, and H. K. Paliwal, “A review on the application of hybrid nanofluids for parabolic trough collector: Recent progress and outlook,” *J. Clean. Prod.*, vol. 292, p. 126031, 2021, doi: 10.1016/j.jclepro.2021.126031.
- [18] A. Asadi, “A guideline towards easing the decision-making process in selecting an effective nanofluid as a heat transfer fluid,” *Energy Convers. Manag.*, vol. 175, pp. 1–10, 2018, doi: 10.1016/j.enconman.2018.08.101.
- [19] H. M. Sandeep and U. C. Arunachala, “Solar parabolic trough collectors: A review on heat transfer augmentation techniques,” *Renew. Sustain. Energy Rev.*, vol. 69, pp. 1218–1231, Mar. 2017, doi: 10.1016/j.rser.2016.11.242.
- [20] Z. Said *et al.*, “Recent advances on the fundamental physical phenomena behind stability, dynamic motion, thermophysical properties, heat transport, applications, and challenges of nanofluids,” *Phys. Rep.*, vol. 946, pp. 1–94, 2022, doi: 10.1016/j.physrep.2021.07.002.
- [21] Z. Said, A. A. Hachicha, S. Aberoumand, B. A. A. Yousef, E. T. Sayed, and E. Bellos, “Recent advances on nanofluids for low to medium temperature solar collectors: energy, exergy, economic analysis and environmental impact,” *Prog. Energy Combust. Sci.*, vol. 84, 2021, doi: 10.1016/j.pecs.2020.100898.
- [22] E. Bellos, Z. Said, and C. Tzivanidis, “The use of nanofluids in solar concentrating technologies: A comprehensive review,” *J. Clean. Prod.*, vol. 196, pp. 84–99, 2018, doi: 10.1016/j.jclepro.2018.06.048.
- [23] O. Mahian *et al.*, “Nano Energy Recent advances in using nanofluids in renewable energy systems and the environmental implications of their uptake,” *Nano Energy*,

- vol. 86, p. 106069, 2021, doi: 10.1016/j.nanoen.2021.106069.
- [24] J. Sarkar, “A critical review on convective heat transfer correlations of nanofluids,” *Renew. Sustain. Energy Rev.*, vol. 15, no. 6, pp. 3271–3277, 2011, doi: 10.1016/j.rser.2011.04.025.
- [25] L. Syam Sundar and M. K. Singh, “Convective heat transfer and friction factor correlations of nanofluid in a tube and with inserts: A review,” *Renew. Sustain. Energy Rev.*, vol. 20, pp. 23–35, 2013, doi: 10.1016/j.rser.2012.11.041.
- [26] K. S. Chaudhari, P. V Walke, U. S. Wankhede, and R. S. Shelke, “An Experimental Investigation of a Nanofluid ($\text{Al}_2\text{O}_3 + \text{H}_2\text{O}$) Based Parabolic Trough Solar Collectors,” *Br. J. Appl. Sci. Technol.*, vol. 9, no. 6, pp. 551–557, 2015, doi: 10.9734/BJAST/2015/11946.
- [27] M. S. Bretado de los Rios, C. I. Rivera-Solorio, and A. J. García-Cuéllar, “Thermal performance of a parabolic trough linear collector using $\text{Al}_2\text{O}_3/\text{H}_2\text{O}$ nanofluids,” *Renew. Energy*, vol. 122, pp. 665–673, 2018, doi: 10.1016/j.renene.2018.01.094.
- [28] M. A. Rehan *et al.*, “Experimental performance analysis of low concentration ratio solar parabolic trough collectors with nanofluids in winter conditions,” *Renew. Energy*, vol. 118, pp. 742–751, 2018, doi: 10.1016/j.renene.2017.11.062.
- [29] J. Subramani, P. K. Nagarajan, O. Mahian, and R. Sathyamurthy, “Efficiency and heat transfer improvements in a parabolic trough solar collector using TiO_2 nanofluids under turbulent flow regime,” *Renew. Energy*, vol. 119, pp. 19–31, 2018, doi: 10.1016/j.renene.2017.11.079.
- [30] G. Coccia, G. Di, L. Colla, L. Fedele, and M. Scattolini, “Adoption of nanofluids in low-enthalpy parabolic trough solar collectors : Numerical simulation of the yearly yield,” *Energy Convers. Manag.*, vol. 118, pp. 306–319, 2016, doi: 10.1016/j.enconman.2016.04.013.

- [31] A. Kasaeian, S. Daviran, R. Danesh, and A. Rashidi, "Performance evaluation and nanofluid using capability study of a solar parabolic trough collector," *Energy Convers. Manag.*, vol. 89, pp. 368–375, 2015, doi: 10.1016/j.enconman.2014.09.056.
- [32] A. Mwesigye and J. P. Meyer, "Optimal thermal and thermodynamic performance of a solar parabolic trough receiver with different nanofluids and at different concentration ratios," *Appl. Energy*, vol. 193, pp. 393–413, 2017.
- [33] A. Mwesigye, Y. Halil, and J. P. Meyer, "Numerical analysis of the thermal and thermodynamic performance of a parabolic trough solar collector using SWCNTs-Therminol® VP-1 nano fluid," *Renew. Energy*, vol. 119, pp. 844–862, 2018, doi: 10.1016/j.renene.2017.10.047.
- [34] A. Mwesigye, Z. Huan, and J. P. Meyer, "Thermal performance and entropy generation analysis of a high concentration ratio parabolic trough solar collector with Cu-Therminol VP-1 nanofluid," *Energy Convers. Manag.*, vol. 120, pp. 449–465, 2016, doi: 10.1016/j.enconman.2016.04.106.
- [35] S. E. Ghasemi and A. A. Ranjbar, "Effect of using nanofluids on efficiency of parabolic trough collectors in solar thermal electric power plants," *Int. J. Hydrogen Energy*, vol. 42, no. 34, pp. 21626–21634, 2017, doi: 10.1016/j.ijhydene.2017.07.087.
- [36] S. M. S. Murshed, "Simultaneous measurement of thermal conductivity, thermal diffusivity, and specific heat of nanofluids," *Heat Transf. Eng.*, vol. 33, no. 8, pp. 722–731, 2012, doi: 10.1080/01457632.2011.635986.
- [37] J. Buongiorno *et al.*, "A benchmark study on the thermal conductivity of nanofluids," *J. Appl. Phys.*, vol. 106, no. 9, 2009, doi: 10.1063/1.3245330.
- [38] S. E. Ghasemi and A. A. Ranjbar, "Numerical thermal study on effect of porous

- rings on performance of solar parabolic trough collector,” *Appl. Therm. Eng.*, vol. 118, pp. 807–816, 2017, doi: 10.1016/j.applthermaleng.2017.03.021.
- [39] S. E. Ghasemi and A. A. Ranjbar, “Thermal performance analysis of solar parabolic trough collector using nanofluid as working fluid: A CFD modelling study,” *J. Mol. Liq.*, vol. 222, pp. 159–166, 2016, doi: 10.1016/j.molliq.2016.06.091.
- [40] G. Saha and M. C. Paul, “Numerical analysis of the heat transfer behaviour of water based Al₂O₃ and TiO₂ nanofluids in a circular pipe under the turbulent flow condition,” *Int. Commun. Heat Mass Transf.*, vol. 56, pp. 96–108, 2014, doi: 10.1016/j.icheatmasstransfer.2014.06.008.
- [41] V. Bianco, O. Manca, and S. Nardini, “Numerical investigation on nano fluids turbulent convection heat transfer inside a circular tube,” *Int. J. Therm. Sci.*, vol. 50, pp. 341–349, 2011, doi: 10.1016/j.ijthermalsci.2010.03.008.
- [42] T. Sokhansefat, A. B. Kasaeian, and F. Kowsary, “Heat transfer enhancement in parabolic trough collector tube using Al₂O₃/synthetic oil nanofluid,” *Renew. Sustain. Energy Rev.*, vol. 33, pp. 636–644, 2014, doi: 10.1016/j.rser.2014.02.028.
- [43] O. Al-Oran, F. Lezsovits, and A. Aljawabrah, “Exergy and energy amelioration for parabolic trough collector using mono and hybrid nanofluids,” *J. Therm. Anal. Calorim.*, vol. 140, no. 3, pp. 1579–1596, 2020, doi: 10.1007/s10973-020-09371-x.
- [44] S. Rostami, M. Sepehrirad, A. Dezfulizadeh, A. K. Hussein, A. S. Goldanlou, and M. S. Shadloo, “Exergy optimization of a solar collector in flat plate shape equipped with elliptical pipes filled with turbulent nanofluid flow: A study for thermal management,” *Water*, vol. 12, no. 8, 2020, doi: 10.3390/w12082294.
- [45] B. Vahedi, E. Golab, A. Nasiri Sadr, and K. Vafai, “Thermal, thermodynamic and exergoeconomic investigation of a parabolic trough collector utilizing nanofluids,” *Appl. Therm. Eng.*, vol. 206, p. 118117, 2022, doi:

- 10.1016/j.applthermaleng.2022.118117.
- [46] T. Fahim, S. Laouedj, A. Abderrahmane, S. Alotaibi, O. Younis, and H. M. Ali, “Heat Transfer Enhancement in Parabolic through Solar Receiver: A Three-Dimensional Numerical Investigation,” *Nanomaterials*, vol. 12, no. 3, pp. 1–19, 2022, doi: 10.3390/nano12030419.
- [47] N. Basbous, M. Taqi, and M. A. Janan, “Thermal performances analysis of a parabolic trough solar collector using different nanofluids,” *Proc. 2016 Int. Renew. Sustain. Energy Conf. IRSEC 2016*, pp. 322–326, 2017, doi: 10.1109/IRSEC.2016.7984006.
- [48] G. Huminic and A. Huminic, “Hybrid nanofluids for heat transfer applications – A state-of-the-art review,” *Int. J. Heat Mass Transf.*, vol. 125, pp. 82–103, 2018, doi: 10.1016/j.ijheatmasstransfer.2018.04.059.
- [49] G. Huminic and A. Huminic, “Heat transfer capability of the hybrid nanofluids for heat transfer applications,” *J. Mol. Liq.*, vol. 272, pp. 857–870, 2018, doi: 10.1016/j.molliq.2018.10.095.
- [50] A. Bhattad, J. Sarkar, and P. Ghosh, “Experimentation on effect of particle ratio on hydrothermal performance of plate heat exchanger using hybrid nanofluid,” *Appl. Therm. Eng.*, vol. 162, p. 114309, 2019, doi: 10.1016/j.applthermaleng.2019.114309.
- [51] S. A. Kaska, R. A. Khalefa, and A. M. Hussein, “Hybrid nanofluid to enhance heat transfer under turbulent flow in a flat tube,” *Case Stud. Therm. Eng.*, vol. 13, p. 100398, 2019, doi: 10.1016/j.csite.2019.100398.
- [52] M. U. Sajid and H. M. Ali, “Thermal conductivity of hybrid nanofluids : A critical review,” *Int. J. Heat Mass Transf.*, vol. 126, pp. 211–234, 2018, doi: 10.1016/j.ijheatmasstransfer.2018.05.021.

- [53] V. Kumar and J. Sarkar, "Particle ratio optimization of Al₂O₃-MWCNT hybrid nanofluid in minichannel heat sink for best hydrothermal performance," *Appl. Therm. Eng.*, vol. 165, p. 114546, 2020, doi: 10.1016/j.applthermaleng.2019.114546.
- [54] J. A. Ranga Babu, K. K. Kumar, and S. Srinivasa Rao, "State-of-art review on hybrid nanofluids," *Renew. Sustain. Energy Rev.*, vol. 77, pp. 551–565, 2017, doi: 10.1016/j.rser.2017.04.040.
- [55] L. S. Sundar, M. K. Singh, and A. C. M. Sousa, "Turbulent heat transfer and friction factor of nanodiamond-nickel hybrid nanofluids flow in a tube : An experimental study," *Int. J. Heat Mass Transf.*, vol. 117, pp. 223–234, 2018, doi: 10.1016/j.ijheatmasstransfer.2017.09.109.
- [56] M. X. Ho and C. Pan, "Experimental investigation of heat transfer performance of molten HITEC salt flow with alumina nanoparticles," *Int. J. Heat Mass Transf.*, vol. 107, pp. 1094–1103, 2017, doi: 10.1016/j.ijheatmasstransfer.2016.11.015.
- [57] A. A. Minea, "Hybrid nanofluids based on Al₂O₃, TiO₂ and SiO₂: Numerical evaluation of different approaches," *Int. J. Heat Mass Transf.*, vol. 104, pp. 852–860, 2017, doi: 10.1016/j.ijheatmasstransfer.2016.09.012.
- [58] L. Syam Sundar, S. Mesfin, Y. Tefera Sintie, V. Punnaiah, A. J. Chamkha, and A. C. M. Sousa, "A Review on the Use of Hybrid Nanofluid in a Solar Flat Plate and Parabolic Trough Collectors and Its Enhanced Collector Thermal Efficiency," *J. Nanofluids*, vol. 10, no. 2, pp. 147–171, 2021, doi: 10.1166/jon.2021.1783.
- [59] M. Becker, "Comparison of heat transfer fluids for use in solar thermal power stations," *Electr. Power Syst. Res.*, vol. 3, no. 3–4, pp. 139–150, 1980, doi: 10.1016/0378-7796(80)90001-2.
- [60] Y. Murakami and B. B. Mikić, "Parametric optimization of multichanneled heat

- sinks for VLSI chip cooling,” *IEEE Trans. Components Packag. Technol.*, vol. 24, no. 1, pp. 2–9, 2001, doi: 10.1109/6144.910795.
- [61] L. A. Weinstein, J. Loomis, B. Bhatia, D. M. Bierman, E. N. Wang, and G. Chen, “Concentrating Solar Power,” *Chem. Rev.*, vol. 115, no. 23, pp. 12797–12838, 2015, doi: 10.1021/acs.chemrev.5b00397.
- [62] A. Lenert, Y. Nam, and E. N. Wang, “Heat Transfer Fluids,” *Annu. Rev. Heat Transf.*, vol. 15, pp. 93–129, 2012, doi: 10.1615/annualrevheattransfer.2012004122.
- [63] F. P. Incropera, D. P. DeWitt, T. L. Bergman, and A. Lavine, *Principles of Heat and Mass Transfer*, Seventh. John Wiley & Sons Singapore Pte. Limited, 2016.
- [64] Y. Xuan and Q. Li, “Investigation on convective heat transfer and flow features of nanofluids,” *ASME J. Heat Mass Transf. Trans. ASME*, vol. 125, pp. 151–155, 2003, doi: 10.1115/1.1532008.
- [65] S. El Bécaye Maïga, S. J. Palm, C. T. Nguyen, G. Roy, and N. Galanis, “Heat transfer enhancement by using nanofluids in forced convection flows,” *Int. J. Heat Fluid Flow*, vol. 26, pp. 530–546, 2005, doi: 10.1016/j.ijheatfluidflow.2005.02.004.
- [66] W. Duangthongsuk and S. Wongwises, “An experimental study on the heat transfer performance and pressure drop of TiO₂-water nanofluids flowing under a turbulent flow regime,” *Int. J. Heat Mass Transf.*, vol. 53, pp. 334–344, 2010, doi: 10.1016/j.ijheatmasstransfer.2009.09.024.
- [67] R. S. Vajjha, D. K. Das, and D. P. Kulkarni, “Development of new correlations for convective heat transfer and friction factor in turbulent regime for nanofluids,” *Int. J. Heat Mass Transf.*, vol. 53, pp. 4607–4618, 2010, doi: 10.1016/j.ijheatmasstransfer.2010.06.032.
- [68] A. R. Sajadi and M. H. Kazemi, “Investigation of turbulent convective heat transfer and pressure drop of TiO₂/water nanofluid in circular tube,” *Int. Commun. Heat*

- Mass Transf.*, vol. 38, pp. 1474–1478, 2011, doi: 10.1016/j.icheatmasstransfer.2011.07.007.
- [69] L. Syam Sundar, M. T. Naik, K. V. Sharma, M. K. Singh, and T. C. Siva Reddy, “Experimental investigation of forced convection heat transfer and friction factor in a tube with Fe₃O₄ magnetic nanofluid,” *Exp. Therm. Fluid Sci.*, vol. 37, pp. 65–71, 2012, doi: 10.1016/j.expthermflusci.2011.10.004.
- [70] M. Hemmat Esfe, A. A. Abbasian Arani, and M. Rezaee, “Experimental thermal analysis of a turbulent nano enriched water flow in a circular tube,” *Phys. A Stat. Mech. its Appl.*, vol. 580, p. 124010, 2021, doi: 10.1016/j.physa.2019.124010.
- [71] L. S. Sundar, M. K. Singh, and A. C. M. Sousa, “Enhanced heat transfer and friction factor of MWCNT-Fe₃O₄/water hybrid nanofluids,” *Int. Commun. Heat Mass Transf.*, vol. 52, pp. 73–83, 2014, doi: 10.1016/j.icheatmasstransfer.2014.01.012.
- [72] H. Yarmand *et al.*, “Graphene nanoplatelets – silver hybrid nanofluids for enhanced heat transfer,” *Energy Convers. Manag.*, vol. 100, pp. 419–428, 2015, doi: 10.1016/j.enconman.2015.05.023.
- [73] S. Suresh, K. P. Venkitaraj, M. S. Hameed, and J. Sarangan, “Turbulent Heat Transfer and Pressure Drop Characteristics of Dilute Water Based Al₂O₃ – Cu Hybrid Nanofluids,” *J. Nanosci. Nanotechnol.*, vol. 14, no. 3, pp. 2563–2572, 2014, doi: 10.1166/jnn.2014.8467.
- [74] D. Madhesh and S. Kalaiselvam, “Experimental study on heat transfer and rheological characteristics of hybrid nanofluids for cooling applications,” *J. Exp. Nanosci.*, vol. 10, no. 15, pp. 1194–1213, 2015, doi: 10.1080/17458080.2014.989551.
- [75] A. Benabderrahmane, A. Benazza, and A. K. Hussein, “Heat Transfer Enhancement Analysis of Tube Receiver for Parabolic Trough Solar Collector with Central

- Corrugated Insert,” *ASME J. Heat Mass Transf. Trans. ASME*, vol. 142, no. 6, pp. 1–8, 2020, doi: 10.1115/1.4046440.
- [76] J. Muñoz and A. Abánades, “Analysis of internal helically finned tubes for parabolic trough design by CFD tools,” *Appl. Energy*, vol. 88, no. 11, pp. 4139–4149, 2011, doi: 10.1016/j.apenergy.2011.04.026.
- [77] I. H. Yılmaz and A. Mwesigye, “Modeling, simulation and performance analysis of parabolic trough solar collectors: A comprehensive review,” *Appl. Energy*, vol. 225, pp. 135–174, 2018, doi: 10.1016/j.apenergy.2018.05.014.
- [78] F. Wang, J. Tan, L. Ma, and C. Wang, “Effects of glass cover on heat flux distribution for tube receiver with parabolic trough collector system,” *Energy Convers. Manag.*, vol. 90, pp. 47–52, 2015, doi: 10.1016/j.enconman.2014.11.004.
- [79] Z. D. Cheng, Y. L. He, F. Q. Cui, R. J. Xu, and Y. B. Tao, “Numerical simulation of a parabolic trough solar collector with nonuniform solar flux conditions by coupling FVM and MCRT method,” *Sol. Energy*, vol. 86, no. 6, pp. 1770–1784, 2012, doi: 10.1016/j.solener.2012.02.039.
- [80] Y. Xu, R. Tian, X. Dai, and L. Shi, “Coupling effect between heat flux distribution and buoyancy of supercritical CO₂ heat transfer with nonuniform heat flux in parabolic-trough collector,” *Int. J. Heat Mass Transf.*, vol. 195, p. 123197, 2022, doi: 10.1016/j.ijheatmasstransfer.2022.123197.
- [81] W. Spirkel, H. Ries, J. Muschaweck, and A. Timinger, “Optimized compact secondary reflectors for parabolic troughs with tubular absorbers,” *Sol. Energy*, vol. 61, pp. 153–158, 1997, doi: 10.1016/S0038-092X(97)00047-9.
- [82] S. Balaji, K. S. Reddy, and T. Sundararajan, “Optical modelling and performance analysis of a solar LFR receiver system with parabolic and involute secondary reflectors,” *Appl. Energy*, vol. 179, pp. 1138–1151, 2016, doi:

- 10.1016/j.apenergy.2016.07.082.
- [83] J. hu Gong *et al.*, “Improving the performance of a 2-stage large aperture parabolic trough solar concentrator using a secondary reflector designed by adaptive method,” *Renew. Energy*, vol. 152, pp. 23–33, 2020, doi: 10.1016/j.renene.2020.01.019.
- [84] S. Shajan and V. Baiju, “Designing a novel small-scale parabolic trough solar thermal collector with secondary reflector for uniform heat flux distribution,” *Appl. Therm. Eng.*, vol. 213, p. 118660, 2022.
- [85] Y. Wang, Q. Liu, J. Lei, and H. Jin, “Performance analysis of a parabolic trough solar collector with non-uniform solar flux conditions,” *Int. J. Heat Mass Transf.*, vol. 82, pp. 236–249, 2015, doi: 10.1016/j.ijheatmasstransfer.2014.11.055.
- [86] H. A. Mohammed, H. B. Vuthaluru, and S. Liu, “Heat transfer augmentation of parabolic trough solar collector receiver’s tube using hybrid nanofluids and conical turbulators,” *J. Taiwan Inst. Chem. Eng.*, vol. 125, pp. 215–242, 2021, doi: 10.1016/j.jtice.2021.06.032.
- [87] O. Chakraborty, B. Das, R. Gupta, and S. Debbarma, “Heat transfer enhancement analysis of parabolic trough collector with straight and helical absorber tube,” *Therm. Sci. Eng. Prog.*, vol. 20, p. 100718, 2020, doi: 10.1016/j.tsep.2020.100718.
- [88] A. Mwesigye and Z. Huan, “Thermodynamic analysis and optimization of fully developed turbulent forced convection in a circular tube with water-Al₂O₃ nanofluid,” *Int. J. Heat Mass Transf.*, vol. 89, pp. 694–706, 2015, doi: 10.1016/j.ijheatmasstransfer.2015.05.099.
- [89] Z. Huang, Z. Li, and W. Tao, “Numerical study on combined natural and forced convection in the fully-developed turbulent region for a horizontal circular tube heated by non-uniform heat flux q ,” *Appl. Energy*, vol. 185, pp. 2194–2208, 2017, doi: 10.1016/j.apenergy.2015.11.066.

- [90] A. F. Polyakov, "Development of secondary free convection currents in forced turbulent flow in horizontal tubes," *J. Appl. Mech. Tech. Physcis*, vol. 15, no. 5, pp. 632–637, 1974.
- [91] R. Balin and K. E. Jansen, "Direct numerical simulation of a turbulent boundary layer over a bump with strong pressure gradients," *J. Fluid Mech.*, vol. 918, pp. 1–32, 2021, doi: 10.1017/jfm.2021.312.
- [92] R. Balachandar, D. Blakely, and J. Bugg, "Friction velocity and power law velocity profile in smooth and rough shallow open channel flows," *Can. J. Civ. Eng.*, vol. 29, pp. 256–266, 2002, doi: 10.1139/101-093.
- [93] A. E. Tejada-Martinez, C. E. Grosch, N. Sinha, C. Akan, and G. Martinat, "Disruption of the bottom log layer in large-eddy simulations of full-depth Langmuir circulation," *J. Fluid Mech.*, vol. 699, pp. 79–93, 2012, doi: 10.1017/jfm.2012.84.
- [94] K. Wang, Z. D. Zhang, X. Y. Zhang, and C. H. Min, "Buoyancy effects on convective heat transfer of supercritical CO₂ and thermal stress in parabolic trough receivers under non-uniform solar flux distribution," *Int. J. Heat Mass Transf.*, vol. 175, p. 121130, 2021, doi: 10.1016/j.ijheatmasstransfer.2021.121130.
- [95] C. Chang, X. Li, and Q. Q. Zhang, "Experimental and numerical study of the heat transfer characteristics in solar thermal absorber tubes with circumferentially non-uniform heat flux," *Energy Procedia*, vol. 49, pp. 305–313, 2014, doi: 10.1016/j.egypro.2014.03.033.
- [96] T. J. Remley, S. I. Abdel-Khalik, S. M. Jeter, S. M. Ghiaasiaan, and M. F. Dowling, "Effect of non-uniform heat flux on wall friction and convection heat transfer coefficient in a trapezoidal channel," *Int. J. Heat Mass Transf.*, vol. 44, pp. 2453–2459, 2001, doi: 10.1016/S0017-9310(00)00295-7.
- [97] S. A. Klein, "Engineering Equation Solver Professional Verison V10.215." F-chart

Software Madison WI, 2017.

- [98] Y. Xuan and W. Roetzel, “Conceptions for heat transfer correlation of nanofluids,” *Int. J. Heat Mass Transf.*, vol. 43, pp. 3701–3707, 2000, doi: 10.1016/j.aej.2017.01.005.
- [99] D. Shin and D. Banerjee, “Specific heat of nanofluids synthesized by dispersing alumina nanoparticles in alkali salt eutectic,” *Int. J. Heat Mass Transf.*, vol. 74, pp. 210–214, 2014, doi: 10.1016/j.ijheatmasstransfer.2014.02.066.
- [100] E. V Timofeeva, J. L. Routbort, and D. Singh, “Particle shape effects on thermophysical properties of alumina nanofluids,” *J. Appl. Phys.*, vol. 106, p. 014304, 2009, doi: 10.1063/1.3155999.
- [101] M. Sahu and J. Sarkar, “Steady-State Energetic and Exergetic Performances of Single-Phase Natural Circulation Loop with Hybrid Nanofluids,” *ASME J. Heat Mass Transf. Trans. ASME*, vol. 141, p. 082401, 2019, doi: 10.1115/1.4043819.
- [102] H. Riazi, T. Murphy, G. B. Webber, R. Atkin, S. S. M. Tehrani, and R. A. Taylor, “Specific heat control of nanofluids: A critical review,” *Int. J. Therm. Sci.*, vol. 107, pp. 25–38, 2016, doi: 10.1016/j.ijthermalsci.2016.03.024.
- [103] I. M. Shahrul, I. M. Mahbubul, S. S. Khaleduzzaman, R. Saidur, and M. F. M. Sabri, “A comparative review on the specific heat of nanofluids for energy perspective,” *Renew. Sustain. Energy Rev.*, vol. 38, pp. 88–98, 2014, doi: 10.1016/j.rser.2014.05.081.
- [104] D. Shin and D. Banerjee, “Enhanced specific heat capacity of nanomaterials synthesized by dispersing silica nanoparticles in eutectic mixtures,” *ASME J. Heat Mass Transf. Trans. ASME*, vol. 135, p. 032801, 2013, doi: 10.1115/1.4005163.
- [105] S. M. S. Murshed, “Determination of effective specific heat of nanofluids,” *J. Exp. Nanosci.*, vol. 6, no. 5, pp. 539–546, 2011, doi: 10.1080/17458080.2010.498838.

- [106] R. S. Vajjha and D. K. Das, “Specific heat measurement of three nanofluids and development of new correlations,” *ASME J. Heat Mass Transf. Trans. ASME*, vol. 131, p. 071601, 2009, doi: 10.1115/1.3090813.
- [107] J. Akhter, S. I. Gilani, H. H. Al-Kayiem, M. Ali, and F. Masood, “Experimental evaluation of thermophysical properties of oil-based titania nanofluids for medium temperature solar collectors,” *Materwiss. Werksttech.*, vol. 51, no. 6, pp. 792–802, 2020, doi: 10.1002/mawe.201900244.
- [108] S. Akilu, A. T. Baheta, K. V. Sharma, and M. A. Said, “Experimental determination of nanofluid specific heat with SiO₂ nanoparticles in different base fluids,” *AIP Conf. Proc.*, vol. 1877, p. 090001, 2017, doi: 10.1063/1.4999896.
- [109] S. U. Ilyas, R. Pendyala, and M. Narahari, “An experimental study on the natural convection heat transfer in rectangular enclosure using functionalized alumina-thermal oil-based nanofluids,” *Appl. Therm. Eng.*, vol. 127, pp. 765–775, 2017, doi: 10.1016/j.applthermaleng.2017.08.088.
- [110] M. Kole and T. K. Dey, “Enhanced thermophysical properties of copper nanoparticles dispersed in gear oil,” *Appl. Therm. Eng.*, vol. 56, pp. 45–53, 2013, doi: 10.1016/j.applthermaleng.2013.03.022.
- [111] R. Hentschke, “On the specific heat capacity enhancement in nanofluids,” *Nanoscale Res. Lett.*, vol. 11, no. 1, pp. 1–11, 2016, doi: 10.1186/s11671-015-1188-5.
- [112] S. M. Fotukian and M. Nasr Esfahany, “Experimental investigation of turbulent convective heat transfer of dilute γ -Al₂O₃/water nanofluid inside a circular tube,” *Int. J. Heat Fluid Flow*, vol. 31, pp. 606–612, Aug. 2010, doi: 10.1016/j.ijheatfluidflow.2010.02.020.
- [113] S. M. Fotukian and M. Nasr Esfahany, “Experimental study of turbulent convective

- heat transfer and pressure drop of dilute CuO/water nanofluid inside a circular tube,” *Int. Commun. Heat Mass Transf.*, vol. 37, pp. 214–219, 2010, doi: 10.1016/j.icheatmasstransfer.2009.10.003.
- [114] E. Sadeghinezhad *et al.*, “An experimental and numerical investigation of heat transfer enhancement for graphene nanoplatelets nanofluids in turbulent flow conditions,” *Int. J. Heat Mass Transf.*, vol. 81, pp. 41–51, 2015, doi: 10.1016/j.ijheatmasstransfer.2014.10.006.
- [115] B. C. Pak and Y. I. Cho, “Hydrodynamic and Heat Transfer Study of Dispersed Fluids With Submicron Metallic Oxide,” *Exp. Heat Transf. A J., Therm. Energy Transp., Storage, Convers.*, vol. 11, pp. 37–41, 2013, doi: 10.1080/08916159808946559.
- [116] M. Fallahiyekta, M. R. J. Nasr, A. Rashidi, and M. Arjmand, “Convective Heat Transfer Enhancement of CNT-Water Nanofluids in Plain Tube Fitted with Wire Coil Inserts,” *Iran. J. Chem. Eng.*, vol. 11, no. 2, pp. 43–55, 2014.
- [117] R. Vutukuru, A. S. Pegallapati, and R. Maddali, “Suitability of various heat transfer fluids for high temperature solar thermal systems,” *Appl. Therm. Eng.*, vol. 159, p. 113973, 2019, doi: 10.1016/j.applthermaleng.2019.113973.
- [118] A. S. Dalkılıç, O. A. Turk, H. Mercan, S. Nakkaew, and S. Wongwises, “An experimental investigation on heat transfer characteristics of graphite-SiO₂/water hybrid nanofluid flow in horizontal tube with various quad-channel twisted tape inserts,” *Int. Commun. Heat Mass Transf.*, vol. 107, pp. 1–13, 2019, doi: 10.1016/j.icheatmasstransfer.2019.05.013.
- [119] L. Syam Sundar, Z. Said, B. Saleh, M. K. Singh, and A. C. M. Sousa, “Combination of Co₃O₄ deposited rGO hybrid nanofluids and longitudinal strip inserts: Thermal properties, heat transfer, friction factor, and thermal performance evaluations,”

- Therm. Sci. Eng. Prog.*, vol. 20, p. 100695, 2020, doi: 10.1016/j.tsep.2020.100695.
- [120] O. Gulzar, A. Qayoum, and R. Gupta, “Experimental study on stability and rheological behaviour of hybrid Al₂O₃-TiO₂ Therminol-55 nanofluids for concentrating solar collectors,” *Powder Technol.*, vol. 352, pp. 436–444, 2019, doi: 10.1016/j.powtec.2019.04.060.
- [121] B. Wei, C. Zou, X. Yuan, and X. Li, “Thermo-physical property evaluation of diathermic oil based hybrid nanofluids for heat transfer applications,” *Int. J. Heat Mass Transf.*, vol. 107, pp. 281–287, 2017, doi: 10.1016/j.ijheatmasstransfer.2016.11.044.
- [122] O. Gulzar, A. Qayoum, and R. Gupta, “Experimental study on thermal conductivity of mono and hybrid Al₂O₃-TiO₂ nanofluids for concentrating solar collectors,” *Int. J. Energy Res.*, vol. 45, no. 3, pp. 4370–4384, 2021, doi: 10.1002/er.6105.
- [123] E. Choi and Y. I. Cho, “Local Friction and Heat Transfer Behavior of Water in a Turbulent Pipe Flow With a Large Heat Flux at the Wall,” *ASME J. Heat Mass Transf. Trans. ASME*, vol. 117, pp. 283–288, 1995.
- [124] A. A. Minea, “Simulation of nanofluids turbulent forced convection at high Reynolds number: A comparison study of thermophysical properties influence on heat transfer enhancement,” *Flow, Turbul. Combust.*, vol. 94, no. 3, pp. 555–575, 2015, doi: 10.1007/s10494-014-9590-0.
- [125] S. Gorji *et al.*, “A comparative study of turbulence models in a transient channel flow,” *Comput. Fluids*, vol. 89, pp. 111–123, 2014, doi: 10.1016/j.compfluid.2013.10.037.
- [126] J. Bayat and A. H. Nikseresht, “Thermal performance and pressure drop analysis of nanofluids in turbulent forced convective flows,” *Int. J. Therm. Sci.*, vol. 60, pp. 236–243, 2012, doi: 10.1016/j.ijthermalsci.2012.04.012.

- [127] ANSYS Inc., *ANSYS Fluent User's Guide 15.0*. 2013.
- [128] H. K. Versteeg and W. Malalasekera, *An Introduction to computational fluid dynamics The Finite Volume Method*, Second. London, 2007.
- [129] Eastman, "Therminol VP-1, Technical Bulletin TF9141," 2020.
- [130] S. K. SOM and G. Biswas, *Introduction to Fluid Mechanics Fluid Machines*, 2nd ed. Tata McGraw-Hill Publishing Company Limited, 2008.
- [131] F. M. White, *Viscous Fluid Flow*, Second. McGraw-Hill, Inc., 1991.
- [132] A. Gimeno-Furio *et al.*, "Stabilization and characterization of a nanofluid based on a eutectic mixture of diphenyl and diphenyl oxide and carbon nanoparticles under high temperature conditions," *Int. J. Heat Mass Transf.*, vol. 113, pp. 908–913, 2017, doi: 10.1016/j.ijheatmasstransfer.2017.05.097.
- [133] V. Kumar and J. Sarkar, "Numerical and experimental investigations on heat transfer and pressure drop characteristics of Al₂O₃ -TiO₂ hybrid nanofluid in minichannel heat sink with different mixture ratio," *Powder Technol.*, vol. 345, pp. 717–727, 2019, doi: 10.1016/j.powtec.2019.01.061.
- [134] B. P. Singh, R. Menchavez, C. Takai, M. Fuji, and M. Takahashi, "Stability of dispersions of colloidal alumina particles in aqueous suspensions," *J. Colloid Interface Sci.*, vol. 291, no. 1, pp. 181–186, 2005, doi: 10.1016/j.jcis.2005.04.091.
- [135] V. S. Sousa and M. R. Teixeira, "Aggregation kinetics and surface charge of CuO nanoparticles: The influence of pH, ionic strength and humic acids," *Environ. Chem.*, vol. 10, no. 4, pp. 313–322, 2013, doi: 10.1071/EN13001.
- [136] F. McClintock and S. Kline, "Describing uncertainties in single-sample experiments," *Mech. Eng.*, vol. 75, no. 1, pp. 3–8, 1953.

LIST OF PUBLICATIONS AND CONFERENCES

Journals:

1. S. Upadhyay, L. Chandra, and J. Sarkar, "A generalized Nusselt number correlation for nanofluids, and look-up diagrams to select a heat transfer fluid for medium-temperature solar thermal applications," *Applied Thermal Engineering*, vol. 190, p. 116469, 2021.
2. S. Upadhyay, P. R. Savant, L. Chandra, and J. Sarkar, "Generalized Nusselt Number Correlation for Binary Hybrid Nano-Oils as Heat Transfer Fluid in Solar Thermal Systems," *Journal of Heat and Mass Transfer-Transactions of the ASME*, vol. 144, p. 072901, 2022.
3. S. Upadhyay, L. Chandra, and J. Sarkar, "New Insights in Turbulent Heat Transfer with Oil and Hybrid Nano-oils, Subject to Discrete Heating, for Parabolic Trough Absorbers," *Journal of Heat and Mass Transfer-Transactions of the ASME*, vol 145,p. 083901, 2023

CONFERENCES:

4. S. Upadhyay, L. Chandra, and J. Sarkar, A look-up diagram for selecting a heat transfer fluid in a concentrated solar thermal system, *25th National and 3rd International ISHMT-ASTFE Heat and Mass Transfer*, 2019.
5. S. Upadhyay, L. Chandra, and J. Sarkar, Computational Fluid Dynamics Analysis of Turbulent Hybrid nano-oil Flow Through a Long Heated Tube, *26th National and 4th International ISHMT-ASTFE Heat and Mass Transfer Conference (IHMTTC-2021)*, 17-20 December 2021