

## LIST OF FIGURES

<b>Figure 2.1.</b>	Measurement system for Through-the-Wall Imaging	<b>29</b>
<b>Figure 2.2.</b>	Measurement set up of wall dielectric calculation [Ahmad <i>et al.</i> (2008)]	<b>35</b>
<b>Figure 2.3.</b>	Range profile plot	<b>37</b>
<b>Figure 3.1.</b>	Geometric of through wall imaging set-up[Ahmad <i>et al.</i> (2008)]	<b>42</b>
<b>Figure 3.2.</b>	Geometry of equivalent 2D problem when the antenna position and the image pixel are at the same height [Ahmad <i>et al.</i> (2008)].	<b>45</b>
<b>Figure 3.3.</b>	Flowchart for the implementation of backprojection imaging algorithm	<b>47</b>
<b>Figure 3.4.</b>	Flowchart for the implementation of delay and sum beamforming imaging algorithm	<b>49</b>
<b>Figure 3.5.</b>	Flowchart for the implementation of frequency-wavenumber imaging algorithm	<b>52</b>
<b>Figure 3.6.</b>	Range profile plot	<b>53</b>
<b>Figure 3.7.</b>	(a) 2D C-scan through-the-wall radar image obtained using backprojectionimaging method on imaging plane along X and Y axis of target id S1	<b>55</b>
	(b) 2D C-scan through-the-wall radar image obtained using delay and sum imaging method on imaging plane along X and Y axis of target id S1	
	(c) 2D C-scan through-the-wall radar image obtained using frequency wave number imaging method on imaging plane along X and Y axis of target id S1	
	(d) 2D C-scan through-the-wall radar image obtained using back projection imaging method on imaging plane along X and Y axis of target id S2	
	(e) 2D C-scan through-the-wall radar image obtained using	

delay and sum imaging method on imaging plane along X and Y axis of target id S2

(f) 2D C-scan through-the-wall radar image obtained using frequency wave imaging number method on imaging plane along X and Y axis of target id S2

(g) 2D C-scan through-the-wall radar image obtained using backprojectionimaging method on imaging plane along X and Y axis of target id S3

(h) 2D C-scan through-the-wall radar image obtained using delay and sum imaging method on imaging plane along X and Y axis of target id S3

(i) 2D C-scan through-the-wall radar image obtained using frequency wave number imaging method on imaging plane along X and Y axis of target id S3

(j) 2D C-scan through-the-wall radar image obtained using back projection imaging method on imaging plane along X and Y axis of target id S4

(k) 2D C-scan through-the-wall radar image obtained using delay and sumimaging method on imaging plane along X and Y axis of target id S4

(l) 2D C-scan through-the-wall radar image obtained using frequency wave number imaging method on imaging plane along X and Y axis of target id S4.

**Figure 3.8.**

(a) Thresholded 2D C-scan through-the-wall radar image obtained using backprojection imaging method on imaging plane along X and Y axis of target id S1.

(b) Thresholded 2D C-scan through-the-wall radar image obtained using delay and sum imaging method on imaging plane along X and Y axis of target id S1.

(c) Thresholded 2D C-scan through-the-wall radar image obtained using frequency-wave number imaging method on

**56**

imaging plane along X and Y axis of target id S1.

**(d)** Reference target shape of target id S1.

**(e)** Thresholded 2D C-scan through-the-wall radar image obtained using backprojection imaging method on imaging plane along X and Y axis of target id S2.

**(f)** Thresholded 2D C-scan through-the-wall radar image obtained using delay and sum imaging method on imaging plane along X and Y axis of target id S2.

**(g)** Thresholded 2D C-scan through-the-wall radar image obtained using frequency-wavenumber imaging method on imaging plane along X and Y axis of target id S2.

**(h)** Reference target shape of target id S2.

**(i)** Thresholded 2D C-scan through-the-wall radar image obtained using back projection imaging method on imaging plane along X and Y axis of target id S3.

**(j)** Thresholded 2D C-scan through-the-wall radar image obtained using delay and sum imaging method on imaging plane along X and Y axis of target id S3.

**(k)** Thresholded 2D C-scan through-the-wall radar image obtained using frequency-wavenumber imaging method on imaging plane along X and Y axis of target id S3.

**(l)** Reference target shape of target id S3.

**(m)** Thresholded 2D C-scan through-the-wall radar image obtained using backprojection imaging method on imaging plane along X and Y axis of target id S4.

**(n)** Thresholded 2D C-scan through-the-wall radar image obtained using delay and sum imaging method on imaging plane along X and Y axis of target id S4.

**(o)** Thresholded 2D C-scan through-the-wall radar image obtained using frequency wavenumber imaging method on imaging plane along X and Y axis of target id S4.

	(p) Reference target shape of target id S4.	
<b>Figure 4.1.</b>	Flowchart of methodology for detection of target shape and size	<b>69</b>
<b>Figure 4.2.</b>	Adaptive median filtered image of targets	<b>74</b>
	(a) T1	
	(b) T2	
	(c) T3	
	(d) T4	
<b>Figure 4.3.</b>	(a) Plot of True positive for different values of n of concealed targets having target id T1, T2, T3 and T4.	<b>76</b>
	(b) Plot of False positive for different values of n of concealed targets having target id T1, T2, T3 and T4.	
<b>Figure 4.4.</b>	(a) 2D C-scan through-the-wall radar image of target T11	<b>81</b>
	(b) 2D C-scan through-the-wall radar image of target T12	
	(c) 2D C-scan through-the-wall radar image of target T11 after proposed thresholding technique	
	(d) 2D C-scan through-the-wall radar image of target T12 after proposed thresholding technique	
	(e) 2D C-scan through-the-wall radar image of target T11 after Sobel edge detection	
	(f) 2D C-scan through-the-wall radar image of target T12 after Sobel edge detection	
	(g) 2D C-scan through-the-wall radar image of target T13	
	(h) 2D C-scan through-the-wall radar image of target T14	
	(i) 2D C-scan through-the-wall radar image of target T13 after proposed thresholding technique	
	(j) 2D C-scan through-the-wall radar image of target T14 after sobel edge detection	
	(k) 2D C-scan through-the-wall radar image of target T13 after Sobel edge detection	
	(l) 2D C-scan through-the-wall radar image of target T14 after	

	Sobel edge detection.	
<b>Figure 5.1.</b>	Flowchart of methodology for recognition of target shape and size	<b>89</b>
<b>Figure 5.2.</b>	2D C-scan through-the-wall radar image obtained using delay and sum beamforming method on imaging plane along X and Y axis of target id	<b>91</b>
	(a) MRR1	
	(b) WRR1	
	(c) MSR1	
	(d) WSR1	
<b>Figure 5.3.</b>	Adaptive median filtered image for target id	<b>93</b>
	(a) MRR1	
	(b) WRR1	
	(c) MSR1	
	(d) WSR1	
<b>Figure 5.4.</b>	(a) Statistics based thresholded 2D C-scan through-the-wall radar image of actual rectangular metal target of size 50cm X 30cm	<b>97</b>
	(b) Horizontally and vertically shrunk 2D C-scan through-the-wall radar image of rectangular metal target of size 25cm X 45cm obtained after applying morphological erosion technique on statics based thresholded 2D C-scan through-the-wall radar image of actual rectangular metal target of size 50cm X 30cm	
	(c) Horizontally and vertically expanded 2D C-scan through-the-wall radar image of rectangular metal target of size 55cm X 35cm obtained after applying morphological dilation technique on statics based thresholded 2D C-scan through-the-wall radar image of actual rectangular metal target of size 50cm X 30cm	
	(d) Horizontally and vertically expanded 2D C-scan through-	

the-wall radar image of rectangular metal target of size 60cm X 40cm obtained after applying morphological dilation technique on statics based thresholded 2D C-scan through-the-wall radar image of Actual Rectangular metal target of size 50cm X 30cm

<b>Figure 5.5.</b>	Configuration of neural network for target recognition	<b>101</b>
<b>Figure 5.6.</b>	2D C-scan through-the wall radar image of targets id	<b>105</b>
	(a) WTR2	
	(b) MTR2	
	(c) MSR2	
	(d) WTR16	
	(e) WTR17	
	(f) WSR16	
	(g) WSR17	
	(h) WRR16	
	(i) WRR17	
	(j) MSR16	
	(k) MSR17	
	(h) MRR16	