

Contents

Preface	v
List of Tables	xv
List of Figures	xvii
Nomenclature	xxv
1 Introduction	1
1.1 General	1
1.2 Literature Survey	4
1.2.1 Primary and backup protection for MTDC grid	4
1.2.2 Primary protection and fault localization scheme for MTDC grid	6
1.2.3 TW based fault localization scheme	8
1.2.4 Wide area backup protection for HVAC network interfacing MMC based HVDC link	11
1.3 Motivation	13
1.4 Research Objective	14
1.5 Overview of major contribution	14
1.6 Organization of the thesis	16
1.7 Summary	17
2 A traveling Wave based Primary and Backup Protection for MMC- MTDC Transmission System using Morphological Un-Decimated Wavelet Scheme	19
2.1 General	19
2.2 MMC-MTDC test system	20

2.3	MUDW based primary and backup protection scheme for MTDC system . . .	21
2.3.1	MUDW based TW polarity and AT detection	21
2.3.2	Principle of TW based primary and backup protection scheme . . .	24
2.3.3	Flowchart of proposed primary and backup protection scheme . . .	28
2.4	Simulation result	30
2.4.1	Effect of fault location on proposed protection scheme	30
2.4.2	Effect of noise on MUDW based TWAT extraction technique	33
2.4.3	Effect of fault impedance and measurement noise on MUDW based primary and backup protection scheme	34
2.4.4	Effect of fault types on proposed protection scheme	36
2.4.5	Effect of sampling frequency on proposed protection scheme	37
2.4.6	Comparative analysis	38
2.5	Summary	41
3	Traveling Wave based Primary Protection and Fault Localization Scheme for MTDC Grid Considering IEC 61869-9 Measurement Standard	43
3.1	General	43
3.1.1	Brief Introduction	43
3.1.2	Motivation and Incitement	44
3.1.3	Contribution	45
3.2	Methodologies of Proposed Primary Protection and Fault Localization Al- gorithm	46
3.2.1	Processing of the Relaying Input Signal	46
3.2.2	Low Sampling Frequency AT Estimation of TW using Modified MM Gradient and Linear Regression Tool	46
3.2.3	Flowchart of Proposed Primary Protection and DC fault Localiza- tion Scheme Compliant to IEC-61869-9 measurement protocol . . .	52
3.3	MMC-MTDC Grid Under Study	53
3.4	Simulation Results and Discussion	55
3.4.1	Impact of DC fault resistance	55
3.4.1.1	Performance of proposed protection scheme	55
3.4.1.2	Performance of proposed fault localization scheme	58

3.4.2	Impact of measurement noise and measurement error	59
3.4.2.1	Impact of measurement noise	59
3.4.2.2	Impact of measurement error	61
3.4.3	Impact of sampling frequency and fault location	62
3.4.3.1	Performance of proposed protection scheme	62
3.4.3.2	Performance of proposed fault localization scheme	64
3.4.4	Impact of communication delay and synchronization error	65
3.4.4.1	Impact of communication and signal processing delay on proposed primary protection scheme	65
3.4.4.2	Impact of synchronization error on proposed real time fault localization scheme	68
3.4.5	Impact of fault type	69
3.4.6	Impact of external fault and MTDC grid parameter variation	71
3.4.7	Comparative assessment	73
3.4.7.1	Comparing DC fault localization performance	73
3.4.7.2	Comparing DC primary protection performance	74
3.4.8	Comparative discussion with existing DC protection system	76
3.5	Real time CHIL validation of proposed primary protection and DC fault localization scheme	78
3.6	Summary	81

4	A Single ended Traveling Wave based DC fault localization for MTDC grid	83
4.1	General	83
4.2	Proposed single ended TW based fault localization scheme	83
4.2.1	Complex frequency content of the TW	84
4.2.2	Operating principle of proposed scheme	86
4.2.3	Proposed TWAT extraction technique for low and high sampling frequency measurement	87
4.3	Test MTDC transmission system	91
4.4	Simulation Results	93
4.4.1	Impact of DC fault location	94

4.4.2	Impact of fault resistance	96
4.4.3	Impact of measurement noise	96
4.4.4	Impact of fault type	98
4.4.5	Comparative analysis	99
4.5	Summary	101
5	Traveling Wave based Wide Area Backup Protection for HVAC network interfacing MMC based HVDC link	103
5.1	Introduction	103
5.1.1	General	103
5.1.2	Motivation and incitement	104
5.1.3	Contribution	105
5.2	Proposed TW based WABPS for HVAC grid interfacing HVDC link	105
5.2.1	Low sampling frequency TW arrival time estimation	105
5.2.1.1	Pre-processing of relay input signal	105
5.2.1.2	Modified fast successive matrix Pencil algorithm (SMPA) based TWAT estimation	106
5.2.2	TWAT based WABPS Using Graph Theory	111
5.2.2.1	Graph theory Representation of VSC Interfaced HVAC Grid	112
5.2.2.2	Fault Equations for Different Segments of VSC Converter Interfaced HVAC System	114
5.2.2.3	Fault Segment Identification for WABPS	115
5.2.3	Proposed TW based WABPS	116
5.3	Test hybrid AC/DC system	117
5.4	Simulation results and discussion	119
5.4.1	Impact of fault location	119
5.4.2	Impact of fault impedance	121
5.4.3	Impact of fault type	122
5.4.4	Impact of time synchronization error	123
5.4.5	Impact of fault inception angle	124
5.4.6	Impact of LVRT control of MMC converter	125
5.5	Summary	128

6 Conclusion and future scope	129
6.1 Main contribution	129
6.2 Advantages and limitations	130
6.3 Scope for future work	131
A	133
A.1 Morphological Preliminaries	133
A.2 Coupled Wavelet Description	134
B	135
B.1 Graph Theory Preliminaries	135
List of Publications	155