

# Contents

<b>Abstract</b>	<b>xvi</b>
<b>List of Figures</b>	<b>xxi</b>
<b>List of Tables</b>	<b>xxvii</b>
<b>List of Abbreviations</b>	<b>xxix</b>
<b>List of Symbols</b>	<b>xxxii</b>
<b>1 Introduction</b>	<b>1</b>
1.1 Background . . . . .	1
1.2 Research Motivation . . . . .	5
1.3 Literature Survey . . . . .	8
1.3.1 Bidirectional AC-DC DAB Converters . . . . .	10
1.3.2 Fundamentals of Soft Switching . . . . .	21
1.3.3 Modulation Techniques . . . . .	27
1.4 Research Gap and Challenges with Existing Literature . . . . .	34
1.5 Objective of the Thesis . . . . .	38
1.6 Organization of the Thesis . . . . .	40
1.7 Conclusion . . . . .	42
<b>2 A Novel Soft-Switched Triangular Modulation for DC-AC Dual Active Bridge</b>	<b>43</b>
2.1 Introduction . . . . .	43
2.2 Converter Topology and Proposed Modulation Technique . . . . .	45
2.2.1 Converter Analysis and Operation . . . . .	46
2.2.2 Modulation Technique Using Method 1 . . . . .	50
2.2.3 Modulation Technique Using Method 2 . . . . .	53

2.3	DSP Based Digital Realization of Proposed Techniques . . . . .	56
2.3.1	Digital Realization of Method 1 . . . . .	56
2.3.2	Digital Realization of Method 2 . . . . .	57
2.4	Simulation and Experimental Validation . . . . .	59
2.4.1	Simulation Validation . . . . .	59
2.4.2	Experimental Validation . . . . .	61
2.5	Discussion . . . . .	65
2.5.1	Dynamic Performance . . . . .	65
2.5.2	Soft Switching Analysis . . . . .	66
2.5.3	Comparison of the Proposed Method with the Existing Literature . . . . .	68
2.5.4	Efficiency Comparisons with Other TRM . . . . .	69
2.6	Conclusion . . . . .	72
<b>3</b>	<b>Improved Benchmark Performance with Triangular Modulation and Quasi Single-Stage AC-DC DAB</b>	<b>73</b>
3.1	Introduction . . . . .	73
3.2	Analysis and Operating Principle of Q1S AC-DC DAB . . . . .	77
3.2.1	Operation of Q1S DAB Using Proposed Technique . . . . .	81
3.3	Realization and Comparison of Switching Sequence for Q1S DAB . . . . .	84
3.3.1	Realization of Conventional TRM . . . . .	84
3.3.2	Realization of Proposed TRM . . . . .	86
3.3.3	Comparison Between Conventional and Proposed TRM . . . . .	87
3.3.4	Benchmark Evaluation of Both TRM . . . . .	89
3.4	Experimental Validation . . . . .	90
3.4.1	Validation of AC→DC Power Flow . . . . .	91
3.4.2	Status of Various Devices at Different Values of $\gamma$ . . . . .	93
3.4.3	Validation of DC→AC Power Flow . . . . .	93
3.4.4	Dynamic Characteristics of the Proposed System . . . . .	95
3.4.5	Analysis of THD and Other Power Quality . . . . .	95
3.5	Comparison With Other Literature . . . . .	97
3.5.1	Efficiency Comparison . . . . .	97
3.5.2	Total Harmonics Distortion Comparison . . . . .	97
3.6	Conclusion . . . . .	99
<b>4</b>	<b>Asymmetric Semi-Variable Frequency Based Triangular Modulation with Improving Light-Load Performance</b>	<b>101</b>
4.1	Introduction . . . . .	101

4.2	Mathematical Modeling and the Proposed TRM . . . . .	104
4.2.1	Mathematical Modeling of the Proposed ASVF TRM . . . . .	104
4.2.2	Relationship of $\zeta$ and $f_s$ with RMS Inductor current . . . . .	108
4.2.3	Relationship Between THD and Switching Frequency . . . . .	109
4.2.4	Optimizing $\zeta$ and $f_s$ in the Proposed ASVF TRM . . . . .	110
4.3	Open Loop Control Realization . . . . .	110
4.3.1	Open Loop Control Realization . . . . .	110
4.3.2	Converter Design . . . . .	115
4.4	Experimental Results . . . . .	118
4.4.1	Steady State Result at Rated Power . . . . .	118
4.4.2	Soft Switching Performance Analysis . . . . .	119
4.4.3	Performance of Conventional and Proposed TRMs at Light Load . . . . .	122
4.4.4	Dynamic Performance at Semi-Variable Frequencies . . . . .	123
4.4.5	THD and Other Power Quality Indices . . . . .	125
4.5	Discussion and Comparison . . . . .	125
4.5.1	Discussion on RMS Current and Conduction Loss . . . . .	125
4.5.2	Losses Distribution . . . . .	126
4.5.3	Experimental Efficiency and THD Comparison . . . . .	128
4.5.4	Comparison with Other Literature . . . . .	129
4.6	Conclusion . . . . .	131
<b>5</b>	<b>Hybrid Energy Input-Based DC Charging System</b>	<b>133</b>
5.1	Introduction . . . . .	133
5.2	Proposed EV Charging System . . . . .	138
5.3	Proposed Adaptive Optimal Power Management Scheme . . . . .	141
5.3.1	MPPT with power constraint and voltage controller for boost converter . . . . .	141
5.3.2	Controller with power factor correction and voltage controller for $3\phi$ converter . . . . .	143
5.3.3	CC-CV charge controller for DAB . . . . .	145
5.4	Experimental Validation . . . . .	145
5.4.1	Dynamic variation of PV during mode 2 operation . . . . .	146
5.4.2	Dynamic variation from mode 2 to mode 3 and vice versa . . . . .	148
5.4.3	Dynamic load variation . . . . .	150
5.4.4	Dynamic variation from mode 1 to mode 2 and vice versa . . . . .	151
5.4.5	Mode 6:- Vehicle to vehicle charging . . . . .	152

---

5.4.6	THD of the grid current during mode 3 operation . . . . .	152
5.5	Comparison with other Charging Systems . . . . .	152
5.6	Challenges and Future Direction . . . . .	154
5.7	Conclusion . . . . .	154
<b>6</b>	<b>Conclusion and Future Directions</b>	<b>157</b>
6.1	Introduction . . . . .	157
6.2	Conclusion . . . . .	159
6.3	Future Directions . . . . .	163
	<b>Appendix A: Loss Calculation</b>	<b>165</b>
A.1	IGBT Conduction Loss . . . . .	165
A.2	MOSFET Conduction and Switching loss . . . . .	165
A.3	Gate loss of the Devices . . . . .	166
A.4	Power Losses in Magnetic Components . . . . .	166
A.5	Power Losses in Capacitor . . . . .	167
	<b>Bibliography</b>	<b>169</b>
	<b>List of Publications</b>	<b>191</b>