

CONTENTS

<i>List of Figures</i>	xviii-xxiii
<i>List of Tables</i>	xxiv
<i>List of Abbreviations</i>	xxv-xxvi
<i>List of Symbols</i>	xxvii
<i>Preface</i>	xxviii-xxix
CHAPTER 1	1-39

Introduction and Scope of the Thesis

1.1	Photodetector.....	3
1.1.1	Device Structures for Photodetectors.....	5
1.1.1.1	Photoconductors.....	5
1.1.2.2	Photodiodes.....	6
1.1.2	Key Performance Parameters of Photodetectors.....	8
1.1.2.1	Responsivity.....	9
1.1.2.2	Detectivity.....	9
1.1.2.3	External Quantum Efficiency (EQE).....	10
1.1.2.4	Response Time.....	10
1.1.2.5	Other Figure of Merits.....	10
1.2	Perovskite Materials for Photodetectors.....	11
1.2.1	Properties of BiFeO ₃ Inorganic Perovskite.....	13
1.2.2	Properties of CH ₃ NH ₃ PbI ₃ Hybrid Perovskite.....	13

1.3	Fabrication Process for Perovskite Photodetectors.....	14
1.3.1	Fabrication of Photoactive Layer.....	15
1.3.2	Charge Transport Layers (ETL and HTL)	17
1.3.3	Fabrication of Contact Electrodes.....	18
1.4	Characterization Techniques for Perovskite Based Photodetectors....	19
1.4.1	Material Characterization Techniques	19
1.4.1.1	X-Ray Diffraction (XRD).....	20
1.4.1.2	Scanning Electron Microscopy (SEM).....	21
1.4.1.3	UV-Visible Spectroscopy (UV-Vis)	22
1.4.1.4	Photoluminescence Spectroscopy (PL).....	23
1.4.2	Device Characterization Techniques.....	24
1.4.2.1	Dark Conditions Measurements.....	24
1.4.2.2	Photoresponse Measurements.....	26
1.5	Literature Review.....	28
1.5.1	Perovskite Materials Based Devices: A General Review.....	28
1.5.2	Review of Inorganic BiFeO ₃ Perovskite Based Photodetectors....	30
1.5.3	Review of Hybrid CH ₃ NH ₃ PbI ₃ Perovskite Based Photodetectors	31
1.6	Major Observation from the Literature Survey.....	34
1.7	Issues and Challenges in Perovskite Photodetectors.....	35
1.8	Motivation and Problem Definition.....	36
1.9	Scope and Layout of the Thesis.....	37

CHAPTER 2**40-59****Solid State Synthesized BiFeO₃ Perovskite Based Fast Response White Light Photodetector**

2.1	Introduction.....	41
2.2	Experimental Details.....	42
2.2.1	Materials Synthesis.....	42
2.2.2	Device Fabrication.....	44
2.2.2.1	Substrate Cleaning.....	44
2.2.2.2	Thin Film Deposition.....	44
2.3	Results and Discussion.....	46
2.3.1	Thin Film Characterizations.....	46
2.3.2	Electrical Characterizations.....	51
2.3.3	Optical Characterizations.....	55
2.4	Conclusion.....	59

CHAPTER 3**60-80****High Performance Photodetector Based on Hybrid Perovskite CH₃NH₃PbI₃/ZnO Heterostructure**

3.1	Introduction.....	61
3.2	Experimental Details.....	62
3.2.1	Materials Synthesis.....	62
3.2.2	Device Fabrication.....	64

3.2.2.1	Substrate Cleaning.....	64
3.2.2.2	Thin Film Deposition.....	64
3.3	Results and Discussion.....	66
3.3.1	Thin Film Characterizations.....	66
3.3.2	Electrical Characterizations.....	72
3.3.3	Optical Characterizations.....	77
3.4	Conclusion.....	79

CHAPTER 4 **81-101**

**BiFeO₃/CH₃NH₃PbI₃ Inorganic-Hybrid Organic Perovskites
Heterojunction Based Wideband Photodetector**

4.1	Introduction.....	82
4.2	Experimental Details.....	83
4.2.1	Materials Synthesis.....	83
4.2.2	Device Fabrication.....	85
4.2.2.1	Substrate Cleaning.....	85
4.2.2.2	Thin Film Deposition.....	85
4.3	Results and Discussion.....	86
4.3.1	Thin Film Characterizations.....	86
4.3.2	Electrical Characterizations.....	92
4.3.3	Optical Characterizations.....	97
4.4	Conclusion.....	101

CHAPTER 5 **102-106**

Conclusion and Future Scope

5.1	Major Observations.....	103
5.2	Future Scope of Work.....	106
	<i>Reference</i>	107-125
	<i>Author's Relevant Publications</i>	126-127
	<i>Achievements</i>	128

LIST OF FIGURES

Figure 1.1:	The diagrammatic representation of the photodetector in (a) vertical structure and (b) horizontal structure.	5
Figure 1.2:	The schematic diagram of the photoconductor device.	6
Figure 1.3:	The schematic diagram of the p-n photodiode device.	7
Figure 1.4:	Representation of the energy band diagram for the p-n photodiode device.	7
Figure 1.5:	Unit cell of the perovskite crystal structure.	12
Figure 1.6:	The schematic structure of (p-i-n) perovskite photodetector.	15
Figure 1.7:	The schematic diagram of the sol-gel formation mechanism.	17
Figure 1.8:	Spin-coating process steps (a) Spin-coating unit (b) Substrate on the spin-coating unit and (c) film deposition on the substrate.	17
Figure 1.9:	Thermal evaporation deposition instrument for metal electrode deposition.	19
Figure 1.10:	Working principle of the X-ray diffraction (XRD).	21
Figure 1.11:	Experimental measurement setup and working of the SEM instrument.	22
Figure 1.12:	Working principle and experimental measurement setup for the UV-Vis spectroscopy.	23
Figure 1.13:	Experimental Setup and working principle of the Photoluminescence spectroscopy.	24
Figure 1.14:	Semiconductor parameter analyser for the measurements of various electrical parameters.	25
Figure 1.15:	Experimental measurement setup for the electrical characterizations.	26
Figure 1.16:	Experimental measurement setup for the photocurrent measurements.	27
Figure 2.1:	Synthesis of the ZnO nanoparticles.	43
Figure 2.2:	Synthesis of the perovskite BiFeO ₃ nanoparticles.	43
Figure 2.3:	Schematic representation of the fabricated steps used for	45

	fabrication of BiFeO ₃ based white Light photodetector device.	
Figure 2.4:	XRD peaks of the ZnO NPs thin film coated on the glass substrate using X-ray diffraction (RIGAKU-Smart XDMAX, PC-20, 18-Kw Cu rotating anode, Rigaku, Tokyo) at room temperature.	46
Figure 2.5:	XRD peaks of the BiFeO ₃ nanoparticles coated on the glass substrate using X-ray diffraction (RIGAKU-Smart XDMAX, PC-20, 18-Kw Cu rotating anode, Rigaku, Tokyo) at room temperature.	47
Figure 2.6:	HRSEM image of the ZnO nanoparticles on the glass substrate using high-resolution scanning electron microscope (HRSEM, Nova Nano SEM 450, USA).	48
Figure 2.7:	HRSEM image of the BiFeO ₃ nanoparticles on the glass substrate using high-resolution scanning electron microscope (HRSEM, Nova Nano SEM 450, USA).	49
Figure 2.8:	Absorbance spectra of the perovskite BiFeO ₃ thin film and ZnO nanoparticles thin film coated on the glass substrate using (UV-Vis) spectroscopy (V-770 from JASCO, Japan).	50
Figure 2.9:	Tauc plot of the perovskite BiFeO ₃ thin film and ZnO nanoparticles thin film coated on the glass substrate for bandgap calculation using (UV-Vis) spectroscopy (V-770 from JASCO, Japan).	51
Figure 2.10:	Capacitance voltage (<i>C-V</i>) characteristics of the fabricated heterostructure device at 1000 Hz frequency using a semiconductor parameter analyzer (B1500A from Keysight, USA).	52
Figure 2.11:	Schematic energy band diagram of the proposed heterojunction photodetector.	53
Figure 2.12:	Current-voltage (<i>I-V</i>) characteristics of the proposed heterojunction photodetector using a semiconductor parameter analyzer (B1500A from Keysight, USA) under dark and light illumination of 1 sun (obtained from solar simulator manufactured by PET, USA) condition.	54
Figure 2.13:	Logarithmic current-voltage (<i>ln I-V</i>) characteristics of the proposed heterojunction photodetector using a semiconductor parameter analyzer (B1500A from Keysight, USA) under dark and light illumination of 1 sun (obtained from solar simulator manufactured by PET, USA) condition.	55
Figure 2.14:	Responsivity of the proposed photodetector device against wavelength in the range of 400-750 nm at an applied bias	56

	voltage of -2V using a monochromator (SP2150i from Princeton Instruments, USA) along with a halogen light source.	
Figure 2.15:	External quantum efficiency (EQE) of the proposed photodetector device against wavelength in the range of 400-750 nm using a monochromator (SP2150i from Princeton Instruments, USA) along with a halogen light source.	57
Figure 2.16:	Transient response of the proposed heterojunction photodetector illuminated by the white pulse light (optical power density of $\sim 40.3 \mu\text{W}/\text{cm}^2$).	58
Figure 2.17:	Single-cycle of the transient response for rise time and fall time calculation.	59
Figure 3.1:	Synthesis of the ZnO nanoparticles.	63
Figure 3.2:	Synthesis of the hybrid perovskite $\text{CH}_3\text{NH}_3\text{PbI}_3$ nanoparticles.	63
Figure 3.3:	Schematic representation of the fabricated steps used for fabrication of hybrid perovskite $\text{CH}_3\text{NH}_3\text{PbI}_3$ based photodetector device.	66
Figure 3.4:	XRD peaks of the ZnO NPs thin film deposited on the glass substrate using X-ray diffraction (RIGAKU-Smart XDMAX, PC-20, 18-Kw Cu rotating anode, Rigaku, Tokyo) at room temperature.	67
Figure 3.5:	XRD pattern of the perovskite $\text{CH}_3\text{NH}_3\text{PbI}_3$ thin film deposited on the glass substrate using X-ray diffraction (RIGAKU-Smart XDMAX, PC-20, 18-Kw Cu rotating anode, Rigaku, Tokyo) at room temperature.	68
Figure 3.6:	HRSEM image of the ZnO nanoparticles on the glass substrate using high-resolution scanning electron microscope (HRSEM, Nova Nano SEM 450, USA).	69
Figure 3.7:	HRSEM image of the perovskite $\text{CH}_3\text{NH}_3\text{PbI}_3$ thin film on the glass substrate using high-resolution scanning electron microscope (HRSEM, Nova Nano SEM 450, USA).	69
Figure 3.8:	Absorbance spectra of the ZnO nanoparticles deposited on the glass substrate, hybrid perovskite $\text{CH}_3\text{NH}_3\text{PbI}_3$ thin film deposited on the glass substrate and perovskite $\text{CH}_3\text{NH}_3\text{PbI}_3$ thin film deposited on ZnO deposited glass substrate using (UV-Vis) spectroscopy (V-770 from JASCO, Japan).	70
Figure 3.9:	Emission spectrum of the ZnO nanoparticles deposited on the glass substrate, hybrid perovskite $\text{CH}_3\text{NH}_3\text{PbI}_3$ thin film deposited on the glass substrate and perovskite $\text{CH}_3\text{NH}_3\text{PbI}_3$ thin film deposited on ZnO deposited glass substrate using	72

	photoluminescence (PL) spectroscopy (FLS 980 from Edinburgh Instruments, UK).	
Figure 3.10:	Capacitance voltage (C - V) characteristics of the fabricated heterostructure device at 1 MHz frequency using a semiconductor parameter analyzer (B1500A from Keysight, USA).	73
Figure 3.11:	Schematic energy band diagram of the proposed heterojunction photodetector.	74
Figure 3.12:	Current-voltage (I - V) characteristics of the proposed heterojunction photodetector at room temperature and in -1 V to 1 V bias voltage range by using a semiconductor parameter analyzer (B1500A from Keysight, USA) under dark and illumination of 1 sun (obtained from solar simulator manufactured by PET, USA) condition.	76
Figure 3.13:	Logarithmic current-voltage ($\ln I$ - V) characteristics of the proposed heterojunction photodetector at room temperature and in -1 V to 1 V bias voltage range by using a semiconductor parameter analyzer (B1500A from Keysight, USA) under dark and illumination of 1 sun (obtained from solar simulator manufactured by PET, USA) condition.	77
Figure 3.14:	Responsivity of the proposed photodetector device against wavelength in the range of 350-700 nm from a monochromator (SP2150i from Princeton Instruments, USA) along with a halogen light source.	78
Figure 3.15:	External quantum efficiency (EQE) of the proposed photodetector device against wavelength in the range of 350-700 nm from a monochromator (SP2150i from Princeton Instruments, USA) along with a halogen light source.	79
Figure 4.1:	Synthesis of the perovskite BiFeO ₃ nanoparticles.	84
Figure 4.2:	Synthesis of the hybrid Perovskite CH ₃ NH ₃ PbI ₃ nanoparticles.	84
Figure 4.3:	Schematic block diagram of the fabricated steps used for fabrication of photodetector device.	86
Figure 4.4:	XRD peaks of the BiFeO ₃ nanoparticles coated on the glass substrate using X-ray diffraction (RIGAKU-Smart XDMAX, PC-20, 18-Kw Cu rotating anode, Rigaku, Tokyo) at room temperature.	87
Figure 4.5:	XRD pattern of the perovskite CH ₃ NH ₃ PbI ₃ thin film deposited on the glass substrate using X-ray diffraction (RIGAKU-Smart XDMAX, PC-20, 18-Kw Cu rotating anode, Rigaku, Tokyo) at	88

	room temperature.	
Figure 4.6:	HRSEM image of the BiFeO ₃ thin film on the glass substrate (Inset HRSEM image of BiFeO ₃ nano-powder) using high-resolution scanning electron microscope (HRSEM, Nova Nano SEM 450, USA).	89
Figure 4.7:	HRSEM image of the perovskite CH ₃ NH ₃ PbI ₃ thin film on the glass substrate using high-resolution scanning electron microscope (HRSEM, Nova Nano SEM 450, USA).	90
Figure 4.8:	Absorbance spectra of the BiFeO ₃ nanoparticles and CH ₃ NH ₃ PbI ₃ thin film deposited on the glass substrate using (UV-Vis) spectroscopy (V-770 from JASCO, Japan).	91
Figure 4.9:	Tauc plot of the BiFeO ₃ nanoparticles and CH ₃ NH ₃ PbI ₃ thin film deposited on the glass substrate using (UV-Vis) spectroscopy (V-770 from JASCO, Japan).	92
Figure 4.10:	Capacitance-voltage (<i>C-V</i>) characteristics of the fabricated heterostructure device at 1000 Hz frequency using a semiconductor parameter analyzer (B1500A from Keysight, USA).	93
Figure 4.11:	Schematic energy band diagram of the proposed heterojunction photodetector.	95
Figure 4.12:	Current-voltage (<i>I-V</i>) characteristics of the proposed heterojunction photodetector at room temperature and in -2 V to 2 V bias voltage range by using a semiconductor parameter analyzer (B1500A from Keysight, USA) under dark and light illumination (monochromatic light of 800 nm with an optical power of ~1.4 μW) condition.	96
Figure 4.13:	Logarithmic current-voltage (<i>I-V</i>) characteristics of the proposed heterojunction photodetector at room temperature and in -2 V to 2 V bias voltage range by using a semiconductor parameter analyzer (B1500A from Keysight, USA) under dark and light illumination (monochromatic light of 800 nm with an optical power of ~1.4 μW) condition.	97
Figure 4.14:	Responsivity and detectivity of the fabricated photodetector device against wavelength in the range of 400-900 nm from a monochromator (SP2150i from Princeton Instruments, USA) along with a halogen light source.	98
Figure 4.15:	External quantum efficiency (EQE) of the fabricated photodetector device against wavelength in the range of 400-900 nm from a monochromator (SP2150i from Princeton Instruments, USA) along with a halogen light source.	99

- Figure 4.16:** Transient photoresponse characteristics of the fabricated photodetector under on-off pulse of monochromatic light of 800 nm with an optical power density of $\sim 44.4 \mu\text{W}/\text{cm}^2$. 100
- Figure 4.17:** Rise time and fall time characteristics of the fabricated photodetector under the illumination of monochromatic light of 800 nm with an optical power density of $\sim 44.4 \mu\text{W}/\text{cm}^2$. 101

LIST OF TABLES

Table 5.1:	Comparison BiFeO ₃ based white light photodetector.	104
Table 5.2:	Comparison of CH ₃ NH ₃ PbI ₃ hybrid perovskite-based broadband photodetector.	105
Table 5.3:	Comparison of perovskite-based ultraviolet to near-infrared region broadband photodetector.	105
Table 5.4:	Comparison of our fabricated Photodetector.	105