

References:

- ABDIZADEH, H., ASHURI, M., MOGHADAM, P. T., NOURIBAHADORY, A. & BAHARVANDI, H. R. 2011. Improvement in physical and mechanical properties of aluminum/zircon composites fabricated by powder metallurgy method. *Materials & Design*, 32, 4417-4423.
- ABDIZADEH, H., BAHARVANDI, H. & MOGHADDAM, K. S. 2008. Comparing the effect of processing temperature on microstructure and mechanical behavior of (ZrSiO₄ or TiB₂)/aluminum composites. *Materials Science and Engineering: A*, 498, 53-58.
- AHN, B.-W., KIM, J.-H., HAMAD, K. & JUNG, S.-B. 2017. Microstructure and mechanical properties of a B₄C particle-reinforced Cu matrix composite fabricated by friction stir welding. *Journal of Alloys and Compounds*, 693, 688-691.
- AKRAMIFARD, H., SHAMANIAN, M., SABBAGHIAN, M. & ESMAILZADEH, M. 2014. Microstructure and mechanical properties of Cu/SiC metal matrix composite fabricated via friction stir processing. *Materials & Design (1980-2015)*, 54, 838-844.
- ALIDOKHT, S., ABDOLLAH-ZADEH, A., SOLEYMANI, S. & ASSADI, H. 2011. Microstructure and tribological performance of an aluminium alloy based hybrid composite produced by friction stir processing. *Materials & Design*, 32, 2727-2733.
- ANANDATHEERTHAN, J. & KUMAR, S. 2008. *Production and Characterisation of Aluminium-Fly ash composite using Stir Casting Method*. NIT Rourkela.
- ANVARI, S., KARIMZADEH, F. & ENAYATI, M. 2013. A novel route for development of Al–Cr–O surface nano-composite by friction stir processing. *Journal of Alloys and Compounds*, 562, 48-55.
- ARBEGAST, W. J. 2008. A flow-partitioned deformation zone model for defect formation during friction stir welding. *Scripta materialia*, 58, 372-376.
- ARCHARD, J. F. 1980. *Wear Theory and Mechanism*, Newyork, M.B. Peterson.

- AREZOUMANDI, M., LOONEY, T. J. & VOLZ, J. S. 2015. Effect of fly ash replacement level on the bond strength of reinforcing steel in concrete beams. *Journal of Cleaner Production*, 87, 745-751.
- ARORA, H., SINGH, H., DHINDAW, B. & GREWAL, H. 2012. Some investigations on friction stir processed zone of AZ91 alloy. *Transactions of the Indian Institute of Metals*, 65, 735-739.
- ASADI, P., FARAJI, G. & BESHARATI, M. K. 2010. Producing of AZ91/SiC composite by friction stir processing (FSP). *The International Journal of Advanced Manufacturing Technology*, 51, 247-260.
- ASADI, P., FARAJI, G., MASOUMI, A. & GIVI, M. B. 2011. Experimental investigation of magnesium-base nanocomposite produced by friction stir processing: effects of particle types and number of friction stir processing passes. *Metallurgical and Materials Transactions A*, 42, 2820-2832.
- AVETTAND-FÈNOËL, M.-N. & SIMAR, A. 2016. A review about friction stir welding of metal matrix composites. *Materials Characterization*, 120, 1-17.
- AVETTAND-FÈNOËL, M.-N., SIMAR, A., SHABADI, R., TAILLARD, R. & DE MEESTER, B. 2014. Characterization of oxide dispersion strengthened copper based materials developed by friction stir processing. *Materials & Design*, 60, 343-357.
- AZIZIEH, M., KOKABI, A. & ABACHI, P. 2011. Effect of rotational speed and probe profile on microstructure and hardness of AZ31/Al₂O₃ nanocomposites fabricated by friction stir processing. *Materials & Design*, 32, 2034-2041.
- B.T. BALAKRISHNA, V. S. A. 1980. *Proc. Indian Acad. Sci. Eng. Sci.*, 3, 275-296.
- BAHRAMI, A., PECH-CANUL, M., GUTIERREZ, C. & SOLTANI, N. 2015. Effect of rice-husk ash on properties of laminated and functionally graded Al/SiC composites by one-step pressureless infiltration. *Journal of Alloys and Compounds*, 644, 256-266.
- BAHRAMI, A., PECH-CANUL, M., SOLTANI, N., GUTIÉRREZ, C., KAMM, P. & GURLO, A. 2017. Tailoring microstructure and properties of bilayer-graded Al/B₄C/MgAl₂O₄ composites by single-stage pressureless infiltration. *Journal of Alloys and Compounds*, 694, 408-418.

- BAHRAMI, A., SOLTANI, N., PECH-CANUL, M. & GUTIÉRREZ, C. 2016. Development of metal-matrix composites from industrial/agricultural waste materials and their derivatives. *Critical Reviews in Environmental Science and Technology*, 46, 143-208.
- BAHRAMI, M., DEHGHANI, K. & GIVI, M. K. B. 2014a. A novel approach to develop aluminum matrix nano-composite employing friction stir welding technique. *Materials & Design*, 53, 217-225.
- BAHRAMI, M., GIVI, M. K. B., DEHGHANI, K. & PARVIN, N. 2014b. On the role of pin geometry in microstructure and mechanical properties of AA7075/SiC nano-composite fabricated by friction stir welding technique. *Materials & Design*, 53, 519-527.
- BALAMURUGAN, P. & UTHAYAKUMAR, M. 2015. Influence of process parameters on Cu–Fly ash composite by powder metallurgy technique. *Materials and Manufacturing Processes*, 30, 313-319.
- BALASUBRAMANIAN, V. 2008. Relationship between base metal properties and friction stir welding process parameters. *Materials Science and Engineering: A*, 480, 397-403.
- BANERJI, A., SURAPPA, M. & ROHATGI, P. 1983. Cast aluminum alloys containing dispersions of zircon particles. *Metallurgical Transactions B*, 14, 273-283.
- BARMOUZ, M., ASADI, P., GIVI, M. B. & TAHERISHARGH, M. 2011a. Investigation of mechanical properties of Cu/SiC composite fabricated by FSP: Effect of SiC particles' size and volume fraction. *Materials Science and Engineering: A*, 528, 1740-1749.
- BARMOUZ, M. & GIVI, M. K. B. 2011. Fabrication of in situ Cu/SiC composites using multi-pass friction stir processing: Evaluation of microstructural, porosity, mechanical and electrical behavior. *Composites Part A: Applied Science and Manufacturing*, 42, 1445-1453.
- BARMOUZ, M., GIVI, M. K. B. & SEYFI, J. 2011b. On the role of processing parameters in producing Cu/SiC metal matrix composites via friction stir processing: Investigating microstructure, microhardness, wear and tensile behavior. *Materials characterization*, 62, 108-117.
- BARMOUZ, M., SEYFI, J., GIVI, M. K. B., HEJAZI, I. & DAVACHI, S. M. 2011c. A novel approach for producing polymer nanocomposites by in-

- situ dispersion of clay particles via friction stir processing. *Materials Science and Engineering: A*, 528, 3003-3006.
- BAURI, R. & SURAPPA, M. 2008. Sliding wear behavior of Al–Li–SiCp composites. *Wear*, 265, 1756-1766.
- BAURI, R., YADAV, D., KUMAR, C. S. & BALAJI, B. 2015. Tungsten particle reinforced Al 5083 composite with high strength and ductility. *Materials Science and Engineering: A*, 620, 67-75.
- BAURI, R., YADAV, D. & SUHAS, G. 2011. Effect of friction stir processing (FSP) on microstructure and properties of Al–TiC in situ composite. *Materials Science and Engineering: A*, 528, 4732-4739.
- BAUTISTA, J., AVILÉS, F., OLIVA, A., CEH, O. & CORONA, J. 2010. Correlations between mechanical stress, electrical conductivity and nanostructure in Al films on a polymer substrate. *Materials Characterization*, 61, 325-329.
- BHAGAT, N., BATRA, V. S. & KATYAL, D. 2011. Preparation and Characterization of Ceramics from Coal Fly Ash. *Asian Journal of Chemistry*, 23, 71-73.
- BHATTACHARJEE, U. & KANDPAL, T. C. 2002. Potential of fly ash utilisation in India. *Energy*, 27, 151-166.
- ÇAM, G. 2011. Friction stir welded structural materials: beyond Al-alloys. *International Materials Reviews*, 56, 1-48.
- CERIANI, L. & VERME, P. 2012. The origins of the Gini index: extracts from *Variabilità e Mutabilità* (1912) by Corrado Gini. *The Journal of Economic Inequality*, 10, 421-443.
- CHAMPION, Y., BOURGON, J. & SAUVAGE, X. 2016. Modified strain rate regime in ultrafine grained copper with silver micro-alloying. *Materials Science and Engineering: A*, 657, 1-5.
- CHANDRASEKHAR, S., SARMA, S. S., RAMAKRISHNA, M., BABU, P. S., RAO, T. N. & KASHYAP, B. 2014. Microstructure and properties of hot extruded Cu–1 wt% Al₂O₃ nano-composites synthesized by various techniques. *Materials Science and Engineering: A*, 591, 46-53.
- CHANG, C., DU, X. & HUANG, J. 2007. Achieving ultrafine grain size in Mg–Al–Zn alloy by friction stir processing. *Scripta Materialia*, 57, 209-212.

- CHANG, C., DU, X. & HUANG, J. 2008. Producing nanogained microstructure in Mg–Al–Zn alloy by two-step friction stir processing. *Scripta materialia*, 59, 356-359.
- CHEN, X.-G., DA SILVA, M., GOUGEON, P. & ST-GEORGES, L. 2009a. Microstructure and mechanical properties of friction stir welded AA6063–B4C metal matrix composites. *Materials Science and Engineering: A*, 518, 174-184.
- CHEN, X., TAO, J., YI, J., LIU, Y., LI, C. & BAO, R. 2018. Strengthening behavior of carbon nanotube-graphene hybrids in copper matrix composites. *Materials Science and Engineering: A*, 718, 427-436.
- CHEN, Y., FUJII, H., TSUMURA, T., KITAGAWA, Y., NAKATA, K., IKEUCHI, K., MATSUBAYASHI, K., MICHISHITA, Y., FUJIYA, Y. & KATOH, J. 2009b. Friction stir processing of 316L stainless steel plate. *Science and Technology of Welding and Joining*, 14, 197-201.
- DADASHPOUR, M., MOSTAFAPOUR, A., YEŞILDAL, R. & ROUHI, S. 2016. Effect of process parameter on mechanical properties and fracture behavior of AZ91C/SiO₂ composite fabricated by FSP. *Materials Science and Engineering: A*, 655, 379-387.
- DAS, A., VERMA, V. & BASAK, C. B. 2016. Elucidating microstructure of spinodal copper alloy through annealing. *Materials Characterization*, 120, 152-158.
- DAS, S., DAS, K. & DAS, S. 2009. Abrasive Wear Behavior of Al-4.5 wt% Cu/(Zircon Sand+ Silicon Carbide) Hybrid Composite. *Journal of composite materials*, 43, 2665-2672.
- DAS, S., DAS, S. & DAS, K. 2007. Abrasive wear of zircon sand and alumina reinforced Al–4.5 wt% Cu alloy matrix composites—A comparative study. *Composites Science and Technology*, 67, 746-751.
- DAS, S., UDHAYABANU, V., DAS, S. & DAS, K. 2006. Synthesis and characterization of zircon sand/Al-4.5 wt% Cu composite produced by stir casting route. *Journal of materials science*, 41, 4668-4677.
- DEHGHANI, K. & MAZINANI, M. 2011. Forming nanocrystalline surface layers in copper using friction stir processing. *Materials and Manufacturing Processes*, 26, 922-925.

- DEVARAJU, A., KUMAR, A., KUMARASWAMY, A. & KOTIVEERACHARI, B. 2013. Influence of reinforcements (SiC and Al₂O₃) and rotational speed on wear and mechanical properties of aluminum alloy 6061-T6 based surface hybrid composites produced via friction stir processing. *Materials & Design*, 51, 331-341.
- DIÁNEZ, M., DONOSO, E., SAYAGUÉS, M., PEREJÓN, A., SÁNCHEZ-JIMÉNEZ, P., PÉREZ-MAQUEDA, L. & CRIADO, J. 2016. The calorimetric analysis as a tool for studying the aging hardening mechanism of a Cu-10wt% Ni-5.5 wt% Sn alloy. *Journal of Alloys and Compounds*, 688, 288-294.
- DINAHARAN, I., KALAISELVAN, K., AKINLABI, E. & DAVIM, J. P. 2017a. Microstructure and wear characterization of rice husk ash reinforced copper matrix composites prepared using friction stir processing. *Journal of Alloys and Compounds*, 718, 150-160.
- DINAHARAN, I., KALAISELVAN, K. & MURUGAN, N. 2017b. Influence of rice husk ash particles on microstructure and tensile behavior of AA6061 aluminum matrix composites produced using friction stir processing. *Composites Communications*, 3, 42-46.
- DINAHARAN, I., NELSON, R., VIJAY, S. & AKINLABI, E. T. 2016a. Microstructure and wear characterization of aluminum matrix composites reinforced with industrial waste fly ash particulates synthesized by friction stir processing. *Materials Characterization*, 118, 149-158.
- DINAHARAN, I., SARAVANAKUMAR, S., KALAISELVAN, K. & GOPALAKRISHNAN, S. 2017c. Microstructure and sliding wear characterization of Cu/TiB₂ copper matrix composites fabricated via friction stir processing. *Journal of Asian Ceramic Societies*, 5, 295-303.
- DINAHARAN, I., SATHISKUMAR, R. & MURUGAN, N. 2016b. Effect of ceramic particulate type on microstructure and properties of copper matrix composites synthesized by friction stir processing. *Journal of Materials Research and Technology*, 5, 302-316.
- DING, R. & GUO, Z. 2001. Coupled quantitative simulation of microstructural evolution and plastic flow during dynamic recrystallization. *Acta materialia*, 49, 3163-3175.

- DOLATKHAH, A., GOLBABAEI, P., GIVI, M. B. & MOLAIEKIYA, F. 2012. Investigating effects of process parameters on microstructural and mechanical properties of Al5052/SiC metal matrix composite fabricated via friction stir processing. *Materials & Design*, 37, 458-464.
- DON-HYUN, C., YONG-HWAN, K., BYUNG-WOOK, A., YONG-IL, K. & SEUNG-BOO, J. 2013. Microstructure and mechanical property of A356 based composite by friction stir processing. *Transactions of Nonferrous Metals Society of China*, 23, 335-340.
- DU, Z., TAN, M. J., GUO, J. F., BI, G. & WEI, J. 2016. Fabrication of a new Al-Al₂O₃-CNTs composite using friction stir processing (FSP). *Materials Science and Engineering: A*, 667, 125-131.
- EFE, G. C., IPEK, M., ZEYTIN, S. & BINDAL, C. 2012. An investigation of the effect of SiC particle size on Cu-SiC composites. *Composites Part B: Engineering*, 43, 1813-1822.
- EFTEKHARINIA, H., AMADEH, A. A., KHODABANDEH, A. & PAIDAR, M. 2016. Microstructure and wear behavior of AA6061/SiC surface composite fabricated via friction stir processing with different pins and passes. *Rare Metals*, 1-7.
- EJIOFO, J., OKORIE, B. & REDDY, R. 1997. Powder processing and properties of zircon-reinforced Al-13.5 Si-2.5 Mg alloy composites. *Journal of Materials Engineering and Performance*, 6, 326-334.
- EL-KADY, O. & FATHY, A. 2014. Effect of SiC particle size on the physical and mechanical properties of extruded Al matrix nanocomposites. *Materials & Design (1980-2015)*, 54, 348-353.
- EL-RAYES, M. M. & EL-DANAF, E. A. 2012. The influence of multi-pass friction stir processing on the microstructural and mechanical properties of Aluminum Alloy 6082. *Journal of Materials Processing Technology*, 212, 1157-1168.
- ELANGO VAN, K. & BALASUBRAMANIAN, V. 2008a. Influences of tool pin profile and tool shoulder diameter on the formation of friction stir processing zone in AA6061 aluminium alloy. *Materials & design*, 29, 362-373.
- ELANGO VAN, K. & BALASUBRAMANIAN, V. 2008b. Influences of tool pin profile and welding speed on the formation of friction stir processing zone

- in AA2219 aluminium alloy. *Journal of materials processing technology*, 200, 163-175.
- ELANGO VAN, K., BALASUBRAMANIAN, V. & VALLIAPPAN, M. 2008. Influences of tool pin profile and axial force on the formation of friction stir processing zone in AA6061 aluminium alloy. *The international journal of advanced manufacturing technology*, 38, 285-295.
- ESKANDARI, H., TAHERI, R. & KHODABAKHSHI, F. 2016. Friction-stir processing of an AA8026-TiB₂-Al₂O₃ hybrid nanocomposite: Microstructural developments and mechanical properties. *Materials Science and Engineering: A*, 660, 84-96.
- EZATPOUR, H. R., SAJJADI, S. A., SABZEVAR, M. H. & HUANG, Y. 2014. Investigation of microstructure and mechanical properties of Al6061-nanocomposite fabricated by stir casting. *Materials & Design*, 55, 921-928.
- FARAJI, G. & ASADI, P. 2011. Characterization of AZ91/alumina nanocomposite produced by FSP. *Materials Science and Engineering: A*, 528, 2431-2440.
- FARAJI, G., DASTANI, O. & MOUSAVI, S. A. A. A. 2011. Effect of process parameters on microstructure and micro-hardness of AZ91/Al₂O₃ surface composite produced by FSP. *Journal of Materials Engineering and Performance*, 20, 1583-1590.
- FARIA, J. P. G. 2010. *Aplicação de ensaios não destrutivos por correntes induzidas à caracterização de propriedades eléctricas de materiais processados no estado sólido*. Faculdade de Ciências e Tecnologia.
- FARNOUSH, H., SADEGHI, A., BASTAMI, A. A., MOZTARZADEH, F. & MOHANDESI, J. A. 2013. An innovative fabrication of nano-HA coatings on Ti-CaP nanocomposite layer using a combination of friction stir processing and electrophoretic deposition. *Ceramics International*, 39, 1477-1483.
- FATHY, A., ELKADY, O. & ABU-OQAIL, A. 2017. Synthesis and characterization of Cu-ZrO₂ nanocomposite produced by thermochemical process. *Journal of Alloys and Compounds*, 719, 411-419.
- FATHY, A. & MEGAHED, A. 2012. Prediction of abrasive wear rate of in situ Cu-Al₂O₃ nanocomposite using artificial neural networks. *The*

International Journal of Advanced Manufacturing Technology, 62, 953-963.

GANDRA, J., MIRANDA, R., VILACA, P., VELHINHO, A. & TEIXEIRA, J. P. 2011. Functionally graded materials produced by friction stir processing.

Journal of Materials Processing Technology, 211, 1659-1668.

GHASEMI-KAHRIZSANGI, A. & KASHANI-BOZORG, S. F. 2012.

Microstructure and mechanical properties of steel/TiC nano-composite surface layer produced by friction stir processing. *Surface and Coatings Technology*, 209, 15-22.

GHASEMI-KAHRIZSANGI, A., KASHANI-BOZORG, S. F., MOSHREF-JAVADI, M. & SHARIFIFAR, M. 2015. Friction stir processing of mild steel/Al₂O₃ nanocomposite: Modeling and experimental studies.

Metallography, Microstructure, and Analysis, 4, 122-130.

GOLMOHAMMADI, M., ATAPOUR, M. & ASHRAFI, A. 2015. Fabrication and wear characterization of an A413/Ni surface metal matrix composite fabricated via friction stir processing. *Materials & Design*, 85, 471-482.

GOPI, K., MOHANDAS, K., REDDAPPA, H. & RAMESH, M. 2013.

Characterization of as Cast and Heat Treated Aluminum 6061/Zircon Sand/Graphite Particulate Hybrid Composites. *Int. J. Eng. Adv. Technol*, 2, 340-344.

GU, L., LIANG, G. & ZHENG, Z. 2007. Investigation of In situ Cu-TiB₂ Composite on the Copper Using Laser Melting Synthesis. *Journal of Materials Engineering and Performance*, 16, 554-558.

GUERRA, M., SCHMIDT, C., MCCLURE, J., MURR, L. & NUNES, A. 2002.

Flow patterns during friction stir welding. *Materials characterization*, 49, 95-101.

GUO, M., YI, L., ZHU, J., LIN, T. & LI, M. 2016. Strain-induced martensitic transformation of particles in a copper-based composite and its effect on mechanical properties. *Materials Characterization*, 120, 109-114.

HASHEMI, R. & HUSSAIN, G. 2015. Wear performance of Al/TiN dispersion strengthened surface composite produced through friction stir process: A comparison of tool geometries and number of passes. *Wear*, 324, 45-54.

HEIDARZADEH, A., JABBARI, M. & ESMAILY, M. 2015. Prediction of grain size and mechanical properties in friction stir welded pure copper joints

- using a thermal model. *The International Journal of Advanced Manufacturing Technology*, 77, 1819-1829.
- HEMALATHA, T., MAPA, M., GEORGE, N. & SASMAL, S. 2016. Physico-chemical and mechanical characterization of high volume fly ash incorporated and engineered cement system towards developing greener cement. *Journal of Cleaner Production*, 125, 268-281.
- HODDER, K., IZADI, H., MCDONALD, A. & GERLICH, A. 2012. Fabrication of aluminum–alumina metal matrix composites via cold gas dynamic spraying at low pressure followed by friction stir processing. *Materials Science and Engineering: A*, 556, 114-121.
- HUANG, Y., WANG, T., GUO, W., WAN, L. & LV, S. 2014. Microstructure and surface mechanical property of AZ31 Mg/SiCp surface composite fabricated by direct friction stir processing. *Materials & Design*, 59, 274-278.
- HUSSAIN, G., HASHEMI, R., HASHEMI, H. & AL-GHAMDI, K. A. 2016. An experimental study on multi-pass friction stir processing of Al/TiN composite: some microstructural, mechanical, and wear characteristics. *The International Journal of Advanced Manufacturing Technology*, 84, 533-546.
- IBRAHIM, I., MOHAMED, F. & LAVERNIA, E. 1991. Particulate reinforced metal matrix composites—a review. *Journal of materials science*, 26, 1137-1156.
- IZADI, H., SANDSTROM, R. & GERLICH, A. P. 2014. Grain growth behavior and Hall–Petch strengthening in friction stir processed Al 5059. *Metallurgical and Materials Transactions A*, 45, 5635-5644.
- JAIN, A. 2016. Status of Availability, Utilization and Potential of Fly Ash Use in Construction. UltraTech Cement Ltd.
- JEONG, E., HAN, S., GOTO, M. & KIM, S. 2009. Effects of thermo-mechanical processing and trace amount of carbon addition on tensile properties of Cu–2.5 Fe–0.1 P alloys. *Materials Science and Engineering: A*, 520, 66-74.
- JOHANNES, L. B., YOWELL, L. L., SOSA, E., AREPALLI, S. & MISHRA, R. S. 2006. Survivability of single-walled carbon nanotubes during friction stir processing. *Nanotechnology*, 17, 3081.

- JUANG, S. H. & XUE, C.-S. 2015. Investigation of mechanical properties and microstructures of aluminum-fly ash composite processed by friction stirring. *Materials Science and Engineering: A*, 640, 314-319.
- KARTHIKEYAN, L., SENTHILKUMAR, V. & PADMANABHAN, K. 2010. On the role of process variables in the friction stir processing of cast aluminum A319 alloy. *Materials & Design*, 31, 761-771.
- KASHANI-BOZORG, S. F., SAMIEE, M. & HONARBAKHSR-RAOUF, A. 2015. Fabrication of Al/AlN nano-composite layers by friction stir processing of 6061 Al-T6 substrate. *Surface and Interface Analysis*, 47, 227-238.
- KAUR, K. & PANDEY, O. 2010. Microstructural characteristics of spray formed zircon sand reinforced LM13 composite. *Journal of Alloys and Compounds*, 503, 410-415.
- KHANDKAR, M., KHAN, J. A. & REYNOLDS, A. P. 2003. Prediction of temperature distribution and thermal history during friction stir welding: input torque based model. *Science and Technology of Welding and Joining*, 8, 165-174.
- KHAYYAMIN, D., MOSTAFAPOUR, A. & KESHMIRI, R. 2013. The effect of process parameters on microstructural characteristics of AZ91/SiO₂ composite fabricated by FSP. *Materials Science and Engineering: A*, 559, 217-221.
- KHORRAMI, M. S., SAMADI, S., JANGHORBAN, Z. & MOVAHEDI, M. 2015. In-situ aluminum matrix composite produced by friction stir processing using FE particles. *Materials Science and Engineering: A*, 641, 380-390.
- KIM, C.-S., SOHN, I., NEZAFATI, M., FERGUSON, J., SCHULTZ, B. F., BAJESTANI-GOHARI, Z., ROHATGI, P. K. & CHO, K. 2013. Prediction models for the yield strength of particle-reinforced unimodal pure magnesium (Mg) metal matrix nanocomposites (MMNCs). *Journal of Materials Science*, 48, 4191-4204.
- KIM, Y., FUJII, H., TSUMURA, T., KOMAZAKI, T. & NAKATA, K. 2006. Three defect types in friction stir welding of aluminum die casting alloy. *Materials Science and Engineering: A*, 415, 250-254.

- KOKSAL, S., FICICI, F., KAYIKCI, R. & SAVAS, O. 2012. Experimental optimization of dry sliding wear behavior of in situ AlB₂/Al composite based on Taguchi's method. *Materials & Design*, 42, 124-130.
- KOUZELI, M. & MORTENSEN, A. 2002. Size dependent strengthening in particle reinforced aluminium. *Acta Materialia*, 50, 39-51.
- KOVTUN, M., ZIOLKOWSKI, M., SHEKHOVTSOVA, J. & KEARSLEY, E. 2016. Direct electric curing of alkali-activated fly ash concretes: a tool for wider utilization of fly ashes. *Journal of Cleaner Production*, 133, 220-227.
- KUMAR, C. S., BAURI, R. & YADAV, D. 2016. Wear properties of 5083 Al-W surface composite fabricated by friction stir processing. *Tribology International*, 101, 284-290.
- KUMAR, K. & KAILAS, S. V. 2008. The role of friction stir welding tool on material flow and weld formation. *Materials Science and Engineering: A*, 485, 367-374.
- KUMAR, N., KOMARASAMY, M., NELATURU, P., TANG, Z., LIAW, P. & MISHRA, R. 2015. Friction stir processing of a high entropy alloy Al 0.1 CoCrFeNi. *Jom*, 67, 1007-1013.
- KUMAR, S., PANWAR, R. S. & PANDEY, O. 2013. Effect of dual reinforced ceramic particles on high temperature tribological properties of aluminum composites. *Ceramics International*, 39, 6333-6342.
- KUMAR, S., SHARMA, V., PANWAR, R. S. & PANDEY, O. 2012. Wear behavior of dual particle size (DPS) zircon sand reinforced aluminum alloy. *Tribology Letters*, 47, 231-251.
- KURT, A., UYGUR, I. & CETE, E. 2011. Surface modification of aluminium by friction stir processing. *Journal of materials processing technology*, 211, 313-317.
- LANGLADE, C., ROMAN, A., SCHLEGEL, D., GETE, E. & FOLEA, M. 2016. Formation of a tribologically transformed surface (TTS) on AISI 1045 steel by friction stir processing. *Materials and Manufacturing Processes*, 31, 1565-1572.
- LEE, J., KIM, N. J., JUNG, J., LEE, E.-S. & AHN, S. 1998. The influence of reinforced particle fracture on strengthening of spray formed Cu-TiB {sub 2} composite. *Scripta Materialia*, 39.

- LEE, W.-B. & JUNG, S.-B. 2004. The joint properties of copper by friction stir welding. *Materials Letters*, 58, 1041-1046.
- LEKATOU, A., KARANTZALIS, A. E., EVANGELOU, A., GOUSIA, V., KAPTAY, G., GÁCSI, Z., BAUMLI, P. & SIMON, A. 2015. Aluminium reinforced by WC and TiC nanoparticles (ex-situ) and aluminide particles (in-situ): Microstructure, wear and corrosion behaviour. *Materials & Design (1980-2015)*, 65, 1121-1135.
- LI, B. & CHAO, C. 1996. Mechanical properties and 95 aging characteristics of zircon-reinforced Zn-4Al-3Cu alloy. *Metallurgical and Materials Transactions A*, 27, 809-818.
- LI, B., SHEN, Y., LUO, L. & HU, W. 2013. Fabrication of TiCp/Ti-6Al-4V surface composite via friction stir processing (FSP): Process optimization, particle dispersion-refinement behavior and hardening mechanism. *Materials Science and Engineering: A*, 574, 75-85.
- LI, C., FENG, X., SHEN, Y. & CHEN, W. 2016. Preparation of Al₂O₃/TiO₂ particle-reinforced copper through plasma spraying and friction stir processing. *Materials & Design*, 90, 922-930.
- LIM, D., SHIBAYANAGI, T. & GERLICH, A. 2009. Synthesis of multi-walled CNT reinforced aluminium alloy composite via friction stir processing. *Materials Science and Engineering: A*, 507, 194-199.
- LIN, Y., ZHANG, Y., XIONG, B. & LAVERNIA, E. J. 2012. Achieving high tensile elongation in an ultra-fine grained Al alloy via low dislocation density. *Materials Letters*, 82, 233-236.
- LIU, Z., XIAO, B., WANG, W. & MA, Z. 2013. Developing high-performance aluminum matrix composites with directionally aligned carbon nanotubes by combining friction stir processing and subsequent rolling. *Carbon*, 62, 35-42.
- LIU, Z., XIAO, B., WANG, W. & MA, Z. 2014. Analysis of carbon nanotube shortening and composite strengthening in carbon nanotube/aluminum composites fabricated by multi-pass friction stir processing. *Carbon*, 69, 264-274.
- LLOYD, D. 1994. Particle reinforced aluminium and magnesium matrix composites. *International materials reviews*, 39, 1-23.

- LU, D., JIANG, Y. & ZHOU, R. 2013. Wear performance of nano-Al₂O₃ particles and CNTs reinforced magnesium matrix composites by friction stir processing. *Wear*, 305, 286-290.
- LU, J., SHU, S., QIU, F., WANG, Y. & JIANG, Q. 2012. Compression properties and abrasive wear behavior of high volume fraction TiC_x-TiB₂/Cu composites fabricated by combustion synthesis and hot press consolidation. *Materials & Design*, 40, 157-162.
- LU, Z.-L., LUO, L.-M., CHEN, J.-B., HUANG, X.-M., CHENG, J.-G. & WU, Y.-C. 2015. Fabrication of W-Cu/CeO₂ composites with excellent electric conductivity and high strength prepared from copper-coated tungsten and Ceria powders. *Materials Science and Engineering: A*, 626, 61-66.
- MA, Z. 2008. Friction stir processing technology: a review. *Metallurgical and Materials Transactions A*, 39, 642-658.
- MAHARANA, H. & BASU, A. 2016. Surface-mechanical and oxidation behavior of electro-co-deposited Cu-Y₂O₃ composite coating. *Surface and Coatings Technology*, 304, 348-358.
- MAHMOUD, E., IKEUCHI, K. & TAKAHASHI, M. 2008. Fabrication of SiC particle reinforced composite on aluminium surface by friction stir processing. *Science and Technology of Welding and Joining*, 13, 607-618.
- MAHMOUD, E., TAKAHASHI, M., SHIBAYANAGI, T. & IKEUCHI, K. 2009a. Effect of friction stir processing tool probe on fabrication of SiC particle reinforced composite on aluminium surface. *Science and Technology of Welding and Joining*, 14, 413-425.
- MAHMOUD, E. R., TAKAHASHI, M., SHIBAYANAGI, T. & IKEUCHI, K. 2009b. Fabrication of surface-hybrid-MMCS layer on aluminum plate by friction stir processing and its wear characteristics. *Materials transactions*, 50, 1824-1831.
- MAHMOUD, E. R., TAKAHASHI, M., SHIBAYANAGI, T. & IKEUCHI, K. 2010. Wear characteristics of surface-hybrid-MMCs layer fabricated on aluminum plate by friction stir processing. *Wear*, 268, 1111-1121.
- MATHUR, R., CHAND, S. & TEZUKA, T. 2003. Optimal use of coal for power generation in India. *Energy policy*, 31, 319-331.

- MAZAHERI, Y., KARIMZADEH, F. & ENAYATI, M. 2011. A novel technique for development of A356/Al₂O₃ surface nanocomposite by friction stir processing. *Journal of Materials Processing Technology*, 211, 1614-1619.
- MEHTA, K. P. & BADHEKA, V. J. 2016. Effects of tilt angle on the properties of dissimilar friction stir welding copper to aluminum. *Materials and Manufacturing processes*, 31, 255-263.
- MENG, Y., SHEN, Y., CHEN, C., LI, Y. & FENG, X. 2013. Microstructures and formation mechanism of W–Cu composite coatings on copper substrate prepared by mechanical alloying method. *Applied Surface Science*, 282, 757-764.
- MIRANDA, R., SANTOS, T. G., GANDRA, J., LOPES, N. & SILVA, R. 2013. Reinforcement strategies for producing functionally graded materials by friction stir processing in aluminium alloys. *Journal of Materials Processing Technology*, 213, 1609-1615.
- MIRONOV, S., SATO, Y. & KOKAWA, H. 2008. Microstructural evolution during friction stir-processing of pure iron. *Acta Materialia*, 56, 2602-2614.
- MISHRA, R. S. & MA, Z. 2005. Friction stir welding and processing. *Materials science and engineering: R: reports*, 50, 1-78.
- MISHRA, R. S., MA, Z. & CHARIT, I. 2003. Friction stir processing: a novel technique for fabrication of surface composite. *Materials Science and Engineering: A*, 341, 307-310.
- MOEF 2015. Ministry of Environment and Forests (MoEF). 2015 the Gazette of India. Municipal Solid Waste (Management and Handling) Rules New Delhi, India.
- MOGHADDAM, M. S., PARVIZI, R., HADDAD-SABZEVAR, M. & DAVOODI, A. 2011. Microstructural and mechanical properties of friction stir welded Cu–30Zn brass alloy at various feed speeds: Influence of stir bands. *Materials & Design*, 32, 2749-2755.
- MORISADA, Y., FUJII, H., NAGAOKA, T. & FUKUSUMI, M. 2006a. Effect of friction stir processing with SiC particles on microstructure and hardness of AZ31. *Materials Science and Engineering: A*, 433, 50-54.

- MORISADA, Y., FUJII, H., NAGAOKA, T. & FUKUSUMI, M. 2006b. MWCNTs/AZ31 surface composites fabricated by friction stir processing. *Materials science and engineering: A*, 419, 344-348.
- NAJAFI, M., NASIRI, A. & KOKABI, A. 2008. Microstructure and hardness of friction stir processed AZ31 with SiC p. *International Journal of Modern Physics B*, 22, 2879-2885.
- NALEPKA, K., SZTWIERTNIA, K. & NALEPKA, P. 2016. Preferred orientation relationships at the Cu/ α -Al₂O₃ interface: identification and theoretical explanation. *Acta Materialia*, 104, 156-165.
- NANDAN, R., DEBROY, T. & BHADESHIA, H. 2008. Recent advances in friction-stir welding—process, weldment structure and properties. *Progress in materials science*, 53, 980-1023.
- NARIMANI, M., LOTFI, B. & SADEGHIAN, Z. 2016. Investigating the microstructure and mechanical properties of Al-TiB₂ composite fabricated by Friction Stir Processing (FSP). *Materials Science and Engineering: A*, 673, 436-442.
- NIA, A. A. & NOURBAKHSI, S. 2016. Microstructure and mechanical properties of AZ31/SiC and AZ31/CNT composites produced by friction stir processing. *Transactions of the Indian Institute of Metals*, 69, 1435-1442.
- OKAFOR, E. & AIGBODION, V. 2010. Effect of Zircon Silicate Reinforcements on the Microstructure and Properties of as Cast Al-4.5 Cu Matrix Particulate Composites Synthesized via Squeeze Cast Route. *Tribology in industry*, 32, 31-37.
- PADMANABAN, G. & BALASUBRAMANIAN, V. 2009. Selection of FSW tool pin profile, shoulder diameter and material for joining AZ31B magnesium alloy—an experimental approach. *Materials & Design*, 30, 2647-2656.
- PALANIVEL, R., DINAHARAN, I., LAUBSCHER, R. & DAVIM, J. P. 2016. Influence of boron nitride nanoparticles on microstructure and wear behavior of AA6082/TiB₂ hybrid aluminum composites synthesized by friction stir processing. *Materials & Design*, 106, 195-204.
- PANDEY, V. C. & SINGH, N. 2010. Impact of fly ash incorporation in soil systems. *Agriculture, ecosystems & environment*, 136, 16-27.

- PANWAR, R. S., KUMAR, S., PANDEY, R. & PANDEY, O. P. 2014. Study of non-lubricated wear of the Al–Si Alloy composite reinforced with different ratios of coarse and fine size zircon sand particles at different ambient temperatures. *Tribology Letters*, 55, 83-92.
- PANWAR, R. S. & PANDEY, O. 2013. Analysis of wear track and debris of stir cast LM13/Zr composite at elevated temperatures. *Materials Characterization*, 75, 200-213.
- PARIS, J. M., ROESSLER, J. G., FERRARO, C. C., DEFORD, H. D. & TOWNSEND, T. G. 2016. A review of waste products utilized as supplements to Portland cement in concrete. *Journal of Cleaner Production*, 121, 1-18.
- PILLAI, U. & PANDEY, R. 1991. Fracture characteristics of Al/zircon particulate composites. *Composites science and technology*, 40, 333-354.
- PIRKLE, F. & PODMEYER, D. 1998. Zircon: origin and uses. Society for mining, metallurgy and exploration. Inc.
- PRADO, R., MURR, L., SHINDO, D. & SOTO, K. 2001. Tool wear in the friction-stir welding of aluminum alloy 6061+ 20 Al₂O₃: a preliminary study. *Scripta materialia*, 1, 75-80.
- QIAN, J., LI, J., XIONG, J., ZHANG, F. & LIN, X. 2012. In situ synthesizing Al₃Ni for fabrication of intermetallic-reinforced aluminum alloy composites by friction stir processing. *Materials Science and Engineering: A*, 550, 279-285.
- QU, J., XU, H., FENG, Z., FREDERICK, D. A., AN, L. & HEINRICH, H. 2011. Improving the tribological characteristics of aluminum 6061 alloy by surface compositing with sub-micro-size ceramic particles via friction stir processing. *Wear*, 271, 1940-1945.
- RAAFT, M., MAHMOUD, T., ZAKARIA, H. & KHALIFA, T. 2011. Microstructural, mechanical and wear behavior of A390/graphite and A390/Al₂O₃ surface composites fabricated using FSP. *Materials Science and Engineering: A*, 528, 5741-5746.
- RAHSEPAR, M. & JARAHIMOGHADAM, H. 2016. The influence of multipass friction stir processing on the corrosion behavior and mechanical properties of zircon-reinforced Al metal matrix composites. *Materials Science and Engineering: A*, 671, 214-220.

- RAI, R., DE, A., BHADSHIA, H. & DEBROY, T. 2011. friction stir welding tools. *Science and Technology of welding and Joining*, 16, 325-342.
- RAJU, L. S. & KUMAR, A. 2014. Influence of Al₂O₃ particles on the microstructure and mechanical properties of copper surface composites fabricated by friction stir processing. *Defence Technology*, 10, 375-383.
- RAMESH, C., AHMED, R. N., MUJEEBU, M. & ABDULLAH, M. 2009a. Development and performance analysis of novel cast copper–SiC–Gr hybrid composites. *Materials & Design*, 30, 1957-1965.
- RAMESH, C., KESHAVAMURTHY, R., CHANNABASAPPA, B. & AHMED, A. 2009b. Microstructure and mechanical properties of Ni–P coated Si₃N₄ reinforced Al6061 composites. *Materials Science and Engineering: A*, 502, 99-106.
- RAO, D., HUBER, K., HEERENS, J., DOS SANTOS, J. & HUBER, N. 2013. Asymmetric mechanical properties and tensile behaviour prediction of aluminium alloy 5083 friction stir welding joints. *Materials Science and Engineering: A*, 565, 44-50.
- RATHEE, S., MAHESHWARI, S., SIDDIQUEE, A. N. & SRIVASTAVA, M. 2017a. Analysis of microstructural changes in enhancement of surface properties in sheet forming of Al alloys via friction stir processing. *Materials Today: Proceedings*, 4, 452-458.
- RATHEE, S., MAHESHWARI, S., SIDDIQUEE, A. N. & SRIVASTAVA, M. 2017b. Effect of tool plunge depth on reinforcement particles distribution in surface composite fabrication via friction stir processing. *Defence technology*, 13, 86-91.
- RATHEE, S., MAHESHWARI, S., SIDDIQUEE, A. N. & SRIVASTAVA, M. 2017c. Investigating effects of groove dimensions on microstructure and mechanical properties of AA6063/SiC surface composites produced by friction stir processing. *Transactions of the Indian Institute of Metals*, 70, 809-816.
- RATHEE, S., MAHESHWARI, S., SIDDIQUEE, A. N., SRIVASTAVA, M. & SHARMA, S. K. 2016. Process parameters optimization for enhanced microhardness of AA 6061/SiC surface composites fabricated via Friction Stir Processing (FSP). *Materials Today: Proceedings*, 3, 4151-4156.

- RATHOD, S., MODI, O., PRASAD, B., CHRYSANTHOU, A., VALLAURI, D., DESHMUKH, V. & SHAH, A. 2009. Cast in situ Cu–TiC composites: synthesis by SHS route and characterization. *Materials Science and Engineering: A*, 502, 91-98.
- REDDY, B., DAS, K. & DAS, S. 2007. A review on the synthesis of in situ aluminum based composites by thermal, mechanical and mechanical–thermal activation of chemical reactions. *Journal of Materials Science*, 42, 9366-9378.
- REJIL, C. M., DINAHARAN, I., VIJAY, S. & MURUGAN, N. 2012. Microstructure and sliding wear behavior of AA6360/(TiC+ B4C) hybrid surface composite layer synthesized by friction stir processing on aluminum substrate. *Materials Science and Engineering: A*, 552, 336-344.
- REYNOLDS, A. & TANG, W. 2001. Alloy, tool geometry, and process parameter effects on friction stir weld energies and resultant FSW joint properties. *Friction stir welding and processing*, 15-23.
- RIOS, P. R. 1987. Overview no. 62: A theory for grain boundary pinning by particles. *Acta Metallurgica*, 35, 2805-2814.
- ROSSI, P., ENGSTLER, M. & MUECKLICH, F. 2014. Homogeneity quantification method and its application to microstructure assessment. *Practical Metallography*, 51, 180-199.
- SABBAGHIAN, M., SHAMANIAN, M., AKRAMIFARD, H. & ESMAILZADEH, M. 2014. Effect of friction stir processing on the microstructure and mechanical properties of Cu–TiC composite. *Ceramics International*, 40, 12969-12976.
- SAHRAEINEJAD, S., IZADI, H., HAGHSHENAS, M. & GERLICH, A. 2015. Fabrication of metal matrix composites by friction stir processing with different particles and processing parameters. *Materials Science and Engineering: A*, 626, 505-513.
- SAI, N. V., KOMARAIHAH, M. & RAJU, A. S. R. 2008. Preparation and properties of sintered copper–tin composites containing copper coated or uncoated fly ash. *Materials and Manufacturing Processes*, 23, 651-657.
- SALEHI, M., SAADATMAND, M. & MOHANDESI, J. A. 2012. Optimization of process parameters for producing AA6061/SiC nanocomposites by

- friction stir processing. *Transactions of Nonferrous Metals Society of China*, 22, 1055-1063.
- SALIH, O. S., OU, H., SUN, W. & MCCARTNEY, D. 2015. A review of friction stir welding of aluminium matrix composites. *Materials & Design*, 86, 61-71.
- SANATY-ZADEH, A. 2012. Comparison between current models for the strength of particulate-reinforced metal matrix nanocomposites with emphasis on consideration of Hall–Petch effect. *Materials Science and Engineering: A*, 531, 112-118.
- SANNINO, A. & RACK, H. 1995. Dry sliding wear of discontinuously reinforced aluminum composites: review and discussion. *Wear*, 189, 1-19.
- SANTELLA, M., ENGSTROM, T., STORJOHANN, D. & PAN, T.-Y. 2005. Effects of friction stir processing on mechanical properties of the cast aluminum alloys A319 and A356. *Scripta Materialia*, 53, 201-206.
- SARAVANAKUMAR, S., GOPALAKRISHNAN, S., DINAHARAN, I. & KALAISELVAN, K. 2017. Assessment of microstructure and wear behavior of aluminum nitrate reinforced surface composite layers synthesized using friction stir processing on copper substrate. *Surface and Coatings Technology*, 322, 51-58.
- SARMADI, H., KOKABI, A. & REIHANI, S. S. 2013. Friction and wear performance of copper–graphite surface composites fabricated by friction stir processing (FSP). *Wear*, 304, 1-12.
- SATHISKUMAR, R., MURUGAN, N., DINAHARAN, I. & VIJAY, S. 2013. Characterization of boron carbide particulate reinforced in situ copper surface composites synthesized using friction stir processing. *Materials characterization*, 84, 16-27.
- SATHISKUMAR, R., MURUGAN, N., DINAHARAN, I. & VIJAY, S. 2014. Prediction of mechanical and wear properties of copper surface composites fabricated using friction stir processing. *Materials & Design*, 55, 224-234.
- SCHUBERT, T., TRINDADE, B., WEIßGÄRBER, T. & KIEBACK, B. 2008. Interfacial design of Cu-based composites prepared by powder metallurgy for heat sink applications. *Materials Science and Engineering: A*, 475, 39-44.

- SHAFIEI-ZARGHANI, A., KASHANI-BOZORG, S. & ZAREI-HANZAKI, A. 2009. Microstructures and mechanical properties of Al/Al₂O₃ surface nano-composite layer produced by friction stir processing. *Materials Science and Engineering: A*, 500, 84-91.
- SHAFIEI-ZARGHANI, A., KASHANI-BOZORG, S. & ZAREI-HANZAKI, A. 2011. Wear assessment of Al/Al₂O₃ nano-composite surface layer produced using friction stir processing. *Wear*, 270, 403-412.
- SHAFIEI-ZARGHANI, A., KASHANI-BOZORG, S. F. & GERLICH, A. P. 2015. Strengthening analyses and mechanical assessment of Ti/Al₂O₃ nano-composites produced by friction stir processing. *Materials Science and Engineering: A*, 631, 75-85.
- SHAHRABI, S., KHORASANI, S., BEHNAGH, R. A., FOTOUHI, Y. & BISADI, H. 2013. Producing of AA5083/ZrO₂ nanocomposite by friction stir processing (FSP). *Metallurgical and Materials Transactions B*, 44, 1546-1553.
- SHAMSIPUR, A., KASHANI-BOZORG, S. F. & ZAREI-HANZAKI, A. 2011. The effects of friction-stir process parameters on the fabrication of Ti/SiC nano-composite surface layer. *Surface and Coatings Technology*, 206, 1372-1381.
- SHARIFITABAR, M., KASHEFI, M. & KHORSHAHIAN, S. 2016. Effect of friction stir processing pass sequence on properties of Mg–ZrSiO₄–Al₂O₃ surface hybrid micro/nano-composites. *Materials & Design*, 108, 1-7.
- SHARIFITABAR, M., SARANI, A., KHORSHAHIAN, S. & AFARANI, M. S. 2011. Fabrication of 5052Al/Al₂O₃ nanoceramic particle reinforced composite via friction stir processing route. *Materials & Design*, 32, 4164-4172.
- SHARMA, A. & DAS, S. 2009. Study of age hardening behavior of Al–4.5 wt% Cu/zircon sand composite in different quenching media–A comparative study. *Materials & Design*, 30, 3900-3903.
- SHARMA, A. S., MISHRA, N., BISWAS, K. & BASU, B. 2013. Fretting wear study of Cu–10 wt% TiB₂ and Cu–10 wt% TiB₂–10 wt% Pb composites. *Wear*, 306, 138-148.

- SHARMA, S., GIRISH, B., SOMASHEKAR, D., SATISH, B. & KAMATH, R. 1999. Sliding wear behaviour of zircon particles reinforced ZA-27 alloy composite materials. *Wear*, 224, 89-94.
- SHARMA, S., SOMASHEKAR, D. & SATISH, B. 2001. A note on the corrosion characterisation of ZA-27/zircon particulate composites in acidic medium. *Journal of materials processing technology*, 118, 62-64.
- SHARMA, V., GUPTA, Y., KUMAR, B. M. & PRAKASH, U. 2016. Friction stir processing strategies for uniform distribution of reinforcement in a surface composite. *Materials and Manufacturing Processes*, 31, 1384-1392.
- SHARMA, V., KUMAR, S., PANWAR, R. S. & PANDEY, O. 2012. Microstructural and wear behavior of dual reinforced particle (DRP) aluminum alloy composite. *Journal of Materials Science*, 47, 6633-6646.
- SHARMA, V., PRAKASH, U. & KUMAR, B. M. 2015. Surface composites by friction stir processing: A review. *Journal of Materials Processing Technology*, 224, 117-134.
- SHEIBANI, S., ATAIE, A. & HESHMATI-MANESH, S. 2010. In-Situ Synthesis of Cu/Cr-Al₂O₃ Nanocomposite by Mechanical Alloying and Heat Treatment. *Metallurgical and Materials Transactions A*, 41, 2606-2612.
- SHOJAEFARD, M. H., AKBARI, M., KHALKHALI, A. & ASADI, P. 2018. Effect of tool pin profile on distribution of reinforcement particles during friction stir processing of B₄C/aluminum composites. *Proceedings of the Institution of Mechanical Engineers, Part L: Journal of Materials: Design and Applications*, 232, 637-651.
- SIDDIQUEE, A. N. & PANDEY, S. 2014. Experimental investigation on deformation and wear of WC tool during friction stir welding (FSW) of stainless steel. *The International Journal of Advanced Manufacturing Technology*, 73, 479-486.
- SINGH, J. & CHAUHAN, A. 2016. Overview of wear performance of aluminium matrix composites reinforced with ceramic materials under the influence of controllable variables. *Ceramics International*, 42, 56-81.
- SOLEYMANI, S., ABDOLLAH-ZADEH, A. & ALIDOKHT, S. 2012. Microstructural and tribological properties of Al5083 based surface hybrid composite produced by friction stir processing. *Wear*, 278, 41-47.

- SU, J.-Q., NELSON, T. & STERLING, C. 2006. Grain refinement of aluminum alloys by friction stir processing. *Philosophical Magazine*, 86, 1-24.
- SUCITHARAN, K., SENTHILKUMAR, P., SHIVALINGAPPA, D. & RINO, J. J. 2013. Wear behaviour of Al6063-Zircon sand metal matrix composite. *Wear*, 3.
- SUN, L., TAO, N. & LU, K. 2015. A high strength and high electrical conductivity bulk CuCrZr alloy with nanotwins. *Scripta Materialia*, 99, 73-76.
- SUN, N. & APELIAN, D. 2011. Friction stir processing of aluminum cast alloys for high performance applications. *JOM*, 63, 44-50.
- SUREKHA, K. & ELS-BOTES, A. 2011. Development of high strength, high conductivity copper by friction stir processing. *Materials & Design*, 32, 911-916.
- SURYANARAYANA, C. & AL-AQEELI, N. 2013. Mechanically alloyed nanocomposites. *Progress in Materials Science*, 58, 383-502.
- TANG, Z., MA, S., DING, J., WANG, Y., ZHENG, S. & ZHAI, G. Current status and prospect of fly ash utilization in China. Proc. of World of Coal Ash Conference (WOCA), 2013. 1-7.
- THANGARASU, A., MURUGAN, N., DINAHARAN, I. & VIJAY, S. 2015. Synthesis and characterization of titanium carbide particulate reinforced AA6082 aluminium alloy composites via friction stir processing. *Archives of civil and mechanical engineering*, 15, 324-334.
- THANKACHAN, T. & PRAKASH, K. S. 2017. Microstructural, mechanical and tribological behavior of aluminum nitride reinforced copper surface composites fabricated through friction stir processing route. *Materials Science and Engineering: A*, 688, 301-308.
- THAPLIYAL, S. & DWIVEDI, D. K. 2016. Microstructure evolution and tribological behavior of the solid lubricant based surface composite of cast nickel aluminum bronze developed by friction stir processing. *Journal of Materials Processing Technology*, 238, 30-38.
- TJONG, S. & WANG, G. 2006. Low-cycle fatigue behavior of in situ TiB₂/Cu composite prepared by reactive hot pressing. *Journal of materials science*, 41, 5263-5268.

- TJONG, S. C. & MA, Z. 2000. Microstructural and mechanical characteristics of in situ metal matrix composites. *Materials Science and Engineering: R: Reports*, 29, 49-113.
- UKWATTAGE, N., RANJITH, P., YELLISHETTY, M., BUI, H. & XU, T. 2015. A laboratory-scale study of the aqueous mineral carbonation of coal fly ash for CO₂ sequestration. *Journal of Cleaner Production*, 103, 665-674.
- UNIWERSAŁ, A., WRÓBEL, M., WIERZBANOWSKI, K., WROŃSKI, S., WROŃSKI, M., KALEMBA-REC, I., SAK, T. & BACROIX, B. 2016. Microstructure, texture and mechanical characteristics of asymmetrically rolled polycrystalline copper. *Materials Characterization*, 118, 575-583.
- VARGAS, J. & HALOG, A. 2015. Effective carbon emission reductions from using upgraded fly ash in the cement industry. *Journal of Cleaner Production*, 103, 948-959.
- VENKATARAMAN, B. & SUNDARARAJAN, G. 1996. The sliding wear behaviour of Al/SiC particulate composites—II. The characterization of subsurface deformation and correlation with wear behaviour. *Acta Materialia*, 44, 461-473.
- VETTIVEL, S., SELVAKUMAR, N., NARAYANASAMY, R. & LEEMA, N. 2013. Numerical modelling, prediction of Cu–W nano powder composite in dry sliding wear condition using response surface methodology. *Materials & Design*, 50, 977-996.
- VIJAYAVEL, P., BALASUBRAMANIAN, V. & SUNDARAM, S. 2014. Effect of shoulder diameter to pin diameter (D/d) ratio on tensile strength and ductility of friction stir processed LM25AA-5% SiCp metal matrix composites. *Materials & Design*, 57, 1-9.
- WANG, F., LI, Y., WANG, X., KOIZUMI, Y., KENTA, Y. & CHIBA, A. 2016a. In-situ fabrication and characterization of ultrafine structured Cu–TiC composites with high strength and high conductivity by mechanical milling. *Journal of Alloys and Compounds*, 657, 122-132.
- WANG, H., ZHANG, Z.-H., HU, Z.-Y., SONG, Q., YIN, S.-P., KANG, Z. & LI, S.-L. 2018. Improvement of interfacial interaction and mechanical properties in copper matrix composites reinforced with copper coated carbon nanotubes. *Materials Science and Engineering: A*, 715, 163-173.

- WANG, H., ZHANG, Z.-H., ZHANG, H.-M., HU, Z.-Y., LI, S.-L. & CHENG, X.-W. 2017a. Novel synthesizing and characterization of copper matrix composites reinforced with carbon nanotubes. *Materials Science and Engineering: A*, 696, 80-89.
- WANG, J., YI, D., SU, X., YIN, F. & LI, H. 2009a. Properties of submicron AlN particulate reinforced aluminum matrix composite. *Materials & Design*, 30, 78-81.
- WANG, T., ZOU, C., CHEN, Z., LI, M., WANG, W., LI, R. & KANG, H. 2015. In situ synthesis of TiB₂ particulate reinforced copper matrix composite with a rotating magnetic field. *Materials & Design (1980-2015)*, 65, 280-288.
- WANG, W., KANG, H., CHEN, Z., CHEN, Z., ZOU, C., LI, R., YIN, G. & WANG, T. 2016b. Effects of Cr and Zr additions on microstructure and properties of Cu-Ni-Si alloys. *Materials Science and Engineering: A*, 673, 378-390.
- WANG, W., SHI, Q.-Y., LIU, P., LI, H.-K. & LI, T. 2009b. A novel way to produce bulk SiCp reinforced aluminum metal matrix composites by friction stir processing. *Journal of materials processing technology*, 209, 2099-2103.
- WANG, X., DING, H., QI, F., LIU, Q., FAN, X. & SHI, Y. 2017b. Mechanism of in situ synthesis of TiC in Cu melts and its microstructures. *Journal of Alloys and Compounds*, 695, 3410-3418.
- WANG, Y., YU, Y., LI, H. & SHEN, C. 2016c. Comparison study of phosphorus adsorption on different waste solids: Fly ash, red mud and ferric–alum water treatment residues. *Journal of Environmental Sciences*, 50, 79-86.
- WĘGŁOWSKI, M. S. & DYMEK, S. 2013. Relationship between friction stir processing parameters and torque, temperature and the penetration depth of the tool. *Archives of civil and mechanical engineering*, 13, 186-191.
- XING, H., CAO, X., HU, W., ZHAO, L. & ZHANG, J. 2005. Interfacial reactions in 3D-SiC network reinforced Cu-matrix composites prepared by squeeze casting. *Materials Letters*, 59, 1563-1566.
- XU, N., UEJI, R. & FUJII, H. 2014. Enhanced mechanical properties of 70/30 brass joint by rapid cooling friction stir welding. *Materials Science and Engineering: A*, 610, 132-138.

- YANG, M., XU, C., WU, C., LIN, K.-C., CHAO, Y. J. & AN, L. 2010. Fabrication of AA6061/Al₂O₃ nano ceramic particle reinforced composite coating by using friction stir processing. *Journal of Materials Science*, 45, 4431-4438.
- YU, R. & SHUI, Z. 2014. Efficient reuse of the recycled construction waste cementitious materials. *Journal of cleaner production*, 78, 202-207.
- YU, Z., ZHANG, W., CHOO, H. & FENG, Z. 2012. Transient heat and material flow modeling of friction stir processing of magnesium alloy using threaded tool. *Metallurgical and Materials Transactions A*, 43, 724-737.
- YUAN, W., PANIGRAHI, S. K. & MISHRA, R. S. 2013. Achieving high strength and high ductility in friction stir-processed cast magnesium alloy. *Metallurgical and Materials Transactions A*, 44, 3675-3684.
- YUVARAJ, N. & ARAVINDAN, S. 2017. Wear characteristics of Al5083 surface hybrid nano-composites by friction stir processing. *Transactions of the Indian Institute of Metals*, 70, 1111-1129.
- ZAHI, S. & DAUD, A. 2011. Fly ash characterization and application in Al-based Mg alloys. *Materials & Design*, 32, 1337-1346.
- ZAHMATKESH, B. & ENAYATI, M. 2010. A novel approach for development of surface nanocomposite by friction stir processing. *Materials Science and Engineering: A*, 527, 6734-6740.
- ZHANG, L., QU, X.-H., DUAN, B.-H., HE, X.-B., QIN, M.-L. & XIN, L. 2008. Preparation of SiCp/Cu composites by Ti-activated pressureless infiltration. *Transactions of Nonferrous Metals Society of China*, 18, 872-878.
- ZHANG, Y., CAO, X., LAROSE, S. & WANJARA, P. 2012. Review of tools for friction stir welding and processing. *Canadian Metallurgical Quarterly*, 51, 250-261.
- ZHANG, Y., HAN, Z., WANG, K. & LU, K. 2006. Friction and wear behaviors of nanocrystalline surface layer of pure copper. *Wear*, 260, 942-948.
- ZHANG, Z. & CHEN, D. 2008. Contribution of Orowan strengthening effect in particulate-reinforced metal matrix nanocomposites. *Materials Science and Engineering: A*, 483, 148-152.
- ZHANG, Z., ZHANG, L. & MAI, Y. 1995. Wear of ceramic particle-reinforced metal-matrix composites. *Journal of materials science*, 30, 1961-1966.

- ZHAO, H., SUN, W., WU, X. & GAO, B. 2015. The properties of the self-compacting concrete with fly ash and ground granulated blast furnace slag mineral admixtures. *Journal of Cleaner Production*, 95, 66-74.
- ZHAO, N., LI, J. & YANG, X. 2004. Influence of the P/M process on the microstructure and properties of WC reinforced copper matrix composite. *Journal of Materials Science*, 39, 4829-4834.
- ZHAO, Y., KAI, X., CHEN, G., LIN, W. & WANG, C. 2016. Effects of friction stir processing on the microstructure and superplasticity of in situ nano-ZrB₂/2024Al composite. *Progress in Natural Science: Materials International*, 26, 69-77.
- ZHENG, R., ZHAN, Z. & WANG, W. 2010. Wear behavior of Cu-La₂O₃ composite with or without electrical current. *Wear*, 268, 72-76.
- ZHUO, H., TANG, J. & YE, N. 2013. A novel approach for strengthening Cu-Y₂O₃ composites by in situ reaction at liquidus temperature. *Materials Science and Engineering: A*, 584, 1-6.
- ZOHOOR, M., GIVI, M. B. & SALAMI, P. 2012. Effect of processing parameters on fabrication of Al-Mg/Cu composites via friction stir processing. *Materials & Design*, 39, 358-365.
- ZOU, C., CHEN, Z., KANG, H., WANG, W., LI, R., LI, T. & WANG, T. 2017. Study of enhanced dry sliding wear behavior and mechanical properties of Cu-TiB₂ composites fabricated by in situ casting process. *Wear*, 392, 118-125.